

# The count verb

DATA MANIPULATION WITH DPLYR



**James Chapman**

Content Developer, DataCamp

# Count

```
counties %>%  
  count()
```

```
# A tibble: 1 x 1  
      n  
  <int>  
1  3138
```

# Count variable

```
counties %>%  
  count(state)
```

```
# A tibble: 50 x 2  
  state      n  
  <chr>    <int>  
1 Alabama    67  
2 Alaska    28  
3 Arizona    15  
4 Arkansas   75  
5 California  58  
6 Colorado   64  
7 Connecticut  8  
8 Delaware    3  
9 Florida    67  
10 Georgia   159  
# ... with 40 more rows
```

# Count and sort

```
counties %>%  
  count(state, sort = TRUE)
```

```
# A tibble: 50 x 2  
  state      n  
  <chr>    <int>  
1 Texas    253  
2 Georgia  159  
3 Virginia 133  
4 Kentucky 120  
5 Missouri 115  
6 Kansas   105  
7 Illinois 102  
8 North Carolina 100  
9 Iowa      99  
10 Tennessee 95  
# ... with 40 more rows
```

# Count population

```
counties %>%  
  select(state, county, population)
```

```
# A tibble: 3,138 x 3  
  state    county  population  
  <chr>   <chr>      <dbl>  
1 Alabama Autauga      55221  
2 Alabama Baldwin    195121  
3 Alabama Barbour     26932  
4 Alabama Bibb        22604  
5 Alabama Blount      57710  
6 Alabama Bullock     10678  
7 Alabama Butler      20354  
8 Alabama Calhoun    116648  
9 Alabama Chambers     34079  
10 Alabama Cherokee    26008  
# ... with 3,128 more rows
```

# Add weight

```
counties %>%  
  count(state, wt = population, sort = TRUE)
```

```
# A tibble: 50 x 2  
  state      n  
  <chr>    <dbl>  
1 California 38421464  
2 Texas      26538497  
3 New York   19673174  
4 Florida    19645772  
5 Illinois   12873761  
6 Pennsylvania 12779559  
7 Ohio       11575977  
8 Georgia    10006693  
9 Michigan    9900571  
10 North Carolina 9845333  
# ... with 40 more rows
```

# Let's practice!

DATA MANIPULATION WITH DPLYR

# The group\_by, summarize, and ungroup verbs

DATA MANIPULATION WITH DPLYR



**James Chapman**

Content Developer, DataCamp



# Summarize

```
counties %>%  
  summarize(total_population = sum(population))
```

```
# A tibble: 1 x 1  
  total_population  
      <dbl>  
1      315845353
```

# Aggregate and summarize

```
counties %>%  
  summarize(total_population = sum(population),  
            average_unemployment = mean(unemployment))
```

```
# A tibble: 1 x 2  
  total_population average_unemployment  
      <dbl>          <dbl>  
1    315845353          7.80
```

# Summary functions

- `sum()`
- `mean()`
- `median()`
- `min()`
- `max()`
- `n()`

# Aggregate within groups

```
counties %>%  
  group_by(state) %>%  
  summarize(total_pop = sum(population),  
            average_unemployment = mean(unemployment))
```

```
# A tibble: 50 x 3  
  state      total_pop average_unemployment  
  <chr>      <dbl>          <dbl>  
1 Alabama    4830620         758.  
2 Alaska     725461         257.  
3 Arizona    6641928         180.  
4 Arkansas   2958208         674.  
5 California 38421464         626.  
6 Colorado   5278906         477.  
7 Connecticut 3593222          65.3  
8 Delaware   926454          23.8  
9 Florida    19645772         696.  
10 Georgia   10006693        1586.  
# ... with 40 more rows
```

# Sorting summaries

```
counties %>%
  group_by(state) %>%
  summarize(total_pop = sum(population),
            average_unemployment = mean(unemployment)) %>%
  arrange(desc(average_unemployment))
```

```
# A tibble: 50 x 3
  state      total_pop average_unemployment
  <chr>      <dbl>          <dbl>
1 Mississippi 2988081         12.0
2 Arizona     6641928         12.0
3 South Carolina 4777576         11.3
4 Alabama     4830620         11.3
5 California  38421464         10.8
6 Nevada      2798636         10.5
7 North Carolina 9845333         10.5
8 Florida     19645772         10.4
9 Georgia     10006693          9.97
10 Michigan    9900571          9.96
# ... with 40 more rows
```

# Metro column

```
counties %>%  
  select(state, metro, county, population)
```

```
# A tibble: 3,138 x 4  
  state  metro  county  population  
  <chr>  <chr>  <chr>      <dbl>  
1 Alabama Metro   Autauga    55221  
2 Alabama Metro   Baldwin  195121  
3 Alabama Nonmetro Barbour   26932  
4 Alabama Metro   Bibb     22604  
5 Alabama Metro   Blount   57710  
6 Alabama Nonmetro Bullock  10678  
7 Alabama Nonmetro Butler    20354  
8 Alabama Metro   Calhoun  116648  
9 Alabama Nonmetro Chambers   34079  
10 Alabama Nonmetro Cherokee   26008  
# ... with 3,128 more rows
```

# Grouping on multiple columns

```
counties %>%  
  group_by(state, metro) %>%  
  summarize(total_pop = sum(population))
```

```
# A tibble: 97 x 3  
# Groups:   state [50]  
   state      metro total_pop  
   <chr>    <chr>    <dbl>  
1 Alabama Metro    3671377  
2 Alabama Nonmetro 1159243  
3 Alaska  Metro    494990  
4 Alaska  Nonmetro 230471  
5 Arizona Metro    6295145  
6 Arizona Nonmetro 346783  
7 Arkansas Metro    1806867  
8 Arkansas Nonmetro 1151341  
9 California Metro    37587429  
10 California Nonmetro 834035  
# ... with 87 more rows
```

# Ungroup

```
counties %>%  
  group_by(state, metro) %>%  
  summarize(total_pop = sum(population)) %>%  
  ungroup()
```

```
# A tibble: 97 x 3  
  state      metro      total_pop  
  <chr>    <chr>      <dbl>  
1 Alabama Metro      3671377  
2 Alabama Nonmetro  1159243  
3 Alaska  Metro      494990  
4 Alaska  Nonmetro   230471  
5 Arizona Metro     6295145  
6 Arizona Nonmetro   346783  
7 Arkansas Metro     1806867  
8 Arkansas Nonmetro   1151341  
9 California Metro     37587429  
10 California Nonmetro    834035  
# ... with 87 more rows
```



# Let's practice!

DATA MANIPULATION WITH DPLYR

# The slice\_min and slice\_max verbs

DATA MANIPULATION WITH DPLYR



**James Chapman**

Content Developer, DataCamp

# slice\_max()

- Returns the **largest** observations in each group

```
counties_selected <- counties %>%  
  select(state, county, population, unemployment, income)  
  
counties_selected %>%  
  group_by(state) %>%  
  slice_max(population, n = 1)
```

# slice\_max() output

```
# A tibble: 50 x 5
# Groups:   state [50]
  state      county      population unemployment income
  <chr>      <chr>          <dbl>          <dbl>    <dbl>
1 Alabama  Jefferson      659026          9.1    45610
2 Alaska   Anchorage Municipality 299107          6.7    78326
3 Arizona   Maricopa      4018143          7.7    54229
4 Arkansas Pulaski       390463          7.5    46140
5 California Los Angeles 10038388         10     56196
6 Colorado El Paso       655024          8.4    58206
7 Connecticut Fairfield    939983          9     84233
8 Delaware New Castle   549643          7.4    65476
9 Florida  Miami-Dade   2639042         10     43129
10 Georgia  Fulton     983903          9.9    57207
# ... with 40 more rows
```

# slice\_min()

- Returns the **smallest** observations in each group

```
counties_selected %>%  
  group_by(state) %>%  
  slice_min(unemployment, n = 1)
```

# slice\_min() output

```
# A tibble: 51 × 5
# Groups:   state [50]
  state      county      population unemployment income
  <chr>      <chr>          <dbl>          <dbl>    <dbl>
1 Alabama  Shelby          203530          5.5    70187
2 Alaska   Aleutians West Census Area    5684          2.1    84306
3 Arizona  Maricopa        4018143         7.7    54229
4 Arkansas Benton         238198          4.2    56239
5 California Marin        258349          5.7    93257
6 Colorado Jackson         1335          1.5    46014
7 Connecticut Middlesex    165165          6      79893
8 Delaware New Castle    549643          7.4    65476
9 Florida  Monroe         75901          6      57290
10 Georgia  Bacon         11222          4.4    37162
# ... with 41 more rows
```

# Number of observations

```
counties_selected %>%  
  group_by(state) %>%  
  slice_max(unemployment, n = 3)
```

```
# A tibble: 153 × 5  
# Groups:   state [50]  
  state      county      population unemployment income  
  <chr>    <chr>          <dbl>         <dbl>    <dbl>  
1 Alabama Conecuh      12865         22.6    24900  
2 Alabama Wilcox       11235         20.8    23750  
3 Alabama Monroe      22217         20.7    27257  
4 Alaska  Northwest Arctic Borough    7732         21.9    63648  
5 Alaska  Yukon-Koyukuk Census Area   5644         18.2    38491  
6 Alaska  Bethel Census Area      17776         17.6    51012  
7 Arizona Navajo      107656         19.8    35921  
8 Arizona Apache       72124         18.2    31757  
9 Arizona Graham      37407         14.1    45964  
10 Arkansas Phillips     20391         18.1    26844  
# ... with 143 more rows
```

# Let's practice!

DATA MANIPULATION WITH DPLYR