# **■** NetApp

## Other major additions

**ONTAP What's New** 

NetApp May 06, 2021

This PDF was generated from https://docs.netapp.com/us-en/ontap-whatsnew/ontap991fo\_other\_major\_additions.html on July 29, 2021. Always check docs.netapp.com for the latest.

## **Table of Contents**

Other major additions		1
Logical space accounting/enforcement – FlexGroup volu	ımes	1
ONTAP S3 user-defined metadata tags		1
NFSv4.2 security labels		2


## Other major additions

In addition to the System Manager enhancements, SAN enhancements, and data protection enhancements, there are a few other big additions to ONTAP 9.9.1.

## Logical space accounting/enforcement – FlexGroup volumes

Logical space accounting was introduced for FlexVol volumes in ONTAP 9.4. It enables storage administrators to mask storage efficiency savings so that end users avoid overallocating their designated storage quotas.

For example, if a user writes 6TB to a 10TB volume and storage efficiencies save 2TB, logical space accounting can control whether the user sees 6TB or 4TB.



ONTAP 9.5 enhanced this feature and added quota enforcement support for FlexVols to give more control to storage administrators by preventing new writes according to the logical space thresholds set. However, FlexGroup volumes were missing this functionality until ONTAP 9.9.1.

## ONTAP S3 user-defined metadata tags

ONTAP 9.8 introduced support for the S3 protocol for basic object storage functionality.

Support for S3 in ONTAP 9.8 included the following:

- Basic PUT/GET object access (does not include access to both S3 and NAS from the same bucket)
  - No object tagging or ILM support; for feature-rich, globally dispersed S3, use NetApp StorageGRID.

- TLS 1.2 encryption
- · Multi-part uploads
- · Adjustable ports
- · Multiple buckets per volume
- · Bucket access policies
- S3 as a NetApp FabricPool target

ONTAP 9.9.1 and later offers support for metadata tagging of objects when using ObjectCreate and MultiPartUpload calls. When HEAD or GET is performed on an object, the user-defined metadata and count of the number of tags is returned as part of the HTTP header in the response. These tags allow you to better categorize your objects within ONTAP buckets for more robust data management and are compatible with applications that require the ability to create metadata and tags.

For more information, see the following resources:

- Tech ONTAP Podcast: Episode 268 NetApp FabricPool and S3 in ONTAP 9.8
- ONTAP S3

## NFSv4.2 security labels

ONTAP 9.9.1 introduces support for the NFSv4.2 feature called Labeled NFS, which is a way to manage granular file and folder access by using SELinux labels and Mandatory Access Control (MAC). These MAC labels are stored with files and folders and works in conjunction with UNIX permissions and NFSv4.x ACLs. Support for labeled NFS means that ONTAP now recognizes and understands the NFS client's SELinux label settings. Labeled NFS is covered in RFC-7204.

Use cases include the following:

- · MAC labeling of virtual machine images
- Data security classification for the public sector (secret, top secret, and so on)
- · Security compliance
- Diskless Linux

In this release, ONTAP supports the following enforcement modes:

- Limited Server Mode. ONTAP cannot enforce the labels, but it can store and transmit them.
  - The ability to change MAC labels is also up to the client to enforce.
- Guest Mode. If the client is not labeled NFS-aware (v4.1 or lower), MAC labels are not transmitted.

ONTAP does not currently support Full Mode (storing and enforcing MAC labels).

#### **Copyright Information**

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

### **Trademark Information**

NETAPP, the NETAPP logo, and the marks listed at <a href="http://www.netapp.com/TM">http://www.netapp.com/TM</a> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.