Deduce the World: How Far Can Reasoning Go?

Jeffrey Wei[1] Brian Cheung[2]


[1]Yale University [2]University of California, San Francisco

Results & figures

1 Theories, not fitted predictors

Science deduces the world from first principles, revising its theories where their predictions fail. Deep learning does not. It fits a predictor to existing data, which binds it to that distribution.

We ask whether a reasoning model can form scientific theories, and whether those theories generalize better than deep learning.



We keep the splits of deep learning and replace the learner. The model states a theory, writes it as code, and revises it against validation.

May	read papers and the web, measure the training data, inspect its own errors
May not	fit parameters to labels, search automatically over rules, store examples, see the test split


What a theory looks like

Selected rules from one program on German credit. The points are judgments stated before measurement, not fitted odds ratios.

Checking account	none $+3$, at least 200 DM $+1$, negative -2
Credit history	critical account elsewhere $+2$, past delay -1
Loan duration	-1 for each twelve months beyond the first twelve
Employment	under a year -1, four years or more $+1$
Output	$P(\text{good}) = 1/(1+e^{-(\text{score}-1)/2})$

2 How much data a theory needs

MNIST, the standard handwritten-digit benchmark: 60,000 training and 10,000 test images of the digits 0 to 9.




Handwritten digits. Best of five reasoning efforts. Dashed lines are trained models on the same split.

> Given no training images at all, a theory of how digits are written classifies most of them.

Reasoning as initialization


A written theory is also a starting point. Training from written weights converges sooner, and by more as reasoning grows.



Held-out error after a fixed training budget against effort rank, both axes logarithmic.

3 The same protocol, ten fields

Ten tasks from TabArena, a curated benchmark of real tabular prediction problems with fixed splits and tuned baselines.




Each task ranks the reasoned theory against five tuned models on the same rows.

> Reasoned theories win on small clinical and credit tables, and trail boosted trees where the signal lies in feature interactions.

4 Deriving a scientific score

A structure predictor returns a complex and an estimate of its own error. Each session receives that matrix alone.



704 designed binders. The middle and right panels hold out an entire target.

Derived, not fitted

Treating the bound complex as a harmonic well, with σ_{iface} the interface precision and σ_0 the precision the binder reaches within itself,

$$\kappa = \left(\frac{\sigma_0}{\sigma_{\text{iface}}}\right)^2, \qquad \mathrm{p}K_{\mathrm{d}} = \mathrm{p}K_{\mathrm{d,ref}} + 3\log_{10}\kappa.$$

The 3 is half the six rigid-body degrees of freedom that association confines. Nothing is fitted.

> A rule derived from physics beats the published score on a target it has never seen.

5 Hypothesis

Deep learning dominates the domains that are data-rich and theory-poor, which are exactly the domains where no one has yet written down the first principles. We hypothesize that as reasoning improves, language models will supply those first principles, and that the theories they state, rather than the predictors we fit, will become how we model these domains.