McMurdo Station, Ross Island

BUILDING INFORMATION SHEET

Fire Pump House (Dorm)

Location ID: B151

Single-story building used as a pump house for the automatic fire sprinkler systems in Dormitories 201, 202, and 206 through 211. Includes a 10,000 gallon water storage tank and a 750 gpm, diesel-powered fire pump.



Photo 1: *Fire Pump House (Dorm)*

General Structure Information

Usage	Fire Pump House
Occupancy Group	B-4 Pump House
Maximum Occupancy	2
Construction Type	Type II, 1-hour, non-combustible; steel-framed structure with 2-1/2" thick foam-insulated metal panel siding and roofing, steel-framed precast concrete floor, no interior partitions.
Year Constructed	1990
Dimensions	38' x 20.5'

Floor Area

Floor	Area
Floor 1	778 sq ft
Total	778 sq ft

HVAC System

Heating	One Lennox forced-air, oil-fired unit (125,000 Btu/hr input)
Air Handling Units	None

Fuel Tank	350 gallon fuel tank

Water and Sewer

Water Service	Refill of water tank provided via 2-inch water line from water plant.
Sewer Service	Not connected
Connections	Sinks: 0None
Water Heater	None

Electrical Service

Service Feeder	Feeder B
Electrical Service	208/120V, 3PH; 100A
Phone and LAN	None

Fire System

Fire Panel Type	King-Fisher KF-24-DS control and KFRTI-WP-8 radio interface/transmitter panels, heat detector, pull station, alarm horn.
Heat Detectors	Located throughout building
Suppression Type	Deluge type sprinkler system. Pipes are charged with water, and they release immediately upon sprinkler head actuation. This building houses a 10,000 gallon reservoir tank and Cat diesel firepump with Firetrol Control Panel interfaced with KF fire alarm panels. This system protects Dorms 201, 202, and 206 through 211. An electric jockey pump keeps the trunk line pressurized. The fire pump kicks in on low pressure, and sprinklers for Building 151 simply tap into the trunk line.