

Report

**BIAI**

Multiclass classification of  
histopathological images of lung and  
colon tissue

18.06.2024

**Autor:**

Joanna Wiekiera

Maryna Żur

## **1. Introduction**

Histopathological image analysis is crucial in modern medical diagnostics, providing insights into tissue characteristics that aid in disease classification and treatment decisions. This project focuses on the multiclass classification of histopathological images from lung and colon tissues, aiming to distinguish between five distinct classes:

- lung benign tissue
- lung adenocarcinoma
- lung squamous cell carcinoma
- colon adenocarcinoma
- colon benign tissue.

## **2. Analysis of the task**

### **2.1. Solve the problem**

The goal of our project was to accurately differentiate between five distinct classes: lung benign tissue, lung adenocarcinoma, lung squamous cell carcinoma, colon adenocarcinoma, and colon benign tissue. By leveraging convolutional neural networks, which excel at learning hierarchical features from image data, we aim to develop a robust model capable of accurately categorizing these histopathological images. This classification task is essential diagnostic accuracy and facilitating more informed medical decisions based on detailed tissue analysis.


### **2.2. Dataset**

The dataset employed comprises 25,000 high-resolution images, each measuring 768 x 768 pixels and stored in JPEG format. These images capture the intricate details of tissue samples, presenting both normal and cancerous conditions across lung and colon tissues. Class representatives are shown in Figure 1.

The original sample consisted of:

- 750 total images of lung tissue:
  - 250 benign lung tissue
  - 250 lung adenocarcinomas
  - 250 lung squamous cell carcinomas
- 500 total images of colon tissue:
  - 250 benign colon tissue
  - 250 colon adenocarcinomas

This original dataset was augmented to 25,000 using the Augmentor package by the dataset author. Equal class sizes resulted in better performance.



*Figure 1: The types of classes in the dataset*

### **2.3. Using tools**

Our project uses PyTorch to train our convolutional neural network (CNN) model due to its robust capabilities in deep learning research and development. PyTorch provides a flexible and intuitive platform for building and optimizing neural networks, making it ideal for our task of histopathological image classification.

To document and describe the results of our training process, we employ Jupyter Notebook. Jupyter Notebook is a web-based interactive environment that allows us to create and share documents containing live code, equations, visualizations, and narrative text. It enables us to present our experimental setup, code implementation, training progress, and evaluation metrics clearly and organized.

## **3. Internal and external specification of software solution**

### **3.1. Internal specification**

#### **a) Data preprocessing**

The data preprocessing pipeline for our dataset involves several steps.

Firstly, as shown in Figure 2, we defined a series of transformations to be applied to each image in the dataset:

- i) Resize – each image was resized to the dimension of 64 x 64 pixels using `transforms.Resize((64, 64))` function
- ii) Random Horizontal Flip – To augment the dataset and introduce variability, each image has a 50% chance of being horizontally flipped using the `transforms.RandomHorizontalFlip()` function

- iii) Tensor – The images are converted to PyTorch tensors using the `transforms.ToTensor()` function. This conversion is necessary for the images to be compatible with PyTorch's neural network modules.

```
# Define transforms
transforms = transforms.Compose([
    transforms.Resize((64, 64)),
    transforms.RandomHorizontalFlip(),
    transforms.ToTensor()
])
```

*Figure 2: Transformation of images in dataset*

Secondly, we load and split the dataset into three subsets: training (70%), validation (10%), and test set (20%). This step is shown in Figure 3.

```
# Load the dataset
dataset = datasets.ImageFolder("../DATA/lung_colon_image_set", transform=transforms)

# Split the dataset into training and testing sets
train_size = int(0.7 * len(dataset)) # 70% for training
val_size = int(0.1 * len(dataset)) # 10% for validation
test_size = len(dataset) - train_size - val_size # 20% for testing
train_dataset, val_dataset, test_dataset = random_split(dataset, [train_size, val_size, test_size])
```

*Figure 3: Splitting the data into training, validation, and test sets*

Data loaders are created for each subset to facilitate efficient batch processing during training and evaluation. The data loaders handle the batching of images and shuffling of the training data to improve the model's learning.

```
# Create DataLoaders
train_loader = DataLoader(train_dataset, batch_size=64, shuffle=True)
val_loader = DataLoader(val_dataset, batch_size=64, shuffle=False)
test_loader = DataLoader(test_dataset, batch_size=64, shuffle=False)
```

*Figure 4: Creating DataLoaders for training, validation, and testing sets*

## **b) Class Net**

Defines the architecture of the convolutional neural network (CNN) employed for image classification. It includes a feature extractor composed of convolutional and pooling layers designed to capture hierarchical features from input images. Subsequently, a classifier module consisting of fully connected layers with activation functions and dropout layers for regularization purposes follows. The

network was trained and optimized using these components, achieving superior performance compared to previously trained models.

```
# Define the neural network
class Net(nn.Module):
    def __init__(self, num_classes):
        super(Net, self).__init__()
        self.feature_extractor = nn.Sequential(
            nn.Conv2d(3, 32, kernel_size=3, padding=1),
            nn.ELU(),
            nn.MaxPool2d(kernel_size=2), # Output: 32x64x64

            nn.Conv2d(32, 64, kernel_size=3, padding=1),
            nn.ELU(),
            nn.MaxPool2d(kernel_size=2), # Output: 64x32x32

            nn.Conv2d(64, 128, kernel_size=3, padding=1),
            nn.ELU(),
            nn.MaxPool2d(kernel_size=2), # Output: 128x8x8

            nn.Flatten()
        )
        #self.classifier = nn.Linear(64*16*16, num_classes)
        self.classifier = nn.Sequential(
            nn.Linear(128*8*8, 256),
            nn.ELU(),
            nn.Dropout(0.5),
            nn.Linear(256, num_classes)
        )

    def forward(self, x):
        x = self.feature_extractor(x)
        x = self.classifier(x)
        return x
```

*Figure 5: The structure of our model*

### c) Function and validation loop

We established a training and validation loop that implemented the CNN training process using stochastic gradient descent (SGD) or the Adam optimizer. This loop computed the loss, executed backpropagation, updated model parameters, and tracked training metrics such as loss and accuracy. In the validation loop, we assessed the model's performance on a validation set after each epoch to monitor potential overfitting and selected the optimal model based on validation loss.

### d) Function Evaluation

The evaluation function on the test set involves calculating the accuracy metric, which assesses the percentage of correctly predicted labels compared to

the total number of samples in the test set. This metric serves as a crucial indicator of the model's overall performance on unseen data.


In our study, the accuracy on the test set reached 97.46%. This high accuracy indicates that the model successfully classified the majority of test samples correctly, demonstrating robust performance in distinguishing between different classes of histopathological images of lung and colon tissues. Such a high accuracy suggests that the model effectively learned relevant features and patterns from the training data, translating into reliable predictions on unseen data.

#### **e) Training result on plot**

We provided the result of training and validation losses and accuracies using a plot. The plotted figures illustrate the progression of training and validation metrics across epochs during the model training process. The Figure 6 represents:

- The left subplot shows the change in training loss and validation loss over each epoch.
- The right subplot displays the evolution of training accuracy and validation accuracy across epochs.

The results of our training are highly satisfactory. The analysis of training results indicates that the model effectively learned, as evidenced by decreasing loss values for both the training and validation datasets. The model's accuracy consistently improved with each epoch, reaching high levels of 95.74% for the training set and impressive 97.52% for the validation set. While initial fluctuations in training accuracy were observed, these values stabilized as the model training progressed. This demonstrates the absence of overfitting and the effectiveness of model learning process.



*Figure 6: Training results plots of our model*

#### **f) Confusion Matrix**

In Figure 7, the confusion matrix generated from the classification of the test data is shown. It is visible that images illustrating colon cancer are most often confused with healthy colon tissue and vice versa, but very rarely with lung tissue. At the same time, diseased lung tissues are confused with each other but are rarely mistaken for healthy lung tissue, which, in the context of medical diagnostics, is the safest outcome. It is crucial to avoid situations where diseased patients are diagnosed as healthy.




Figure 7: The types of classes in the dataset

### 3.2. External specification

We used Jupyter Notebook, which serves as the primary interface for documenting the project, executing code cells, and visualizing results such as training/validation losses and accuracies using Matplotlib. We used tqdm library to show the progress of the training and validation loop.

## 4. Experiments

Initially, our convolutional neural network consisted of two convolutional layers and a single linear classification layer. However, the learning results from this model were unsatisfactory. Therefore, we decided to enhance the model by adding convolutional layers and restructuring the entire classification function. This involved incorporating extra layers and a dropout function.



At the beginning of creating our model, we noticed alarmingly high results in the early epochs of network training. This could indicate that the task complexity was too simple for the method we were using. After a thorough review of the dataset, we found that its folders were incorrectly organized, resulting in binary classification instead of the intended five-class classification. After correcting the data loading, the model showed the expected outcomes.

## 5. Summary

We presented our project on the multiclass classification of histopathological images of lung and colon tissues using convolutional neural networks. We accurately differentiated between five classes and employed a dataset of 25,000. Utilizing PyTorch, we implemented a robust preprocessing pipeline and model architecture, achieving a test accuracy of 97.46%. Detailed analysis, including a confusion matrix, demonstrated effective learning and reliable performance. Our findings underscore the potential of deep learning in medical image analysis, aiding accurate diagnostics.

## 6. References

a) PyTorch documentation:

[PyTorch documentation — PyTorch 2.3 documentation](#)

b) Articles:

[Convolutional neural networks in medical image understanding: a survey - PMC \(nih.gov\)](#)

[Convolutional Neural Networks, Explained | by Mayank Mishra | Towards Data Science](#)

c) YouTube:

 [Neural Networks Part 8: Image Classification with Convolutional Neural Networ...](#)

d) DataCamp:

<https://app.datacamp.com/learn/courses/intermediate-deep-learning-with-pytorch>

## 7. GitHub

Link to GitHub repository with all files of our project:

<https://github.com/jwiekiera/histopathological-classification/tree/main>