
Overview

- What we will cover and why
- How this course will operate
- What is Deep Learning really?
- How do I train a neural network in Pytorch?

- **Deep Learning** (DL) is a subset of Machine Learning where algorithms perform tasks by extracting *high-level features* from datasets that are usually very large and unstructured.
- Models are usually based on artificial neural networks (ANNs or NNs).
 - Deep here refers to ANNs with many layers.




Why Deep Learning?


- Explosion in amount of data available and in computing power
 - Neural networks are often complicated models with many parameters, necessitating a lot of data and a lot of computing power
- Increasingly important aspect of data science
 - Image Science
 - Natural Language Processing

Why Deep Learning?

- Explosion in amount of data available and in computing power
 - Neural networks are often complicated models with many parameters, necessitating a lot of data and a lot of computing power
- Increasingly important aspect of data science
 - Image Science
 - Natural Language Processing








What we will learn

- How to effectively train neural networks using PyTorch
 - Learning rates, batch norm, regularization,
 data augmentation, transfer learning, ...



What we will learn

- How to effectively train neural networks using PyTorch
 - Learning rates, batch norm, regularization, data augmentation, transfer learning, ...
- Image data
 - Common imaging tasks (classification, segmentation, ...)
 - Architectures for spatial data: CNNs
- Text data
 - Common NLP tasks (classification, comparison, ...)
 - Architectures for sequences/text (RNNs, Attention)

What we will learn

- How to effectively train neural networks using PyTorch
 - Learning rates, batch norm, regularization, data augmentation, transfer learning, ...
- Image data
 - Common imaging tasks (classification, segmentation, ...)
 - Architectures for spatial data: CNNs
- Text data
 - Common NLP tasks (classification, comparison, ...)
 - Architectures for sequences/text (RNNs, Attention)
- Very Briefly
 - GANs (style transfer, synthetic images/text)
 - Reinforcement Learning

- Too much in Deep Learning to go over everything!
- Goals
 - Provide a good foundation for whatever most interests you
 - Good mix of conceptual understanding and implementation in PyTorch

- Too much in Deep Learning to go over everything!
- Goals
 - Provide a good foundation for whatever most interests you
 - Good mix of conceptual understanding and implementation in PyTorch
- Changes every year (sometimes multiple times)
 - What techniques work the best
 - Why a certain technique works
 - What is really going on in Deep Learning
 - What is the hot stuff everyone wants to do

- Too much in Deep Learning to go over everything!
- Goals
 - Provide a good foundation for whatever most interests you
 - Good mix of conceptual understanding and implementation in PyTorch
- Changes every year (sometimes multiple times)
 - What techniques work the best
 - Why a certain technique works
 - What is really going on in Deep Learning
 - What is the hot stuff everyone wants to do
- Don't accept a research paper as the absolute truth

- Too much in Deep Learning to go over everything!
- Goals
 - Provide a good foundation for whatever most interests you
 - Good mix of conceptual understanding and implementation in PyTorch
- Changes every year (sometimes multiple times)
 - What techniques work the best
 - Why a certain technique works
 - What is really going on in Deep Learning
 - What is the hot stuff everyone wants to do
- Don't accept a research paper as the absolute truth
- Why "peak under the hood"? Why not just use Hugging Face?

- **Deep Learning** (DL) is a subset of Machine Learning where algorithms perform tasks by extracting *high-level features* from datasets that are usually very large and unstructured.



Why do you think this is a cat?

- **Deep Learning** (DL) is a subset of Machine Learning where algorithms perform tasks by extracting *high-level features* from datasets that are usually very large and unstructured.



High Level Features

- Two Ears
- Two Eyes
- Whiskers
- Looks fluffy

- **Deep Learning** (DL) is a subset of Machine Learning where algorithms perform tasks by extracting *high-level features* from datasets that are usually very large and unstructured.




High Level Features

- Two Ears
- Two Eyes
- Whiskers
- Looks fluffy

Collectively: a representation of the image

- **Deep Learning** (DL) is a subset of Machine Learning where algorithms perform tasks by extracting *high-level features* from datasets that are usually very large and unstructured.



- **Deep Learning** (DL) is a subset of Machine Learning where algorithms perform tasks by extracting *high-level features* from datasets that are usually very large and unstructured.



Low-level geometric Features

- Edge detection
- Noisiness
- Blob detection

0	0	0	 0
.5	.75	1	 .25
:	:	:	:
.333	0	1	 0

- **Deep Learning** (DL) is a subset of Machine Learning where algorithms perform tasks by extracting *high-level features* from datasets that are usually very large and unstructured.



DL high-level features

- learned from data
- Constructed from learned low-level features
- Usually NOT interpretable

```
\begin{bmatrix} 0 & 0 & 0 & \dots & 0 \\ .5 & .75 & 1 & \dots & .25 \\ \vdots & \vdots & \vdots & & \vdots \\ .333 & 0 & 1 & \dots & 0 \end{bmatrix}
```

- **Deep Learning** (DL) is a subset of Machine Learning where algorithms perform tasks by extracting *high-level features* from datasets that are usually very large and unstructured.




DL high-level features

- Usually NOT interpretable
- Only as good as your data...

Is this a snow leopard or regular leopard?

- **Deep Learning** (DL) is a subset of Machine Learning where algorithms perform tasks by extracting *high-level features* from datasets that are usually very large and unstructured.




DL high-level features

- Usually NOT interpretable
- Only as good as your data...

Is this a snow leopard or regular leopard?

- **Deep Learning** (DL) is a subset of Machine Learning where algorithms perform tasks by extracting *high-level features* from datasets that are usually very large and unstructured.




DL high-level features


- Usually NOT interpretable
- Only as good as your data...

Is this a snow leopard or regular leopard?


- One-Hot Embeddings -> Word Embeddings
- Unstructured data -> Represented by meaningful features
- Simple linear function




- One-Hot Embeddings -> Word Embeddings
- Unstructured data -> Represented by meaningful features
- Simple linear function




- Array -> Representation by "meaningful" features
- Simple linear functions stacked on top of each other




- Array -> Representation by "meaningful" features
- Simple linear functions stacked on top of each other




- Array -> Representation by "meaningful" features
- Simple linear functions stacked on top of each other



- Word embedding: simple linear mapping
- Neural Network: stack linear functions one after the other (layers)
- Any function can be approximated this way (rigorous!)



- Word embedding: simple linear mapping
- Neural Network: stack linear functions one after the other (layers)
- Any function can be approximated this way (rigorous!)
- Idea: create low level features in early layers to create high level features in later layers (none of these are necessarily interpretable!)



- Training a Neural Network: just a supervised learning problem!

- Training a Neural Network: just a supervised learning problem!
- Labelled data: $(x^{(1)}, y^{(1)}), \dots, (x^{(N)}, y^{(N)})$
- Model and parameters: $F(x; \theta)$
- Loss Function: $\mathcal{L}(F(x;\theta),y)$

- Training a Neural Network: just a supervised learning problem!
- Labelled data: $(x^{(1)},y^{(1)}),\ldots,(x^{(N)},y^{(N)})$
- Model and parameters: $F(x; \theta)$
- Loss Function: $\mathcal{L}(F(x;\theta),y)$

Find parameters θ that minimize

$$rac{1}{N} \sum_{i=1}^{N} \mathcal{L}\left(F(x^{(i)}; heta), y^{(i)}
ight)$$

- What's so special about using a Neural Network for $F(x; \theta)$?

- What's so special about using a Neural Network for $F(x; \theta)$?



Input data: 5D vector (Input layer)

- First step: linear transformation



- First step: linear transformation




$$b^{[1]} = egin{bmatrix} b_1^{[1]} \ b_2^{[1]} \ b_3^{[1]} \end{bmatrix}$$


$$W^{[1]}x+b^{[1]}$$

Input data: 5D vector (Input layer)


- Second step: nonlinearity (activation function)



- Second step: nonlinearity (activation function)



- Let's do it again!




$$W^{[2]} = egin{bmatrix} w_{11}^{[2]} & w_{12}^2 & w_{13}^{[2]} \ w_{21}^{[2]} & w_{22}^2 & w_{23}^{[2]} \ w_{31}^{[2]} & w_{32}^2 & w_{33}^{[2]} \end{bmatrix} \qquad b^{[2]} = egin{bmatrix} b^{[2]} & w_{32}^2 & w_{33}^{[2]} \end{bmatrix}$$


$$a^{[2]} = h(W^{[2]}a^{[1]} + b^{[2]})$$

$$m{a}^{[1]} = h(m{W}^{[1]} x + m{b}^{[1]})$$

- Final Output



- 3-layer "Feed-Forward" Neural Network



- All architectures are, at their core, linearity + nonlinearity successively
 - Easy to compute gradient this way (chain rule)
- In theory all you need is a FF NN
- In practice, intuition, experience, and understanding the problem are needed to make NNs work effectively
- We will not learn every architecture under the sun (boring)

- All architectures are, at their core, linearity + nonlinearity successively
 - Easy to compute gradient this way (chain rule)
- In theory all you need is a FF NN
- In practice, intuition, experience, and understanding the problem are needed to make NNs work effectively
- We will not learn every architecture under the sun (boring)

Let's do this in PyTorch!