

Lab 2

Launch the Employee Directory Application on Amazon EC2

AWS Technical Essentials • Lab 2 of 6

🏷️ Resource Names for This Lab

Replace <ID> with your assigned student ID (for example user7).

Resource	Name
EC2 instance (Name tag)	employee-directory-app-<ID>
Key pair	employee-dir-key-<ID>
Security group	employee-directory-app-sg-<ID>

> ⚠️ **Shared account:** the console lists every student's instances, key pairs and security groups together. Filter or sort by your ID so you only touch your own.

📋 Lab Overview

🎯 Objectives

- Launch an EC2 instance with Amazon Linux 2023
- Configure a security group for HTTP access
- Bootstrap Apache with a user data script
- Verify the web application in a browser
- Observe public IP behavior on stop/start

📝 Lab Details

- **Duration:** ~20 minutes
- **Region:** `us-east-1` (N. Virginia) — same for every lab
- **Instance type:** t2.micro (Free Tier)

> ⚠️ **Important:** Do NOT terminate this instance — it will be used in later labs.

🚀 Launch an Instance

1. Navigate to **EC2**, click **Launch instance**
2. Name: `employee-directory-app-<ID>`
3. AMI: **Amazon Linux 2023** (default)
4. Instance type: **t2.micro**
5. Key pair: **Create new key pair** named `employee-dir-key-<ID>`, download the .pem file

> 💡 **Tip:** Save the key pair file — you cannot download it again.

🔒 Configure Security Group

Under **Network settings**, click **Edit**:

1. Security group name: `employee-directory-app-sg-<ID>`
2. Description: *Allow HTTP access*

Type	Port	Source
SSH	22	My IP
HTTP	80	0.0.0.0/0

📜 Add User Data Script

In **Advanced details**, scroll to **User data** and paste:

```
#!/bin/bash -ex
yum update -y
yum install -y httpd
systemctl start httpd
systemctl enable httpd
echo '<!DOCTYPE html>
<html><head><title>Employee Directory</title>
<style>body{font-family:Arial,sans-serif;max-width:800px;margin:50px auto;padding:20px}
h1{color:#1a365d}table{border-collapse:collapse;width:100%}th,td{border:1px solid #ddd;padding:12px;text-align:left}
th{background:#2b6cb0;color:white}tr:nth-child(even){background:#f7fafc}</style></head>
<body><h1>Employee Directory</h1>
<p>Welcome to the Employee Directory Application</p>
<table><tr><th>Name</th><th>Department</th><th>Location</th></tr>
<tr><td>John Smith</td><td>Engineering</td><td>Seattle</td></tr>
<tr><td>Jane Doe</td><td>Marketing</td><td>New York</td></tr>
<tr><td>Bob Johnson</td><td>Sales</td><td>Austin</td></tr></table>
</body></html>' > /var/www/html/index.html
```

🚀 Launch and Wait

1. Click **Launch instance**
2. Click the **instance ID** link in the success message
3. Wait for **Instance state** to show **Running**
4. Wait for **Status checks** to show **2/2 checks passed**

> 🕒 **Note:** The user data script takes 1-2 minutes after "Running" to finish installing Apache.

🌐 Test — Browse to Public IP

1. Select your instance and copy the **Public IPv4 address**
2. Open a new browser tab: `http://<PUBLIC_IP>`

> ✅ **Expected:** The Employee Directory page displays with the employee table.

> **Not loading?** Verify: (1) using `http://` not `https://`, (2) security group allows port 80, (3) public IP is correct.

🔍 Explore Instance Details

With your instance selected, review these tabs:

Details Tab

- Instance ID
- Public / Private IP
- AMI ID, Instance type
- Availability Zone

Security Tab

- Security group rules
- Inbound / Outbound rules

🔄 Stop and Start — Note IP Change

1. Select your instance, click **Instance state → Stop instance**
2. Wait for state to show **Stopped**
3. Note the **Public IPv4 address** is now blank
4. Click **Instance state → Start instance**
5. Once running, note the **new Public IP**
6. Browse to the new IP — the app should load

> ✅ **Expected:** The app loads at the new IP. Apache starts automatically because we used `systemctl enable`.

⚠️ Keep This Instance Running

> **Do NOT terminate this instance.** It will be used as a reference in Lab 3 (VPC). You will launch a new instance in a custom VPC and compare it to this one.

Make sure your instance is in the **Running** state before proceeding.

🎉 Lab 2 Complete!

Employee Directory Running on EC2

🎯 Key Takeaways

🛠️ What You Did

- Launched an EC2 instance with Amazon Linux 2023
- Configured a security group
- Bootstrapped Apache via user data
- Observed public IP change on stop/start

📚 Key Concepts

- **User data** runs once at first boot
- **Security groups** are stateful firewalls
- **Public IPs** change on stop/start
- **systemctl enable** persists across reboots



Questions?

Ask your instructor before proceeding to the next module