

# Rubocop

v1.2.1

# Lesson Objectives

- After completing this lesson, you should be able to
  - Evaluate your Ruby coding style against community standards
  - Improve your code by iterating through style warnings
  - Prevent specific rules from generating warnings

# The Problem and the Success Criteria

- **The Problem:** We want to make sure our Apache cookbook follows best practice for Ruby code
- **Success Criteria:** We use Rubocop to check our cookbook before committing it

# Rubocop

- New Ruby developers often ask for guidance on writing idiomatic Ruby
- Rubocop gives the same kind of feedback for your Ruby style that Foodcritic gives for your Chef Code
- Evaluates your Chef code for Ruby best practices, not for Chef style
- Documentation located here

<https://github.com/bbatsov/rubocop>

# Navigate to Apache Cookbook

```
$ cd cookbooks/apache
```

# Exercise: Use Additional Rules

```
$ rubocop
```

```
recipes/default.rb:53:7: C: Use the new Ruby 1.9 hash syntax.
```

```
  :site_name => site_name,  
  ^^^^^^^^^^^
```

```
recipes/default.rb:54:7: C: Use the new Ruby 1.9 hash syntax.
```

```
  :port => site_data["port"]  
  ^^^^^^^
```

```
recipes/default.rb:54:26: C: Prefer single-quoted strings when you don't need  
string interpolation or special symbols.
```

```
  :port => site_data["port"]  
                ^^^^^
```

```
4 files inspected, 50 offences detected
```

# Fixing Rubocop Offenses

- We can mask offenses using the rubocop configuration file `.rubocop.yml`
- Rubocop can automatically generate a configuration called file named `.rubocop_todo.yml` that contains entries to mask all of your offenses
- We can use `.rubocop_todo.yml` to iterate through the offenses
- `.rubocop_todo.yml` settings are documented at <https://github.com/bbatsov/rubocop/blob/master/README.md>

# Exercise: Generate .rubocop\_todo.yml

```
$ rubocop --auto-gen-config
```

```
recipes/default.rb:54:7: C: Use the new Ruby 1.9 hash syntax.
```

```
  :port => site_data["port"]  
  ^^^^^^^
```

```
recipes/default.rb:54:26: C: Prefer single-quoted strings when you don't need  
string interpolation or special symbols.
```

```
  :port => site_data["port"]  
                ^^^^^^^
```

```
7 files inspected, 38 offences detected
```

```
Created .rubocop_todo.yml.
```

```
Run rubocop with --config .rubocop_todo.yml, or  
add inherit from: .rubocop_todo.yml in a .rubocop.yml file.
```



# Exercise: Review .rubocop\_todo.yml



## OPEN IN EDITOR: .rubocop\_todo.yml

```
This configuration was generated by `rubocop --auto-gen-config`  
# on 2014-10-09 10:42:37 -0400 using RuboCop version 0.18.1.  
# The point is for the user to remove these configuration records  
# one by one as the offences are removed from the code base.  
# Note that changes in the inspected code, or installation of new  
# versions of RuboCop, may require this file to be generated again.  
  
# Offence count: 4  
# Cop supports --auto-correct.  
# Configuration parameters: SupportedStyles.  
HashSyntax:  
  EnforcedStyle: hash_rockets  
  
# Offence count: 2  
LineLength:  
  Max: 127
```

# Exercise: Review .rubocop\_todo.yml



**OPEN IN EDITOR:** .rubocop\_todo.yml

```
# Offence count: 2
# Cop supports --auto-correct.
SpaceInsideBrackets:
  Enabled: false

# Offence count: 28
# Cop supports --auto-correct.
# Configuration parameters: EnforcedStyle, SupportedStyles.
StringLiterals:
  Enabled: false

# Offence count: 1
# Cop supports --auto-correct.
TrailingWhitespace:
  Enabled: false
```

# Exercise: Update .rubocop.yml



**OPEN IN EDITOR:** .rubocop.yml

```
inherit from: .rubocop_todo.yml
```

**SAVE FILE!**

# Exercise: Re-run rubocop

```
$ rubocop
```

```
Inspecting 7 files
```

```
.....
```

```
4 files inspected, no offences detected
```

# Work Through the Issues

- We now have a configuration file that masks all of our offenses
- We want to fix some of the offenses and mask the others
- Move the configuration rules for the offenses we want to continue masking from  
`.rubocop_todo.yml` to `.rubocop.yml`

# Exercise: Update Rubocop Configuration



**OPEN IN EDITOR:** cookbooks/apache/.rubocop.yml

```
#inherit from: .rubocop_todo.yml <<- Comment out this line
```

```
Encoding:
```

```
  Enabled: false
```

```
LineLength:
```

```
  Max: 200
```

```
HashSyntax:
```

```
  EnforcedStyle: hash_rockets
```

```
StringLiterals:
```

```
  Enabled: false
```

**SAVE FILE!**

# Exercise: Re-generate .rubocop\_todo.yml

```
$ rubocop --auto-gen-config
```

```
recipes/default.rb:15:11: C: Space inside square brackets detected.
  action [ :enable, :start ]
           ^
recipes/default.rb:15:27: C: Space inside square brackets detected.
  action [ :enable, :start ]
           ^
recipes/default.rb:19:87: C: Trailing whitespace detected.
execute "mv /etc/httpd/conf.d/welcome.conf /etc/httpd/conf.d/welcome.conf.disabled" do
                                                                 ^

7 files inspected, 4 offences detected
Created .rubocop_todo.yml.
Run rubocop with --config .rubocop_todo.yml, or
add inherit from: .rubocop_todo.yml in a .rubocop.yml file.
```

# Fixing Rubocop Offenses

We decide we want to fix these offenses

1. Add `inherit from: to .rubocop.yml`
2. Remove an entry from `.rubocop_todo.yml`
3. Fix offenses
4. Verify fix by running Rubocop
5. Lather-Rinse-Repeat (steps 2-4)
6. Remove `.rubocop_todo.yml`



# Exercise: Update .rubocop.yml



**OPEN IN EDITOR:** .rubocop.yml

```
inherit from: .rubocop_todo.yml <<- Un-comment this line
```

```
Encoding:
```

```
  Enabled: false
```

```
LineLength:
```

```
  Max: 200
```

```
HashSyntax:
```

```
  EnforcedStyle: hash_rockets
```

```
StringLiterals:
```

```
  Enabled: false
```

**SAVE FILE!**

# Exercise: Delete Entry From .rubocop\_todo.yml



**OPEN IN EDITOR:** .rubocop\_todo.yml

```
# Offence count: 1
# Cop supports --auto-correct.
Style/SpaceAfterComma:
  Enabled: false
```

```
# Offence count: 2
# Cop supports --auto-correct.
Style/SpaceInsideBrackets:
  Enabled: false
```

```
# Offence count: 1
# Cop supports --auto-correct.
Style/TrailingWhitespace:
  Enabled: false
```

**SAVE FILE!**

# Exercise: Re-run rubocop

```
$ rubocop
```

```
Offences:
```

```
recipes/default.rb:19:87: C: Trailing whitespace detected.  
execute "mv /etc/httpd/conf.d/welcome.conf /etc/httpd/conf.d/welcome.conf.disabled" do  
                                                                    ^
```

```
4 files inspected, 1 offence detected
```

# Exercise: Fix Default Recipe



**OPEN IN EDITOR:** `recipes/default.rb`

```
package "httpd" do
  action :install
end
```

```
service "httpd" do
  action [ :enable, :start ]
end
```

```
# Disable the default virtual host
execute "mv /etc/httpd/conf.d/welcome.conf /etc/httpd/conf.d/
welcome.conf.disabled" do
```

Remove trailing whitespace  
from line 19

**SAVE FILE!**

# Exercise: Re-run rubocop

```
$ rubocop
```

```
Inspecting 7 files  
.....  
7 files inspected, 0 offenses detected
```



# Review Questions

- What guidelines does Rubocop help you enforce?
- Why might you want to exclude certain cops?
- What is the name of Rubocop configuration file?