





#### 100 X






















- Can't go below step 0
- 0.1 % chance of falling down the stairs
- Bet: you'll reach step 60

### How to solve?

- Analytical
- Simulate the process
  - Hacker statistics!

## Random generators

```
import numpy as np
np.random.rand() # Pseudo-random numbers
                     # Mathematical formula
0.9535543896720104
np.random.seed(123)
                     # Starting from a seed
np.random.rand()
0.6964691855978616
np.random.rand()
0.28613933495037946
```



### Random generators

```
np.random.seed(123)
np.random.rand()

0.696469185597861  # Same seed: same random numbers!

np.random.rand()  # Ensures "reproducibility"

0.28613933495037946
```



### Coin toss

game.py

```
import numpy as np
np.random.seed(123)
coin = np.random.randint(0,2) # Randomly generate 0 or 1
print(coin)
```

0



### Coin toss

game.py

```
import numpy as np
np.random.seed(123)
coin = np.random.randint(0,2) # Randomly generate 0 or 1
print(coin)
if coin == 0:
    print("heads")
else:
    print("tails")
```


0 heads

# Let's practice!

INTERMEDIATE PYTHON



## Random Step



### Random Walk

100 X



-1



+1



+1 +2 +3 +4 +5 +6

Known in Science

- Path of molecules
- Gambler's financial status

### **Heads or Tails**

headtails.py

```
import numpy as np
np.random.seed(123)
outcomes = []
for x in range(10) :
    coin = np.random.randint(0, 2)
    if coin == 0 :
        outcomes.append("heads")
    else :
        outcomes.append("tails")
print(outcomes)
```

```
['heads', 'tails', 'heads', 'heads', 'heads', 'heads', 'heads', 'heads', 'tails', 'tails', 'heads']
```

### Heads or Tails: Random Walk

headtailsrw.py

```
import numpy as np
np.random.seed(123)
tails = [0]
for x in range(10) :
    coin = np.random.randint(0, 2)
    tails.append(tails[x] + coin)
print(tails)
```

```
[0, 0, 1, 1, 1, 1, 1, 1, 2, 3, 3]
```

## Step to Walk

outcomes

```
['heads', 'tails', 'heads', 'heads',
'heads', 'heads', 'tails', 'heads']
```

tails


```
[0, 0, 1, 1, 1, 1, 1, 1, 2, 3, 3]
```

# Let's practice!

INTERMEDIATE PYTHON



### Distribution



#### Random Walk

headtailsrw.py

```
import numpy as np
np.random.seed(123)
tails = [0]
for x in range(10) :
    coin = np.random.randint(0, 2)
    tails.append(tails[x] + coin)
```

#### **100 runs**

distribution.py

```
import numpy as np
np.random.seed(123)
final_tails = []
for x in range(100) :
    tails = [0]
    for x in range(10) :
        coin = np.random.randint(0, 2)
        tails.append(tails[x] + coin)
    final_tails.append(tails[-1])
print(final_tails)
```


```
[3, 6, 4, 5, 4, 5, 3, 5, 4, 6, 6, 8, 6, 4, 7, 5, 7, 4, 3, 3, ..., 4]
```

## Histogram, 100 runs

distribution.py

```
import numpy as np
import matplotlib.pyplot as plt
np.random.seed(123)
final_tails = []
for x in range(100):
    tails = [0]
    for x in range(10) :
        coin = np.random.randint(0, 2)
        tails.append(tails[x] + coin)
    final_tails.append(tails[-1])
plt.hist(final_tails, bins = 10)
plot.show()
```

## Histogram, 100 runs






## Histogram, 1,000 runs

distribution.py

```
import numpy as np
import matplotlib.pyplot as plt
np.random.seed(123)
final_tails = []
for x in range(1000) : # <--</pre>
    tails = [0]
    for x in range(10) :
        coin = np.random.randint(0, 2)
        tails.append(tails[x] + coin)
    final_tails.append(tails[-1])
plt.hist(final_tails, bins = 10)
plot.show()
```



## Histogram, 1,000 runs






## Histogram, 10,000 runs

distribution.py

```
import numpy as np
import matplotlib.pyplot as plt
np.random.seed(123)
final_tails = []
for x in range(10000) : # <--</pre>
    tails = [0]
    for x in range(10) :
        coin = np.random.randint(0, 2)
        tails.append(tails[x] + coin)
    final_tails.append(tails[-1])
plt.hist(final_tails, bins = 10)
plot.show()
```

## Histogram, 10,000 runs





# Let's practice!

INTERMEDIATE PYTHON

