
Betta Lights BettaTwo

Betta Lights

Results based on test procedures detailed in IEC 62257-9-5, ed. 2.0

Verify Online: www.lightingglobal.org/specs/bl-bettatwo

Valid Until: April, 2014







Meets Lighting Global Minimum Quality Standards



Mobile Charging

2 Light Points

Warranty Information

The units are guaranteed for 15 months from the FOB date. The warranty is nullified if the product is tampered with, misused or installed incorrectly.

Performance Details		
	Brightness Setting***	
Performance Measure	2 lamps	
Full battery run time* (hours)	10	
Run time per day of solar charging* (hours)	10	
Total light output (lumens)	180	
Total area with illumination > 25 lux** (m²)	0.6	
Total lighting service (lumen-hours / solar-day)	1800	

^{*} Run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

^{***} Additional brightness settings (not tested):

Lighting Details	
Lamp type	LED
Description of light points	Identical light points; 22 LEDs per light point
Colour characteristics	CRI 70
	CCT "Cool" (5000-7000 K)
Distribution type	Wide
Lumen maintenance	93% of the original output remains after 2,000
	hours run time

^{**} Total area with illumination > 25 lux is determined by the maximum area with adequate illumination at a 0.75 m distance and at the distance from which the product would normally provide task lighting service.

Special Features		
Mobile charging	Adapters included to charge mobile phone from	
	battery	
	- Callery	
Durability		
Overall durability and workmanship	Pass	
Durability tests passed	Drop test, switch and connector cycling, physical	
	ingress protection test, and no water ingress	
	protection	
Solar Details		
PV module type	Monocrystalline silicon	
PV maximum power point	5.6 watts	
D 11 D 1 11		
Battery Details	le a la la su	
Battery replaceability	Easily replaceable with common tools Sealed lead-acid	
Battery chemistry	Sealed lead-acid	
Battery package type Battery capacity	4000 mAh	
Battery nominal voltage	6 V	
Appropriate battery protection circuit	Pass	
Appropriate battery protection circuit	ji d55	
Marks and Certifications		
Factory certification	ISO 9001, 14001	
Product Details		
Manufacturer name	Betta Lights	
Product name	Betta Lights BettaTwo	
Product model / ID number	BettaTwo	
Contact information	marius.botes@bettalights.com	
Website	www.bettalights.com	
SSS Information		
Specs sheet expiration date	April, 2014	
Minimum Quality Standards Framework Version	2011	
Revision	2013.09	
TIOVISION	12010.00	