Pico Solar Home System 7000

fosera Group

Results based on test procedures detailed in IEC 62257-9-5, ed. 2.0


Verify www.lightingglobal.org/products/fs-pshs7000

Valid Until: February 28, 2017













Meets Lighting Global
Quality Standards



Mobile Charging

1 Light Point

Warranty Information

A 3-year warranty covering defects in material or workmanship in the product, and a 2-year warranty for the battery.

| Performance Details | |
|---|--------------------|
| | Brightness Setting |
| Performance Measure | On |
| Full battery run time* (hours) | 19 |
| Run time per day of solar charging* (hours) | 12 |
| Total light output (lumens) | 170 |
| Total area with illumination > 50 lux** (m ²) | 0.9 |
| Total lighting service (lumen-hours / solar-day) | 2000 |

^{*} Run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

^{**} Total area with illumination > 50 lux is determined by the maximum area with adequate illumination at a 0.75 m distance and at the distance from which the product would normally provide task lighting service.

| Lighting Details | |
|-----------------------------|---|
| Lamp type | LED |
| Description of light points | 8 LEDs per light point |
| Colour characteristics | CRI 84 |
| | CCT "Cool" (5000K) |
| Distribution type | Wide |
| Lumen maintenance | 100% of the original output remains after 2,000 |
| | hours run time |

| Special Features | | |
|--|---|--|
| Mobile charging | Includes USB port for mobile charging. | |
| Indicators | Four LEDs to indicate battery state of charge and | |
| | one LED to indicate solar charging. | |
| Optional night light function | Can be activated. | |
| Optional radio | FM/MW/SW band radio with AUX-IN input | |
| | | |
| Durability | | |
| Overall durability and workmanship | Pass | |
| Durability tests passed | Switch and connector cycling, strain relief test, | |
| | physical ingress protection test, and no water | |
| | ingress protection | |
| | · | |
| Solar Details | | |
| PV module type | Polycrystalline silicon | |
| PV maximum power point | 5 watts | |
| | | |
| Battery Details | | |
| Battery replaceability | Easily replaceable with common tools | |
| Battery chemistry | Lithium iron phosphate | |
| Battery package type | custom | |
| Battery capacity | 7900 mAh | |
| Battery nominal voltage | 3.2 V | |
| Appropriate battery protection circuit | Pass | |
| Marks and Certifications | | |
| Other certification | CE | |
| Other certification | | |
| Product Details | | |
| Manufacturer name | fosera Group | |
| Product name | Pico Solar Home System 7000 | |
| Product model / ID number | PSHS 7000 | |
| Contact information | info@fosera.com | |
| Website | www.fosera.com | |
| | · | |
| SSS Information | | |
| Specs sheet expiration date | February 28, 2017 | |
| Quality Standards Framework Version | 2015 | |
| Revision | 2015.04 | |
| | | |