
## **Marathoner Beacon MB2-200**

**Marathoner CLP** 

Results based on test procedures detailed in IEC 62257-9-5, ed. 2.0

Verify Online: www.lightingglobal.org/product s/mar-mb2200 Valid Until: December, 2015







Meets Lighting Global Minimum Quality Standards



**Mobile Charging** 



**Light Points** 

## **Warranty Information**

A 2-year warranty against material or manufacturing defects.

Performance Details  Brightness Setting***		
Performance Measure	Main Super	Torch On
Full battery run time* (hours)	5.3	5
Run time per day of solar charging* (hours)	4.4	3.4
Total light output (lumens)	210	32
Total area with illumination > 25 lux** (m²)	1	0.2
Total lighting service (lumen-hours / solar-day)	920	110

<sup>\*</sup> Run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

<sup>\*\*\*</sup> Additional brightness settings (not tested): Main lamp Normal, Main lamp Bed Light

Lighting Details		
Lamp type	LED	
Description of light points	One main lamp and one torch	
Colour characteristics	CRI 72 CCT "Near Daylight" (3000-5000 K)	
Distribution type	Wide	
Lumen maintenance	93% (Main) and 96% (Torch) of the original output remains after 2,000 hours run time	

<sup>\*\*</sup> Total area with illumination > 25 lux is determined by the maximum area with adequate illumination at a 0.75 m distance and at the distance from which the product would normally provide task lighting service.

Special Features		
Mobile charging	Adapters included to charge mobile phone from Main	
5 6	lamp battery	
Product box	Box acts as a stand to use Main lamp and Secondary	
	lamp as desk lights	
LEDs	UV-free LEDs	
Batteries	High-temperature batteries used	
Remote	Torch acts as wireless remote to turn Main and	
	Secondary lamp on/off	
Durability		
Overall durability and workmanship	Pass	
Durability tests passed	Drop test, switch and connector cycling, strain relief	
Durability tests passed	test, physical ingress protection test, and protection	
	from occassional rain	
	mom occassional rain	
Solar Details		
PV module type	Monocrystalline silicon	
PV maximum power point	2.6 watts	
Battery Details	<b>1</b> =	
Battery replaceability	Easily replaceable with common tools	
Battery chemistry	Lithium iron phosphate	
Appropriate battery protection circuit	Pass	
Replacement batteries are available from the produ	ct manufacturer	
Product Details		
Manufacturer name	Marathoner CLP	
Product name	Marathoner Beacon MB2-200	
Product model / ID number	MB2-200	
Contact information	sales@marathonerclp.com (Africa)	
Website	www.marathonerclp.com (Africa)	
SSS Information		
Specs sheet expiration date	December, 2015	
Minimum Quality Standards Framework Version	2012	
Revision	2014.01	
	•	