Trony Sundial TSL01

Verify specs at: www.lightingglobal.org/specs/tr-tsl01

Overall Performance

"High" setting: 140 lumens for 3.4 hours after

one day of solar charging

"Medium-high" setting: 85 lumens for 7.8 hours

after one day of solar charging



General Inform	nation		
Manufacturer		Trony Solar Holdings Co., Ltd.	
Product Name		Sundial	
Model Number		TSL01	
Contact		customersupport@trony.com	
Website		www.trony.com	
Warranty		2 Years	
Run Time			
Autonomous Run Time		3.8 hours on "high" setting	
(full battery)		9.2 hours on "medium-high" setting	
Lighting hours per solar day		3.4 hours on "high" setting	
(PV only)		7.8 hours on "medium-high" setting	
Lighting Syste	em	150	
Lamp type		LED "III III III	
Light output		140 lumens on "high" setting	
		85 lumens on "medium-high" setting 120 lumens on "high" setting	
Light output at 2000 hours		77 lumens on "medium-high" setting	
			ht Cool
Light Distribution	Wide K	Color Appearance Warm Dayligh	(more blue)
		4	
		Color Rendering (50%)	(100%)
		CRI: 66	
Charging Syst	em		
Charge type(s)		PV	
Storage Syste	m		
Storage Type		Rechargeable lithium iron phosphate ba	ttery
Nominal Battery Voltage		6.4 volts DC	
Battery Capacity		1,400 milliamp hours	
Battery Protection		Active HVD and LVD	
Easily Replacea		No	
	ormation & Sp	ecial Features	
Lamp Housing		Polycarbonate	
Mobile Charging (Standard)		Auxiliary power (310 mA at 4.25 VDC, mini-USB connector) with 4 adapters available for various phones	
Factory Certifications		ISO9000, ISO14000, IEC, VDE, TUV	
Date of Sampl		nt for Testing	April, 2012
			Revision 2012.10