

ovBeacon MB2-290

ovSolar (Omnivoltaic Power Company Limited)

Verify Online: www.lightingglobal.org/products/mar-mb2290


Results based on test procedures detailed in
IEC 62257-9-5, ed. 2.0

Valid Until: June 30, 2018

Lumens



Solar Run Time



Meets Lighting Global Minimum
Quality Standards



Mobile Charging

3

Light Points



Warranty Information

A 2-year warranty against material or manufacturing defects.

Performance Details

Performance Measure	Brightness Setting***		
	Main Super	Sec. 1 Super	Torch On
Full battery run time* (hours)	5.3	6	5
Run time per day of solar charging* (hours)	4.2	5.7	3.6
Total light output (lumens)	210	92	32
Total area with illumination > 50 lux** (m ²)	1.1	--	0.2
Total lighting service (lumen-hours / solar-day)	880	520	120

* Run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

** Total area with illumination > 50 lux is determined by the maximum area with adequate illumination at a 0.75 m distance and at the distance from which the product would normally provide task lighting service.

*** Additional brightness settings (not tested): Main lamp Normal, Main lamp Bed Light, Secondary lamp Normal, Secondary lamp Bed Light

Lighting Details

Lamp type	LED
Description of light points	One main lamp, one secondary lamp, and one torch
Colour characteristics	CRI 72 CCT "Near Daylight" (3000-5000 K)
Distribution type	Wide
Lumen maintenance	93% (Main), 93% (Secondary), and 96% (Torch) of the original output remains after 2,000 hours run time

Special Features	
Mobile charging	Adapters included to charge mobile phone from Main lamp battery
Product box	Box acts as a stand to use Main lamp and Secondary lamp as desk lights
LEDs	UV-free LEDs
Batteries	High-temperature batteries used
Remote	Torch acts as wireless remote to turn Main and Secondary lamp on/off

Durability	
Overall durability and workmanship	Pass
Durability tests passed	Drop test, switch and connector cycling, strain relief test, physical ingress protection test, and protection from occasional rain

Solar Details	
PV module type	Monocrystalline silicon
PV maximum power point	3.9 watts

Battery Details	
Battery replaceability	Easily replaceable with common tools
Battery chemistry	Lithium iron phosphate
Battery Package Type	Main Lamp: 26650 Secondary Lamp: 18650 Torch: 14500
Battery Capacity	Main Lamp: 3200 mAh Secondary Lamp: 1500 mAh Torch: 540 mAh
Battery nominal voltage	3.2 V
Appropriate battery protection circuit	Pass
Replacement batteries are available from the product manufacturer	

Product Details	
Manufacturer name	ovSolar (Omnivoltaic Power Company Limited)
Product name	ovBeacon MB2-290
Product model / ID number	MB2-290
Contact information	info@ovsolar.com
Website	www.ovsolar.com

SSS Information	
Specs sheet expiration date	June 30, 2018
Quality Standards Framework Version	2016
Revision	2016.06