## Arundhati


## **Global Telelinks**

Results based on test procedures detailed in IEC 62257-9-5, ed. 2.0

Verify Online: www.lightingglobal.org/products/gt-

arundhati

Valid Until: December, 2013







**Meets Lighting Global Minimum Quality Standards** 



**Mobile Charging** 

1 Light Point

## **Warranty Information**

A 2-year service warranty for the LED lantern body, PCB, and battery; a 10-year warranty for the solar panel.

Performance Details		
	Brightness Setting***	
Performance Measure	High	Low
Full battery run time* (hours)	6.7	36
Run time per day of solar charging* (hours)	6.3	34
Total light output (lumens)	80	19
Total area with illumination > 25 lux** (m²)	0.85	0.09
Total lighting service (lumen-hours / solar-day)	500	650

<sup>\*</sup> Run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

<sup>\*\*\*</sup> Additional brightness settings (not tested): Medium

Lighting Details	
Lamp type	LED
Description of light points	Single LED
Colour characteristics	CRI 75
	CCT "Cool" (5000-7000 K)
Distribution type	Wide
Lumen maintenance	98% of the original output remains after 2,000
	hours run time

<sup>\*\*</sup> Total area with illumination > 25 lux is determined by the maximum area with adequate illumination at a 0.75 m distance and at the distance from which the product would normally provide task lighting service.

Special Features		
Charging options	Plug for grid-charging included	
Durability		
Overall durability and workmanship	Pass	
Durability tests passed	Drop test, switch and connector cycling, physical	
	ingress protection test, and protection from	
	occassional rain	
Solar Details		
PV module type	Polycrystalline silicon	
PV maximum power point	4.7 watts	
Bettem: Detaile		
Battery Details	Casily ranks as also with common tools	
Battery replaceability	Easily replaceable with common tools	
Battery chemistry	Lithium-ion	
Battery package type	1x 1865 package	
Battery capacity	2000 mAh	
Battery nominal voltage	3.7 V	
Appropriate battery protection circuit	Pass	
Product Details		
Manufacturer name	Global Telelinks	
Product name	Arundhati	
Product model / ID number	ASL 1W	
Contact information	prakruthipower@gmail.com, cvraosd@gmail.com	
Website	www.prakruthipower.com	
SSS Information		
Specs sheet expiration date	December, 2013	
Minimum Quality Standards Framework Version	2011	
Revision	2014.01	