
Betta Lights BettaTwo

Betta Lights

Results based on test procedures detailed in IEC 62257-9-5, ed. 2.0

Verify Online: www.lightingglobal.org/products/blbettatwo Valid Until: April, 2014







Meets Lighting Global Minimum Quality Standards



Mobile Charging

2 Light Points

Warranty Information

The units are guaranteed for 15 months from the FOB date. The warranty is nullified if the product is tampered with, misused or installed incorrectly.

Performance Details	
	Brightness Setting***
Performance Measure	2 lamps
Full battery run time* (hours)	10
Run time per day of solar charging* (hours)	10
Total light output (lumens)	180
Total area with illumination > 25 lux** (m²)	0.6
Total lighting service (lumen-hours / solar-day)	1800

^{*} Run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

^{***} Additional brightness settings (not tested):

Lighting Details	
Lamp type	LED
Description of light points	Identical light points; 22 LEDs per light point
Colour characteristics	CRI 70
	CCT "Cool" (5000-7000 K)
Distribution type	Wide
Lumen maintenance	93% of the original output remains after 2,000
	hours run time

^{**} Total area with illumination > 25 lux is determined by the maximum area with adequate illumination at a 0.75 m distance and at the distance from which the product would normally provide task lighting service.

Special Features	
Mobile charging	Adapters included to charge mobile phone from
Wobile charging	battery
	Dattery
Durability	
Overall durability and workmanship	Pass
Durability tests passed	Drop test, switch and connector cycling, physical
, ,	ingress protection test, and no water ingress
	protection
	Ib. coorse.
Solar Details	
PV module type	Monocrystalline silicon
PV maximum power point	5.6 watts
Battery Details	
Battery replaceability	Easily replaceable with common tools
Battery chemistry	Sealed lead-acid
Battery package type	
Battery capacity	4000 mAh
Battery nominal voltage	6 V
Appropriate battery protection circuit	Pass
Marks and Certifications	liaa aaa i i iaa i
Factory certification	ISO 9001, 14001
Product Details	
Manufacturer name	Betta Lights
Product name	Betta Lights BettaTwo
Product model / ID number	BettaTwo
Contact information	marius.botes@bettalights.com
Website	www.bettalights.com
	1
SSS Information	
Specs sheet expiration date	April, 2014
Minimum Quality Standards Framework Version	2011
Revision	2014.01