
d.light Design

Results based on test procedures detailed in IEC 62257-9-5, ed. 2.0

Verify Online: www.lightingglobal.org/products/dl-s2

Valid Until: August 31, 2015





Meets Lighting Global Minimum Quality Standards

1 Light Point



Warranty Information

A 2-year product replacement warranty for verified manufacturing defects.

Performance Details		
	Brightness Setting***	
Performance Measure	On	
Full battery run time* (hours)	6.5	
Run time per day of solar charging* (hours)	4.7	
Total light output (lumens)	25	
Total area with illumination > 25 lux** (m ²)	0.12	
Total lighting service (lumen-hours / solar-day)	120	

^{*} Run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

^{***} Additional brightness settings (not tested):

Lighting Details	
Lamp type	LED
Description of light points	Single LED
Colour characteristics	CRI 85
	CCT "Cool" (5000-7000 K)
Distribution type	Wide
Lumen maintenance	97% of the original output remains after 2,000
	hours run time

^{**} Total area with illumination > 25 lux is determined by the maximum area with adequate illumination at a 0.75 m distance and at the distance from which the product would normally provide task lighting service.

Durability	
Overall durability and workmanship	Pass
Durability tests passed	Drop test, switch cycling, physical ingress
·	protection test, and protection from frequent rain
Solar Details	
PV module type	Monocrystalline silicon
Battery Details	
Battery replaceability	Not easily replaceable with common tools
Battery chemistry	Lithium-based chemistry
Appropriate battery protection circuit	Pass
Product Details	
Manufacturer name	d.light Design
Product name	S2
Product model / ID number	S2
Contact information	www.dlightdesign.com/contact-us/
Website	www.dlightdesign.com
SSS Information	
Specs sheet expiration date	August 31, 2015
Minimum Quality Standards Framework Version	2012
Revision	2015.04