
Foce/Austa Solar Lamp

Deutrex 818

Results based on test procedures detailed in IEC 62257-9-5, ed. 2.0

Verify Online: www.lightingglobal.org/specs/

foce-austa-sl Valid Until: December, 2013





Meets Lighting Global Minimum Quality Standards

1 Light Point



Warranty Information

The unit is warranted against faulty materials and workmanship for a period of 12 months from the date of purchase.

| Performance Details | |
|---|-----------------------|
| | Brightness Setting*** |
| Performance Measure | High |
| Full battery run time* (hours) | 5.9 |
| Run time per day of solar charging* (hours) | 5.1 |
| Total light output (lumens) | 26 |
| Total area with illumination > 25 lux** (m ²) | 0.01 |
| Total lighting service (lumen-hours / solar-day) | 130 |

^{*} Run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

^{***} Additional brightness settings (not tested): Medium. Low

| Lighting Details | | |
|-----------------------------|---|--|
| Lamp type | LED | |
| Description of light points | Single column containing 16 LEDs | |
| Colour characteristics | CRI 78 | |
| | CCT "Cool" (5000-7000 K) | |
| Distribution type | Omnidirectional | |
| Lumen maintenance | 101% of the original output remains after 2,000 | |
| | hours run time | |
| Special Features | | |
| Charging option | Grid-charger included | |

^{**} Total area with illumination > 25 lux is determined by the maximum area with adequate illumination at a 0.75 m distance and at the distance from which the product would normally provide task lighting service.

| Durability | | |
|---|---|--|
| Overall durability and workmanship | Pass | |
| Durability tests passed | Drop test, switch and connector cycling, physical | |
| | ingress protection test, and protection from | |
| | occassional rain | |
| | | |
| Solar Details | | |
| PV module type | Polycrystalline silicon | |
| PV maximum power point | 2.5 watts | |
| | | |
| Battery Details | | |
| Battery replaceability | Easily replaceable with common tools | |
| Battery chemistry | Nickel-metal hydride | |
| Appropriate battery protection circuit | Pass | |
| Replacement batteries are available from the product manufacturer | | |
| | | |
| Product Details | | |
| Manufacturer name | Deutrex 818 | |
| Product name | Foce/Austa Solar Lamp | |
| Product model / ID number | DT-1588 (Foce) / A1008 (Austa) | |
| Contact information | deutrex818@gmail.com | |
| Website | www.deutrex818.com | |
| | | |
| SSS Information | | |
| Specs sheet expiration date | December, 2013 | |
| Minimum Quality Standards Framework Version | 2011 | |
| Revision | 2013.09 | |