## Pico Solar Home System 7000

fosera Group

Results based on test procedures detailed in IEC 62257-9-5, ed. 2.0


Verify www.lightingglobal.org/products/fs-pshs7000

Valid Until: February 2017

## Lumens











Meets Lighting Global Quality Standards



**Mobile Charging** 

1 Light Point

## **Warranty Information**

A 3-year warranty covering defects in material or workmanship in the product, and a 2-year warranty for the battery.

Performance Details	
	Brightness Setting
Performance Measure	On
Full battery run time* (hours)	19
Run time per day of solar charging* (hours)	9.5
Total light output (lumens)	170
Total area with illumination > 50 lux** (m <sup>2</sup> )	0.9
Total lighting service (lumen-hours / solar-day)	1600

<sup>\*</sup> Run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

<sup>\*\*</sup> Total area with illumination > 50 lux is determined by the maximum area with adequate illumination at a 0.75 m distance and at the distance from which the product would normally provide task lighting service.

Lighting Details	
Lamp type	LED
Description of light points	8 LEDs per light point
Colour characteristics	CRI 84
	CCT "Cool" (5000-7000 K)
Distribution type	Wide
Lumen maintenance	100% of the original output remains after 2,000
	hours run time

Chariel Factures		
Special Features Makilo charging	Included LISP part for mobile oberging	
Mobile charging	Includes USB port for mobile charging.	
Indicators	Four LEDs to indicate battery state of charge and	
Ontion of winds light from stion	one LED to indicate solar charging.	
Optional night light function	Can be activated.	
Durability		
Overall durability and workmanship	Pass	
Durability tests passed	Switch and connector cycling, strain relief test,	
Darabinity toolo paoood	physical ingress protection test, and no water	
	ingress protection	
	migross protestion	
Solar Details		
PV module type	Monocrystalline silicon	
PV maximum power point	4.8 watts	
<u> </u>		
Battery Details		
Battery replaceability	Easily replaceable with common tools	
Battery chemistry	Lithium iron phosphate	
Battery package type	custom	
Battery capacity	7900 mAh	
Battery nominal voltage	3.2 V	
Appropriate battery protection circuit	Pass	
Marks and Certifications		
Other certification	CE	
Other Certification	ICE .	
Product Details		
Manufacturer name	fosera Group	
Product name	Pico Solar Home System 7000	
Product model / ID number	PSHS 7000	
Contact information	info@fosera.com	
Website	www.fosera.com	
SSS Information		
Specs sheet expiration date	February 2017	
Quality Standards Framework Version	2015	
Revision	2015.02	