Connect 600


Barefoot Power

Results based on test procedures detailed in IEC 62257-9-5, ed. 2.0

Verify Online: www.lightingglobal.org/products/bf-

connect600

Valid Until: March 31, 2018







Meets Lighting Global Minimum Quality Standards



Mobile Charging

4

Light Points

Warranty Information

The product warranty covers all included components for 2 years (24 months) from date of purchase by first user.

Performance Details	
	Brightness Setting***
Performance Measure	4 lamps
Full battery run time* (hours)	11
Run time per day of solar charging* (hours)	6.3
Total light output (lumens)	300
Total area with illumination > 50 lux** (m ²)	0.24
Total lighting service (lumen-hours / solar-day)	1900

^{*} Run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

^{***} Additional brightness settings (not tested): 3 lamps, 2 lamps, 1 lamp

Lighting Details	
Lamp type	LED
Description of light points	Identical light points; 12 LEDs per light point
Colour characteristics	CRI 73
	CCT "Cool" (5000-7000 K)
Distribution type	Wide
Lumen maintenance	103% of the original output remains after 2,000
	hours run time

^{**} Total area with illumination > 50 lux is determined by the maximum area with adequate illumination at a 0.75 m distance and at the distance from which the product would normally provide task lighting service.

Special Features		
Mobile charging	Adapters included to charge mobile phone from battery	
Outputs	4x 12 V lighting outputs, 2 USB outputs, 1x 12 V output	
Included accessories	USB radio cable adaptor (for 6 V radios), 12 V cigarette plug adaptor, mounting screws and clips	
Enclosure	Made from UV-resistant plastic	
Durability		
Durability Overall durability and workmanship	Pass	
Durability tests passed	Switch and connector cycling, strain relief test, physical ingress protection test, and no water ingress protection	
Solar Details		
PV module type	Polycrystalline silicon	
PV maximum power point	6.6 watts	
Battery Details		
Battery replaceability	Easily replaceable with common tools	
Battery chemistry	Sealed lead-acid	
Appropriate battery protection circuit	Pass	
Replacement batteries are available from the product manufacturer		
Product Details		
Manufacturer name	Barefoot Power	
Product name	Connect 600	
Product model / ID number	020-30-0001-1	
Contact information	info@barefootpower.com	
Website	www.barefootpower.com	
SSS Information		
Specs sheet expiration date	March 31, 2018	
Minimum Quality Standards Framework Version	2016	
Revision	2016.03	