The Plasma Blackout Problem Equation Cheat Sheet

Jack Nelson

October 2016

Intro to the Blackout Problem

Plasma Electron Frequency

$$\omega_e = \sqrt{\frac{n_e e^2}{\epsilon_0 m_e}} \; rad/sec \tag{1}$$

This can be approximated as

$$f_e \approx 9\sqrt{n_e} \; Hz \tag{2}$$

Lorentz Windows

These are the equations used by Kim et. al. in the computer modeling of a plasma sheath in the vicinity of an $\mathbf{E} \times \mathbf{B}$ field [1].

Ion Transport Equations

$$\nabla \cdot (\mathbf{V_i} n) = 0 \tag{3}$$

$$m_i n (\mathbf{V_i} \cdot \nabla \mathbf{V_i}) = en(\mathbf{E} + \mathbf{V_i} \times \mathbf{B}) - m_i n \nu_c \mathbf{V_i} \tag{4}$$

Current Density of Plasma Sheath The current density of the plasma is derived from the generalized Ohm's Law, and includes the Hall effect:

$$\mathbf{j} = \sigma \left(\mathbf{E} + \frac{kT_e}{e} \nabla \ln n - \frac{\mathbf{j} \times \mathbf{B}}{en} + (\mathbf{V_i} \times \mathbf{B}) \right) \tag{5}$$

The x and z components of the current density used in the 2D simulations simplify to:

$$j_x = \sigma \left(E_x + \frac{kT_e}{e} \frac{\partial \ln n}{\partial x} - V_y B_z \right) \tag{6}$$

$$j_z = \sigma \left(E_z + \frac{kT_e}{e} \frac{\partial \ln n}{\partial z} \right) \tag{7}$$

Current Density Conservation

$$\nabla \cdot \mathbf{j} = 0 \tag{8}$$

References

[1] M. Kim, M. Keidar, and I. D. Boyd, "Analysis of an Electromagnetic Mitigation Scheme for Reentry Telemetry Through Plasma," 2008.