


SIDEWALK SECTION

NOTES:

1. SIDEWALK: USE APWA PLAN 231 SIDEWALK. CONTRACTION JOINTS SHALL BE PLACED EVERY 5' FOR 5' WALKS AND EVERY 6' FOR 6' WALKS. EXPANSION JOINTS SHALL BE PLACED EVERY 50' MAXIMUM.
2. CURB AND GUTTER: USE APWA PLAN 205.1 TYPE A – 30" CURB AND GUTTER UNLESS OTHERWISE AUTHORIZED BY THE CITY ENGINEER TO MATCH EXISTING.
3. MOUNTABLE CURB AND GUTTER: USE APWA PLAN 205.3 TYPE H – 30" STANDARD CURB AND GUTTER UNLESS OTHERWISE AUTHORIZED BY THE CITY ENGINEER TO MATCH EXISTING.
4. CROSS GUTTER: USE APWA PLAN 211 AND 213 6' WATERWAY UNLESS OTHERWISE AUTHORIZED BY THE CITY ENGINEER TO MATCH EXISTING.

STATEMENT OF USE

THIS DOCUMENT AND ANY ILLUSTRATIONS HEREON ARE PROVIDED AS STANDARD CONSTRUCTION DETAILS WITHIN THE TOWN OF VINEYARD. DEVEATION FROM THIS DOCUMENT REQUIRES APPROVAL FROM THE TOWN OF VINEYARD. THE TOWN OF VINEYARD CORPORATION CAN NOT BE HELD LIABLE FOR MISUSE OR CHANGES REGARDING THIS DOCUMENT.

REVISION

NO.	DESCRIPTION	BY	APR.	DATE
1	STANDARDS UPDATE	JMM	DEO	8/08/16
2	HANSEN, ALLEN & LUCE	DCL	CMT	9/12/25
3				
4				

VINEYARD
STAY CONNECTED

CURB, GUTTER, AND SIDEWALK

VINEYARD

STANDARD DRAWING NUMBER: 5

CAD DWG:	STANDARD DRAWINGS
PLOT SCALE:	1.000
DRAWN BY:	JMM
DESIGN BY:	CRW
CHECKED BY:	DEO
ADOPTED DATE:	SEPTEMBER 1, 2016