Pollstr Grammar

Jayme Woogerd

December 20, 2014

```
\langle program \rangle ::= \langle decl \rangle^* \langle survey \rangle
\langle survey \rangle ::= Survey \langle upper \rangle : \langle meta \rangle (\langle section \rangle^* \mid \langle item \rangle^*)?
\langle meta \rangle ::= \langle title \rangle? \langle author \rangle? \langle description \rangle?
\langle section \rangle ::= Section \langle upper \rangle : \langle title \rangle \langle item \rangle^*
\langle delc \rangle
                 ::= \langle questDelc \rangle \mid \langle respDecl \rangle
\langle respDecl \rangle ::= Response \langle lower \rangle = \langle respExp \rangle
\langle questDecl \rangle ::= Question \langle lower \rangle = \langle questExp \rangle
\langle respExp \rangle ::= \langle options \rangle \mid Multi \langle options \rangle \mid Free \langle natural \rangle
\langle options \rangle ::= [(\langle stringLit \rangle) (, \langle stringLit \rangle)^*]
\langle questExp \rangle ::= \langle stringLit \rangle
\langle item \rangle ::= \langle itemID \rangle : \langle question \rangle \langle response \rangle (\langle skipTo \rangle)^*
\langle question \rangle ::= \langle questExp \rangle \mid \langle lower \rangle
\langle response \rangle ::= \langle respExp \rangle \mid \langle lower \rangle
\langle skipTo \rangle ::= skipTo (\langle itemID \rangle, \langle options \rangle)
\langle itemID \rangle ::= Q \langle alphaNum \rangle^*
\langle title \rangle
                 ::= \langle stringLit \rangle
\langle upper \rangle ::= \langle identifier \rangle with capitalized first character
\langle lower \rangle ::= \langle identifier \rangle with lowercase first character
\langle stringLit \rangle ::= As defined in Text.Parsec.Token
\langle natural \rangle ::= As defined in Text.Parsec.Token
\langle identifier \rangle ::= As defined in Text.Parsec.Token
\langle alphaNum \rangle ::= As defined in Text.Parsec.Char
```