

Untitled-1

```

/* howManyBits – return the minimum number of bits required to represent x in
 *      two's complement
 * Examples: howManyBits(12) = 5
 *      howManyBits(298) = 10
 *      howManyBits(-5) = 4
 *      howManyBits(0) = 1
 *      howManyBits(-1) = 1
 *      howManyBits(0x80000000) = 32
 * Legal ops: ! ~ & ^ | + << >>
 * Max ops: 90
 * Rating: 4
 */
int howManyBits(int x) {
    // keep in mind that this asks for the minimum number of bits required
    // to represent a number in binary, not the number of bits set (equal to 1)

    // the concept behind this is simple, we first get the sign from x
    // because the MSB is always the sign

    // if the number is negative then we add one to the final result
    // otherwise we can disregard the MSB because it would be 0

    // 1) get the sign from the number
    // 2) flip all the bits if the number is negative (turn it into a
    // positive number
    // 3) starting from the middle of the binary array, check if the left side is equal
    // to 0 using !(x >> 16)
    // 3.1) if the left side is equal to zero, that means there's no data there, so we
    don't need
    // to shift x (when x = 0, !(x >> 16) is 0, therefore 0 << 4 is still 0)
    // 3.2) if the left side is not zero, then that means all the bits to the right
    contains USEFUL
    // information, hence we set pos16 to 16 and then shift x by 16 bits to the left
    // Rinse and repeat with 8 bit, 4 bit, 2 bit, and one bit shifts

    // This is like doing a binary search for the position of the last set bit after the
    MSB

    int sign = x >> 31;
    // printf("%d\n", sign);
    int pos16, pos8, pos4, pos2, pos1, pos0;
    x = x ^ sign; // flip each bit of x if x < 0

    pos16 = !(x >> 16) << 4; // pos16 = 16 if (x >> 16) != 0
    x >>= pos16;

    pos8 = !(x >> 8) << 3; // pos8 = 8 if (x >> 8) != 0
    x >>= pos8;

    pos4 = !(x >> 4) << 2; // pos4 = 4 if (x >> 4) != 0
    x >>= pos4;

    pos2 = !(x >> 2) << 1; // pos2 = 2 if (x >> 2) != 0

```

```
x >>= pos2;

pos1 = !(x >> 1); // pos1 = 1 if (x >> 1) != 0
x >>= pos1;

pos0 = x;

// because we disregarded the MSB earlier, add a 1 because the MSB is always required
to
// differentiate between positive and negative numbers
// we always add a one because the MSB is required regardless of the sign
return pos16 + pos8 + pos4 + pos2 + pos1 + pos0 + 1;

// int sign = x >> 31;
// int not_x = ~x;
// int mask = sign | not_x;
// int num_bits = 0;

// int i = 0;
// i += 2;

// num_bits = (mask >> 16) & 16;
// num_bits |= ((mask >> (num_bits + 8)) & 8);
// num_bits |= ((mask >> (num_bits + 4)) & 4);
// num_bits |= ((mask >> (num_bits + 2)) & 2);
// num_bits |= ((mask >> (num_bits + 1)) & 1);

// return num_bits + 1;
}
```