

Bottle Detection in the Wild Using Low-Altitude Unmanned Aerial Vehicles

Jinwang Wang Wei Guo Ting Pan Huai Yu Lin Duan Wen Yang

Wuhan University, Wuhan, China

FUSION 2018 International Conference, Cambridge UK, July 2018



武汉大学
WUHAN UNIVERSITY



Outline

1. Introduction
2. UAV-Bottle Dataset
3. Baselines and Methods
4. Conclusion and Future Work



Introduction

Motivation

It's very **dangerous** for the sanitation workers who pick up the waste bottles on the mountain. Can we help them? Yes!




The sanitation workers were collecting the waste bottles at the Huashan Mountain.



Motivation


It's very **dangerous** for the sanitation workers who pick up the waste bottles on the mountain. Can we help them? Yes!



UAVs can help them!




Pipeline




challenges

In UAV images, the bottles look completely different from the bottles in datasets such as PASCAL VOC, ImageNet, Microsoft COCO, etc.



challenges

In UAV images, the bottles look completely different from the bottles in datasets such as PASCAL VOC, ImageNet, Microsoft COCO, etc.



challenges

As to UAV images, detecting bottles exists several unique challenges.



- ◎ The bottle size in image is very small, generally less than 50×50 pixels.



challenges

As to UAV images, detecting bottles exists several unique challenges.



- ◎ The bottle size in image is very small, generally less than 50×50 pixels.
- ◎ Backgrounds are very complex.



challenges

As to UAV images, detecting bottles exists several unique challenges.



- The bottle size in image is very small, generally less than 50×50 pixels.
- Backgrounds are very complex.
- Arbitrary orientations.



challenges

As to UAV images, detecting bottles exists several unique challenges.



- The bottle size in image is very small, generally less than 50×50 pixels.
- Backgrounds are very complex.
- Arbitrary orientations.
- Plastic bottles are often transparent.



UAV-Bottle Dataset

Dataset

To build a baseline for bottle detection in UAV images, we first establish a large scale dataset which called [UAV-Bottle Dataset\(UAV-BD\)](#).



Dataset Collection

We used **DJI Phantom 4 Pro** to collect images. The resolution of the captured images are **5472 × 3078 pixels**.



- ◎ Wide range of scale and aspect ratios.



Dataset Collection

We used **DJI Phantom 4 Pro** to collect images. The resolution of the captured images are **5472 × 3078 pixels**.



- ◎ Wide range of scale and aspect ratios.
- ◎ Different backgrounds.



Dataset Collection

We used **DJI Phantom 4 Pro** to collect images. The resolution of the captured images are **5472 × 3078 pixels**.



- ◎ Wide range of scale and aspect ratios.
- ◎ Different backgrounds.
- ◎ Different orientation.



Dataset Collection

We used **DJI Phantom 4 Pro** to collect images. The resolution of the captured images are **5472 × 3078 pixels**.



- Wide range of scale and aspect ratios.
- Different backgrounds.
- Different orientation.
- As many types of bottles as possible.



Dataset Collection

8 different scenes are chosen and annotated in our UAV-BD:

- Bushes
- Waste land
- Steps
- Mixture
- Cement ground
- Plastic ground
- Sands
- Grassland



Annotation Method

A common description of horizontal bounding boxes is (c_x, c_y, h, w) , where (c_x, c_y) is the center location, h, w are the height and width, respectively.



However, horizontal bounding box cannot accurately or compactly outline oriented instances such as the bottles in UAV images. Instead we use (c_x, c_y, h, w, θ) to describe bounding boxes, where θ is the angle from the vertical direction of the main-axis direction of the bottle.




Dataset Statistics

The size of each original image(OI) in UAV-BD is 5472×3078 pixels, it's too large to be trained for CNN-based algorithms. Therefore we segment each OI into 144 small subimages(SIs), and the size of each SI is 342×342 pixels. The numbers of images and instances in UAV-BD are shown in the table below.

Scenes	OI	SI	Instances in OI	Instances in SI
Bushes	230	4134	3047	1812
Waste land	379	7598	5800	4355
Steps	135	2691	2106	1325
Mixture	285	5724	4891	3702
Cement ground	134	2803	2142	1538
Plastic ground	336	6807	4998	4180
Sands	249	5570	4008	2704
Grassland	456	9029	7787	5778
Total	2204	44356	34779	25394




Dataset Statistics



Angle distribution of UAV-BD.
The angle ranges from 0° to 180° .




Dataset Statistics



Ratio distribution of UAV-BD.
The aspect ratio ranges from 1.0 to 5.0.



Dataset Statistics



Size distribution of UAV-BD. The size ranges from 64 to 4000 pixels.



Baselines and Methods


Dataset Partition

We randomly select **64%**, **16%** and **20%** of the UAV-BD as the **training**, **validation** and **testing** data. The whole UAV-BD contains 16,258 images with 22,211 instances for training, 4,055 images with 5,624 instances for validation and 5,081 images with 6,944 instances for testing.




Baselines with Horizontal Bounding Boxes(HBB)

We select [Faster R-CNN\[1\]](#), [SSD\[2\]](#), [YOLOv2\[3\]](#) as baselines for bottle detection with horizontal bounding box. The experimental results of HBB prediction are shown in figure below.




Baselines with Oriented Bounding Boxes(OBB)

For oriented object detection, we employ the [Rotation Region Proposal Network\(RRPN\)\[4\]](#) algorithm to predict properly oriented bounding boxes. The RRPN's network structure is shown in figure below.



Baseline with Oriented Bounding Boxes(OBB)



The experimental results of OBB prediction are shown in figure below.



Experimental Analysis



Some Details



Conclusion and Future Work

Conclusion and Future Work

Contribution

- ⑤ Built a large-scale dataset for bottle detection in UAV images named UAV-BD.

Future Work



Conclusion and Future Work

Contribution

- ⑤ Built a large-scale dataset for bottle detection in UAV images named UAV-BD.
- ⑤ Established a benchmark for bottle detection in UAV images.

Future Work



Conclusion and Future Work

Contribution

- ⑤ Built a large-scale dataset for bottle detection in UAV images named UAV-BD.
- ⑤ Established a benchmark for bottle detection in UAV images.

Future Work



Conclusion and Future Work

Contribution

- ⑤ Built a large-scale dataset for bottle detection in UAV images named UAV-BD.
- ⑤ Established a benchmark for bottle detection in UAV images.

Future Work

- ⑤ Locating and recycling bottles in the real-world using UAVs.



Get UAV-Bottle Dataset

UAV-Bottle Dataset and Development Kit can be downloaded on the Webpage and Github.

UAV-Bottle Dataset

<https://jwwangchn.github.io/UAV-BD/>

Development Kit

<https://github.com/jwwangchn/UAV-BD.git>



References

-  Ren S, He K, Girshick R, et al.
Faster R-CNN: Towards Real-time Object Detection with Region Proposal Networks
Advances in Neural Information Processing Systems, 2015
-  Liu W, Anguelov D, Erhan D, et al.
SSD: Single Shot Multibox Detector
ECCV, 2016
-  Redmon J, Farhadi A.
YOLO9000: Better, Faster, Stronger
IEEE CVPR, 2017
-  Ma J, Shao W, Ye H, et al.
Arbitrary-oriented Scene Text Detection via Rotation Proposals
IEEE Transactions on Multimedia, 2018
-  Xia G S, Bai X, Ding J, et al.
DOTA: A large-scale dataset for object detection in aerial images
IEEE CVPR, 2018



Comments and Questions!