

SSPREW 2017 Training

Breaking Obfuscated Programs with Symbolic Execution

Sebastian Banescu

Technical University of Munich, Germany

Chair of Software Engineering

Prof. Alexander Pretschner

- 1 Introduction
- 2 Obfuscation in Theory
- 3 Obfuscation in Practice
 - Static Obfuscation
 - Compiler Optimizations
 - Automated Code Obfuscation
 - Software Diversity
 - Dynamic Obfuscation
- 4 The Strength of Obfuscation
- 5 Hands-on Tutorial
- 6 Conclusions

- We assume you have Docker installed and have basic user knowledge
- Docker installation instructions
<https://docs.docker.com/engine/installation/>
- Docker image based on Ubuntu contains: Tigress, KLEE, STP, Z3, SatGraf, etc.
\$ docker pull banescusebi/obfuscation-symex
\$ docker run -it banescusebi/obfuscation-symex
- For instructions on how to start the Docker image read description at <https://hub.docker.com/r/banescusebi/obfuscation-symex/>
- Instructions for running GUI apps available for Ubuntu and Mac OS (not mandatory, only needed for SatGraf)




After this training you will have a better understanding of the following:


- The theory and practice of obfuscation and software diversity
- Practical static & dynamic obfuscation transformations
- Tools for applying symbolic execution on obfuscated programs
- Which obfuscation transformations help against symbolic execution



1. Man-in-the-middle (MITM) attacks communication channels




1. **Man-in-the-middle (MITM)** attacks communication channels
2. **Remote attacker** exploits vulnerabilities (e.g. buffer overflows)




1. Man-in-the-middle (MITM)


attacks communication channels



2. Remote attacker exploits vulnerabilities (e.g. buffer overflows)




3. Man-at-the-end (MATE) reverse engineers software




1. Man-in-the-middle (MITM)


attacks communication channels



2. Remote attacker exploits vulnerabilities (e.g. buffer overflows)




3. Man-at-the-end (MATE) reverse engineers software



We focus on **MATE** during this tutorial.


Informal Definition of Obfuscation:

To obfuscate a program P means to transform it into a executable program P' from which it is harder to extract information than from P .



Informal Definition of Obfuscation:

To obfuscate a program P means to transform it into a executable program P' from which it is harder to extract information than from P .




Motivation:

- Obfuscation is last layer of software defense against attackers (e.g. after attacker bypasses OS authentication)
- Obfuscation raises the bar for reverse engineering

Informal Definition of Obfuscation:

To obfuscate a program P means to transform it into a executable program P' from which it is harder to extract information than from P .



Motivation:

- Obfuscation is last layer of software defense against attackers (e.g. after attacker bypasses OS authentication)
- Obfuscation raises the bar for reverse engineering

Popular questions:

- Wasn't obfuscation proved to be impossible back in 2001?
- Isn't obfuscation the same as security by obscurity?

- 1 Introduction
- 2 Obfuscation in Theory
- 3 Obfuscation in Practice
 - Static Obfuscation
 - Compiler Optimizations
 - Automated Code Obfuscation
 - Software Diversity
 - Dynamic Obfuscation
- 4 The Strength of Obfuscation
- 5 Hands-on Tutorial
- 6 Conclusions

Formal Definition of Black-Box Obfuscation:

A probabilistic algorithm O is an obfuscator if the following conditions hold:

- For every program P , the obfuscated program $O(P)$ has the same functionality (e.g. input-output behavior)

Formal Definition of Black-Box Obfuscation:

A probabilistic algorithm O is an obfuscator if the following conditions hold:

- For every program P , the obfuscated program $O(P)$ has the same functionality (e.g. input-output behavior)
- The memory size increase and execution slowdown of $O(P)$ w.r.t. P are less than polynomial

Formal Definition of Black-Box Obfuscation:

A probabilistic algorithm O is an obfuscator if the following conditions hold:

- For every program P , the obfuscated program $O(P)$ has the same functionality (e.g. input-output behavior)
- The memory size increase and execution slowdown of $O(P)$ w.r.t. P are less than polynomial
- Any probabilistic polynomial time attacker only has a negligible probability of guessing any bit of information about P , given $O(P)$



- In 2001 Barak et al. [3]:
 - Proved there exists no **general obfuscator** applicable to **all** programs

- In 2001 Barak et al. [3]:
 - Proved there exists no **general obfuscator** applicable to **all** programs
 - Proof performed by giving a counter-example using 2 programs:

$$C_{\alpha,\beta}(x) = \begin{cases} \beta & \text{if } x = \alpha \\ 0^k & \text{otherwise} \end{cases}$$

$$D_{\alpha,\beta}(C) = \begin{cases} 1 & \text{if } C(\alpha) = \beta \\ 0 & \text{otherwise} \end{cases}$$

- In 2001 Barak et al. [3]:
 - Proved there exists no **general obfuscator** applicable to **all** programs
 - Proof performed by giving a counter-example using 2 programs:

$$C_{\alpha,\beta}(x) = \begin{cases} \beta & \text{if } x = \alpha \\ 0^k & \text{otherwise} \end{cases}$$

$$D_{\alpha,\beta}(C) = \begin{cases} 1 & \text{if } C(\alpha) = \beta \\ 0 & \text{otherwise} \end{cases}$$

- Attacker is defined as $A(C, D) = D(C)$. If $A(C, D) = 1$ then the attacker is successful

- In 2001 Barak et al. [3]:
 - Proved there exists no **general obfuscator** applicable to **all** programs
 - Proof performed by giving a counter-example using 2 programs:

$$C_{\alpha,\beta}(x) = \begin{cases} \beta & \text{if } x = \alpha \\ 0^k & \text{otherwise} \end{cases}$$

$$D_{\alpha,\beta}(C) = \begin{cases} 1 & \text{if } C(\alpha) = \beta \\ 0 & \text{otherwise} \end{cases}$$

- Attacker is defined as $A(C, D) = D(C)$. If $A(C, D) = 1$ then the attacker is successful
- If the attacker is given $O(C)$ and $O(D)$ then $A(O(C), O(D)) = 1$ with 100% probability

- In 2001 Barak et al. [3]:
 - Proved there exists no **general obfuscator** applicable to **all** programs
 - Proof performed by giving a counter-example using 2 programs:

$$C_{\alpha,\beta}(x) = \begin{cases} \beta & \text{if } x = \alpha \\ 0^k & \text{otherwise} \end{cases}$$

$$D_{\alpha,\beta}(C) = \begin{cases} 1 & \text{if } C(\alpha) = \beta \\ 0 & \text{otherwise} \end{cases}$$

- Attacker is defined as $A(C, D) = D(C)$. If $A(C, D) = 1$ then the attacker is successful
- If the attacker is given $O(C)$ and $O(D)$ then $A(O(C), O(D)) = 1$ with 100% probability
- If the attacker only has black box access to C and D , then the probability of a successful attack is negligible

- In 2001 Barak et al. [3]:
 - Proved there exists no **general obfuscator** applicable to **all** programs
 - Proof performed by giving a counter-example using 2 programs:

$$C_{\alpha,\beta}(x) = \begin{cases} \beta & \text{if } x = \alpha \\ 0^k & \text{otherwise} \end{cases}$$

$$D_{\alpha,\beta}(C) = \begin{cases} 1 & \text{if } C(\alpha) = \beta \\ 0 & \text{otherwise} \end{cases}$$

- Attacker is defined as $A(C, D) = D(C)$. If $A(C, D) = 1$ then the attacker is successful
 - If the attacker is given $O(C)$ and $O(D)$ then $A(O(C), O(D)) = 1$ with 100% probability
 - If the attacker only has black box access to C and D , then the probability of a successful attack is negligible
- This proof does not imply that every obfuscator fails on a **subset** of programs


- In 2001 Barak et al. [3]:
 - Proved there exists no **general obfuscator** applicable to **all** programs
 - Proof performed by giving a counter-example using 2 programs:

$$C_{\alpha,\beta}(x) = \begin{cases} \beta & \text{if } x = \alpha \\ 0^k & \text{otherwise} \end{cases}$$


$$D_{\alpha,\beta}(C) = \begin{cases} 1 & \text{if } C(\alpha) = \beta \\ 0 & \text{otherwise} \end{cases}$$

- Attacker is defined as $A(C, D) = D(C)$. If $A(C, D) = 1$ then the attacker is successful
 - If the attacker is given $O(C)$ and $O(D)$ then $A(O(C), O(D)) = 1$ with 100% probability
 - If the attacker only has black box access to C and D , then the probability of a successful attack is negligible
- This proof does not imply that every obfuscator fails on a **subset** of programs
- There may exist non-black-box obfuscators for some programs that leak bits of information, but are “good enough”


- In 2013 Garg et al. [8] proposed indistinguishability obfuscation:
 - The obfuscated versions of 2 semantically equivalent programs cannot be distinguished




- In 2013 Garg et al. [8] proposed indistinguishability obfuscation:
 - The obfuscated versions of 2 semantically equivalent programs cannot be distinguished
 - [9] proved this obfuscation is the best-possible obfuscation



- In 2013 Garg et al. [8] proposed indistinguishability obfuscation:
 - The obfuscated versions of 2 semantically equivalent programs cannot be distinguished
 - [9] proved this obfuscation is the best-possible obfuscation
 - Implementations still far from being practical: [1, 2]



- In 2013 Garg et al. [8] proposed indistinguishability obfuscation:
 - The obfuscated versions of 2 semantically equivalent programs cannot be distinguished
 - [9] proved this obfuscation is the best-possible obfuscation
 - Implementations still far from being practical: [1, 2]



Cool stuff, but let's look at obfuscation we can use in practice.

- 1 Introduction
- 2 Obfuscation in Theory
- 3 Obfuscation in Practice
 - Static Obfuscation
 - Compiler Optimizations
 - Automated Code Obfuscation
 - Software Diversity
 - Dynamic Obfuscation
- 4 The Strength of Obfuscation
- 5 Hands-on Tutorial
- 6 Conclusions

What types of obfuscation transformations exist?

- **Static Vs. Dynamic**

- **Static obfuscation:**

- Obfuscated programs remain fixed at runtime
 - Raises the bar against static analysis
 - Can be attacked through dynamic techniques (debugging, emulation, tracing)

What types of obfuscation transformations exist?

- **Static Vs. Dynamic**

- **Static obfuscation:**

- Obfuscated programs remain fixed at runtime
 - Raises the bar against static analysis
 - Can be attacked through dynamic techniques (debugging, emulation, tracing)

- **Dynamic obfuscation:**

- Programs change during load-/run-time
 - Raises the bar against dynamic analysis
 - Different executions of the same program with the same input may produce different execution traces

What types of obfuscation transformations exist?

- **Static Vs. Dynamic**

- **Static obfuscation:**

- Obfuscated programs remain fixed at runtime
 - Raises the bar against static analysis
 - Can be attacked through dynamic techniques (debugging, emulation, tracing)

- **Dynamic obfuscation:**

- Programs change during load-/run-time
 - Raises the bar against dynamic analysis
 - Different executions of the same program with the same input may produce different execution traces

- **Point of insertion:**

- Source code
 - Intermediate representation
 - Machine code

What types of obfuscation transformations exist?

- **Static Vs. Dynamic**

- **Static obfuscation:**

- Obfuscated programs remain fixed at runtime
 - Raises the bar against static analysis
 - Can be attacked through dynamic techniques (debugging, emulation, tracing)

- **Dynamic obfuscation:**

- Programs change during load-/run-time
 - Raises the bar against dynamic analysis
 - Different executions of the same program with the same input may produce different execution traces

- **Point of insertion:**

- Source code
 - Intermediate representation
 - Machine code

- **Transformation targets:**

- **Layout** → scramble identifiers and code layout
 - **Data** → obfuscate data (structures) embedded in code
 - **Control flow** → obfuscate secret algorithms

- 1 Introduction
- 2 Obfuscation in Theory
- 3 Obfuscation in Practice
 - Static Obfuscation
 - Compiler Optimizations
 - Automated Code Obfuscation
 - Software Diversity
 - Dynamic Obfuscation
- 4 The Strength of Obfuscation
- 5 Hands-on Tutorial
- 6 Conclusions





Compiler Optimizations

- In-lining function bodies
- Loop unrolling
- Loop-invariant code motion
- Common sub-expression elimination
- Constant folding and propagation
- Dead code elimination
- Strength reduction
- more @ http://en.wikipedia.org/wiki/Optimizing_compiler

Replace function call by function body

Before

```
1 int foo(int a, int b) {  
2     return a + b;  
3 }  
4 ...  
5 c = foo(a, b+1);
```

After

```
1 ...  
2 c = a + b + 1;
```

Remove “end-of-loop” test overhead

Before

```
1 ...  
2 for (i = 0; i < 2; i++)  
3 {  
4     a[i] = 0;  
5 }
```

After

```
1 ...  
2 a[0] = 0;  
3 a[1] = 0;
```

Extract operations whose results are independent of loop execution

Before

```
1 ...  
2 for (i = 0; i < 2; i++)  
3 {  
4     a[i] = p + q;  
5 }
```

After

```
1 ...  
2 temp = p + q;  
3 for (i = 0; i < 2; i++)  
4 {  
5     a[i] = temp;  
6 }
```

Replace re-occurring identical (sub-)expressions by a single variable holding the result

Before

```
1 ...  
2 a = b + (z + 1);  
3 p = q + (z + 1);
```

After

```
1 ...  
2 temp = z + 1;  
3 a = b + temp;  
4 p = q + temp;
```

Simplify constant expressions and substitute the values of known constants in expressions

Before

```
1 ...  
2 a = 3 + 5;  
3 b = a + 1;  
4 func(a, b);
```

After

```
1 ...  
2 func(8, 9);
```

Remove code which does not affect program results: unreachable code and code that affects variables that are irrelevant for the program

Before

```
1 ...  
2 a = 1;  
3 if (a < 0)  
4 {  
5     printf("This should never be printed!");  
6 }
```

After

```
1 ...  
2 a = 1;
```


Replace expensive operations with equivalent cheap ones


Before


```
1 ...  
2 y = x / 8;  
3 p = q * 15;
```

After

```
1 ...  
2 y = x >> 3;  
3 p = (q << 4) - x;
```

- 1 Introduction
- 2 Obfuscation in Theory
- 3 Obfuscation in Practice
 - Static Obfuscation
 - Compiler Optimizations
 - Automated Code Obfuscation
 - Software Diversity
 - Dynamic Obfuscation
- 4 The Strength of Obfuscation
- 5 Hands-on Tutorial
- 6 Conclusions





Obfuscation Techniques:

- Scramble identifiers
- Instruction substitution
- Garbage code insertion
- Merging and splitting functions
- Encode Literals
- Encode Arithmetic
- Opaque predicates
- Control-flow flattening
- Virtualization obfuscation
- White-box cryptography

Replace identifier names with random strings

Before

```
1 ...  
2 sum = 0;  
3 for (i = 0; i < arr_len; i++)  
4     sum += arr[i];  
5 average /= arr_len;
```

After

```
1 ...  
2 za82b547bcb = 0;  
3 for (z1c0ab7cf0c = 0; z1c0ab7cf0c < za862d19cbc;  
      z1c0ab7cf0c++)  
4     za82b547bcb += zc1c28ca67f[z1c0ab7cf0c];  
5 z8c8f7c7867 /= za862d19cbc
```

This layout obfuscation has high potency, but low resilience

Replace binary operation (e.g. +, -, AND, OR, XOR, etc.) by functionally equivalent, but more complicated computations

Before

```
1 ...  
2 a = b + c
```

After

```
1 ...  
2 r = rand();  
3 a = b + r;  
4 a = a + c;  
5 a = a - r;
```

Insert code that executes, but does not affect the IO behavior

Before

```
1 ...
2 sum = 0;
3 for (i = 0; i < arr_len; i++)
4     sum += arr[i];
5 average = sum / arr_len;
```

After

```
1 ...
2 sum = 0; prod = 1;
3 for (i = 0; i < arr_len; i++) {
4     sum += arr[i];
5     prod *= arr[i];
6 }
7 average = sqrt(prod);
8 average = sum / arr_len;
```

- Merging implies combining the code of two or more functions into a single function
- Splitting implies dividing the code one function into two or more functions

Split

```
1 func1(int a, int b) {  
2     x = 4;  
3     if (a < 3)  
4         x = x + 6;  
5     x *= b;  
6 }  
7  
8 func2(int a, int c) {  
9     y = a + 12;  
10    y = y/c;  
11 }
```

Merged

```
1 func3(int a, int b, int c) {  
2     if (c % 2 == 0) {  
3         x = 4;  
4         if (a < 3)  
5             x = x + 6;  
6         x *= b;  
7     } else {  
8         y = a + 12;  
9         y = y/b;  
10    }  
11 }
```


- Literals are constant (hard-coded) strings and numeric values
- Literals can be encoded in numerous ways using encoder functions
- At runtime they are decoded back to their original value

Before

```
1 main(int ac, char* av[]) {  
2     printf("hello\n");  
3     return 0;  
4 }
```

After

```
1 gen_str(char str[]) {  
2     int i = 0;  
3     str[i++] = 'h';  
4     str[i++] = 'e';  
5     str[i++] = 'l';  
6     str[i++] = 'l';  
7     str[i++] = 'o';  
8     str[i++] = '\n';  
9     str[i] = '\000';  
10 }  
11  
12 main(int ac, char* av[]) {  
13     char str[7];  
14     gen_str(str);  
15     printf(str);  
16     return 0;  
17 }
```

- Replace arithmetic or Boolean expressions with more complex ones
- Complex expressions contain both arithmetic and boolean operators
- Transformation can be applied recursively to increase strength

Before

```
1 func(int x, int y) {  
2   return x + y;  
3 }
```

After (Version 1)

```
1 func(int x, int y) {  
2   return 2*(x | y) - (x ^ y);  
3 }
```

After (Version 2)

```
1 func(int x, int y) {  
2   return (x | y) + (x & y);  
3 }
```

Informal Definition:

An expression whose value is known to the defender (at obfuscation time), but which is difficult for an attacker to figure out statically.

Informal Definition:

An expression whose value is known to the defender (at obfuscation time), but which is difficult for an attacker to figure out statically.

Notation:


- P^T for an opaquely true predicate
- P^F for an opaquely false predicate
- $P^?$ for an opaquely intermediate predicate (range divider)
- E^v for an opaque expression of value v

Informal Definition:




An expression whose value is known to the defender (at obfuscation time), but which is difficult for an attacker to figure out statically.

Notation:

- P^T for an opaquely true predicate
- P^F for an opaquely false predicate
- $P^?$ for an opaquely intermediate predicate (range divider)
- $E=v$ for an opaque expression of value v



- Opaque predicates facilitate insertion of bogus control-flow:
 - Does not affect I/O behavior
 - Attacker does not know which code is bogus
 - Increases attack / analysis time
- Resilience of bogus control-flow reduced to resilience of opaque predicates




Bogus control-flow via opaque predicates

E.g. add an opaquely true predicate (P^T) to a *while* loop condition (P)


Before

```
1 i = 1;  
2 while (i < 100) {  
3   dostuff(i);  
4   i++;  
5 }
```



After

```
1 i = 1; j = 100;  
2 while ((i < 100) &&  
3   (j*j*(j+1)*(j+1)%4 == 0)) {  
4   dostuff(i);  
5   i++;  
6   j = j*i+3;  
7 }
```



- Dalla Preda et al. [7] used abstract interpretation to break opaque predicates:
 - Opaque predicates are confined in a single basic block
 - Only opaque predicate of the following form: $n|p(x), \forall x \in \mathbb{Z}$, where $p(x)$ is a polynomial in x and $n \in \mathbb{N}$

- Dalla Preda et al. [7] used abstract interpretation to break opaque predicates:
 - Opaque predicates are confined in a single basic block
 - Only opaque predicate of the following form: $n|p(x), \forall x \in \mathbb{Z}$, where $p(x)$ is a polynomial in x and $n \in \mathbb{N}$
- E.g. opaquely true predicate: $2|(x^2 + x), \forall x \in \mathbb{Z}$

- Dalla Preda et al. [7] used abstract interpretation to break opaque predicates:
 - Opaque predicates are confined in a single basic block
 - Only opaque predicate of the following form: $n|p(x), \forall x \in \mathbb{Z}$, where $p(x)$ is a polynomial in x and $n \in \mathbb{N}$
- E.g. opaquely true predicate: $2|(x^2 + x), \forall x \in \mathbb{Z}$

x is odd

```
1 x = ...; // any odd number
2 y = x * x; // odd
3 y = y + x; // even
4 if ( y % 2 == 0) // always
5 ...           // true
6 else // dead branch
7 ...
```

- Dalla Preda et al. [7] used abstract interpretation to break opaque predicates:
 - Opaque predicates are confined in a single basic block
 - Only opaque predicate of the following form: $n|p(x), \forall x \in \mathbb{Z}$, where $p(x)$ is a polynomial in x and $n \in \mathbb{N}$
- E.g. opaquely true predicate: $2|(x^2 + x), \forall x \in \mathbb{Z}$

x is odd

```
1 x = ...; // any odd number
2 y = x * x; // odd
3 y = y + x; // even
4 if ( y % 2 == 0) // always
5 ...           // true
6 else // dead branch
7 ...
```

x is even

```
1 x = ...; // any even number
2 y = x * x; // even
3 y = y + x; // even
4 if ( y % 2 == 0) // always
5 ...           // true
6 else // dead branch
7 ...
```

- Dalla Preda et al. [7] used abstract interpretation to break opaque predicates:
 - Opaque predicates are confined in a single basic block
 - Only opaque predicate of the following form: $n|p(x), \forall x \in \mathbb{Z}$, where $p(x)$ is a polynomial in x and $n \in \mathbb{N}$
- E.g. opaquely true predicate: $2|(x^2 + x), \forall x \in \mathbb{Z}$

x is odd

```
1 x = ...; // any odd number
2 y = x * x; // odd
3 y = y + x; // even
4 if ( y % 2 == 0 ) // always
5 ...           // true
6 else // dead branch
7 ...
```

x is even

```
1 x = ...; // any even number
2 y = x * x; // even
3 y = y + x; // even
4 if ( y % 2 == 0 ) // always
5 ...           // true
6 else // dead branch
7 ...
```

- Abstract interpretation is able to infer that regardless of x 's value, the *IF* condition is always true

- Range dividers can lead to different paths in the code
- No dead code
- All branches have the same behavior but different syntax

Before

```
1 int main(int ac, char* av[]){
2     char *str = av[1];
3     int hash = 0;
4     for(int i = 0;
5         i < strlen(str);
6         str++, i++) {
7         hash = (hash<<7)^(*str);
8     }
9     if (hash == 809267)
10        printf("You win!");
11    return 0;
12 }
```


After

```
1 int main(int ac, char* av[]){
2     char *str = av[1];
3     int hash = 0;
4     for(int i = 0;
5         i < strlen(str);
6         str++, i++) {
7         char chr = *str;
8         if (chr > 42) {
9             hash = (hash << 7) ^ chr;
10        } else {
11            hash = (hash * 128) ^ chr;
12        }
13    }
14    if (hash == 809267)
15        printf("You win!");
16    return 0;
17 }
```

- Remove the control-flow structure of functions:
 1. Put each basic block as a case inside a switch statement
 2. Wrap the switch inside an infinite loop

- Remove the control-flow structure of functions:
 1. Put each basic block as a case inside a switch statement
 2. Wrap the switch inside an infinite loop
- Let's take one function, e.g. GCD

```
1 int gcd(int a, int b){  
2     while (a != b)  
3         if (a > b)  
4             a = a - b;  
5         else  
6             b = b - a;  
7     return a;  
8 }
```



Before


```
1 int gcd(int a, int b){
2     while (a != b)
3         if (a > b)
4             a = a - b;
5         else
6             b = b - a;
7     return a;
8 }
```

After

```
1 int gcd(int a, int b){
2     int next = 0;
3     while(1) {
4         switch(next) {
5             case 0:
6                 next = (int)(a != b) + 1;
7                 break;
8             case 1: return a;
9                 break;
10            case 2:
11                next = (a > b) + 3;
12                break;
13            case 3: b = b - a;
14                    next = 0;
15                    break;
16            case 4: a = a - b;
17                    next = 0;
18                    break;
19            default:
20                break;
21        }
22    }
```


Control-flow flattening GCD example

The CFG of the resulting code:



Performance penalty:

- For 3 SPEC programs: $4\times$ slowdown, $2\times$ size
- Reasons:
 - The wrapper loop condition check, plus jump
 - The switch next value check, plus indirect jump
- How to optimize:
 - Keep tight loops as one switch entry (don't split)
 - Use gcc's *labels-as-values* \rightarrow allows jumping to next basic block

Performance penalty:

- For 3 SPEC programs: $4\times$ slowdown, $2\times$ size
- Reasons:
 - The wrapper loop condition check, plus jump
 - The switch next value check, plus indirect jump
- How to optimize:
 - Keep tight loops as one switch entry (don't split)
 - Use gcc's *labels-as-values* → allows jumping to next basic block

Attack on control-flow flattening:

1. Find next block of every basic block
2. Rebuild original CFG

Performance penalty:

- For 3 SPEC programs: $4\times$ slowdown, $2\times$ size
- Reasons:
 - The wrapper loop condition check, plus jump
 - The switch next value check, plus indirect jump
- How to optimize:
 - Keep tight loops as one switch entry (don't split)
 - Use gcc's *labels-as-values* \rightarrow allows jumping to next basic block

Attack on control-flow flattening:

1. Find next block of every basic block
2. Rebuild original CFG

Mitigation: assign opaque expressions ($E^=v$) to next

Question: How do we build such opaque expressions?

1. A statically initialized **array with seemingly random values**:

$g =$

10	5	13	3	27	5	24	38	0	73	115	3	66	60	17	31
----	---	----	---	----	---	----	----	---	----	-----	---	----	----	----	----

2. The values are generated such that some **invariants** hold, e.g.:
 - Every 3rd cell starting from cell 0, contains a value $v \equiv 3 \pmod{7}$
 - Every 3rd cell starting from cell 1, contains a value $v \equiv 5 \pmod{11}$
 - Cells 2, 5, 8, 11 and 14 contain values 13, 5, 0, 3, respectively 17
3. **Update array cells** with values that respect invariants

1. A statically initialized **array with seemingly random values**:

$g =$

10	5	13	3	27	5	24	38	0	73	115	3	66	60	17	31
----	---	----	---	----	---	----	----	---	----	-----	---	----	----	----	----

2. The values are generated such that some **invariants** hold, e.g.:

- Every 3rd cell starting from cell 0, contains a value $v \equiv 3 \pmod{7}$
- Every 3rd cell starting from cell 1, contains a value $v \equiv 5 \pmod{11}$
- Cells 2, 5, 8, 11 and 14 contain values 13, 5, 0, 3, respectively 17

3. **Update array cells** with values that respect invariants

Let's replace right-hand values 0, 1, 2, 3 and 4 of assignments to `next` with $E=0, E=1, E=2, E=3$, respectively $E=4$:

- `next = 0` \rightarrow `next = g[3] % g[11] - g[8]`
- `next = 1` \rightarrow `next = 3 * g[11] - 4 * (g[4] % g[5])`
- `next = 2` \rightarrow `next = g[5] - g[3]`
- `next = 3` \rightarrow `next = g[2] % g[1]`
- `next = 4` \rightarrow `next = g[15] - g[4]`

Next slide shows how this looks in the flattened GCD example


```
1 int gcd(int a, int b){
2 int g[] = {10, 5, 13, 3, 27, 5, 24, 38, 0, 73, 115,
3           3, 66, 60, 17, 31};
4 int next = g[3] % g[11] - g[11]; // 0
5 while(1) {
6     switch(next) {
7         case 0:
8             if(a != b)
9                 next = 3 * g[11] - 4 * (g[4] % g[5]); // 1
10            else next = g[5] - g[3]; // 2
11            break;
12        case 1:
13            if (a > b) next = g[2] % g[1]; // 3
14            else next = g[15] - g[4]; // 4
15            break;
16        case 2: return a;
17            break;
18        case 3: a = a - b;
19            next = g[3] % g[11] - g[8]; // 0
20            break;
21        case 4: b = b - a;
22            next = g[3] % g[11] - g[8]; // 0
23            break;
24        default:
25            break;
26    }
27 }
```


Assumption: pointer aliasing is a computationally hard static analysis problem

1. Construct one or more linked-lists
2. Set pointers into those linked-lists
3. Create opaque predicates by checking properties you know to be true / false, e.g.:
 - q_1 points to a node with value $v > 53$
 - q_2 points to a node with value $v \leq 53$

Assumption: pointer aliasing is a computationally hard static analysis problem


1. Construct one or more linked-lists
2. Set pointers into those linked-lists
3. Create opaque predicates by checking properties you know to be true / false, e.g.:
 - q_1 points to a node with value $v > 53$
 - q_2 points to a node with value $v \leq 53$






- One opaquely true predicate: $(*q_1 > *q_2)^T$
- After performing several operations to confuse alias analysis another opaque predicate is: $(q_1 \neq q_2)^T$


- **Goal:** Hide secret **algorithm** of program P




- **Goal:** Hide secret **algorithm** of program P
- **Obfuscation Procedure:**
 1. Generate random bytecode ISA (L) covering all instructions of P




- **Goal:** Hide secret **algorithm** of program P
- **Obfuscation Procedure:**
 1. Generate random bytecode ISA (L) covering all instructions of P
 2. Translate P to L bytecode program



- **Goal:** Hide secret **algorithm** of program P
- **Obfuscation Procedure:**
 1. Generate random bytecode ISA (L) covering all instructions of P
 2. Translate P to L bytecode program
 3. Generate emulator to interpret L bytecode on x86 machine



- **Goal:** Hide secret **algorithm** of program P
- **Obfuscation Procedure:**
 1. Generate random bytecode ISA (L) covering all instructions of P
 2. Translate P to L bytecode program
 3. Generate emulator to interpret L bytecode on x86 machine
- Obfuscated program (P') consists of bytecode program and emulator



We apply virtualization obfuscation to function `foo`, written in C

```
1 void foo(int x){  
2   int y = 10;  
3   y++;  
4   y++;  
5   if (x > 0){  
6     y++;  
7   }  
8   else {}  
9   printf("%d\n",y);  
10 }
```




Figure : CFG of `foo`

Step 1: Generate random bytecode ISA covering all instructions of foo

```
1 void foo(int x){  
2   int y = 10;  
3   y++;  
4   y++;  
5   if (x > 0){  
6     y++;  
7   }  
8   else {}  
9   printf("%d\n",y);  
10 }
```

Random ISA:

1. Integer assignment (line 2)
 $\xrightarrow{\text{encode}}$ 52, LH_op, RH_op

Step 1: Generate random bytecode ISA covering all instructions of foo

```
1 void foo(int x){  
2   int y = 10;  
3   y++;  
4   y++;  
5   if (x > 0){  
6     y++;  
7   }  
8   else {}  
9   printf("%d\n",y);  
10 }
```

Random ISA:

1. Integer assignment (line 2)
 $\xrightarrow{\text{encode}}$ 52, LH_op, RH_op
2. Integer increment (lines 3,4,6)
 $\xrightarrow{\text{encode}}$ 03, op

Step 1: Generate random bytecode ISA covering all instructions of foo

```
1 void foo(int x){  
2   int y = 10;  
3   y++;  
4   y++;  
5   if (x > 0){  
6     y++;  
7   }  
8   else {}  
9   printf("%d\n",y);  
10 }
```

Random ISA:

1. Integer assignment (line 2)
 $\xrightarrow{\text{encode}}$ 52, LH_op, RH_op
2. Integer increment (lines 3,4,6)
 $\xrightarrow{\text{encode}}$ 03, op
3. Branch if > 0 (line 5)
 $\xrightarrow{\text{encode}}$ 08, tst_op, jmp_offset

Step 1: Generate random bytecode ISA covering all instructions of foo

```
1 void foo(int x){  
2   int y = 10;  
3   y++;  
4   y++;  
5   if (x > 0){  
6     y++;  
7   }  
8   else {}  
9   printf("%d\n",y);  
10 }
```

Random ISA:

1. Integer assignment (line 2)
 $\xrightarrow{\text{encode}}$ 52, LH_op, RH_op
2. Integer increment (lines 3,4,6)
 $\xrightarrow{\text{encode}}$ 03, op
3. Branch if > 0 (line 5)
 $\xrightarrow{\text{encode}}$ 08, tst_op, jmp_offset
4. Call to printf (line 9)
 $\xrightarrow{\text{encode}}$ 18, op

Variables and constants of bytecode program stored in array: data

- data[0] represents variable x
- data[1] represents variable y
- data[2] represents constant for initialization to 10 (line 2 of foo)
- data[3] represents constant jump offset of conditional branch

```
1 void foo(int x){  
2   int y = 10;  
3   y++;  
4   y++;  
5   if (x > 0){  
6     y++;  
7   }  
8   else {}  
9   printf("%d\n", y);  
10 }
```

Random ISA:

1. Integer assignment (line 2)
 $\xrightarrow{\text{encode}}$ 52, LH_op, RH_op
2. Integer increment (lines 3,4,6)
 $\xrightarrow{\text{encode}}$ 03, op
3. Branch if > 0 (line 5)
 $\xrightarrow{\text{encode}}$ 08, tst_op, jmp_offset
4. Call to printf (line 9)
 $\xrightarrow{\text{encode}}$ 18, op

Step 2: Translate foo to bytecode program

- data = {00,00,10,05} // {x, y, init_const, jmp_offset}
- Bytecode: {52, 01, 02, 03, 01, 03, 01, 08, 00, 03, 03, 01, 18, 01, 00}

```
1 void foo(int x){// bytecode
2   int y = 10; // 52, 01, 02
3   y++;        // 03, 01
4   y++;        // 03, 01
5   if (x > 0){ // 08, 00, 03
6     y++;      // 03, 01
7   }
8   else {}
9   printf("%d",y); // 18, 01
10 }
```

Random ISA:

1. Integer assignment (line 2)
 $\xrightarrow{\text{encode}}$ 52, LH_op, RH_op
2. Integer increment (lines 3,4,6)
 $\xrightarrow{\text{encode}}$ 03, op
3. Branch if > 0 (line 5)
 $\xrightarrow{\text{encode}}$ 08, tst_op, jmp_offset
4. Call to printf (line 9)
 $\xrightarrow{\text{encode}}$ 18, op

Step 3: Generate emulator to
interpret bytecode on x86 machine

```
int data = {00,00,10,05};  
{x, y, init_const, jmp_off}
```

```
int code = {  
52, 01, 02,  
03, 01,  
03, 01,  
08, 00, 03,  
03, 01,  
18, 01,  
00};
```

Step 3: Generate emulator to interpret bytecode on x86 machine

```
int data = {00,00,10,05};  
{x, y, init_const, jmp_off}
```

```
int code = {  
52, 01, 02,  
03, 01,  
03, 01,  
08, 00, 03,  
03, 01,  
18, 01,  
00};
```

```
1 int vpc = 0, op1, op2;  
2 while (true) {  
3     switch(code[vpc]) {  
4         case 03: // increment  
5             op1 = code[vpc + 1];  
6             data[op1]++;  
7             vpc += 2; break;  
8         case 08: // conditional jump  
9             op1 = code[vpc + 1];  
10            op2 = code[vpc + 2];  
11            if (data[op1] > 0)  
12                vpc += 3;  
13            else  
14                vpc += data[op2];  
15            break;  
16        case 18: // call printf  
17            op1 = code[vpc + 1];  
18            printf("%d\n", data[op1]);  
19            vpc += 2; break;  
20        case 52: // assignment  
21            op1 = code[vpc + 1];  
22            op2 = code[vpc + 2];  
23            data[op1] = data[op2];  
24            vpc += 3; break;  
25        default: return; // halt  
26    } // end switch  
27 } // end while
```





Figure : Control flow graph of obfuscated foo

- **Goal:** obfuscate secret algorithm (not secret data)

Virtualization Obfuscation

- **Goal:** obfuscate secret algorithm (not secret data)
- **Strengths:**
 - Random ISA, different for each instance

- **Goal:** obfuscate secret algorithm (not secret data)
- **Strengths:**
 - Random ISA, different for each instance
 - Control-flow flattening → Different locations in original program mapped to same case branch

- **Goal:** obfuscate secret algorithm (not secret data)
- **Strengths:**
 - Random ISA, different for each instance
 - Control-flow flattening → Different locations in original program mapped to same case branch
 - Many other obfuscation techniques can be added on top of:
 - Each case branch
 - The switch statement
 - The data and code arrays

- **Goal:** obfuscate secret algorithm (not secret data)
- **Strengths:**
 - Random ISA, different for each instance
 - Control-flow flattening → Different locations in original program mapped to same case branch
 - Many other obfuscation techniques can be added on top of:
 - Each case branch
 - The switch statement
 - The data and code arrays
- **Tools:**
 - CodeVirtualizer (59 € - 119 €)
 - VMProtect (69 € - 599 €)
 - Tigress, Diablo (Free research tools)




- **Idea:**
 - Embed the key inside the cipher (e.g. in S-boxes)
 - Convert cipher computation into large network of look-up tables

- Idea:


- Embed the key inside the cipher (e.g. in S-boxes)
- Convert cipher computation into large network of look-up tables

Source: <http://www.whiteboxcrypto.com/>



- **Idea:**
 - Embed the key inside the cipher (e.g. in S-boxes)
 - Convert cipher computation into large network of look-up tables
- **Attack:** WB-AES and WB-DES broken (2^{22} operations)

Source: <http://www.whiteboxcrypto.com/>



Some Details on WBC

Before

```
1 char xor(char inputs)
2 {
3     char a = inputs & 0x0F;
4     char b = inputs >> 4;
5     return a ^ b;
6 }
```

After

```
1 char lut[256] =
2 {
3     0x00, 0x01, 0x02, ..., 0x0F,
4     0x01, 0x00, 0x03, ..., 0x0E,
5     0x02, 0x03, 0x00, ..., 0x0D,
6     |                                     |
7     0x0F, 0x0E, 0x0D, ..., 0x00
8 };
9
10 char xor(char inputs)
11 {
12     return lut[inputs];
13 }
```


Some Details on WBC

Before

```
1 char xor(char inputs)
2 {
3     char a = inputs & 0x0F;
4     char b = inputs >> 4;
5     return a ^ b;
6 }
```

After


```
1 char lut[256] =
2 {
3     0x00, 0x01, 0x02, ..., 0x0F,
4     0x01, 0x00, 0x03, ..., 0x0E,
5     0x02, 0x03, 0x00, ..., 0x0D,
6     |                                     |
7     0x0F, 0x0E, 0x0D, ..., 0x00
8 };
9
10 char xor(char inputs)
11 {
12     return lut[inputs];
13 }
```




Source: PhD
presentation
of B. Wyseur

- 1 Introduction
- 2 Obfuscation in Theory
- 3 Obfuscation in Practice
 - Static Obfuscation
 - Compiler Optimizations
 - Automated Code Obfuscation
 - Software Diversity
 - Dynamic Obfuscation
- 4 The Strength of Obfuscation
- 5 Hands-on Tutorial
- 6 Conclusions


1. Software developer distributes software X to all end-users




1. Software developer distributes software X to all end-users
2. Some end-users are MATE attackers




1. Software developer distributes software X to all end-users
2. Some end-users are MATE attackers
3. MATE reverse engineers X and builds a hijacker of X




1. Software developer distributes software X to all end-users
2. Some end-users are MATE attackers
3. MATE reverse engineers X and builds a hijacker of X
4. MATE distributes hijacker to other end-users of X




- What can we do to protect victims?




- What can we do to protect victims?
- Give everyone a different version




- What can we do to protect victims?
- Give everyone a different version
- Generate 1000s of different versions using obfuscation



- What can we do to protect victims?
- Give everyone a different version
- Generate 1000s of different versions using obfuscation
- **Assumption:** Same attack will not work on different binaries



- What can we do to protect victims?
- Give everyone a different version
- Generate 1000s of different versions using obfuscation
- **Assumption:** Same attack will not work on different binaries
- **Issues:**
 - Analyzing crash-dumps
 - Incremental updates
 - Digitally signing all versions



Pre-Distribution Software Diversity

- Obfuscation transformations involve randomly generated code & data
- Many different binaries generated by software developer
- Different binaries distributed to different end-users
- All previously presented techniques can be used for pre-distribution diversification

Pre-Distribution Software Diversity


- Obfuscation transformations involve randomly generated code & data
- Many different binaries generated by software developer
- Different binaries distributed to different end-users
- All previously presented techniques can be used for pre-distribution diversification

Post-Distribution Software Diversity

- Software developer embeds self-modifying code in application
- All end-users may get the same binary from software developer
- Code may change differently for different users depending on inputs
- Next we present dynamic obfuscation techniques which can be used for post-distribution diversification

- 1 Introduction
- 2 Obfuscation in Theory
- 3 Obfuscation in Practice
 - Static Obfuscation
 - Compiler Optimizations
 - Automated Code Obfuscation
 - Software Diversity
 - Dynamic Obfuscation
- 4 The Strength of Obfuscation
- 5 Hands-on Tutorial
- 6 Conclusions


- A dynamic obfuscator runs in two phases:
 1. At **compile-time**:
 - Transform the program to an initial configuration
 - Add a runtime code-transformer



- A dynamic obfuscator runs in two phases:


1. At **compile-time**:

- Transform the program to an initial configuration
- Add a runtime code-transformer



2. At **runtime**:

- Interleave execution of the program with calls to the transformer T
- T changes the code segment content at runtime
- Ideally a non-repeating series of configurations, **in practice** they repeat



General Techniques:

- **Build-and-execute:** generate code for a routine at runtime, and jump to it
- **Self-modification:** modify the executable code
- **Encryption:** the self-modification is decrypting the encrypted code before executing it
- **Move code:** every time the code executes, it is in a different location

General Techniques:

- **Build-and-execute:** generate code for a routine at runtime, and jump to it
- **Self-modification:** modify the executable code
- **Encryption:** the self-modification is decrypting the encrypted code before executing it
- **Move code:** every time the code executes, it is in a different location

These techniques can be applied at the following levels of **granularity**:

- File level
- Function level
- Basic block level
- Instruction level

General Techniques:

- **Build-and-execute:** generate code for a routine at runtime, and jump to it
- **Self-modification:** modify the executable code
- **Encryption:** the self-modification is decrypting the encrypted code before executing it
- **Move code:** every time the code executes, it is in a different location

These techniques can be applied at the following levels of **granularity**:

- File level
- Function level
- Basic block level
- Instruction level


The **attacker's goals** can be to:

- Recover the original code
- Modify the original code

- **Motivation:** prevent code recovery via memory snapshot

- **Motivation:** prevent code recovery via memory snapshot
- **Algorithm idea:**
 1. Replace real instructions by bogus instructions
 2. Just before execution, replace bogus instruction with real instruction
 3. After execution, replace real instruction with bogus instruction

- **Motivation:** prevent code recovery via memory snapshot
- **Algorithm idea:**
 1. Replace real instructions by bogus instructions
 2. Just before execution, replace bogus instruction with real instruction
 3. After execution, replace real instruction with bogus instruction
- **Implementation** by choosing 3 points A , B and C in the CFG:
 1. All paths to B must flow through A and all paths from B must flow through C
 2. A replaces bogus instruction at B with real instruction
 3. C replaces real instruction at B with bogus instruction



- **Motivation:** keep code in constant flux

- **Motivation:** keep code in constant flux
- **Algorithm idea:**
 1. Have two or more **functions share the same location in memory**
 2. Create **templates for functions** that share same location
 3. Before a function is called, patch memory using **edit script** to load it

- **Motivation:** keep code in constant flux
- **Algorithm idea:**
 1. Have two or more **functions share the same location in memory**
 2. Create **templates for functions** that share same location
 3. Before a function is called, patch memory using **edit script** to load it
- **Implementation** example for program with 2 functions f_1 and f_2 :
 1. Create template T with the same size as the largest function, i.e. f_1
 2. T contains values at memory offsets which are common for f_1 and f_2 , i.e. offsets 1 and 2
 3. T contains wildcard values at all other memory offsets

	f_1					f_2			
memory offset:	0	1	2	3	4	0	1	2	3
memory value:	b7	48	a0	53	fa	e9	48	a0	33

- **Implementation** example for program with 2 functions f_1 and f_2 :
 1. Create template T with the same size as the largest function, i.e. f_1
 2. T contains values at memory offsets which are common for f_1 and f_2 , i.e. offsets 1 and 2
 3. T contains wildcard values at all other memory offsets

	f_1				
memory offset:	0	1	2	3	4
memory value:	b7	48	a0	53	fa

	f_2			
	0	1	2	3
	e9	48	a0	33

	T				
memory offset:	0	1	2	3	4
memory value:	?	48	a0	?	?

Edit Scripts

$$e_1 = [0 \rightarrow b7, 3 \rightarrow 53, 4 \rightarrow fa]$$
$$e_2 = [0 \rightarrow e9, 3 \rightarrow 33]$$

- **Implementation** example for program with 2 functions f_1 and f_2 :
 1. Create template T with the same size as the largest function, i.e. f_1
 2. T contains values at memory offsets which are common for f_1 and f_2 , i.e. offsets 1 and 2
 3. T contains wildcard values at all other memory offsets
 4. Create **edit scripts** e_1 and e_2 which replace wildcards of T to load the functions f_1 , respectively f_2

	f_1				
memory offset:	0	1	2	3	4
memory value:	b7	48	a0	53	fa


	f_2			
	0	1	2	3
	e9	48	a0	33

	T				
memory offset:	0	1	2	3	4
memory value:	?	48	a0	?	?

Edit Scripts


$$e_1 = [0 \rightarrow b7, 3 \rightarrow 53, 4 \rightarrow fa]$$
$$e_2 = [0 \rightarrow e9, 3 \rightarrow 33]$$

1. Execute current basic block
2. At some point in the current basic block decrypt the next basic block
3. Decryption key could be hash of some other basic block
4. Jump to decrypted basic block
5. Encrypt the previously executed basic block
6. Go to step 1




Source: <http://tigress.cs.arizona.edu/>

1. Execute current basic block
2. At some point in the current basic block decrypt the next basic block
3. Decryption key could be hash of some other basic block
4. Jump to decrypted basic block
5. Encrypt the previously executed basic block
6. Go to step 1




Source: <http://tigress.cs.arizona.edu/>

1. Execute current basic block
2. At some point in the current basic block decrypt the next basic block
3. Decryption key could be hash of some other basic block
4. Jump to decrypted basic block
5. Encrypt the previously executed basic block
6. Go to step 1




Source: <http://tigress.cs.arizona.edu/>

1. Execute current basic block
2. At some point in the current basic block decrypt the next basic block
3. Decryption key could be hash of some other basic block
4. Jump to decrypted basic block
5. Encrypt the previously executed basic block
6. Go to step 1




Source: <http://tigress.cs.arizona.edu/>

1. Execute current basic block
2. At some point in the current basic block decrypt the next basic block
3. Decryption key could be hash of some other basic block
4. Jump to decrypted basic block
5. Encrypt the previously executed basic block
6. Go to step 1



Source: <http://tigress.cs.arizona.edu/>

1. Execute current basic block
2. At some point in the current basic block decrypt the next basic block
3. Decryption key could be hash of some other basic block
4. Jump to decrypted basic block
5. Encrypt the previously executed basic block
6. Go to step 1



Source: <http://tigress.cs.arizona.edu/>

1 Introduction

2 Obfuscation in Theory

3 Obfuscation in Practice

- Static Obfuscation
 - Compiler Optimizations
 - Automated Code Obfuscation
- Software Diversity
- Dynamic Obfuscation

4 The Strength of Obfuscation

5 Hands-on Tutorial

6 Conclusions

According to Collberg et al. [5] we should keep the following 4 factors in mind when choosing obfuscation transformations:

According to Collberg et al. [5] we should keep the following 4 factors in mind when choosing obfuscation transformations:

- **Potency** → comprehensibility of code by humans
 - Time and skills needed to understand how the code works
 - Directly proportional with software complexity and size

According to Collberg et al. [5] we should keep the following 4 factors in mind when choosing obfuscation transformations:

- **Potency** → comprehensibility of code by humans
 - Time and skills needed to understand how the code works
 - Directly proportional with software complexity and size
- **Stealth** → identifiability of obfuscated code
 - Time and computation needed to identify the parts of the code which were obfuscated

According to Collberg et al. [5] we should keep the following 4 factors in mind when choosing obfuscation transformations:

- **Potency** → comprehensibility of code by humans
 - Time and skills needed to understand how the code works
 - Directly proportional with software complexity and size
- **Stealth** → identifiability of obfuscated code
 - Time and computation needed to identify the parts of the code which were obfuscated
- **Resilience** → resistance against automatic deobfuscation
 - Time and computation needed to deobfuscate the code with a software tool
 - Plus resources needed to build such a tool

According to Collberg et al. [5] we should keep the following 4 factors in mind when choosing obfuscation transformations:

- **Potency** → comprehensibility of code by humans
 - Time and skills needed to understand how the code works
 - Directly proportional with software complexity and size
- **Stealth** → identifiability of obfuscated code
 - Time and computation needed to identify the parts of the code which were obfuscated
- **Resilience** → resistance against automatic deobfuscation
 - Time and computation needed to deobfuscate the code with a software tool
 - Plus resources needed to build such a tool
- **Cost** → performance and resource overhead of obfuscation
 - Time overhead added to program execution after obfuscation
 - Size of the obfuscated binary relative to original binary

- **Question:** Which obfuscation transformation is better?

- **Question:** Which obfuscation transformation is better?
- **Answer:** It depends ...

- **Question:** Which obfuscation transformation is better?
- **Answer:** It depends ...
 - What do you want to protect?:
 - intellectual property
 - keys
 - integrity of software

- **Question:** Which obfuscation transformation is better?
- **Answer:** It depends ...
 - What do you want to protect?:
 - intellectual property
 - keys
 - integrity of software
 - What kind of attacker are you facing? (e.g. amateur hacker, professional organization, nation state)

- **Question:** Which obfuscation transformation is better?
- **Answer:** It depends ...
 - What do you want to protect?:
 - intellectual property
 - keys
 - integrity of software
 - What kind of attacker are you facing? (e.g. amateur hacker, professional organization, nation state)
 - What is economically feasible for the attacker? (e.g. static attacks, dynamic attacks)

- **Question:** Which obfuscation transformation is better?
- **Answer:** It depends ...
 - What do you want to protect?:
 - intellectual property
 - keys
 - integrity of software
 - What kind of attacker are you facing? (e.g. amateur hacker, professional organization, nation state)
 - What is economically feasible for the attacker? (e.g. static attacks, dynamic attacks)
 - What is the impact of protection on performance?

- **Question:** Which obfuscation transformation is better?
- **Answer:** It depends ...
 - What do you want to protect?:
 - intellectual property
 - keys
 - integrity of software
 - What kind of attacker are you facing? (e.g. amateur hacker, professional organization, nation state)
 - What is economically feasible for the attacker? (e.g. static attacks, dynamic attacks)
 - What is the impact of protection on performance?
- **Example Scenario:** Protecting a hard-coded password / license key
 - Software: offline game / word processor, costs 50 USD

- **Question:** Which obfuscation transformation is better?
- **Answer:** It depends ...
 - What do you want to protect?:
 - intellectual property
 - keys
 - integrity of software
 - What kind of attacker are you facing? (e.g. amateur hacker, professional organization, nation state)
 - What is economically feasible for the attacker? (e.g. static attacks, dynamic attacks)
 - What is the impact of protection on performance?
- **Example Scenario:** Protecting a hard-coded password / license key
 - Software: offline game / word processor, costs 50 USD
 - **cost** (obfuscation overhead) < 10% performance impact
 - **stealth** less important for this scenario

- **Question:** Which obfuscation transformation is better?
- **Answer:** It depends ...
 - What do you want to protect?:
 - intellectual property
 - keys
 - integrity of software
 - What kind of attacker are you facing? (e.g. amateur hacker, professional organization, nation state)
 - What is economically feasible for the attacker? (e.g. static attacks, dynamic attacks)
 - What is the impact of protection on performance?
- **Example Scenario:** Protecting a hard-coded password / license key
 - Software: offline game / word processor, costs 50 USD
 - **cost** (obfuscation overhead) < 10% performance impact
 - **stealth** less important for this scenario
 - Each user needs a different password / license key
 - **potency** > 50 USD (exclude: professional org., nation state)


- **Question:** Which obfuscation transformation is better?
- **Answer:** It depends ...
 - What do you want to protect?:
 - intellectual property
 - keys
 - integrity of software
 - What kind of attacker are you facing? (e.g. amateur hacker, professional organization, nation state)
 - What is economically feasible for the attacker? (e.g. static attacks, dynamic attacks)
 - What is the impact of protection on performance?
- **Example Scenario:** Protecting a hard-coded password / license key
 - Software: offline game / word processor, costs 50 USD
 - **cost** (obfuscation overhead) < 10% performance impact
 - **stealth** less important for this scenario
 - Each user needs a different password / license key
 - **potency** > 50 USD (exclude: professional org., nation state)
 - Attacker develops automated crack based on symbolic execution
 - **resilience** > 50 USD × Nr. of users not willing to pay

- Interpret program using symbolic values instead of concrete ones

```
int main(int ac, char* av[]) {  
    int a = atoi(av[1]);  
    int b = atoi(av[2]);  
    int c = atoi(av[3]);  
  
    if (a > b)  
        a = a - b  
  
    if (b < 1)  
        c = a + b  
  
    b = 1;  
  
    return 0;  
}
```


- Interpret program using symbolic values instead of concrete ones
- Fork execution on each branch dependent on symbolic values

```
int main(int ac, char* av[]) {  
    int a = atoi(av[1]);  
    int b = atoi(av[2]);  
    int c = atoi(av[3]);  
  
    if (a > b)  
        a = a - b;  
  
    if (b < 1)  
        c = a + b;  
  
    b = 1;  
  
    return 0;  
}
```




- Interpret program using symbolic values instead of concrete ones
- Fork execution on each branch dependent on symbolic values
- Collect *path constraints* for each execution path

```
int main(int ac, char* av[]) {  
    int a = atoi(av[1]);  
    int b = atoi(av[2]);  
    int c = atoi(av[3]);  
  
    if (a > b)  
        a = a - b;  
  
    if (b < 1)  
        c = a + b;  
  
    b = 1;  
  
    return 0;  
}
```




- Interpret program using symbolic values instead of concrete ones
- Fork execution on each branch dependent on symbolic values
- Collect *path constraints* for each execution path
- Get concrete input values from path conditions using SMT solver

```
int main(int ac, char* av[]) {  
    int a = atoi(av[1]);  
    int b = atoi(av[2]);  
    int c = atoi(av[3]);  
  
    if (a > b)  
        a = a - b;  
  
    if (b < 1)  
        c = a + b;  
  
    b = 1;  
  
    return 0;  
}
```




1. Make license input symbolic
2. Indicate distinct statement executed when license key is correct
3. Explore paths until desired instruction (sequence) is found
4. Solve path constraints on paths that lead to desired instruction via SMT solver
5. Find satisfiable path constraints → concrete inputs to bypass check




Are other Attacks Possible via Symbolic Execution?

- Yes! Symbolic execution is a prerequisite for several attacks:
 - Simplify control-flow graph
 - Identify & disable tamper-proofing checks
 - Bypass authentication checks / trigger conditions




Simplifying the CFG (Yadegari et al. [14])

1. Explore paths such that all code is covered
2. Simplify traces using compiler optimization tricks
3. Reconstruct CFG from traces




1. Taint code segment
2. Explore paths until enough self-checks disabled (cyclic checks \rightarrow explore all code)
3. Disable self-checking instructions




- **Common sub-problem:** path exploration
- How do we explore paths of a given program?

- **Common sub-problem:** path exploration
- How do we explore paths of a given program?
- Generate test cases:
 - **Black-box test generation:** Fuzzing, Random testing
 - **White-box test generation:** Symbolic/Concolic execution




VS



- **Strength of obfuscation:** increase in test case generation time


- **Strength of obfuscation:** increase in test case generation time
- **Observation:** Generally, obfuscation does not change input-output behavior
 - No increase in black-box test case generation time

- **Strength of obfuscation:** increase in test case generation time
- **Observation:** Generally, obfuscation does not change input-output behavior
 - No increase in black-box test case generation time
- **Example:**




- **Strength of obfuscation:** increase in test case generation time
- **Observation:** Generally, obfuscation does not change input-output behavior
 - No increase in black-box test case generation time

- **Example:**



- **Observation:** Could be faster to use black-box test generator than white-box

- **Strength of obfuscation:** increase in test case generation time
- **Observation:** Generally, obfuscation does not change input-output behavior
 - No increase in black-box test case generation time
- **Example:**



- **Observation:** Could be faster to use black-box test generator than white-box
- **Conclusion:** Apply obfuscation transformations until white-box slower than black-box test case generation

- **Question:** Why do we need code obfuscation? Just use cryptographic hash

- **Question:** Why do we need code obfuscation? Just use cryptographic hash
- **Example:**

```
if (SHA256(arg[1]) == 0xa49...3793)  
    // do this  
else  
    // do that
```

- **Question:** Why do we need code obfuscation? Just use cryptographic hash
- **Example:**

```
if (SHA256(arg[1]) == 0xa49...3793)  
    // do this  
else  
    // do that
```

- Hard for symbolic execution (SMT solver) to break crypto hash functions

- **Question:** Why do we need code obfuscation? Just use cryptographic hash
- **Example:**

```
if (SHA256(arg[1]) == 0xa49...3793)  
    // do this  
else  
    // do that
```

- Hard for symbolic execution (SMT solver) to break crypto hash functions
- **Answer:**
 - Test case generation is non-invasive attack, i.e. code is read, not changed
 - Obfuscation aims to defend against MATE attacker (can tamper with code)
 - Easy to find and patch-out crypto hash functions

- Number of lines of code
- McCabe cyclomatic complexity
- Nesting complexity
- Data flow complexity
- Object oriented design metrics
- Data structure complexity
- ...

- Number of lines of code
- McCabe cyclomatic complexity
- Nesting complexity
- Data flow complexity
- Object oriented design metrics
- Data structure complexity
- ...
- SAT metrics: Graph metrics on a SAT formula represented as a graph

$$(x + y + z) \cdot (!x + !y + z) \cdot (x + !y + !z)$$





Figure : Before Obfuscation (7.5 sec)



```
1 unsigned int SDBMHash(char* str, unsigned int len)
2 {
3     unsigned int hash = 0;
4     unsigned int i = 0;
5     for(i = 0; i < len; str++, i++)
6         hash = (*str) + (hash << 6)
7             + (hash << 16) - hash;
8     return hash;
9 }
10
11 int main(int argc, char* argv[]) {
12     unsigned char *str = argv[1];
13     unsigned int hash = SDBMHash(str, strlen(str));
14
15     if (hash == 0x89dcd66e)
16         printf("You win!\n");
17     return 0;
18 }
```

Figure : Before Obfuscation (7.5 sec)





Figure : After Obfuscation (438 sec)



Strong obfuscation transformations destroy community structures

- 1 Introduction
- 2 Obfuscation in Theory
- 3 Obfuscation in Practice
 - Static Obfuscation
 - Compiler Optimizations
 - Automated Code Obfuscation
 - Software Diversity
 - Dynamic Obfuscation
- 4 The Strength of Obfuscation
- 5 Hands-on Tutorial**
- 6 Conclusions

Example of bypassing password check in C programs

1. Start with plain unobfuscated program (break with static analysis)
2. Discuss the option of using hash functions (break with patching)
3. Add one obfuscation layer (break with symbolic execution)
4. Add more obfuscation layers (harder to break)

Example of bypassing password check in C programs

1. Start with plain unobfuscated program (break with static analysis)
 2. Discuss the option of using hash functions (break with patching)
 3. Add one obfuscation layer (break with symbolic execution)
 4. Add more obfuscation layers (harder to break)
- Tools we are going to use:
 - We assume you have Docker installed and have basic user knowledge
 - Docker image based on Ubuntu contains: Tigress, KLEE, STP, Z3, SatGraf, etc.

```
$ docker pull banescusebi/obfuscation-symex
```

```
$ docker run -it banescusebi/obfuscation-symex
```
 - For instructions on how to start the Docker image read description at <https://hub.docker.com/r/banescusebi/obfuscation-symex/>
 - Instructions for running GUI apps available for Ubuntu and Mac OS (not mandatory, only needed for SatGraf)

Example C Program with Hard-Coded Password

```
1 #include <stdlib.h>
2 #include <stdio.h>
3 #include <string.h>
4
5 int main(int argc, char* argv[]) {
6     if (strcmp(argv[1],
7         "my_license_key") == 0)
8         printf("You win!\n");
9     return 0;
10 }
```

- Hard-coded password can be found via static analysis

```
$ ./nohash my_license_key
```

```
You win!
```

```
$ strings nohash | grep 'license'
```

```
my_license_key
```

Example C Program where Hard-Coded Password Replaced with Hash

```
1 unsigned int BPHash(char* str, unsigned int len)
2 {
3     unsigned int hash = 0;
4     unsigned int i     = 0;
5     for(i = 0; i < len; str++, i++) {
6         hash = hash << 7 ^ (*str);
7     }
8     return hash;
9 }
10
11 int main(int argc, char* argv[]) {
12     unsigned char *str = argv[1];
13     unsigned int hash = BPHash(str, strlen(str));
14     if (hash == 0x5bfaf2f9)
15         printf("You win!\n");
16     return 0;
17 }
```

- Check can still be disabled using binary patching

```
$ strings bphash | grep 'license'
```

```
$ objdump -D bphash
```

- Use vi in hex editor mode (:%!xxd) to patch check (jne)

- Add one layer of obfuscation:

```
$ tigress --Transform=EncodeArithmetic  
--Functions=DEKHash --out=dekhash-obf/dekhash-encA.c  
dekhash.c
```

```
$ tigress --Transform=Flatten --Functions=DEKHash  
--out=dekhash-obf/dekhash-flat.c dekhash.c
```

```
$ tigress --Transform=Virtualize --Functions=DEKHash  
--out=dekhash-obf/dekhash-virt.c dekhash.c
```


- **Add one layer of obfuscation:**

```
$ tigress --Transform=EncodeArithmetic  
--Functions=DEKHash --out=dekhsh-obf/dekhsh-encA.c  
dekhsh.c
```

```
$ tigress --Transform=Flatten --Functions=DEKHash  
--out=dekhsh-obf/dekhsh-flat.c dekhsh.c
```

```
$ tigress --Transform=Virtualize --Functions=DEKHash  
--out=dekhsh-obf/dekhsh-virt.c dekhsh.c
```

- **Add another layer of obfuscation:**

```
$ tigress --Transform=Flatten --Functions=DEKHash  
--Transform=EncodeArithmetic --Functions=DEKHash  
--out=dekhsh-obf/dekhsh-flat-encA.c dekhsh.c
```

- **Add one layer of obfuscation:**

```
$ tigress --Transform=EncodeArithmetic  
--Functions=DEKHash --out=dekhash-obf/dekhash-encA.c  
dekhash.c
```

```
$ tigress --Transform=Flatten --Functions=DEKHash  
--out=dekhash-obf/dekhash-flat.c dekhash.c
```

```
$ tigress --Transform=Virtualize --Functions=DEKHash  
--out=dekhash-obf/dekhash-virt.c dekhash.c
```

- **Add another layer of obfuscation:**

```
$ tigress --Transform=Flatten --Functions=DEKHash  
--Transform=EncodeArithmetic --Functions=DEKHash  
--out=dekhash-obf/dekhash-flat-encA.c dekhash.c
```

- **Apply symbolic execution** to each of these programs (see KLEE command on next slide)

```
$ ~/scripts/step05-klee-symex-until-win.sh . exe 15
```

```
1 klee --optimize
2 // Optimize before execution
3 --emit-all-errors
4 // Don't stop on first error
5 --libc=uclibc
6 // Choose libc version
7 --posix-runtime
8 // Link with POSIX runtime
9 --only-output-states-covering-new
10 // Only tests covering new code
11 --max-time=3600
12 // Halt after given nr. of sec.
13 --write-smt2s
14 // Write smt2 file per test
15 --output-dir=klee-out-${file_name}
16 // Output directory for tests
17 ./${file_name}.bc
18 // Bitcode file under test
19 --sym-arg 5
20 // Length of symbolic arg.
```

Viewing Results

- See number of nanoseconds needed for KLEE to analyze a bitcode program

```
$ cat klee-time-to-win.txt
```

- Check differences between 1 and 2 layers of obfuscation

Viewing Results

- See number of nanoseconds needed for KLEE to analyze a bitcode program

```
$ cat klee-time-to-win.txt
```

- Check differences between 1 and 2 layers of obfuscation
- Convert the SMT2 instances generated by KLEE into CNF instances

```
$ ~/scripts/step07-convert-smt-to-cnf.sh .  
obfuscated-cnf-instances.txt
```

```
$ ll ./obfuscated-cnf-instances
```

Viewing Results

- See number of nanoseconds needed for KLEE to analyze a bitcode program

```
$ cat klee-time-to-win.txt
```

- Check differences between 1 and 2 layers of obfuscation
- Convert the SMT2 instances generated by KLEE into CNF instances

```
$ ~/scripts/step07-convert-smt-to-cnf.sh .  
obfuscated-cnf-instances.txt
```

```
$ ll ./obfuscated-cnf-instances
```

- View CNF instances in SatGraf:

```
$ java -jar ~/satgraf/dist/SatGraf.jar com -f  
obfuscated-cnf-instances/dekhash-virt.cnf
```

- Check differences between 1 and 2 layers of obfuscation

- 1 Introduction
- 2 Obfuscation in Theory
- 3 Obfuscation in Practice
 - Static Obfuscation
 - Compiler Optimizations
 - Automated Code Obfuscation
 - Software Diversity
 - Dynamic Obfuscation
- 4 The Strength of Obfuscation
- 5 Hands-on Tutorial
- 6 Conclusions

- Theoretical obfuscation offers security guarantees, but is unpractical

- Theoretical obfuscation offers security guarantees, but is unpractical
- Practical obfuscation raises the bar against MATE attackers

- Theoretical obfuscation offers security guarantees, but is unpractical
- Practical obfuscation raises the bar against MATE attackers
- Static obfuscation transformations:
 - Applied on source code, IR or machine code
 - Obfuscated program fixed (doesn't change at runtime)
 - Makes static analysis harder
 - Many transformations available: compiler optimizations, scramble identifiers, instruction substitution, merging & splitting functions, opaque predicates & expressions, control flow flattening, virtualization obfuscation, white-box cryptography, etc.

- Theoretical obfuscation offers security guarantees, but is unpractical
- Practical obfuscation raises the bar against MATE attackers
- Static obfuscation transformations:
 - Applied on source code, IR or machine code
 - Obfuscated program fixed (doesn't change at runtime)
 - Makes static analysis harder
 - Many transformations available: compiler optimizations, scramble identifiers, instruction substitution, merging & splitting functions, opaque predicates & expressions, control flow flattening, virtualization obfuscation, white-box cryptography, etc.
- Software diversity improves potency and resilience against reverse engineering attacks

- Theoretical obfuscation offers security guarantees, but is unpractical
- Practical obfuscation raises the bar against MATE attackers
- Static obfuscation transformations:
 - Applied on source code, IR or machine code
 - Obfuscated program fixed (doesn't change at runtime)
 - Makes static analysis harder
 - Many transformations available: compiler optimizations, scramble identifiers, instruction substitution, merging & splitting functions, opaque predicates & expressions, control flow flattening, virtualization obfuscation, white-box cryptography, etc.
- Software diversity improves potency and resilience against reverse engineering attacks
- Dynamic obfuscation transformations:
 - Program changes during execution
 - Makes dynamic analysis harder
 - Several transformations available: replacing instructions, dynamic code merging, dynamic decryption and re-encryption.

- Theoretical obfuscation offers security guarantees, but is unpractical
- Practical obfuscation raises the bar against MATE attackers
- Static obfuscation transformations:
 - Applied on source code, IR or machine code
 - Obfuscated program fixed (doesn't change at runtime)
 - Makes static analysis harder
 - Many transformations available: compiler optimizations, scramble identifiers, instruction substitution, merging & splitting functions, opaque predicates & expressions, control flow flattening, virtualization obfuscation, white-box cryptography, etc.
- Software diversity improves potency and resilience against reverse engineering attacks
- Dynamic obfuscation transformations:
 - Program changes during execution
 - Makes dynamic analysis harder
 - Several transformations available: replacing instructions, dynamic code merging, dynamic decryption and re-encryption.
- Multiple transformations should be combined to improve strength

Thank you for your attention

Questions ?



S. Banescu, M. Ochoa, A. Pretschner, and N. Kunze.

Benchmarking indistinguishability obfuscation - a candidate implementation.

In *Proc. of 7th International Symposium on ESSoS*, number 8978 in LNCS, 2015.



Boaz Barak.

Hopes, fears, and software obfuscation.

Communications of the ACM, 59(3):88–96, 2016.



Boaz Barak, Oded Goldreich, Russell Impagliazzo, Steven Rudich, Amit Sahai, Salil Vadhan, and Ke Yang.

On the (im) possibility of obfuscating programs.

In *Advances in Cryptology CRYPTO 2001*, pages 1–18. Springer, 2001.



Christian Collberg and Jasvir Nagra.

Surreptitious Software: Obfuscation, Watermarking, and Tamperproofing for Software Protection.

Addison-Wesley, 2009.



Christian Collberg, Clark Thomborson, and Douglas Low.

A taxonomy of obfuscating transformations.




Technical report, Department of Computer Science, The University of Auckland, New Zealand, 1997.



Christian Collberg, Clark Thomborson, and Douglas Low.

Manufacturing cheap, resilient, and stealthy opaque constructs.

In *Proceedings of the 25th ACM SIGPLAN-SIGACT symposium on Principles of programming languages*, POPL '98, pages 184–196, New York, NY, USA, 1998. ACM.

-  M. Dalla Preda, M. Madou, K. De Bosschere, and R. Giacobazzi.
Opaque predicates detection by abstract interpretation.
In Michael Johnson and Varmo Vene, editors, *Algebraic Methodology and Software Technology*, volume 4019 of *Lecture Notes in Computer Science*, pages 81–95. Springer Berlin Heidelberg, 2006.
-  S. Garg, C. Gentry, S. Halevi, M. Raykova, A Sahai, and B. Waters.
Candidate indistinguishability obfuscation and functional encryption for all circuits.
In *Proc. of the 54th Annual Symp. on Foundations of Computer Science*, pages 40–49, 2013.
-  S. Goldwasser and G. N. Rothblum.
On best-possible obfuscation.
In *Theory of Cryptography*, pages 194–213. Springer, 2007.



Yuichiro Kanzaki, Akito Monden, Masahide Nakamura, and Ken-ichi Matsumoto.

Exploiting self-modification mechanism for program protection.

In *Computer Software and Applications Conference, 2003.*

COMPSAC 2003. Proceedings. 27th Annual International, pages 170–179, 2003.



J. Kinder.

Towards static analysis of virtualization-obfuscated binaries.

In *19th Working Conference on Reverse Engineering (WCRE)*, pages 61–70, Oct 2012.



Matias Madou, Bertrand Anckaert, Patrick Moseley, Saumya Debray, Bjorn De Sutter, and Koen De Bosschere.

Software protection through dynamic code mutation.

In *Information Security Applications*, pages 194–206. Springer, 2006.



Jing Qiu, Babak Yadegari, Brian Johannismeyer, Saumya Debray, and Xiaohong Su.

Identifying and understanding self-checksumming defenses in software.

In Proceedings of the 5th ACM Conference on Data and Application Security and Privacy, pages 207–218. ACM, 2015.



Babak Yadegari, Brian Johannismeyer, Ben Whitely, and Saumya Debray.

A generic approach to automatic deobfuscation of executable code.

In Security and Privacy (SP), 2015 IEEE Symposium on, pages 674–691. IEEE, 2015.