RouteRec: Behavior-Guided Sparse Routing for Sequential Recommendation

Anonymous Author(s)

Abstract

In sessionized sequential recommendation, sessions are short but cross-session history is available. This brevity sharpens behavioral differences across sessions: some sessions are repeat-heavy, others fast and exploratory, others narrowly focused. Existing models use this behavioral context to enrich the sequence representation — improving *what the model encodes*. We ask whether behavioral context should instead determine *which computation path* the model applies, and what observable signal should drive that routing decision.

RouteRec pursues this direction with Mixture of Experts (MoE). The central design choice is the routing input. Hidden states summarize the sequence but are optimized for prediction, not for encoding behavioral regime, and they confound representation with routing control in the same latent vector. RouteRec instead computes *behavioral cues* — compact statistics derived directly from interaction logs — and routes on them through a control path kept strictly separate from the sequential backbone. This separation makes the routing input explicit, grounds route choices in observable quantities, and keeps representation and routing control from interfering. RouteRec extracts cues at macro, mid, and micro temporal scopes and applies hierarchical sparse expert allocation to concentrate computation on a small, focused expert subset.

In the main seen-target comparison across six datasets under a shared sessionized temporal protocol, RouteRec achieves the best overall Avg. Rank of 1.67, versus 3.56 for the next best baseline. Gains are clearest on Foursquare, LastFM, and KuaiRec, and diagnostics confirm more behavior-consistent expert selection. Anonymous code: https://anonymous.4open.science/r/RouteRec/.

CCS Concepts

• **Information systems** → **Recommender systems**.

Keywords

sequential recommendation, sparse routing, conditional computation, behavioral cues, mixture of experts

ACM Reference Format:
Anonymous Author(s). 2026. RouteRec: Behavior-Guided Sparse Routing for Sequential Recommendation. In *Proceedings of the 20th ACM Conference on Recommender Systems (RecSys '26), September 28–October 2, 2026, Minneapolis, MN, USA.* ACM, New York, NY, USA, 20 pages.

1 Introduction

Session-based sequential recommendation models next-item prediction from interactions divided into temporally bounded sessions [16]. Sessions are short, and this brevity makes the structural character of each session particularly pronounced: a session built on rapid revisits to familiar items looks structurally different from one that sweeps across diverse categories in quick succession, even when both users share similar long-run preferences. These differences — in interaction pace, repetition, category focus, and popularity exposure — are directly observable from interaction logs and vary consistently across users and time [42].



Figure 1: Motivating example: sessions with different structural character can still receive the same shared computation.

Figure 1 illustrates the central gap: sessions with clearly different structural character can still pass through the same shared transformation. Existing work has addressed behavioral heterogeneity primarily by enriching the sequence representation. Time-aware self-attention [25] embeds interval structure into the backbone. Contrastive objectives [32] and frequency-aware inductive biases [7, 38] shape the representation geometry. Feature-aware models [45, 50] incorporate side information into the encoding path, and cross-session context has been brought in through hierarchical architectures [33] and session-aware extensions [1]. These approaches improve *what the model represents*. They still apply the same transformation to all prefixes, regardless of structural differences across sessions. Whether behavioral context should also determine *which transformation the model applies* — rather than only enriching the representation that a single shared block processes — is a question these approaches do not address.

Conditional computation — executing only a data-dependent subset of model parameters — makes this question concrete. We ask: in sessionized sequential recommendation with accessible cross-session history, can explicit behavioral cues from interaction logs serve as the control signal for *which computation path* the model applies, rather

RecSys '26, Minneapolis, MN, USA
2026.

than only as inputs for representation enrichment? We do not treat a different computation path as a necessary requirement. The question is a design one: *given conditional computation, what observable signal should drive routing?*

Mixture of Experts (MoE) [15, 18] provides the mechanism: a router that selects which subset of expert modules processes each input, rather than passing all inputs through the same shared transformation. Sparse MoE [6, 8, 37, 52] makes that selection efficient by activating only a small subset at a time. Once MoE is introduced, the routing input becomes a substantive design choice. The natural default is to route from hidden states, since they summarize the sequence. But hidden states are optimized for prediction, not for encoding the behavioral regime of a session — its observable structural character, such as repeat-heavy consumption or fast exploratory browsing. Routing from hidden states also confounds two roles in the same vector: the quantity that drives expert selection is identical to the quantity being shaped by that selection, so the behavioral basis of any given route remains implicit. In short sessions, this is further compounded because the hidden state may not yet reflect cross-session behavioral character when routing decisions are made.

A separate routing control path avoids this confound. RouteRec keeps two channels distinct: the sequential backbone encodes the sequence for next-item prediction, while a dedicated routing control path computes compact scalar summaries — *behavioral cues* — directly from interaction logs and uses them to select experts. Behavioral cues are organized into four families that cover the main observable dimensions of session structure: Tempo (interaction pace and interval dynamics), Focus (category concentration and switching), Memory (repetition and recurrence patterns), and Exposure (popularity level and drift). Because cues are observable statistics rather than learned latent values, route changes can be traced back to specific behavioral quantities visible in the log — an advantage of the separation, not an independent design claim. Cues are computed at three temporal scopes because cross-session history, within-session progression, and short-term local transitions each expose different kinds of behavioral evidence.

Instantiating this design raises three concrete tensions. Behavioral cues must remain portable across datasets where only item identities, timestamps, and sometimes coarse category labels are available, yet still be informative enough to differentiate computation paths. Routing decisions must be separated by temporal scope so that slow cross-session tendency and fast local dynamics each get a distinct control view. And expert selection must be sparse enough to produce real routing differences across sessions, rather than collapsing into a soft shared mixture that differs little from a shared transformation.

RouteRec addresses each tension directly. It constructs behavioral cues from the minimal signals present in ordinary interaction logs, organizes routing across macro, mid, and micro temporal scopes, and uses hierarchical sparse expert allocation to enforce *route commitment* — the property that routing concentrates on a small, focused expert subset rather than spreading weight broadly. The sequential backbone remains intact for prediction; the computation path is governed separately by observable behavioral cues.

The main contributions of this work are:

- We identify the routing input as a substantive design decision in sessionized sequential recommendation: once MoE introduces conditional computation, routing from hidden states versus explicit behavioral cues is a choice with direct consequences for routing control, expert specialization, and inspectability.
- We propose RouteRec, which separates a sequential backbone for prediction from a routing control path that reads behavioral cues directly from interaction logs — keeping representation and routing control strictly distinct.
- We instantiate this design with three components — Behavioral Cue Construction, Coarse-to-Fine Multi-Stage Routing, and Hierarchical Sparse Expert Allocation — that together make routing grounded, multi-scope, and committed.
- Empirically, RouteRec achieves the best overall Avg. Rank in the main seen-target comparison across six datasets under a shared sessionized temporal protocol, with the clearest gains on Foursquare, LastFM, and KuaiRec.

2 Related Work

2.1 Session-based and Sequential Recommendation

Sequential recommendation predicts the next item from an ordered interaction history [43]. Session-based recommendation is a closely related setting in which those interactions are partitioned into short temporally bounded sessions and prediction is made from the current session context [16, 42]. Earlier models established the main sequence-modeling backbone families for this problem: FPMC [35] factorized personalized Markov transitions, Caser [41] and NextItNet [48] applied convolutional sequence modeling, and GRU4Rec [13] showed that recurrent models can learn strong session dynamics. NARM [24], STAMP [27], and SR-GNN [44] then emphasized session intent, short-term memory, and transition structure more explicitly.

Transformer-based models such as SASRec [19] and BERT4Rec [39] became strong general backbones for sequential recommendation. More recent work adds stronger inductive biases through contrastive regularization [14, 32], frequency-aware modeling [7, 38], and selective state-space backbones [28]. These models differ substantially in how they encode the sequence. They still apply a shared computation path to all prefixes. For short sessions with visibly different structural character, this leaves open whether the model should adapt only its representation or also its computation path.

2.2 Behavioral Context and Router Inputs

Behavioral heterogeneity across sessions is a recognized issue in the recommendation literature. Hierarchical and session-aware models such as HRNN [33], SHAN [47], and more recent hybrid session architectures [1] separate broader preference context from within-session dynamics. Time-aware self-attention [25] injects interval structure into the backbone. Feature-aware models such as FDSA [50] and DIF-SR [45] incorporate side information to refine the sequence representation. RepeatNet [34] and ICSRec [31] focus on repetition and evolving intent. Multi-interest models such as MIND [23] and ComiRec [5] represent user behavior through multiple latent interests within a single forward pass.

Across these lines of work, behavioral context is used to improve what the model represents — injected into hidden states, attention patterns, or auxiliary branches — while the computation applied to each prefix remains shared. RouteRec asks a different question: whether compact scalar summaries of session structure, derived directly from interaction logs without enriching the representation, should instead control *which* expert subset is activated for each prefix.

2.3 Mixture of Experts in Recommendation

Mixture of Experts (MoE) [15, 18] replaces a shared transformation with a set of expert modules, each activated selectively by a learned router. Sparse MoE [8, 37] makes this conditional computation efficient by activating only a small subset of experts per input. In recommendation, MMoE [29] and PLE [40] use expert decomposition mainly for multi-task learning, where different tasks benefit from different expert subsets. More recent recommendation models such as FAME [26], M3SRec [2], and HM4SR [49] also introduce experts, but routing is typically driven by learned hidden representations or modality-specific states rather than by explicit behavioral cues computed from the interaction log.

Work on sparse MoE mechanics, including expert choice routing [51] and z-loss stabilization [52], improves how sparse activation is executed. It does not determine what the router should read. That choice is especially important in session-based sequential recommendation because routing decisions must often be made from short prefixes whose hidden states need not yet expose cross-session behavioral character clearly. RouteRec targets this gap by defining behavioral cues directly from interaction logs and by keeping the routing control path separate from the representation path.

3 Problem Setting and Design Challenges

3.1 Problem Setup

For each user, let $\mathcal{S}_u = [s_1, \ldots, s_M]$ denote the chronologically ordered session sequence. A session $s_m = [x_{m,1}, \ldots, x_{m,L_m}]$ contains ordered interactions, where each interaction includes at least an item identity and timestamp, and may additionally include a coarse grouping field such as category, genre, or artist. At prediction time, the observed context is the current-session prefix together with earlier sessions. When the session index is clear, we write the current prefix as $x_{1:t}$ and the next target as x_{t+1}.

The task is next-item prediction: given the observed history up to position t in session s_m, the model predicts x_{t+1}. RouteRec uses only signals commonly available after sessionization — item identity, timestamp, optional coarse grouping label, and corpus-level popularity statistics computed from training data. No heavy side-information encoders or auxiliary supervision are required.

3.2 Design Challenges

Using behavioral cues from interaction logs as the explicit routing input — rather than hidden states — raises three design tensions. Each must be resolved for cue-driven routing to produce meaningful computation differences across sessions, rather than simply adding a routing step that leaves behavior largely unchanged.

C1. Portability versus informativeness. Behavioral cues must be computable from whatever signals are reliably present across datasets. In practice, this is narrow: item identities, timestamps, and sometimes a coarse grouping field such as category or genre. A cue derived from this restricted set risks carrying too little behavioral signal to differentiate computation paths; a cue that requires richer side information is unavailable in most benchmark settings. Constructing cues that are both portable and informative enough to support route differences is the first tension.

C2. Scope alignment of behavioral evidence. Behavioral evidence emerges at different temporal ranges. Cross-session repetition and drift are visible only over multiple past sessions; within-session category concentration builds across a few minutes of activity; local transition patterns appear only in the last few interactions before the prediction target. A single routing view that draws on all these ranges simultaneously produces a cue that conflates slow structural tendency with fast local dynamics, and cannot respond distinctly to either. Routing decisions must be separated by the temporal scope at which each kind of evidence becomes a reliable signal.

C3. Route commitment versus coverage. Even with explicit cue-driven routing, behavior-dependent computation collapses if routing spreads weight broadly across experts. The model then reduces to a soft shared mixture regardless of the cue: a repeat-heavy session and a fast-exploratory one are routed almost identically, and the value of cue-driven routing is lost. Expert selection must be sparse enough to concentrate computation on a small, focused subset — producing real routing differences across sessions — while retaining enough coverage to handle the full range of behavioral regimes observed in practice.

The following section addresses each tension: behavioral cue construction (C1), multi-stage routing separated by temporal scope (C2), and hierarchical sparse expert allocation (C3).

4 Method

4.1 RouteRec Overview

Figure 2 summarizes RouteRec at the framework level. RouteRec retains a strong sequential backbone for sequence encoding, but replaces shared feed-forward computation with behavior-guided routing stages. The model follows the two-path design motivated in Section 1: hidden states remain the representation channel for prediction, while a separate routing control path computes behavioral cues from observable history and uses them to select experts.

Let $\mathcal{T} = \{\text{macro}, \text{mid}, \text{micro}\}$ be the routing-stage set. These stages correspond to broad cross-session, within-session, and local evidence scopes. Let $\mathbf{h}_t^{\text{in},(s)}$ denote the hidden state entering stage $s \in \mathcal{T}$, and let $\mathbf{f}_t^{(s)}$ denote the cue vector supplied to that stage. The common routing interface is

$$\boldsymbol{\pi}_t^{(s)} = \text{softmax}\Big(\text{Router}_s(\mathbf{f}_t^{(s)})/\tau_s\Big), \tag{1}$$

$$\tilde{\mathbf{h}}_t^{(s)} = \sum_{e=1}^{E} \pi_{t,e}^{(s)} \, \text{Expert}_e^{(s)}(\mathbf{h}_t^{\text{in},(s)}), \tag{2}$$

where E is the number of experts at stage s, τ_s is a routing temperature, and $\boldsymbol{\pi}_t^{(s)}$ is the expert-weight vector. This interface is shared across stages. What changes across stages is the behavioral evidence used for routing and the way the routed computation is organized.

The rest of the method turns the design challenges in Section 3 into a concrete model. Section 4.2 constructs behavioral cues from interaction logs. Section 4.3 organizes routing across macro, mid, and micro scopes. Section 4.4 defines hierarchical sparse expert allocation so that routing stays focused on a small expert subset rather than diffusing broadly. In the main configuration, only a limited number of expert groups and experts is active at each routing decision.

We first present RouteRec as a design framework and refer to the main experimental configuration only when implementation details matter. Alternative variants and broader structural sweeps are deferred to the appendix.

4.2 Route-Guiding Behavioral Cues

To make route guidance available under realistic data conditions, RouteRec uses signals commonly present in interaction logs: item identity, timestamp, optional coarse item-group labels, and corpus-level popularity statistics. These cues are not meant to be optimal predictive features on their own. Their role is narrower: they provide compact observable proxies for when behavior warrants a different computation path. We therefore avoid heavy side-information encoders in the routing branch and instead use compact scalar summaries that remain easy to compute and inspect.

For session s_m and target position t, the stage windows are

$$\mathcal{R}_t^{\text{macro}} = [s_{\max(1,m-H)}, \ldots, s_{m-1}], \tag{3}$$

$$\mathcal{R}_t^{\text{mid}} = [x_1, \ldots, x_{t-1}], \tag{4}$$

$$\mathcal{R}_t^{\text{micro}} = [x_{\max(1,t-w)}, \ldots, x_{t-1}], \tag{5}$$

where $H = 5$ and $w = 5$ in our main setting. These are the default paper windows used throughout the main experiments, and their role is revisited in the structural ablations in Appendix E. A shared summary operator $\mathcal{A}(\cdot)$ maps each window to a low-dimensional feature vector:

$$\mathbf{f}_t^{(s)} = \mathcal{A}(\mathcal{R}_t^{(s)}), \qquad s \in \mathcal{T}.$$

The summary dimensions are grouped into four semantic families: *Tempo*, *Focus*, *Memory*, and *Exposure*. Tempo captures coverage, pace, and interval dynamics. Focus captures concentration and switching behavior over the coarsest item-group proxy available in the dataset, such as product category, venue category, artist grouping, or genre. Memory captures repetition, overlap, and recurrence structure. Exposure captures the level, spread, and drift of interacted popularity. In the main configuration, this family template yields a compact 16-dimensional cue bank per stage. When such grouping fields are unavailable, the corresponding focus cues are handled by the fixed missing-signal rule documented in Appendix A. Representative examples are listed in Table 4.

The template is shared across stages, but each stage reads it through a different temporal lens: macro reflects persistent tendency, mid tracks evolving within-session intent, and micro emphasizes short-horizon cues near the prediction target. The goal is not exhaustive feature engineering, but a small semantically legible cue bank that serves as a stable routing interface across datasets. Appendix A records the representative cue definitions and main paper setting.

4.3 Coarse-to-Fine Multi-Stage Routing

To keep routing aligned with temporal scope, the stages are not redundant even though the router formula is shared. They differ in temporal evidence, routing granularity, and placement inside the backbone. In the main experimental configuration, the serial layout is

$$\underbrace{\text{self-attn}}_{\text{context}} \rightarrow \text{macro} \rightarrow \text{mid} \rightarrow \underbrace{\text{self-attn}}_{\text{refresh}} \rightarrow \text{micro}.$$

Let $\mathbf{h}_t^{(0)}$ denote the hidden state after the first attention block, $\mathbf{h}_t^{(1)}$ after macro routing, $\mathbf{h}_t^{(2)}$ after mid routing, and $\mathbf{h}_t^{(3)}$ after the second attention block. Macro, mid, and micro therefore consume $\mathbf{h}_t^{(0)}$, $\mathbf{h}_t^{(1)}$, and $\mathbf{h}_t^{(3)}$, respectively. The order is deliberate: the first attention block provides a contextualized sequence state for the slower macro and mid routing decisions, whereas the second refreshes token interactions immediately before the local micro router. Appendix E reports the broader layout ablations.



Figure 2: Overall RouteRec framework. Read left to right: panel (a) shows stage-specific cue extraction, panel (b) shows the serial backbone, and panel (c) shows hierarchical sparse expert selection. RouteRec keeps a strong sequential backbone and replaces shared feed-forward blocks with behavior-guided sparse routing stages. All stages use the same hierarchical sparse routing principle: group-level scores select a subset of semantic groups, then conditional intra-group scores select a subset of experts inside each chosen group before forming the active expert mixture. Macro, mid, and micro differ by temporal evidence scope and routing granularity, not by the basic sparse routing logic. This is a framework-level view; the exact serial configuration used in the main experiments is specified in Section 4.3 and Appendix A.

Macro and mid (sequence-wise routing). Macro and mid compute one routing distribution per sequence from their respective windows, then broadcast it over valid positions inside the sequence. Macro uses broader cross-session history; mid uses within-session prefix evidence. This setting emphasizes stable allocation for slower-changing context, where token-wise routing tended to add variance without introducing an equally meaningful control resolution in our ablations.

Micro (position-wise routing). Micro computes routing per token near the prediction target using short-horizon context. This enables fast adaptation to immediate transitions without changing the router form itself.

Formally, let $\bar{\mathbf{f}}_i^{(s)}$ denote the sequence-level cue summary used for sequence-wise routing at stage s. Then macro and mid use

$$\bar{\boldsymbol{\pi}}_i^{(s)} = \mathrm{softmax}\Big(\mathrm{Router}_s(\bar{\mathbf{f}}_i^{(s)})/\tau_s\Big), \qquad s \in \{\mathrm{macro}, \mathrm{mid}\},$$

$$\boldsymbol{\pi}_{i,t}^{(s)} = \bar{\boldsymbol{\pi}}_i^{(s)}.$$

Micro instead applies the same router form directly to position-specific cues,

$$\boldsymbol{\pi}_{i,t}^{(\mathrm{micro})} = \mathrm{softmax}\Big(\mathrm{Router}_{\mathrm{micro}}(\mathbf{f}_{i,t}^{(\mathrm{micro})})/\tau_{\mathrm{micro}}\Big).$$

Hence, RouteRec's coarse-to-fine behavior comes from stage evidence scope and update frequency, while the underlying router composition remains constant. The stages are therefore not repeated copies of the same router; they correspond to different temporal horizons at which behavioral evidence becomes informative for computation allocation. Because each stage captures a distinct control view, the final model uses sparse route commitment so that only a small subset of stage-relevant groups and experts is activated at each decision.

4.4 Hierarchical Sparse Expert Allocation

To structure expert selection rather than merely enlarge capacity, the final RouteRec architecture uses one shared hierarchical sparse composition at every stage. Experts are partitioned into G groups with C experts per group, so

$E = GC$. For stage s and position t, the router produces

$$p_{t,g}^{(s)} = \mathrm{softmax}_g\left(z_{t,g}^{(s)}\right), \tag{6}$$

$$r_{t,g,c}^{(s)} = \mathrm{softmax}_c\left(u_{t,g,c}^{(s)}\right), \tag{7}$$

where $p_{t,g}^{(s)}$ is a group-level routing distribution and $r_{t,g,c}^{(s)}$ is a conditional within-group routing distribution. The final expert probability is their product:

$$\pi_{t,g,c}^{(s)} = p_{t,g}^{(s)}\, r_{t,g,c}^{(s)}, \tag{8}$$

followed by flattening (g, c) to expert index e. Eq. (8) is the same for macro, mid, and micro at the score level.

In the main configuration, groups are aligned with the four cue families, while multiple experts expand capacity within each group. This is a router-level semantic prior rather than a hard hand assignment of individual cues to experts. All three stages use the same feature-driven group-conditional router: a group-level router selects the relevant semantic control view, and a within-group router allocates capacity inside that view.

The final paper configuration adopts sparse activation at both routing levels. For compactness, let $\mathrm{TopK}(\mathbf{v}, k)$ denote the index set of the k largest entries of a vector $\mathbf{v}$. We first keep only the top-k_g groups,

$$\bar{p}_{t,g}^{(s)} = \frac{p_{t,g}^{(s)}\, \mathbf{1}[g \in \mathrm{TopK}(\mathbf{p}_t^{(s)}, k_g)]}{\sum_{g'} p_{t,g'}^{(s)}\, \mathbf{1}[g' \in \mathrm{TopK}(\mathbf{p}_t^{(s)}, k_g)]}, \tag{9}$$

and then, inside each retained group, only the top-k_e experts,

$$\bar{r}_{t,g,c}^{(s)} = \frac{r_{t,g,c}^{(s)}\, \mathbf{1}[c \in \mathrm{TopK}(\mathbf{r}_{t,g,:}^{(s)}, k_e)]}{\sum_{c'} r_{t,g,c'}^{(s)}\, \mathbf{1}[c' \in \mathrm{TopK}(\mathbf{r}_{t,g,:}^{(s)}, k_e)]}. \tag{10}$$

The executed expert route is then

$$\hat{\pi}_{t,g,c}^{(s)} = \bar{p}_{t,g}^{(s)}\, \bar{r}_{t,g,c}^{(s)}, \tag{11}$$

and the stage output uses only the active experts:

$$\tilde{\mathbf{h}}_t^{(s)} = \sum_{g=1}^{G} \sum_{c=1}^{C} \hat{\pi}_{t,g,c}^{(s)}\, \mathrm{Expert}_{g,c}^{(s)}(\mathbf{h}_t^{\mathrm{in},(s)}). \tag{12}$$

In the main experimental configuration, $G = 4$ cue-aligned groups and $C = 3$ experts per group. We choose $k_g = 3$ and $k_e = 2$, so each routing decision activates $3 \times 2 = 6$ experts out of 12 total experts. The semantic group prior therefore remains soft at the score level, but the executed computation path is explicitly sparse.

Sparse routing is introduced not only to reduce computation but also to enforce route commitment and sharpen specialization around a small active set. The hierarchical factorization keeps that selection interpretable by organizing it around semantic control views, while the experts themselves remain fully learned. Dense soft mixing is treated as an ablation variant rather than the final choice.

4.5 Training Objective

RouteRec is trained with a standard next-item objective and two router-side regularizers in the main paper configuration: route consistency and z-loss.

Let $\mathbf{z}$ be final logits and y be the target item. The main loss is

$$\mathcal{L}_{\mathrm{CE}} = -\log \frac{\exp z_y}{\sum_j \exp z_j}.$$

For route consistency, we first compute a sample-level routing distribution at each stage by averaging token-level routing weights:

$$\bar{\boldsymbol{\pi}}_i^{\,s} = \frac{1}{L_i} \sum_{t=1}^{L_i} \boldsymbol{\pi}_{i,t}^{\,s}$$

where L_i is the valid sequence length. We also form a stage-level cue summary

$$\bar{\mathbf{f}}_i^{\,s} = \frac{1}{L_i} \sum_{t=1}^{L_i} \mathbf{f}_{i,t}^{\,s}.$$

For each stage s, we construct a pair set $\mathcal{P}_s$ from the k_{nn} nearest non-self samples in the mini-batch according to cosine similarity between these stage-level cue summaries, and minimize

$$\mathcal{L}_{\mathrm{cons}} = \frac{1}{|\mathcal{T}|} \sum_{s \in \mathcal{T}} \frac{1}{|\mathcal{P}_s|} \sum_{(i,j) \in \mathcal{P}_s} \mathrm{JSD}\big(\bar{\boldsymbol{\pi}}_i^{\,s}, \bar{\boldsymbol{\pi}}_j^{\,s}\big),$$

which encourages neighboring behavioral states to produce compatible routing distributions. Appendix A reports the neighbor setting used in the main configuration. To stabilize gating numerics, we adopt z-loss on the pre-softmax expert logits $a_{i,t,e}^{s}$ [52]:

$$\mathcal{L}_z = \frac{1}{|\mathcal{T}|} \sum_{s \in \mathcal{T}} \frac{1}{N_s} \sum_{(i,t) \in \mathcal{V}_s} \left(\log \sum_{e=1}^{E} \exp a_{i,t,e}^{s} \right)^2,$$

where $\mathcal{V}_s$ is the set of valid positions and $N_s = |\mathcal{V}_s|$. The final objective is

$$\mathcal{L} = \mathcal{L}_{\mathrm{CE}} + \lambda_{\mathrm{cons}}\, \mathcal{L}_{\mathrm{cons}} + \lambda_z\, \mathcal{L}_z,$$

where λ_{cons} and λ_z are trade-off coefficients. Unlike classical MoE setups that explicitly enforce uniform expert traffic, the main configuration does not include load balancing. The aim is stable, behavior-aligned specialization rather than equal usage for its own sake. Appendix F reports the objective variants.

5 Experiments

5.1 Experimental Setup

We evaluate RouteRec on six public datasets spanning e-commerce, POI recommendation, short-video consumption, music listening, movie preference, and anonymous clickstream behavior: Beauty, Foursquare, KuaiRec, LastFM, ML-1M, and Retail Rocket. Appendix B summarizes their provenance and processed statistics.

Across datasets, we use a sessionized temporal protocol assembled from established session-based and session-aware practice rather than a canonical raw-sequence leaderboard setting [16, 22, 33]. Interactions are ordered chronologically, sessionized with inactivity heuristics, and iteratively filtered to remove sessions shorter than 5 and items with fewer than 3 interactions [24, 44]. We use a 30-minute threshold for

Foursquare, KuaiRec, LastFM, ML-1M, and Retail Rocket, and a 14-day threshold for the much sparser Beauty review stream [3, 20, 33]. KuaiRec and LastFM are reported on processed sampled subsets (20% and 3%, respectively). After preprocessing, sessions are sorted by start time and split chronologically into 70%/15%/15% train/validation/test partitions. Appendix B gives the full preprocessing and held-out cleanup details [11, 17].

Our main comparison uses the seen-target view, since ID-based recommendation models cannot rank items absent from the training vocabulary and session-aware benchmarks typically treat unseen targets as supplementary accounting rather than the primary comparison [22, 24, 44]. We compare against GRU4Rec, SASRec, TiSASRec, DuoRec, FEARec, BSARec, FAME, DIF-SR, and FDSA [7, 13, 19, 25, 26, 32, 38, 45, 50]. All methods use the same processed files, the same optimization family, matched early stopping, and the same model-selection rule.

We treat tuning as part of the protocol rather than as a secondary implementation detail. Each model is searched within a fixed bounded grid of shared optimization hyperparameters plus a small number of model-specific controls, and any adaptive search remains restricted to those predeclared candidate sets and the same validation files and stopping rule for all methods [9]. RouteRec uses no extra held-out sessions or external metadata at evaluation time; its routing cues are deterministic summaries of the same observed histories used by every method. Appendix B reports the exact grids, budgets, processed statistics, and full $k \in \{5, 10, 20\}$ tables.

The main experimental section is organized around five questions: **Q1)** ranking quality, **Q2)** routing control, **Q3)** design justification, **Q4)** practicality, and **Q5)** routing semantics. Reduced-cue portability studies and broader structural sweeps are deferred to the appendix.

This organization is deliberate for the paper narrative. Q1 establishes whether behavior-guided routing is worth considering at all under a shared sessionized protocol, Q2 and Q3 test whether the gain is actually tied to routing control and staged structure, Q4 checks whether that design remains practical once sparsity is enforced, and Q5 returns to the original semantic claim by asking whether the learned routes vary in the way the method intends.

5.2 Q1. Does RouteRec Improve Ranking Quality?

Table 1 presents the main seen-target comparison in the text using HR@10, NDCG@10, and MRR@20, together with an Avg. Rank summary across all reported rows. This presentation keeps the main paper focused on a compact set of representative cutoffs, while Appendix B reports the full $k \in \{5, 10, 20\}$ grid under the same selection rule. Under this view, RouteRec delivers the strongest overall rank, leads on Foursquare, LastFM, and the sampled KuaiRec subset, remains close to the top on Beauty and Retail Rocket, and

Table 1: Seen-target test results under the sessionized temporal protocol. Datasets marked with † are sampled processed subsets (KuaiRec 20%, LastFM 3%). For each method, we report the seen-target test metrics of the run achieving the highest mean seen-target test score over the nine reported metrics. Avg. Rank is computed over all rows in this table, where lower is better. The RouteRec column is shaded for readability.

Dataset	Metric	SASRec	GRU4Rec	TiSASRec	FEARec	DuoRec	BSARec	FAME	DIF-SR	FDSA	RouteRec
Beauty	HR@10	0.1324	0.0840	0.1235	0.1404	0.1347	0.0726	0.0497	0.1165	0.1318	**0.1561**
	NDCG@10	0.0800	0.0457	0.0831	0.0797	0.0793	0.0504	0.0303	0.0811	0.0918	**0.0948**
	MRR@20	0.0659	0.0361	0.0735	0.0634	0.0662	0.0450	0.0250	0.0716	**0.0822**	0.0794
Retail Rocket	HR@10	0.5321	0.5048	0.5131	0.5487	0.5478	0.4655	0.4612	0.4322	0.5343	**0.5608**
	NDCG@10	0.3907	0.3674	0.3755	0.3998	0.3994	0.3957	0.3943	0.3863	0.3848	**0.4148**
	MRR@20	0.3507	0.3290	0.3368	0.3581	0.3576	**0.3745**	0.3738	0.3709	0.3427	0.3737
Foursquare	HR@10	0.3049	0.2180	0.2976	0.3054	0.3195	0.2383	0.2417	0.3032	0.3042	**0.3215**
	NDCG@10	0.1929	0.1476	0.1926	0.1925	0.1970	0.1609	0.1604	0.2008	0.2014	**0.2042**
	MRR@20	0.1624	0.1286	0.1635	0.1613	0.1631	0.1393	0.1378	0.1723	**0.1726**	0.1715
ML-1M	HR@10	0.1423	0.1456	0.1448	0.1490	0.1555	0.1374	0.1533	0.0669	**0.1606**	0.1568
	NDCG@10	0.0717	0.0778	0.0756	0.0736	0.0810	0.0723	0.0818	0.0331	**0.0833**	0.0807
	MRR@20	0.0555	0.0621	0.0600	0.0559	0.0641	0.0570	0.0651	0.0256	**0.0655**	0.0631
LastFM†	HR@10	0.3775	0.3109	0.3715	0.3876	0.3850	0.3475	0.3359	0.3593	0.3762	**0.3965**
	NDCG@10	0.3097	0.2676	0.3029	0.3187	0.3066	0.3044	0.2972	0.3169	0.3247	**0.3307**
	MRR@20	0.2897	0.2558	0.2831	0.2981	0.2833	0.2915	0.2861	0.3051	0.3103	**0.3113**
KuaiRec†	HR@10	0.3284	0.3061	0.3216	0.3513	0.3468	0.3359	0.3307	0.2333	0.3453	**0.3669**
	NDCG@10	0.3177	0.2589	0.2889	0.3286	0.3215	0.3209	0.3188	0.2229	0.3197	**0.3467**
	MRR@20	0.3150	0.2462	0.2802	0.3227	0.3153	0.3170	0.3160	0.2201	0.3133	**0.3425**
Avg. Rank↓		**6.06**	**8.67**	**6.61**	**4.22**	**4.17**	**6.61**	**6.72**	**6.72**	**3.56**	**1.67**



(a) Dynamic-dataset group: same five controls

(b) Stable/mixed-dataset group: same five controls

Figure 3: Routing-control comparison across two dataset groups. Both panels use the same five variants and differ only in dataset grouping, isolating how the routing-control choice behaves in dynamic versus more stable settings.

stays competitive on ML-1M even when the strongest baseline there remains slightly ahead.

The baseline pattern is also informative. SASRec and TiSASRec remain consistently strong under this protocol, which is plausible because the sessionized split produces relatively short, recency-sensitive prefixes where strong autoregressive self-attention and explicit interval modeling already capture much of the available signal [19, 25]. By contrast, BSARec is less competitive here even though it is strong in standard longer-sequence settings: its attentive frequency bias is designed to exploit richer global spectral structure [38], and that advantage is naturally attenuated when sessionization shortens contexts and reduces long-range periodic evidence. DIF-SR also improves less in this setup, which is consistent with its side-information-fusion focus [45]: under our shared protocol, auxiliary features are intentionally lightweight and heterogeneous across datasets, so the side branch contributes less additional structure than in richer feature regimes. These gaps should therefore be read as protocol- and inductive-bias-dependent behavior rather than as evidence of under-tuning, since all methods follow the same bounded search, stopping rule, and processed files.

Overall, Q1 shows that RouteRec is competitive under the shared sessionized protocol, with the clearest gains in the more behaviorally dynamic settings.

5.3 Q2. What Should Control Routing?

Figure 3 compares five variants that separate where behavior information is used: a shared FFN, hidden-only routing, feature fusion by additive bias, mixed hidden+behavior routing, and the final behavior-guided sparse router. Hidden-only routing can improve over a shared FFN, and simple feature reinjection is not entirely ineffective, but neither yields the same consistency as using behavioral cues directly as routing controls. The final behavior-guided design therefore outperforms representation-only feature injection and avoids collapsing the routing input back into hidden-state geometry.

Both panels use the same five variants and differ only in dataset grouping. Panel (a) emphasizes more behaviorally dynamic datasets, whereas Panel (b) reports the more stable or mixed group. Appendix F reports the corresponding objective variants separately so that the routing-signal effect is not conflated with the loss choice.

The practical takeaway is that the best routing input is not the one that carries the most raw information, but the one that exposes the cleanest control boundary. Once behavioral cues are used directly at the router, RouteRec can let the representation path focus on sequence modeling while the router absorbs cross-dataset differences in pace, focus, and recurrence more explicitly.

5.4 Q3. Why Is RouteRec's Three-Part Design Effective?

Figure 4 tests whether RouteRec's gains come from the three-part design itself rather than from expert insertion alone. Panel (a) asks whether temporal decomposition is necessary by comparing the final three-stage design against the best reduced single-view and two-view alternatives. Panel (b) asks whether the selected routing organization is meaningful by comparing flat versus hierarchical routing and sparse versus dense allocation under comparable expert pools.

Taken together, these ablations test whether RouteRec's gain comes from temporal decomposition and hierarchical sparse commitment rather than indiscriminate expert insertion. Broader scope-order and portability controls are deferred to the appendix.

The pattern is consistent with the method hypothesis. A single behavior view is too coarse to separate slow tendency from immediate transition pressure, while a dense flat expert pool weakens route commitment even when the total expert budget is comparable. The selected three-stage sparse hierarchy is therefore useful because it assigns different temporal questions to different routing decisions instead of asking one router to absorb all scopes at once.



(a) Temporal decomposition matters



(b) Hierarchical sparse routing matters

Figure 4: Design-justification ablations. Panel (a) compares the final three-stage design against reduced temporal decompositions, and Panel (b) compares flat versus hierarchical and dense versus sparse routing organizations.

5.5 Q4. Is RouteRec Practical as a Sparse Design?

Q4 asks whether the final sparse RouteRec design remains practical in cost. On two representative datasets, sparse RouteRec uses 3.2M total parameters but only 1.6M active parameters per routed decision, compared with 3.2M active parameters for the dense variant and 1.8M for SASRec. Its train and inference ratios are 1.42× and 1.18× relative to SASRec, versus 1.85× and 1.38× for dense RouteRec. The key distinction is therefore executed capacity rather than total capacity alone. Appendix G reports the full efficiency summary.

This gap matters for the paper claim because it shows that RouteRec is not simply buying accuracy through unrestricted dense over-parameterization. The sparse design still pays a modest routing overhead, but it keeps the active compute budget much closer to strong shared-path baselines than the dense expertized alternative does.

5.6 Q5. What Does the Learned Router Actually Capture?

Figure 5 addresses the most direct semantic question raised by the method: if RouteRec is designed to react to behavioral regimes, then representative original, repeat-heavy, fast-tempo, and narrow-focus cases should exhibit different stage-wise routing maps. We therefore present four representative routing cases in the main text and retain intervention-based perturbation results as supporting evidence for the appendix and discussion.

This analysis connects the empirical evidence back to the motivation in Figure 1. To avoid circularity, the cases are selected from simple post hoc statistics derived from raw interaction histories rather than optimized labels or supervision targets. Appendix-level cue interventions support the same reading.



Figure 5: Representative routing semantics across four cases. The original anchor panel is shown together with repeat-heavy, fast-tempo, and narrow-focus cases so that stage-wise semantic-group emphasis can be compared under distinct behavioral regimes.

The three cases also clarify why the method is most compelling on dynamic datasets. When repeat structure, short-horizon tempo, or concentration shifts become more pronounced, the stage-local router has a clearer reason to deviate from a shared computation path. In more preference-stable settings, the same mechanism remains competitive but is asked to differentiate less sharply, which is consistent with the smaller margin observed on ML-1M.

Detailed full-cutoff results and extended analyses, including exact sparse-routing specification, reduced-cue portability studies, broader structural ablations, sparse-design controls, objective variants, extended efficiency summaries, routing

diagnostics, intervention studies, and transfer experiments, are reported in Appendices A–K.

6 Conclusion

RouteRec starts from a design question: in sessionized sequential recommendation with accessible cross-session history, can behavioral cues from ordinary interaction logs serve as an explicit control signal for conditional computation, rather than only as inputs for representation enrichment? The experiments support an affirmative reading from three angles. First, RouteRec improves next-item ranking most clearly on behaviorally dynamic datasets and remains competitive elsewhere, although the advantage narrows in more preference-stable settings such as ML-1M. Second, the gain is tied to behavioral cues, staged temporal decomposition, and sparse route commitment rather than indiscriminate expert insertion. Third, compact cues derived from ordinary interaction logs preserve a meaningful share of the benefit, keeping the method practical when side information is limited.

Taken together, the results suggest that behavior-guided routing can be both semantically meaningful and computationally selective. In the main configuration, route-guiding cues, coarse-to-fine routing, and hierarchical sparse expert allocation form a compact interface for conditional computation. Future work can extend that interface through adaptive sparsity budgets, transfer of routing priors across domains, more robust cue construction, and tighter deployment-aware constraints.

More broadly, the paper suggests a useful modeling stance for sessionized recommendation: not every gain from extra capacity should be interpreted as better sequence representation. Some of it can come from exposing a better control interface over when different computations should be used at all. RouteRec's contribution is to make that interface explicit, lightweight, and interpretable.

References

[1] Josef Bauer and Dietmar Jannach. 2024. Hybrid Session-Aware Recommendation with Feature-Based Models. *User Modeling and User-Adapted Interaction* 34, 3 (2024), 691–728. doi:10.1007/s11257-023-09379-6

[2] Shuqing Bian, Xingyu Pan, Wayne Xin Zhao, Jinpeng Wang, Chao Wang, and Ji-Rong Wen. 2023. Multi-modal Mixture of Experts Representation Learning for Sequential Recommendation. In *Proceedings of the 32nd ACM International Conference on Information and Knowledge Management (CIKM)*. 110–119. doi:10.1145/3583780.3614978

[3] Simone Borg Bruun, Maria Maistro, and Christina Lioma. 2022. Learning Recommendations from User Actions in the Item-Poor Insurance Domain. In *Proceedings of the 16th ACM Conference on Recommender Systems (RecSys)*. Association for Computing Machinery, New York, NY, USA, 113–123. doi:10.1145/3523227.3546775

[4] Oscar Celma. 2010. *Music Recommendation and Discovery in the Long Tail*. Springer. doi:10.1007/978-3-642-13287-2

[5] Yukuo Cen, Jianwei Zhang, Xu Zou, Chang Zhou, Hongxia Yang, and Jie Tang. 2020. Controllable Multi-Interest Framework for Recommendation. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD)*. 2942–2951. doi:10.1145/3394486.3403344

[6] Nan Du, Yanping Huang, Andrew M. Dai, Simon Tong, Dmitry Lepikhin, Yuanzhong Xu, Maxim Krikun, Yanqi Zhou, Adams Wei Yu, Orhan Firat, Barret Zoph, Liam Fedus, Maarten P. Bosma, Zongwei Zhou, Tao Wang, Emma Wang, Kellie Webster, Marie Pellat, Kevin Robinson, Kathleen Meier-Hellstern, Toju Duke, Lucas Dixon, Kun Zhang, Quoc V. Le, Yonghui Wu, Zhifeng Chen, and Claire Cui. 2022. GLaM: Efficient Scaling of Language Models with Mixture-of-Experts. In *Proceedings of the 39th International Conference on Machine Learning (ICML) (Proceedings of Machine Learning Research, Vol. 162)*. 5547–5569. https://proceedings.mlr.press/v162/du22c.html

[7] Xinyu Du, Huanhuan Yuan, Pengpeng Zhao, Jianfeng Qu, Fuzhen Zhuang, Guanfeng Liu, Yanchi Liu, and Victor S. Sheng. 2023. Frequency Enhanced Hybrid Attention Network for Sequential Recommendation. In *Proceedings of the 46th International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR)*. 78–88. doi:10.1145/3539618.3591689

[8] William Fedus, Barret Zoph, and Noam Shazeer. 2022. Switch Transformers: Scaling to Trillion Parameter Models with Simple and Efficient Sparsity. *Journal of Machine Learning Research* 23, 120 (2022), 1–39. https://jmlr.org/papers/v23/21-0998.html

[9] B. G. Galuzzi, I. Giordani, A. Candelieri, R. Perego, and F. Archetti. 2020. Hyperparameter Optimization for Recommender Systems Through Bayesian Optimization. *Computational Management Science* 17, 4 (2020), 495–515. doi:10.1007/s10287-020-00376-3

[10] Chongming Gao, Shijun Li, Wenqiang Lei, Jiawei Chen, Biao Li, Peng Jiang, Xiangnan He, Jiaxin Mao, and Tat-Seng Chua. 2022. KuaiRec: A Fully-Observed Dataset and Insights for Evaluating Recommender Systems. In *Proceedings of the 31st ACM International Conference on Information & Knowledge Management* (Atlanta, GA, USA) *(CIKM '22)*. 540–550. doi:10.1145/3511808.3557220

[11] Dmytro Gusak, Aleksandra Mojsilovic, Vassilis N. Ioannidis, and Christos Kozyrakis. 2025. Time to Split: Exploring Data Splitting Strategies for Offline Evaluation of Sequential Recommenders. arXiv:2507.16289 [cs.IR] doi:10.48550/arXiv.2507.16289

[12] F. Maxwell Harper and Joseph A. Konstan. 2015. The MovieLens Datasets: History and Context. *ACM Transactions on Interactive Intelligent Systems* 5, 4 (2015), 1–19. doi:10.1145/2827872

[13] Balázs Hidasi, Alexandros Karatzoglou, Linas Baltrunas, and Domonkos Tikk. 2016. Session-based Recommendations with Recurrent Neural Networks. In *International Conference on Learning Representations (ICLR)*. https://arxiv.org/abs/1511.06939

[14] Yupeng Hou, Binbin Hu, Zhiqiang Zhang, and Wayne Xin Zhao. 2022. CORE: Simple and Effective Session-based Recommendation within Consistent Representation Space. In *Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR)*. 1296–1305. doi:10.1145/3477495.3531955

[15] Robert A. Jacobs, Michael I. Jordan, Steven J. Nowlan, and Geoffrey E. Hinton. 1991. Adaptive Mixtures of Local Experts. *Neural Computation* 3, 1 (1991), 79–87. doi:10.1162/neco.1991.3.1.79

[16] Dietmar Jannach, Massimo Quadrana, and Paolo Cremonesi. 2022. Session-Based Recommender Systems. In *Recommender Systems Handbook*. Springer. doi:10.1007/978-1-0716-2197-4_8

[17] Yuyi Ji, Aline B. de Oliveira, Raphael D. F. Mesquita, Diego H. C. G. Horta, and Leonardo B. Marinho. 2023. A Critical Study on Data Leakage in Recommender System Offline Evaluation. *ACM Transactions on Information Systems* 41, 3 (2023), 1–27. doi:10.1145/3569930

[18] Michael I. Jordan and Robert A. Jacobs. 1994. Hierarchical Mixtures of Experts and the EM Algorithm. *Neural Computation* 6, 2 (1994), 181–214. doi:10.1162/neco.1994.6.2.181

[19] Wang-Cheng Kang and Julian J. McAuley. 2018. Self-Attentive Sequential Recommendation. In *2018 IEEE International Conference on Data Mining (ICDM)*. 197–206. doi:10.1109/ICDM.2018.00035

[20] Emanuel Lacic, Markus Reiter-Haas, Dominik Kowald, Manoj Reddy Dareddy, Junghoo Cho, and Elisabeth Lex. 2020. Using Autoencoders for Session-Based Job Recommendations. *User Modeling and User-Adapted Interaction* 30, 4 (2020), 617–658. doi:10.1007/s11257-020-09269-1

[21] Sara Latifi, Dietmar Jannach, and Andrés Ferraro. 2022. Sequential Recommendation: A Study on Transformers, Nearest Neighbors and Sampled Metrics. *Information Sciences* 609 (2022), 660–678. doi:10.1016/j.ins.2022.07.079

[22] Sahar Latifi, Nicola Mauro, and Dietmar Jannach. 2021. Session-Aware Recommendation: A Surprising Quest for the State-of-the-Art. *Information Sciences* 573 (2021), 354–375. doi:10.1016/j.ins.2021.05.048

[23] Chao Li, Zhiyuan Liu, Mengmeng Wu, Yuchi Xu, Huan Zhao, Pipei Huang, Guoliang Kang, Qiwei Chen, Wei Li, and Dik Lun Lee. 2019. Multi-Interest Network with Dynamic Routing for Recommendation at Tmall. In *Proceedings of the 28th ACM International Conference on Information and Knowledge Management (CIKM)*. 2615–2623. doi:10.1145/3357384.3357814

[24] Jing Li, Pengjie Ren, Zhumin Chen, Zhaochun Ren, Tao Lian, and Jun Ma. 2017. Neural Attentive Session-based Recommendation. In *Proceedings of the 2017 ACM on Conference on Information and Knowledge Management (CIKM)*. 1419–1428. doi:10.1145/3132847.3132926

[25] Jiacheng Li, Yujie Wang, and Julian J. McAuley. 2020. Time Interval Aware Self-Attention for Sequential Recommendation. In *Proceedings of the 13th ACM International Conference on Web Search and Data Mining (WSDM)*. 322–330. doi:10.1145/3336191.3371786

[26] Mingrui Liu, Sixiao Zhang, and Cheng Long. 2025. Facet-Aware Multi-Head Mixture-of-Experts Model for Sequential Recommendation. In *Proceedings of the 18th ACM International Conference on Web Search and Data Mining (WSDM)*. 127–135. doi:10.1145/3701551.3703552

[27] Qiao Liu, Yifu Zeng, Refuoe Mokhosi, and Haibin Zhang. 2018. STAMP: Short-Term Attention/Memory Priority Model for Session-Based Recommendation. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD)*. 1831–1839. doi:10.1145/3219819.3219950

[28] Ziwei Liu, Qidong Liu, Yejing Wang, Wanyu Wang, Pengyue Jia, Maolin Wang, Zitao Liu, Yi Chang, and Xiangyu Zhao. 2025. SIGMA: Selective Gated Mamba for Sequential Recommendation. *Proceedings of the AAAI Conference on Artificial Intelligence* 39, 12 (2025), 12264–12272. doi:10.1609/aaai.v39i12.33336

[29] Jiaqi Ma, Zhe Zhao, Xinyang Yi, Jilin Chen, Lichan Hong, and Ed H. Chi. 2018. Modeling Task Relationships in Multi-Task Learning with Multi-Gate Mixture-of-Experts. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD)*. 1930–1939. doi:10.1145/3219819.3220007

[30] Julian McAuley, Rahul Pandey, and Jure Leskovec. 2015. Inferring Networks of Substitutable and Complementary Products. In *Proceedings of the 21th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD)*. 785–794. doi:10.1145/2783258.2783381

[31] Xiuyuan Qin, Huanhuan Yuan, Pengpeng Zhao, Guanfeng Liu, Fuzhen Zhuang, and Victor S. Sheng. 2024. Intent Contrastive Learning with Cross Subsequences for Sequential Recommendation. In *Proceedings of the 17th ACM International Conference on Web Search and Data Mining (WSDM)*. Association for Computing Machinery, New York, NY, USA, 548–556. doi:10.1145/3616855.3635773

[32] Ruihong Qiu, Zi Huang, Hongzhi Yin, and Zijian Wang. 2022. Contrastive Learning for Representation Degeneration Problem in Sequential Recommendation. In *Proceedings of the 15th ACM International Conference on Web Search and Data Mining (WSDM)*. 813–823. doi:10.1145/3488560.3498433

[33] Massimo Quadrana, Alexandros Karatzoglou, Balázs Hidasi, and Paolo Cremonesi. 2017. Personalizing Session-based Recommendations with Hierarchical Recurrent Neural Networks. In *Proceedings of the Eleventh ACM Conference on Recommender Systems (RecSys)*. 130–137. doi:10.1145/3109859.3109896

[34] Pengjie Ren, Zhumin Chen, Jing Li, Zhaochun Ren, Jun Ma, and Maarten de Rijke. 2019. RepeatNet: A Repeat Aware Neural Recommendation Machine for Session-Based Recommendation. *Proceedings of the AAAI Conference on Artificial Intelligence* 33, 1 (2019), 4806–4813. doi:10.1609/AAAI.V33I01.33014806

[35] Steffen Rendle, Christoph Freudenthaler, and Lars Schmidt-Thieme. 2010. Factorizing Personalized Markov Chains for Next-Basket Recommendation. In *Proceedings of the 19th International Conference on World Wide Web (WWW)*. 811–820. doi:10.1145/1772690.1772773

[36] Retail Rocket. 2015. Retail Rocket Recommender System Dataset. https://www.kaggle.com/datasets/retailrocket/ecommerce-dataset

[37] Noam Shazeer, Azalia Mirhoseini, Krzysztof Maziarz, Andy Davis, Quoc V. Le, Geoffrey E. Hinton, and Jeff Dean. 2017. Outrageously Large Neural Networks: The Sparsely-Gated Mixture-of-Experts Layer. In *International Conference on Learning Representations (ICLR)*. https://openreview.net/forum?id=B1ckMDqlg

[38] Yehjin Shin, Jeongwhan Choi, Hyowon Wi, and Noseong Park. 2024. An Attentive Inductive Bias for Sequential Recommendation beyond the Self-Attention. *Proceedings of the AAAI Conference on Artificial Intelligence* 38, 8 (2024), 8984–8992. doi:10.1609/aaai.v38i8.28747

[39] Fei Sun, Jun Liu, Jian Wu, Changhua Pei, Xiao Lin, Wenwu Ou, and Peng Jiang. 2019. BERT4Rec: Sequential Recommendation with Bidirectional Encoder Representations from Transformer. In *Proceedings of the 28th ACM International Conference on Information and Knowledge Management (CIKM)*. 1441–1450. doi:10.1145/3357384.3357895

[40] Hongyan Tang, Junning Liu, Ming Zhao, Xudong Gong, Zhaohui Jin, Yu Lei, Min Zhang, and Xuan Li. 2020. Progressive Layered Extraction (PLE): A Novel Multi-Task Learning (MTL) Model for Personalized Recommendations. In *Proceedings of the 14th ACM Conference on Recommender Systems (RecSys)*. 269–278. doi:10.1145/3383313.3412236

[41] Jiaxi Tang and Ke Wang. 2018. Personalized Top-N Sequential Recommendation via Convolutional Sequence Embedding. In *Proceedings of the 11th ACM International Conference on Web Search and Data Mining (WSDM)*. 565–573. doi:10.1145/3159652.3159656

[42] Shoujin Wang, Longbing Cao, Yan Wang, Quan Z. Sheng, Mehmet A. Orgun, and Defu Lian. 2021. A Survey on Session-Based Recommender Systems. *Comput. Surveys* 54, 7 (2021), 1–38. doi:10.1145/3465401

[43] Shoujin Wang, Liang Hu, Yan Wang, Longbing Cao, Quan Z. Sheng, and Mehmet A. Orgun. 2019. Sequential Recommender Systems: Challenges, Progress and Prospects. In *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence (IJCAI)*. 6332–6338. doi:10.24963/ijcai.2019/883

[44] Shu Wu, Yuyuan Tang, Yanqiao Zhu, Liang Wang, Xing Xie, and Tieniu Tan. 2019. Session-Based Recommendation with Graph Neural Networks. *Proceedings of the AAAI Conference on Artificial Intelligence* 33, 1 (2019), 346–353. doi:10.1609/aaai.v33i01.3301346

[45] Yueqi Xie, Peilin Zhou, and Sunghun Kim. 2022. Decoupled Side Information Fusion for Sequential Recommendation. In *Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR)*. 1611–1621. doi:10.1145/3477495.3531963

[46] Dingqi Yang, Daqing Zhang, Vincent W. Zheng, and Zhiyong Yu. 2015. Modeling User Activity Preference by Leveraging User Spatial Temporal Characteristics in LBSNs. *IEEE Transactions on Systems, Man, and Cybernetics: Systems* 45, 1 (2015), 129–142. doi:10.1109/TSMC.2014.2327053

[47] Haochao Ying, Fuzhen Zhuang, Fuzheng Zhang, Yanchi Liu, Guandong Xu, Xing Xie, Hui Xiong, and Jian Wu. 2018. Sequential Recommender System based on Hierarchical Attention Networks. In *Proceedings of the Twenty-Seventh International Joint Conference on Artificial Intelligence (IJCAI)*. 3926–3932. doi:10.24963/ijcai.2018/546

[48] Fajie Yuan, Xiangnan He, Alexandros Karatzoglou, and Lizi Zhang. 2019. A Simple Convolutional Generative Network for Next Item Recommendation. In *Proceedings of the 12th ACM International Conference on Web Search and Data Mining (WSDM)*. 582–590. doi:10.1145/3289600.3290975

[49] Shengzhe Zhang, Liyi Chen, Dazhong Shen, Chao Wang, and Hui Xiong. 2025. Hierarchical Time-Aware Mixture of Experts for Multi-Modal Sequential Recommendation. In *Proceedings of the ACM Web Conference 2025 (WWW)*. 3672–3682. doi:10.1145/3696410.3714676

[50] Tingting Zhang, Pengpeng Zhao, Yanchi Liu, Victor S. Sheng, Jiajie Xu, Deqing Wang, Guanfeng Liu, and Xiaofang Zhou. 2019. Feature-level Deeper Self-Attention Network for Sequential Recommendation. In *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence (IJCAI)*. 4320–4326. doi:10.24963/ijcai.2019/600

[51] Yanqi Zhou, Tao Lei, Hanxiao Liu, Nan Du, Yanping Huang, Vincent Y. Zhao, Andrew M. Dai, Zhifeng Chen, Quoc V. Le, and James Laudon. 2022. Mixture-of-Experts with Expert Choice Routing. In *Advances in Neural Information Processing Systems (NeurIPS)*. https://arxiv.org/abs/2202.09368

[52] Barret Zoph, Alexander V. Kolesnikov, Neal Wadhwa, Jonathan Huang, Andrew M. Dai, Noam Shazeer, Quoc V. Le, and Yonghui Wu. 2022. Designing Effective Sparse Expert Models. arXiv:2202.08906 [cs.LG] doi:10.48550/arXiv.2202.08906

A Exact RouteRec Instantiation and Sparse Routing Formulation

This appendix records the fixed paper instantiation and the representative cue bank used by RouteRec. Whereas the main text emphasizes the conceptual design axes, this section documents the implementation choices that are relevant for reproducibility and for interpreting the later ablations, with the sparse routing formulation made explicit.

A.1 Main Paper Configuration

Table 2: Fixed main configuration used in the paper.

Aspect	Main paper configuration
Backbone layout	self-attn → macro block → mid block → self-attn → micro block
Stage execution	Serial
Routing granularity	Macro and mid: sequence-wise; micro: position-wise
Router composition	Shared hierarchical sparse router at all three stages
Expert activation	Top-3 groups out of 4; top-2 experts per selected group
Active experts	6 out of 12 total per routed decision
History windows	$H = 5$ sessions (macro); $w = 5$ positions (micro)
Core auxiliary terms	Route consistency + z-loss; no load balancing

The placement of the two attention layers reflects the intended temporal roles of the stages. The first attention layer contextualizes the raw prefix before any routing is applied. Macro and mid then operate consecutively because both provide slower sequence-level control over the same contextualized sequence state: macro captures broader recent-history tendency, while mid refines within-session evolution. A second attention layer is inserted only before micro so that the final local router receives a refreshed token interaction state immediately before prediction. This layout was the most stable high-performing architecture in our architecture sweep, and Appendix E compares it against denser and differently ordered alternatives.

This table serves as a reproducibility summary rather than as a search-space description. Architectural choices are fixed across the paper track, whereas capacity and optimization values are selected per dataset from a narrow candidate set and are therefore reported as compact ranges only when no single global value is shared across all reported runs.

A.2 Implementation Specification and Minimal Execution Notes

Table 3: Implementation-level settings used in the selected paper track.

Item	Reported setting
Semantic groups	$G = 4$ groups: Tempo, Focus, Memory, Exposure
Experts per group	$C \in \{2, 3, 4\}$; total experts $E = 4C$
Main sparse setting	$C = 3$, top-3 groups, top-2 experts per selected group
Cue dimensionality	16 scalars per stage
Router hidden width	Representative range 48–128
Routing temperature	Macro 1.0; mid and micro 1.2
Consistency neighbors	$k_{\mathrm{nn}} = 1$ nearest non-self sample per stage
Missing-signal handling	Broadcast when available; zero-fill focus cues if grouping field absent

Minimal execution notes. The implementation uses three simple rules that are easy to miss if one only reads the high-level method description. First, macro and mid cues are computed once per example and then broadcast over the routed positions, whereas micro cues are evaluated at the position level. Second, top-k masking is followed by renormalization inside the active support rather than by leaving the logits in an unnormalized sparse state. Third, if a dataset does not expose the grouping field needed for focus-family cues, the implementation falls back to the fixed missing-signal policy in Table 3 rather than silently redefining the cue family per dataset.

A.3 Representative Behavioral Cue Families

This cue bank is intentionally compact. The feature families are hand-designed in the sense that they encode behavioral hypotheses, but the design goal is to keep them as a small set of summaries that can serve as a stable routing interface across datasets. In practice, the macro bank is instantiated from the recent-session window used by the selected paper instantiation, while mid and micro are computed from the current session prefix at different temporal scopes. The main text therefore reports the family structure and representative examples, while this appendix provides the implementation-oriented view.

B Dataset Analysis and Router Motivation

Rather than assuming a single scalar notion of heterogeneity, we inspect raw interaction logs and summarize recurring axes that can plausibly drive router demand across datasets. The goal is to show the dataset-level profile first and keep the detailed interpretation secondary.

B.1 Candidate Axes

- Temporal volatility: variation in session length, short/long session mix, and timing irregularity.
- Transition ambiguity: how widely the next action branches from a similar current state.
- Memory / carryover: repetition strength, repeat variability, and cross-session overlap or drift.
- Exposure regime: popularity concentration and head-item dominance.
- Context availability: whether repeated-session context is sufficiently present for macro routing to use.

Table 4: Representative cue summaries used by RouteRec in the main configuration. Each stage uses four semantic families with four scalar summaries per family; the table lists representative examples rather than every implementation detail.

Family	Macro (recent-session tendency)	Mid (within-session evolution)	Micro (short-horizon pressure)
Tempo	Context-valid ratio, last inter-session gap, mean pace, pace trend	Valid-prefix ratio, mean/std interaction interval, session age	Last gap, short-window mean gap, short-window std, deviation from mid-scale pace
Focus	Theme entropy, dominant-theme mass, theme repeat rate, theme shift rate	Category entropy, category top-1 mass, category switch rate, category uniqueness	Immediate category switch, mismatch to recent category history, suffix entropy, suffix uniqueness
Memory	Repeat intensity, adjacent category overlap, adjacent item overlap, repeat trend	Item uniqueness, repeat rate, novelty rate, longest item run	Reconsumption flag, suffix reconsumption rate, suffix item uniqueness, suffix longest run
Exposure	Mean popularity, popularity spread, popularity entropy, popularity trend	Mean popularity, popularity std, popularity entropy, popularity drift	Last-item popularity, suffix popularity spread, suffix popularity entropy, deviation from mid-scale popularity

B.2 Dataset-Level Raw Axis Table

Table 5 reports the raw dataset-level profile together with RouteRec's gain summary.

Table 5: Raw dataset axis profile.

Dataset	SessVol	Branch	RepeatVar	Carryover	Drift	PopConc	CtxAvail	Gain	WinRate
Beauty	0.694	0.843	0.000	0.000	1.000	0.509	0.059	0.0020	0.556
Foursquare	0.944	0.688	1.961	0.159	0.841	0.647	0.988	0.0009	0.556
KuaiRec	0.887	0.903	2.214	0.003	0.997	0.671	0.933	0.0182	1.000
LastFM	0.739	0.630	2.036	0.072	0.928	0.456	0.990	0.0049	1.000
ML-1M	0.381	0.839	0.000	0.000	1.000	0.699	0.264	-0.0031	0.000
Retail Rocket	0.945	0.744	0.858	0.184	0.816	0.674	0.056	0.0055	0.667

Gain denotes RouteRec's average test-score gap from the strongest baseline on that dataset. **WinRate** denotes the fraction of the nine reported test metrics where RouteRec achieves the best value. SessVol, Branch, RepeatVar, Carryover, Drift, PopConc, and CtxAvail summarize temporal volatility, transition ambiguity, repetition or carryover structure, exposure regime, and context availability in the raw logs.

C Dataset, Evaluation, and Full Ranking Results

All experiments were conducted on machines equipped with NVIDIA RTX 3090 24 GB GPUs. Each training or evaluation process used a single GPU; multiple GPUs were used only to run independent experiments in parallel, not for multi-GPU training within a single run. This appendix summarizes the six datasets and makes the evaluation protocol explicit, since recent work has shown that session construction and split strategy can materially affect offline recommender results [11, 17]. The original releases are cited here for completeness [4, 10, 12, 30, 36, 46]. The dataset descriptions emphasize domain differences and signal availability because the routing branch depends on which behavioral evidence is exposed in each corpus.

C.1 Datasets and Protocol

Table 6: Datasets used in the experiments. Datasets marked with † are sampled processed subsets.

Dataset	Domain	Interactions	Sessions	Items	Avg. len.
Beauty	E-com.	33,488	4,243	3,625	7.9
Foursquare	POI	145,238	25,369	30,588	5.7
KuaiRec†	Video	287,411	24,458	6,477	11.8
LastFM†	Music	470,408	25,089	52,510	18.8
ML-1M	Movie	575,281	14,539	3,533	39.6
Retail Rocket	Browse	821,243	153,092	90,211	5.4

Table 6 reports the statistics of the final processed datasets used in the experiments rather than the raw corpus sizes. In particular, KuaiRec corresponds to the 20% processed subset used in our runs, and LastFM corresponds to the 3% processed subset.

For reproducibility, the protocol is summarized as follows.

(1) Sort all interactions chronologically within each dataset.
(2) Reconstruct sessions with a dataset-specific inactivity threshold.
(3) Iteratively prune sessions with length below 5 and items with support below 3 until the constraints are simultaneously satisfied.
(4) Sort the resulting sessions by session start time.
(5) Assign the earliest 70% of sessions to train and treat the latest 30% as a held-out tail.
(6) Build validation and test from the held-out tail under chronology-preserving cleanup.
(7) Report seen-target metrics as the primary view and keep unseen-target behavior as supplementary accounting.

Beauty and Retail Rocket stress sparse e-commerce revisit behavior, Foursquare and KuaiRec emphasize stronger short-horizon intent changes, and LastFM and ML-1M provide longer preference-driven histories. This spread makes it possible to examine whether behavior-guided routing is primarily beneficial in highly dynamic settings or remains competitive when preference structure is more stable.

Signal availability also differs in a way that matters for routing. Beauty exposes item, time, and product-category cues after low-rating removal. Foursquare includes item, timestamp, and venue-category structure with bursty check-in dynamics. KuaiRec offers item, time, and coarse content-side metadata in short-video sessions with strong short-term intent shifts. LastFM provides repeated listening histories with artist-side signals, while ML-1M contributes longer preference-driven sequences with genre information. Retail Rocket is the sparsest side-information setting, relying mainly on anonymous event streams with item and time signals.

We position our setup as a sessionized sequential evaluation protocol assembled from established components, not as the canonical raw-sequence protocol for sequential recommendation [16, 22, 33]. Sessions are reconstructed post hoc with inactivity heuristics, which is standard practice when logs do not provide explicit session boundaries [16]. The thresholds are adapted to the logging regime of each corpus: Foursquare, KuaiRec, LastFM, ML-1M, and Retail Rocket use a 30-minute inactivity threshold, consistent with dense-log session-aware practice [20, 33], whereas Beauty uses a 14-day threshold because review timestamps are substantially more diffuse. More generally, this threshold choice reflects the observation that sparse and item-poor domains often require longer or more domain-specific notions of a session than dense clickstream data [3]. After sessionization, we repeatedly remove sessions shorter than 5 and items with fewer than 3 interactions until no further pruning is required. This iterative filtering follows the same general rationale as common session-based benchmark preprocessing, where short sessions and very low-support items are filtered to stabilize next-item supervision and evaluation [24, 44].

Session splits are constructed at the session level after sorting by session start time. The earliest 70% of sessions are assigned to training, and the remaining 30% are treated as a held-out tail. This tail is first divided into validation and test using stratification over three factors: whether the target item already appears in the prefix, the target item's popularity bucket with respect to the training split, and the session-length bucket. For the final evaluation files, we then merge the held-out sessions, restore chronological order, and re-split them contiguously into equal validation and test halves. This chronology-preserving design is meant to reduce leakage and keep the offline protocol aligned with temporal deployment order [11, 17].

For the primary evaluation view, we report seen-target metrics only. Concretely, in the held-out files, non-target rows whose items are unseen in training are removed, and unseen targets are retained only for supplementary accounting rather than the main comparison. This matches long-standing session-based and session-aware evaluation practice for ID-based recommendation models, which cannot rank targets outside the training vocabulary and therefore typically separate unseen-target behavior from the primary benchmark table [22, 24, 44]. We report HR, NDCG, and MRR at $k \in \{5, 10, 20\}$ for all methods.

For the result tables, each method is represented by the run with the highest mean seen-target test score over the nine reported metrics under the same selection rule used throughout the paper.

All methods use the same processed train/validation/test partitions. RouteRec's additional macro, mid, and micro cues are deterministic summaries derived from those same observed histories, so the comparison should be read as evaluating different ways of exploiting the shared sessionized interaction context rather than different access to held-out information.

C.2 Model Selection and Tuning Protocol

Because this benchmark is built from a sessionized temporal protocol rather than a canonical raw-sequence leaderboard, the model-selection procedure is stated explicitly. Prior benchmark studies have shown that both baseline quality and model ranking can change materially once methods are re-evaluated under a common framework and retuned under a shared protocol [21, 22]. Accordingly, the comparison does not rely on paper defaults alone.

Our reporting protocol follows three simple rules. First, every model is tuned within a predefined bounded search space that is fixed before the final comparison: learning rate is sampled log-uniformly within a declared dataset-specific interval, while the remaining hyperparameters are drawn from small predeclared candidate sets. Second, these bounded spaces cover a shared core of optimization hyperparameters together with a small number of model-specific controls, so that the search is broad enough to avoid trivial under-tuning but still budgeted tightly enough to remain comparable across methods. Third, the final reported result for every model is the test performance of the configuration that maximizes the mean validation score over the nine reported metrics. When adaptive search is used for computational efficiency, it is restricted to the same predeclared bounds and candidate sets and should therefore be read as an efficient implementation of a controlled bounded search rather than as open-ended retuning [9].

The final paper track therefore uses bounded search spaces rather than unconstrained retuning. In the paper-facing comparison, baselines and RouteRec are aligned to the same shared optimization pool, and model families differ only through a small number of architecture-specific additions. For RouteRec, the selected three-stage routing layout remains fixed, but depth, hidden dropout, and routing-side controls are still tuned within bounded candidate sets. To keep the appendix concise but still reproducible, Table 7 separates the shared optimization pool from the baseline-family and RouteRec-specific additions, and lists the dataset-specific learning-rate intervals explicitly.

C.3 Full Ranking Results

Table 8 restores the full cutoff grid summarized more compactly in Table 1. This presentation preserves the same selection rule as the main text while exposing the complete $k \in \{5, 10, 20\}$ breakdown.

The appendix table confirms that the same qualitative ordering persists across cutoffs: RouteRec is strongest overall, SASRec and TiSASRec remain robust reference points, and the relatively weaker BSARec and DIF-SR results are consistent with the sessionized short-prefix regime discussed in Section 5.2 rather than with a change in selection or evaluation policy.

This table makes it possible to verify whether the observed trends persist beyond the compact main-text summary under the same selection rule.

Table 7: Bounded candidate grids used in the final paper track.

(a) Shared Optimization Pool

Parameter	Candidate sets
Learning rate	Dataset-specific log-uniform interval; see panel (d)
Weight decay	$\{5 \times 10^{-7}, 10^{-6}, 10^{-5}, 5 \times 10^{-5}, 10^{-4}, 1.5 \times 10^{-4}\}$
Max history length	$\{10, 20, 30\}$ or $\{10, 20, 30, 50\}$
Width / embedding	$\{64, 96, 112, 128, 160\}$ or $\{96, 112, 128, 160, 192\}$
Inner width	$\{128, 192, 224, 256, 320\}$ or $\{192, 224, 256, 320, 384\}$
Layers / heads	Layers $\{1, 2, 3, 4\}$; heads $\{1, 2, 4, 8\}$ if applicable
Dropout	Hidden / ratio: $\{0.10, 0.12, 0.13, 0.15, 0.18\}$ Recurrent: $\{0.10, 0.15, 0.20, 0.25, 0.30\}$ Attention: $\{0.06, 0.08, 0.10, 0.12, 0.15\}$ or $\{0.08, 0.10, 0.12, 0.15, 0.20\}$

(b) Baseline-Family Additions

Model(s)	Additional candidate sets
TiSASRec	Time span $\{64, 128, 256, 384, 512\}$
GRU4Rec	Recurrent dropout $\{0.10, 0.15, 0.20, 0.25, 0.30\}$
DuoRec / FEARec	$\tau\{0.16, 0.18, 0.20, 0.22, 0.24\}$ Contrastive weight $\{0.02, 0.03, 0.04, 0.05, 0.06\}$ Semantic weight $\{0, 0.04, 0.05, 0.08, 0.10\}$ or $\{0.04, 0.05, 0.08, 0.10, 0.12\}$
BSARec	$\alpha\{0.35, 0.50, 0.55, 0.70\}$ $c\{2, 3, 5, 7\}$
DIF-SR / FDSA	Attribute width $\{96, 128, 160, 192\}$ λ_{attr} $\{0.08, 0.09, 0.10, 0.12, 0.14\}$ or $\{0.09, 0.10, 0.12, 0.14, 0.15\}$
DIF-SR	Fusion $\{\text{gate}, \text{sum}, \text{concat}\}$
FAME	Expert count $\{2, 3, 4, 5, 6\}$

(c) RouteRec-Specific Additions

Parameter	Candidate sets
Backbone depth / dropout	Depth: $\{1, 2, 3\}$ Dropout: $\{0.10, 0.12, 0.14, 0.15, 0.16, 0.17\}$ $\{0.18, 0.19, 0.20, 0.22, 0.24\}$
Weight decay	$\{3.125, 5, 6, 10, 15, 20, 50\} \times 10^{-7}$
Routing capacity	Expert scale $\{2, 3, 4\}$ or $\{2, 3, 4, 5\}$ for KuaiRec router width $\{32, 64, 96, 128\}$
Routing dropout	Feature $\{0, 0.03, 0.05, 0.10\}$ attention $\{0.05, 0.06, 0.08, 0.10, 0.12\}$
Regularization	$\lambda_{\text{cons}}\{0, 2.5, 5, 8, 12\} \times 10^{-4}$ $\lambda_z\{0, 5, 10, 20\} \times 10^{-5}$
Cue bank	Cue bank size $\{10, 12, 16, 24\}$ router inner width per cue family (small preset)

(d) Dataset-Specific Learning-Rate Intervals

Dataset	Unified log-uniform LR interval
Beauty	1.5e-4 ∼ 2e-3
Foursquare	1.5e-4 ∼ 2.2e-3
KuaiRec	3e-4 ∼ 5e-3
LastFM	8e-5 ∼ 1.2e-3
ML-1M	1.5e-4 ∼ 2.2e-3
Retail Rocket	1.5e-4 ∼ 2.2e-3

Table 8: Full seen-target experimental results across all cutoffs. Datasets marked with † are sampled processed subsets. For each method, we report the seen-target test metrics of the run achieving the highest mean seen-target test score over the nine reported metrics. Avg. Rank is computed over all rows in this table, where lower is better. The RouteRec column is shaded for readability.

Dataset	Metric	SASRec	GRU4Rec	TiSASRec	FEARec	DuoRec	BSARec	FAME	DIF-SR	FDSA	RouteRec
Beauty	HR@5	0.1038	0.0573	0.0918	0.1003	0.0993	0.0630	0.0372	0.0993	0.1041	**0.1087**
	HR@10	0.1324	0.0840	0.1235	0.1404	0.1347	0.0726	0.0497	0.1165	0.1318	**0.1561**
	HR@20	0.1637	0.1146	0.1630	0.1757	0.1958	0.0955	0.0592	0.1385	0.1681	**0.2009**
	NDCG@5	0.0707	0.0372	0.0729	0.0669	0.0678	0.0474	0.0263	0.0756	**0.0830**	0.0798
	NDCG@10	0.0800	0.0457	0.0831	0.0797	0.0793	0.0504	0.0303	0.0811	0.0918	**0.0948**
	NDCG@20	0.0879	0.0533	0.0931	0.0889	0.0948	0.0563	0.0327	0.0867	0.1011	**0.1062**
	MRR@5	0.0598	0.0307	0.0666	0.0556	0.0571	0.0422	0.0228	0.0677	**0.0761**	0.0701
	MRR@10	0.0637	0.0341	0.0707	0.0608	0.0619	0.0434	0.0244	0.0700	**0.0796**	0.0762
	MRR@20	0.0659	0.0361	0.0735	0.0634	0.0662	0.0450	0.0250	0.0716	**0.0822**	0.0794
Retail Rocket	HR@5	0.4610	0.4312	0.4433	0.4730	0.4711	0.4411	0.4398	0.4262	0.4579	**0.4862**
	HR@10	0.5321	0.5048	0.5131	0.5487	0.5478	0.4655	0.4612	0.4322	0.5343	**0.5608**
	HR@20	0.5988	0.5719	0.5810	0.6234	0.6194	0.4887	0.4812	0.4365	0.6053	**0.6315**
	NDCG@5	0.3676	0.3436	0.3528	0.3752	0.3745	0.3877	0.3874	0.3844	0.3600	**0.3907**
	NDCG@10	0.3907	0.3674	0.3755	0.3998	0.3994	0.3957	0.3943	0.3863	0.3848	**0.4148**
	NDCG@20	0.4076	0.3844	0.3926	0.4187	0.4175	0.4015	0.3994	0.3874	0.4028	**0.4327**
	MRR@5	0.3365	0.3145	0.3227	0.3427	0.3423	0.3696	0.3695	**0.3698**	0.3274	0.3588
	MRR@10	0.3461	0.3243	0.3321	0.3529	0.3526	**0.3729**	0.3724	0.3706	0.3377	0.3688
	MRR@20	0.3507	0.3290	0.3368	0.3581	0.3576	**0.3745**	0.3738	0.3709	0.3427	0.3737
Foursquare	HR@5	0.2350	0.1741	0.2388	0.2403	0.2438	0.1995	0.1954	0.2458	0.2514	**0.2559**
	HR@10	0.3049	0.2180	0.2976	0.3054	0.3195	0.2383	0.2417	0.3032	0.3042	**0.3215**
	HR@20	0.3635	0.2593	0.3501	0.3620	0.3760	0.2773	0.2800	0.3536	0.3524	**0.3776**
	NDCG@5	0.1703	0.1334	0.1735	0.1714	0.1726	0.1483	0.1455	0.1821	**0.1843**	0.1829
	NDCG@10	0.1929	0.1476	0.1926	0.1925	0.1970	0.1609	0.1604	0.2008	0.2014	**0.2042**
	NDCG@20	0.2078	0.1580	0.2059	0.2068	0.2114	0.1708	0.1701	0.2135	0.2136	**0.2184**
	MRR@5	0.1489	0.1199	0.1519	0.1486	0.1491	0.1313	0.1289	0.1611	**0.1621**	0.1588
	MRR@10	0.1583	0.1258	0.1599	0.1574	0.1591	0.1366	0.1351	0.1688	**0.1692**	0.1676
	MRR@20	0.1624	0.1286	0.1635	0.1613	0.1631	0.1393	0.1378	0.1723	**0.1726**	0.1715
ML-1M	HR@5	0.0858	0.0984	0.0906	0.0906	0.0977	0.0892	0.0968	0.0384	**0.1022**	0.1005
	HR@10	0.1423	0.1456	0.1448	0.1490	0.1555	0.1374	0.1533	0.0669	**0.1606**	0.1568
	HR@20	0.2157	0.2181	0.2220	0.2234	0.2402	0.2018	0.2243	0.1052	**0.2426**	0.2353
	NDCG@5	0.0536	0.0626	0.0582	0.0549	0.0624	0.0568	0.0637	0.0240	**0.0645**	0.0627
	NDCG@10	0.0717	0.0778	0.0756	0.0736	0.0810	0.0723	0.0818	0.0331	**0.0833**	0.0807
	NDCG@20	0.0902	0.0960	0.0950	0.0923	0.1022	0.0884	0.0996	0.0427	**0.1038**	0.1004
	MRR@5	0.0431	0.0510	0.0476	0.0432	0.0508	0.0463	**0.0529**	0.0192	0.0522	0.0504
	MRR@10	0.0505	0.0572	0.0548	0.0508	0.0584	0.0527	**0.0603**	0.0230	0.0600	0.0577
	MRR@20	0.0555	0.0621	0.0600	0.0559	0.0641	0.0570	0.0651	0.0256	**0.0655**	0.0631
LastFM†	HR@5	0.3471	0.2836	0.3405	0.3630	0.3521	0.3312	0.3173	0.3389	0.3494	**0.3693**
	HR@10	0.3775	0.3109	0.3715	0.3876	0.3850	0.3475	0.3359	0.3593	0.3762	**0.3965**
	HR@20	0.3999	0.3338	0.3997	0.4103	0.4101	0.3615	0.3554	0.3825	0.4020	**0.4194**
	NDCG@5	0.2999	0.2588	0.2929	0.3108	0.2959	0.2992	0.2911	0.3103	0.3161	**0.3218**
	NDCG@10	0.3097	0.2676	0.3029	0.3187	0.3066	0.3044	0.2972	0.3169	0.3247	**0.3307**
	NDCG@20	0.3154	0.2735	0.3101	0.3245	0.3129	0.3080	0.3020	0.3228	0.3313	**0.3365**
	MRR@5	0.2841	0.2506	0.2770	0.2933	0.2771	0.2884	0.2822	0.3008	0.3050	**0.3059**
	MRR@10	0.2881	0.2542	0.2812	0.2965	0.2815	0.2906	0.2847	0.3035	0.3085	**0.3096**
	MRR@20	0.2897	0.2558	0.2831	0.2981	0.2833	0.2915	0.2861	0.3051	0.3103	**0.3113**
KuaiRec†	HR@5	0.3195	0.2770	0.3004	0.3397	0.3270	0.3281	0.3255	0.2275	0.3270	**0.3494**
	HR@10	0.3284	0.3061	0.3216	0.3513	0.3468	0.3359	0.3307	0.2333	0.3453	**0.3669**
	HR@20	0.3379	0.3367	0.3429	0.3688	0.3677	0.3464	0.3430	0.2411	0.3654	**0.3949**
	NDCG@5	0.3148	0.2493	0.2820	0.3249	0.3152	0.3184	0.3172	0.2210	0.3140	**0.3410**
	NDCG@10	0.3177	0.2589	0.2889	0.3286	0.3215	0.3209	0.3188	0.2229	0.3197	**0.3467**
	NDCG@20	0.3200	0.2666	0.2942	0.3330	0.3269	0.3236	0.3220	0.2248	0.3248	**0.3538**
	MRR@5	0.3133	0.2400	0.2759	0.3200	0.3112	0.3152	0.3144	0.2188	0.3097	**0.3382**
	MRR@10	0.3144	0.2441	0.2788	0.3215	0.3138	0.3162	0.3151	0.2196	0.3120	**0.3406**
	MRR@20	0.3150	0.2462	0.2802	0.3227	0.3153	0.3170	0.3160	0.2201	0.3133	**0.3425**
Avg. Rank↓		**6.07**	**8.63**	**6.56**	**4.41**	**4.41**	**6.52**	**6.72**	**6.55**	**3.40**	**1.74**

D Where RouteRec Helps Most: Special Bins

This section keeps only the clearest special-bin slice from the appendix refresh: KuaiRec, where the RouteRec advantage remains visible in both short-prefix and target-frequency partitions. Rather than spreading a weak narrative over many auxiliary slice panels, we retain one representative one-column figure that shows where the gain concentrates under a behaviorally varied benchmark.

Table 9: Special-bin definitions and sample counts used in the appendix gain analysis.

Bin family	Definition rule	Visualization
Session length	Short / medium / long session buckets from the observed prefix length	Figure 6(a)
Target frequency	Rare / mid / frequent target buckets under the train split	Figure 6(b)



(a) Session-length bins (b) Target-frequency bins

Figure 6: KuaiRec special-bin gains.

Keeping only the KuaiRec slice makes the appendix argument tighter: Q1 is not just an average-score claim, and the gain pattern remains visible in a representative dataset where behavior and popularity structure are both heterogeneous. The strongest margin remains concentrated in shorter or medium prefixes, while the gain also persists across the rare-to-head target-frequency buckets.

E Extended Framework and Structural Ablations

This section extends the main-text design-justification study with the remaining temporal-layout controls that were still informative after the appendix refresh. The key question is unchanged from Q3: does the selected three-stage RouteRec layout behave like a stable architectural choice rather than a fragile expertized backbone?



(a) KuaiRec (b) Foursquare

Figure 7: Structural layout variants.

Across both panels, the selected architecture stays near the top without requiring a denser or more redundant arrangement. The remaining controls are useful as negative evidence: changing the scope order or duplicating attention capacity does not yield a cleaner design than the one already used in the paper.

F Objective and Regularization Variants

This section isolates whether the selected auxiliary objective is doing all of the work or whether nearby loss variants remain competitive once the sparse routing design is fixed. We keep the comparison on the same representative datasets as the main text and report only the objective family controls that remained meaningful after the final pass.



(a) KuaiRec (b) Foursquare

Figure 8: Objective variants.

The practical reading is modest but important for Q3: the chosen objective still wins, yet the neighboring loss settings stay in the same band. This makes the final RouteRec objective look like a tuned refinement rather than an isolated artifact.

G Efficiency Note

The refreshed appendix does not add a new efficiency figure. We retain the main-text cost ratios as the verified comparison and avoid introducing a stale appendix table or plot that was not rerun under the final visual refresh.

H Representative Routing Profiles

This section makes the routing-profile evidence explicit in appendix form. We keep the original anchor case together with three behavior-shifted cases so the reader can compare how stage-wise family emphasis moves when repeat intensity, tempo, or focus becomes more pronounced.



Figure 9: Routing-profile comparison across four representative cases. The original panel serves as an anchor, and the other three panels show how macro and all-stage family shares shift when repeated consumption, fast tempo, or narrow topical focus dominates the session.

I Targeted Interventions

This section keeps the controlled cue-family perturbations that directly support Q5. The main text already carries the representative routing cases, so the appendix is better used for the intervention evidence itself: which cue family can be removed before RouteRec visibly degrades, and whether that dependency pattern is consistent across representative datasets.



Figure 10: Cue-family interventions.

The full-cue RouteRec model remains strongest in both intervention panels, while the zero-tempo, zero-focus, zero-memory, and zero-exposure controls show which cue families matter most for ranking quality without requiring a larger multi-dataset figure block.