

1.

1 / 1 point

Softmax regression (4 possible outputs)

✗

$z_1 = \vec{w}_1 \cdot \vec{x} + b_1$

$a_1 = \frac{e^{z_1}}{e^{z_1} + e^{z_2} + e^{z_3} + e^{z_4}}$

$= P(y = 1|\vec{x})$

0.30

○

$z_2 = \vec{w}_2 \cdot \vec{x} + b_2$

$a_2 = \frac{e^{z_2}}{e^{z_1} + e^{z_2} + e^{z_3} + e^{z_4}}$

$= P(y = 2|\vec{x})$

0.20

□

$z_3 = \vec{w}_3 \cdot \vec{x} + b_3$

$a_3 = \frac{e^{z_3}}{e^{z_1} + e^{z_2} + e^{z_3} + e^{z_4}}$

$= P(y = 3|\vec{x})$

0.15

△

$z_4 = \vec{w}_4 \cdot \vec{x} + b_4$

$a_4 = \frac{e^{z_4}}{e^{z_1} + e^{z_2} + e^{z_3} + e^{z_4}}$

$= P(y = 4|\vec{x})$

0.35

For a multiclass classification task that has 4 possible outputs, the sum of all the activations adds up to 1. For a multiclass classification task that has 3 possible outputs, the sum of all the activations should add up to ....

- ☐ More than 1
- ☒ 1
- ☐ Less than 1
- ☐ It will vary, depending on the input x.

✔ Correct

Yes! The sum of all the softmax activations should add up to 1. One way to see this is that if  $e^{z_1} = 10, e^{z_2} = 20, e^{z_3} = 30$ , then the sum of  $a_1 + a_2 + a_3$  is equal to  $\frac{e^{z_1} + e^{z_2} + e^{z_3}}{e^{z_1} + e^{z_2} + e^{z_3}}$  which is 1.

2.

1 / 1 point

Logistic regression

$z = \vec{w} \cdot \vec{x} + b$

$a_1 = g(z) = \frac{1}{1 + e^{-z}} = P(y = 1|\vec{x})$

$a_2 = 1 - a_1 = P(y = 0|\vec{x})$

$loss = -y \log a_1 - (1 - y) \log(1 - a_1)$

$J(\vec{w}, b) = \text{average loss}$

Cost

Softmax regression

$a_1 = \frac{e^{z_1}}{e^{z_1} + e^{z_2} + \dots + e^{z_N}} = P(y = 1|\vec{x})$

$\vdots$

$a_N = \frac{e^{z_N}}{e^{z_1} + e^{z_2} + \dots + e^{z_N}} = P(y = N|\vec{x})$

Crossentropy loss

$loss(a_1, \dots, a_N, y) = \begin{cases} -\log a_1 & \text{if } y = 1 \\ -\log a_2 & \text{if } y = 2 \\ \vdots \\ -\log a_N & \text{if } y = N \end{cases}$

$loss = -\log a_j \text{ if } y = j$

For multiclass classification, the cross entropy loss is used for training the model. If there are 4 possible classes for the output, and for a particular training example, the true class of the example is class 3 (y=3), then what does the cross entropy loss simplify to? [Hint: This loss should get smaller when  $a_3$  gets larger.]

- ☐ z\_3
- ☐ z\_3/(z\_1+z\_2+z\_3+z\_4)
- ☐  $\frac{-\log(a_1) + -\log(a_2) + -\log(a_3) + -\log(a_4)}{4}$
- ☒  $-\log(a_3)$

✔ Correct

Correct. When the true label is 3, then the cross entropy loss for that training example is just the negative of the log of the activation for the third neuron of the softmax. All other terms of the cross entropy loss equation ( $-\log(a_1)$ ,  $-\log(a_2)$ , and  $-\log(a_4)$ ) are ignored

3.

1 / 1 point

MNIST (more numerically accurate)

```
model      import tensorflow as tf
           from tensorflow.keras import Sequential
           from tensorflow.keras.layers import Dense
           model = Sequential([
               Dense(units=25, activation='relu')
               Dense(units=15, activation='relu')
               Dense(units=10, activation='linear') ])

loss       from tensorflow.keras.losses import
           SparseCategoricalCrossentropy

model.compile(..., loss=SparseCategoricalCrossentropy(from_logits=True) )

fit        model.fit(X,Y, epochs=100)

predict    logits = model(X)
           f_x = tf.nn.softmax(logits)
```

For multiclass classification, the recommended way to implement softmax regression is to set from\_logits=True in the loss function, and also to define the model's output layer with...

- ☒ a 'linear' activation
- ☐ a 'softmax' activation

✔ Correct

Yes! Set the output as linear, because the loss function handles the calculation of the softmax with a more numerically stable method.