

Rajalakshmi Engineering College

Name: jyoshini n t
Email: 241801111@rajalakshmi.edu.in
Roll no: 241801111
Phone: 6382935798
Branch: REC
Department: I AI & DS FB
Batch: 2028
Degree: B.E - AI & DS

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 1

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Your task is to create a program to manage a playlist of items. Each item is represented as a character, and you need to implement the following operations on the playlist.

Here are the main functionalities of the program:

Insert Item: The program should allow users to add items to the front and end of the playlist. Items are represented as characters. Display Playlist: The program should display the playlist containing the items that were added.

To implement this program, a doubly linked list data structure should be used, where each node contains an item character.

Input Format

The input consists of a sequence of space-separated characters, representing the items to be inserted into the doubly linked list.

The input is terminated by entering - (hyphen).

Output Format

The first line of output prints "Forward Playlist: " followed by the linked list after inserting the items at the end.

The second line prints "Backward Playlist: " followed by the linked list after inserting the items at the front.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: a b c -

Output: Forward Playlist: a b c

Backward Playlist: c b a

Answer

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {  
    char item;  
    struct Node* next;  
    struct Node* prev;  
};
```

```
void insertAtEnd(struct Node** head, char item) {  
    struct Node* new1 = (struct Node*)malloc(sizeof(struct Node));  
    new1->item = item;  
    new1->next = NULL;  
    new1->prev = NULL;  
  
    if (*head == NULL) {  
        *head = new1;  
    } else {
```

```

        struct Node* tail1 = *head;
        while (tail1->next != NULL) {
            tail1 = tail1->next;
        }
        tail1->next = new1;
        new1->prev = tail1;
    }
}

```

```

// Function to display the list forward
void displayForward(struct Node* head) {
    struct Node* temp = head;
    while (temp != NULL) {
        printf("%c ", temp->item);
        temp = temp->next;
    }
    printf("\n");
}

```

```

// Function to display the list backward
void displayBackward(struct Node* head) {
    struct Node* temp = head;

    // Go to the last node
    if (temp == NULL) return;
    while (temp->next != NULL) {
        temp = temp->next;
    }

    // Print from last to first
    while (temp != NULL) {
        printf("%c ", temp->item);
        temp = temp->prev;
    }
    printf("\n");
}

```

```

// Function to free the entire playlist
void freePlaylist(struct Node* head) {
    struct Node* temp;
    while (head != NULL) {
        temp = head;

```

```
        head = head->next;
        free(temp);
    }
}
```

```
int main() {
    struct Node* playlist = NULL;
    char item;

    while (1) {
        scanf("%c", &item);
        if (item == '-') {
            break;
        }
        insertAtEnd(&playlist, item);
    }

    struct Node* tail = playlist;
    while (tail->next != NULL) {
        tail = tail->next;
    }

    printf("Forward Playlist: ");
    displayForward(playlist);

    printf("Backward Playlist: ");
    displayBackward(tail);

    freePlaylist(playlist);

    return 0;
}
```

Status : Correct

Marks : 10/10