

# Rajalakshmi Engineering College

Name: jyoshini n t  
Email: 241801111@rajalakshmi.edu.in  
Roll no: 241801111  
Phone: 6382935798  
Branch: REC  
Department: I AI & DS FB  
Batch: 2028  
Degree: B.E - AI & DS

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 2\_COD\_Question 5

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Ashwin is tasked with developing a simple application to manage a list of items in a shop inventory using a doubly linked list. Each item in the inventory has a unique identification number. The application should allow users to perform the following operations:

Create a List of Items: Initialize the inventory with a given number of items. Each item will be assigned a unique number provided by the user and insert the elements at end of the list.

Delete an Item: Remove an item from the inventory at a specific position.

Display the Inventory: Show the list of items before and after deletion.

If the position provided for deletion is invalid (e.g., out of range), it should

display an error message.

### ***Input Format***

The first line contains an integer  $n$ , representing the number of items to be initially entered into the inventory.

The second line contains  $n$  integers, each representing the unique identification number of an item separated by spaces.

The third line contains an integer  $p$ , representing the position of the item to be deleted from the inventory.

### ***Output Format***

The first line of output prints "Data entered in the list:" followed by the data values of each node in the doubly linked list before deletion.

If  $p$  is an invalid position, the output prints "Invalid position. Try again."

If  $p$  is a valid position, the output prints "After deletion the new list:" followed by the data values of each node in the doubly linked list after deletion.

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 4

1 2 3 4

5

Output: Data entered in the list:

node 1 : 1

node 2 : 2

node 3 : 3

node 4 : 4

Invalid position. Try again.

### ***Answer***

```
// You are using GCC
```

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
// Node structure
```

```
struct Node {  
    int data;  
    struct Node* prev;  
    struct Node* next;  
};
```

```
struct Node* head = NULL;
```

```
// Create node at end
```

```
void insertAtEnd(int value) {  
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));  
    newNode->data = value;  
    newNode->next = NULL;  
    newNode->prev = NULL;  
  
    if (head == NULL) {  
        head = newNode;  
    } else {  
        struct Node* temp = head;  
        while (temp->next != NULL) temp = temp->next;  
        temp->next = newNode;  
        newNode->prev = temp;  
    }  
}
```

```
// Display the list
```

```
void displayList() {  
    struct Node* temp = head;  
    int i = 1;  
    while (temp != NULL) {  
        printf(" node %d : %d\n", i++, temp->data);  
        temp = temp->next;  
    }  
}
```

```
// Delete node at a given position
```

```
void deleteAtPosition(int pos, int totalNodes) {  
    if (pos < 1 || pos > totalNodes) {  
        printf("Invalid position. Try again.\n");  
        return;  
    }
```

```

    }

    struct Node* temp = head;

    // Deleting first node
    if (pos == 1) {
        head = head->next;
        if (head != NULL)
            head->prev = NULL;
        free(temp);
        return;
    }

    // Traverse to the position
    for (int i = 1; i < pos; i++)
        temp = temp->next;

    // Update links and delete
    if (temp->prev != NULL)
        temp->prev->next = temp->next;
    if (temp->next != NULL)
        temp->next->prev = temp->prev;

    free(temp);
}

// Main function
int main() {
    int n, val, pos;

    scanf("%d", &n);
    for (int i = 1; i <= n; i++) {
        scanf("%d", &val);
        insertAtEnd(val);
    }

    printf("Data entered in the list:\n");
    displayList();

    scanf("%d", &pos);

    if (pos >= 1 && pos <= n) {

```

```
        deleteAtPosition(pos, n);
        printf("\n After deletion the new list:\n");
        displayList();
    } else {
        printf("Invalid position. Try again.\n");
    }

    return 0;

}
```

**Status :** Correct

**Marks :** 10/10