Today 12:26 PM

Will you explain what the brain tumor project did yesterday? I want to create a document on the project; will you help me out with this clearly? What are the tools used and what are the models used?


Worked for 43s


Yes, absolutely! Let's prepare a clear, professional document for your **Brain Tumor MRI Classification Using Deep Learning** project. I'll explain what you worked on yesterday, the tools and models involved, how the project works step by step, and how you can describe it in interviews.

Based on our previous discussion, your project compares a **Custom Convolutional Neural Network (CNN)** with **MobileNetV2 transfer learning** and uses a Streamlit application to classify uploaded brain MRI images.

Brain Tumor Detection Using Deep Learning

1. Project overview





Project title: Brain Tumor Classification Using Deep Learning

Domain: Artificial Intelligence, Machine Learning, Deep Learning, Medical Image Analysis

Objective: To develop a deep learning system that analyzes brain MRI images and predicts the tumor category associated with an uploaded image.

Brain MRI scans contain visual patterns that may help distinguish different brain tumor categories. Manually reviewing these images requires medical expertise. This project explores how deep learning can learn image

features and classify MRI scans automatically.

The project trains and compares two approaches:

- **Custom CNN:** A convolutional neural network built using layers designed for this project.
- **MobileNetV2:** A pretrained image classification architecture adapted to the brain MRI dataset using transfer learning.

The trained model is then connected to a Streamlit web interface so users can upload an MRI image and view a prediction.

Important: This is an educational image-classification project, not a clinically validated diagnostic system. Its predictions should not be used to make medical decisions.

2. Tools and technologies used



Python

The main programming language used to build the training pipeline, process MRI images, evaluate the models, and connect the application.



TensorFlow and Keras

Used to create and train the custom CNN, load and adapt MobileNetV2, manage neural network layers, and save trained models.



Streamlit

Used to create the interactive web application for uploading MRI images and displaying predictions.



NumPy

Used for numerical operations and preparing image data as arrays for model prediction.



Matplotlib and Seaborn

Used to visualize training and validation accuracy and loss, and to create plots for model evaluation and comparison.



Scikit-learn

Used for evaluation metrics such as accuracy, precision, recall, F1-score, classification reports, and confusion matrices.

Pillow (PIL)

Used in the application to open uploaded images, convert them to RGB format, and resize them to the input dimensions expected by the model.


Git and GitHub

Used for source-code version control and project sharing. We also discussed removing the `.venv` directory from Git because it contained very large TensorFlow-related files.

Other supporting tools include **VS Code or another Python IDE**, a Python virtual environment (`.venv`), and the terminal for running training and launching the application.

3. Models used in the project

The central part of your project is the comparison of two deep learning models.



Model 1: Custom CNN

CNN — Convolutional Neural Network


A CNN is a deep learning model designed to identify patterns in images. It learns useful features directly from training images, rather than requiring us to manually define every feature.

How it works:

1. Input layer receives a brain MRI image.
2. Convolutional layers learn visual patterns such as edges, shapes, and textures.
3. Pooling layers reduce the spatial dimensions of the extracted features.

4. Flattening or global pooling converts the feature maps into a representation suitable for classification.
5. Dense layers learn to distinguish the image classes.
6. The output layer produces class scores or probabilities.

Why it is used: To build an image classifier specifically trained on the brain MRI dataset and establish a baseline for comparison.



Model 2: MobileNetV2

MobileNetV2 — Transfer Learning

MobileNetV2 is a convolutional neural network architecture originally developed for efficient image recognition. In this project, a pretrained MobileNetV2 model is adapted to classify brain MRI images.

How it works:

1. An MRI image is resized to the expected input size, typically 224 × 224 pixels.
2. The image passes through the pretrained MobileNetV2 feature extractor.
3. The pretrained layers extract useful visual features.
4. A task-specific classification head maps these features to the brain MRI dataset's classes.
5. The model outputs the predicted class scores or probabilities.

Why it is used: Transfer learning reuses visual features learned from a large image dataset. It can reduce the amount of training needed compared with learning every feature from scratch.

MobileNetV2 uses inverted residual blocks and depthwise separable convolutions to make the architecture computationally efficient.

Custom CNN vs. MobileNetV2

Feature	Custom CNN	MobileNetV2
Approach	Trained for this project	Transfer learning
Initial weights	Usually randomly initialized	Pretrained weights
Feature learning	Learns features from the MRI dataset	Reuses pretrained visual features
Main advantage	Simple baseline and greater control over architecture	Efficient feature extraction
Main consideration	May need more data to learn robust features	Input preprocessing and fine-tuning must be handled correctly

The purpose of training both models is to compare their performance on the same classification task. **Neither model should be described as the winner until the actual evaluation results confirm it.**

4. Dataset and folder structure

Your project uses separate training and testing directories inside a `data` folder.

```
Plain text

Brain_Tumor_Project/
│
├── data/
│   ├── train/
│   │   ├── class_1/
│   │   ├── class_2/
│   │   └── ...
│   │
│   └── test/
│       ├── class_1/
│       ├── class_2/
│       └── ...
│
├── models/
│   └── saved trained models
│
├── results/
│   ├── accuracy and loss plots
│   ├── confusion matrices
│   └── model comparison results
│
├── train.py
├── app.py
```

The class folder names shown above are placeholders. Your actual dataset may use names such as `glioma`, `meningioma`, `notumor`, and `pituitary`; use the exact folder names from your dataset.

How the dataset is used

- **Training set:** Supplies images used to learn the model parameters.
- **Validation set:** If configured, helps monitor performance during training and guide model selection.
- **Test set:** Evaluates how the trained model performs on images not used to fit its weights.

If the code uses `ImageDataGenerator`, `image_dataset_from_directory`, or another directory loader, the folder names may be used to assign class labels automatically.

One important distinction: having a `train` and `test` folder does not automatically mean that a validation set exists. That depends on how the training code creates or loads it.

5. What we worked on yesterday

On October 11–12, 2026, we worked on setting up and correcting the brain tumor project training code and application. These are the main points from our discussion.

1. **Dataset directory correction**

   You explained that your data folder already contains directories named `train` and `test`. We discussed configuring the code to use `data/train` and `data/test`, with class-specific folders inside each directory.

2. **Training script corrections**

   We reviewed errors in the training code, including model saving and training-history references. The important corrections discussed included defining `model_path` before saving a model and using the correct `history` variable for plotting training results rather than referencing an undefined `history_mobilenet` variable.

3. **Keras model serialization error**

   You encountered a Keras error while loading or deserializing a model. We discussed replacing a Lambda layer used for MobileNetV2 preprocessing with a Rescaling layer and retraining the model. This requires the input scaling to match MobileNetV2's expected preprocessing; a Rescaling layer is not automatically an equivalent replacement for every `preprocess_input` configuration.

4. **Separating training and application code**

   We discussed keeping `train.py` responsible for training and evaluation, and `app.py` responsible for loading the saved model and running predictions. This makes the project easier to maintain and avoids retraining whenever a user opens the application.

5. **Application image handling**


   The Streamlit application was designed to accept an uploaded image, convert it to RGB, resize it to 224 × 224 pixels, and pass the resulting image array to the model for prediction.

6. **Evaluation and result files**

We discussed generating MobileNetV2 evaluation outputs, including a confusion matrix, accuracy/loss plots, and a `model_comparison.csv` file. These outputs help compare the custom CNN and MobileNetV2.

These were the issues and fixes discussed, not confirmation that every error has been completely resolved. We would need to inspect your latest `train.py`, `app.py`, and actual output files to verify the final state.

6. Complete project workflow



How prediction works inside the application

When a user uploads a brain MRI image:

1. Streamlit receives the uploaded file.

2. Pillow opens the image and converts it to RGB.
3. The image is resized to the model's expected dimensions.
4. NumPy converts the image into an array, and a batch dimension is added.
5. The saved model performs inference.
6. The application identifies the class with the highest output score, assuming the model produces class scores or probabilities.
7. The predicted class and, if implemented correctly, its associated confidence score are displayed.

The preprocessing performed by `app.py` must match the preprocessing used during training. Otherwise, the model may produce unreliable predictions even when the application runs without errors.

7. Evaluation metrics

These metrics help determine whether the models classify the test images correctly.

Metric	Meaning
Accuracy	Proportion of all predictions that are correct
Precision	Of the images predicted as a particular class, how many truly belong to that class
Recall	Of the images belonging to a particular class, how many the model correctly identifies
F1-score	Harmonic mean of precision and recall
Confusion matrix	Shows correct predictions and which classes are confused with one another
Training/validation loss	Helps monitor how well the model fits the data and whether overfitting may be occurring

Accuracy alone may be misleading if the dataset has imbalanced classes. Precision, recall, F1-score, per-class results, and a separate test set give a more complete picture.

8. Ready-to-use project documentation

You can copy the following document into Microsoft Word and use it as your project report. It describes the project, technologies, models, workflow, and evaluation without inventing accuracy results or claiming that the project is clinically validated.

Writing




BRAIN TUMOR CLASSIFICATION USING DEEP LEARNING

1. Abstract

Brain Tumor Classification Using Deep Learning is an image-classification project that uses brain Magnetic Resonance Imaging (MRI) scans to predict the corresponding image category. The project explores deep learning techniques for extracting visual features from medical images and distinguishing between multiple

classes.

Two approaches are considered: a custom Convolutional Neural Network (CNN) and MobileNetV2 using transfer learning. Their performance can be compared using classification metrics and visualization techniques. A Streamlit-based web application provides an interface for uploading an MRI image and viewing the model's prediction.

The project demonstrates the use of deep learning, image preprocessing, model evaluation, and web application development in medical image analysis. It is intended for educational purposes and does not replace professional medical diagnosis.

2. Objectives

- Develop a deep learning model for brain MRI image classification.
- Preprocess MRI images into the format required by the models.
- Train a custom CNN and implement MobileNetV2 transfer learning.
- Evaluate and compare the models using suitable classification metrics.
- Visualize model training and evaluation results.
- Develop an interactive Streamlit application for image upload and prediction.

3. Technologies Used

- **Programming language:** Python
- **Deep learning framework:** TensorFlow and Keras
- **Image processing:** Pillow (PIL)
- **Numerical computation:** NumPy
- **Data analysis:** Pandas, if used in the training and evaluation scripts
- **Visualization:** Matplotlib and Seaborn
- **Evaluation:** Scikit-learn
- **Web application:** Streamlit
- **Development environment:** Visual Studio Code or another Python IDE
- **Version control:** Git and GitHub

4. Models Used

4.1 Custom Convolutional Neural Network (CNN)

A CNN is a deep learning architecture commonly used for image classification. It learns visual features from training images through convolutional and pooling layers. These features are passed to classification layers to predict the image category.

In this project, the custom CNN serves as a model trained specifically on the brain MRI dataset.

4.2 MobileNetV2 Transfer Learning

MobileNetV2 is a lightweight convolutional neural network architecture designed for efficient image recognition. Transfer learning allows the project to reuse features learned from a pretrained model and adapt its classification output to the MRI dataset.

The input image is prepared according to the model's expected dimensions and preprocessing requirements. A classification head produces the output scores for the dataset's classes.

4.3 Model Comparison

The two models are evaluated to understand their classification performance. The comparison can include accuracy, precision, recall, F1-score, confusion matrices, and training/validation curves. The preferred model should be selected based on verified test results rather than assumptions.

5. Dataset Description

The project uses a brain MRI image dataset organized into separate training and testing directories. Each directory contains subdirectories representing the image classes.

- **Training data:** Used to learn model parameters.
- **Validation data:** Used to monitor training and guide model selection, if configured.
- **Testing data:** Used to evaluate the trained model on unseen images.

The exact number of images, class names, and class distribution should be documented from the actual dataset.

6. Methodology

1. **Dataset organization:** Organize MRI images into the appropriate training and testing directories.
2. **Image preprocessing:** Load images, resize them to the expected input dimensions, convert them into suitable color formats, and apply the required scaling or preprocessing.
3. **Model development:** Create the custom CNN and adapt MobileNetV2 for the classification task.
4. **Model training:** Train the custom CNN and configure the MobileNetV2 training process.
5. **Model evaluation:** Evaluate predictions and generate classification metrics and confusion matrices.
6. **Result visualization:** Plot accuracy and loss curves and save comparison results.
7. **Model saving:** Save the trained models for later inference.
8. **Application development:** Use Streamlit to provide an interface for uploading an MRI image and displaying the prediction.

7. System Architecture

The system consists of two main components.

Training component: Reads the dataset, preprocesses images, trains the models, evaluates their performance, and saves the trained models and results.

Prediction component: Loads the saved model, accepts an MRI image through the Streamlit interface, preprocesses the image consistently with training, and displays the predicted class.

8. Application Features

- Upload a brain MRI image.
- Prepare the uploaded image for model inference.
- Generate a prediction using the loaded model.
- Display the predicted image category.
- Display a confidence score if it is implemented and correctly derived from the model output.
- Present a user-friendly interface through Streamlit.

9. Evaluation

The following metrics can be used to evaluate classification performance:

- Accuracy
- Precision
- Recall
- F1-score
- Confusion matrix
- Training and validation accuracy
- Training and validation loss

The final report should include the actual test results for both models. No numerical performance claims should be added until they have been verified from the generated evaluation outputs.

10. Expected Outcome

The expected outcome is a working educational application that classifies brain MRI images into the categories represented in the dataset. The model comparison provides an opportunity to study the differences between training a custom CNN and adapting a pretrained model using transfer learning.

11. Conclusion

This project demonstrates an end-to-end deep learning workflow for medical image classification, from

dataset preparation and model training to performance evaluation and application development. Comparing a custom CNN with MobileNetV2 provides practical experience with convolutional neural networks and transfer learning. The Streamlit application makes the prediction process accessible through a simple interface.

The system is a learning and experimentation tool, not a clinically validated diagnostic solution.

12. Future Scope

- Evaluate the models on additional independent MRI datasets.
- Improve generalization through suitable data augmentation and model tuning.
- Add detailed per-class evaluation and explainability visualizations.
- Improve the application's error handling and input validation.
- Explore deployment and performance monitoring after appropriate testing.
- Conduct further clinical validation before considering any real-world medical use.

9. How to run the project

From your project directory, activate your existing virtual environment and run the scripts in the appropriate order.

Bash

```bash
# Activate the virtual environment on Windows
.venv\Scripts\activate

# Install dependencies if requirements.txt is available
pip install -r requirements.txt

# Train the models and generate evaluation results
python train.py

# Launch the Streamlit application
streamlit run app.py
```

Run the training command only if `train.py` is your actual training-script filename and its current code is ready to execute. The Streamlit application also requires a trained model at the exact path expected by `app.py`.

10. Final details to complete your report

To make this documentation fully specific to your project rather than a general template, we should verify three things from your actual code:

- The exact MRI class names and total number of images.

- The CNN architecture and the exact MobileNetV2 configuration, including whether pretrained weights were frozen or fine-tuned.
- The actual accuracy and other evaluation results produced by your training script.

Please upload your latest `train.py` and `app.py` files. I'll use those files to identify the exact models, tools, workflow, and implemented features, then help you finalize the report with accurate technical details and an interview-ready explanation.