

Hands on 2

Spring Core – Load Country from Spring Configuration XML

An airlines website is going to support booking on four countries. There will be a drop down on the home page of this website to select the respective country. It is also important to store the two-character ISO code of each country.

Code Name

US United States

DE Germany

IN India

JP Japan

Above data has to be stored in spring configuration file. Write a program to read this configuration file and display the details.

Code –

1.country.xml

```
<?xml version="1.0" encoding="UTF-8"?>

<beans xmlns="http://www.springframework.org/schema/beans"
       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
       xsi:schemaLocation="
           http://www.springframework.org/schema/beans
           http://www.springframework.org/schema/beans/spring-beans.xsd">

    <bean id="country" class="com.cognizant.springlearn.Country">
        <property name="code" value="IN"/>
        <property name="name" value="India"/>
    </bean>

</beans>
```

2.country.java

```
package com.cognizant.springlearn;
```

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;

public class Country {

    private static final Logger LOGGER =
        LoggerFactory.getLogger(Country.class);

    private String code;
    private String name;

    public Country() {
        LOGGER.debug("Inside Country Constructor.");
    }

    public String getCode() {
        LOGGER.debug("Inside getCode()");
        return code;
    }

    public void setCode(String code) {
        LOGGER.debug("Inside setCode()");
        this.code = code;
    }

    public String getName() {
        LOGGER.debug("Inside getName()");
        return name;
    }

    public void setName(String name) {
        LOGGER.debug("Inside setName()");
        this.name = name;
    }

    @Override
    public String toString() {
        return "Country [code=" + code + ", name=" + name + "];"
    }
}
```

```

    }
}

3.SpringLearnApplication.java

package com.cognizant.springlearn;

import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
import org.springframework.context.ApplicationContext;
import org.springframework.context.support.ClassPathXmlApplicationContext;

@SpringBootApplication
public class SpringLearnApplication {

    private static final Logger LOGGER =
        LoggerFactory.getLogger(SpringLearnApplication.class);

    public static void main(String[] args) {
        SpringApplication.run(SpringLearnApplication.class, args);
        displayCountry();
    }

    public static void displayCountry() {
        ApplicationContext context =
            new ClassPathXmlApplicationContext("country.xml");

        Country country =
            context.getBean("country", Country.class);
        LOGGER.debug("Country : {}", country.toString());
    }
}

```

OUTPUT –

Inside Country Constructor.

Inside setCode()

Inside setName()

Country : Country [code=IN, name=India]