Exp 13: Experiment to handle missing values and inappropriate data is a given data set.

AIM: Understand the procedure to handle missing and inappropriate data.

SAMPLE CODE:

```
import numpy as np
 import pandas as pd
df=pd.read_csv("Hotel_Dataset.csv")
 df
df.duplicated()
df.info()
df.drop_duplicates(inplace=True)
df
len(df)
index=np.array(list(range(0,len(df))))
df.set_index(index,inplace=True)
index
df
df.drop(['Age_Group.1'],axis=1,inplace=True)
df
df.CustomerID.loc[df.CustomerID<0]=np.nan
df.Bill.loc[df.Bill<0]=np.nan
df.EstimatedSalary.loc[df.EstimatedSalary<0]=np.nan
df
df['NoOfPax'].loc[(df['NoOfPax']20)]=np.nan
```

df

df.Age_Group.unique()

df.Hotel.unique()

df.Hotel.replace(['Ibys'],'Ibis',inplace=True)

df.FoodPreference.unique

df.FoodPreference.replace(['Vegetarian','veg'],'Veg',inplace=True)
df.FoodPreference.replace(['non-Veg'],'Non-Veg',inplace=True)

df.EstimatedSalary.fillna(round(df.EstimatedSalary.mean()),inplace=True)
df.NoOfPax.fillna(round(df.NoOfPax.median()),inplace=True) df['Rating(1-5)'].fillna(round(df['Rating(1-5)'].median()), inplace=True)
df.Bill.fillna(round(df.Bill.mean()),inplace=True) df

OUTPUT:

Upload Hotel.csv and convert it into dataFrame

import numpy as np

import pandas as pd

df=pd.read_csv("Hotel_Dataset.csv")

df

	CustomerID	Age_Group	Rating(1-5)	Hotel	FoodPreference	Bill	NoOfPax	EstimatedSalary	Age_Group.1
0	1	20-25	4	Ibis	veg	1300	2	40000	20-25
1	2	30-35	5	LemonTree	Non-Veg	2000	3	59000	30-35
2	3	25-30	6	RedFox	Veg	1322	2	30000	25-30
3	4	20-25	-1	LemonTree	Veg	1234	2	120000	20-25
4	5	35+	3	Ibis	Vegetarian	989	2	45000	35+
5	6	35+	3	Ibys	Non-Veg	1909	2	122220	35+
6	7	35+	4	RedFox	Vegetarian	1000	-1	21122	35+
7	8	20-25	7	LemonTree	Veg	2999	-10	345673	20-25
8	9	25-30	2	Ibis	Non-Veg	3456	3	-99999	25-30
9	9	25-30	2	Ibis	Non-Veg	3456	3	-99999	25-30
10	10	30-35	5	RedFox	non-Veg	-6755	4	87777	30-35

#From the dataframe identify the duplicate row(i.e row 9)

The duplicated() method returns a Series with True and False values that describe which rows in the DataFrame are duplicated and not.

df.duplicated()

```
0     False
1     False
2     False
3     False
4     False
5     False
6     False
7     False
8     False
9      True
10    False
dtype: bool
```

The info() method prints information about the DataFrame. The information contains the number of columns, column labels, column data types, memory usage, range index, and the number of cells in each column (non-null values).

df.info()

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 11 entries, 0 to 10
Data columns (total 9 columns):
 #   Column           Non-Null Count  Dtype 
---  ------           --------------  ----- 
 0   CustomerID       11 non-null     int64 
 1   Age_Group        11 non-null     object
 2   Rating(1-5)      11 non-null     int64 
 3   Hotel            11 non-null     object
 4   FoodPreference   11 non-null     object
 5   Bill             11 non-null     int64 
 6   NoOfPax          11 non-null     int64 
 7   EstimatedSalary  11 non-null     int64 
 8   Age_Group.1      11 non-null     object
dtypes: int64(5), object(4)
memory usage: 924.0+ bytes
```

The drop_duplicates() method removes duplicate rows.

df.drop_duplicates(inplace=True)

df

	CustomerID	Age_Group	Rating(1-5)	Hotel	FoodPreference	Bill	NoOfPax	EstimatedSalary	Age_Group.1
0	1	20-25	4	Ibis	veg	1300	2	40000	20-25
1	2	30-35	5	LemonTree	Non-Veg	2000	3	59000	30-35
2	3	25-30	6	RedFox	Veg	1322	2	30000	25-30
3	4	20-25	-1	LemonTree	Veg	1234	2	120000	20-25
4	5	35+	3	Ibis	Vegetarian	989	2	45000	35+
5	6	35+	3	Ibys	Non-Veg	1909	2	122220	35+
6	7	35+	4	RedFox	Vegetarian	1000	-1	21122	35+
7	8	20-25	7	LemonTree	Veg	2999	-10	345673	20-25
8	9	25-30	2	Ibis	Non-Veg	3456	3	-99999	25-30
10	10	30-35	5	RedFox	non-Veg	-6755	4	87777	30-35

#While removing duplicate record row index also removed

The len() function to return the length of an object. With a dataframe, the function returns the number of rows.

len(df)

10

#Reset the index

index=np.array(list(range(0,len(df))))

df.set_index(index,inplace=True)

index

```
array([0, 1, 2, 3, 4, 5, 6, 7, 8, 9])
```

df

	CustomerID	Age_Group	Rating(1-5)	Hotel	FoodPreference	Bill	NoOfPax	EstimatedSalary	Age_Group.1
0	1	20-25	4	Ibis	veg	1300	2	40000	20-25
1	2	30-35	5	LemonTree	Non-Veg	2000	3	59000	30-35
2	3	25-30	6	RedFox	Veg	1322	2	30000	25-30
3	4	20-25	-1	LemonTree	Veg	1234	2	120000	20-25
4	5	35+	3	Ibis	Vegetarian	989	2	45000	35+
5	6	35+	3	Ibys	Non-Veg	1909	2	122220	35+
6	7	35+	4	RedFox	Vegetarian	1000	-1	21122	35+
7	8	20-25	7	LemonTree	Veg	2999	-10	345673	20-25
8	9	25-30	2	Ibis	Non-Veg	3456	3	-99999	25-30
9	10	30-35	5	RedFox	non-Veg	-6755	4	87777	30-35

Axis refers to the dimensions of a DataFrame (index and columns) or Series (index only) Use axis=0 to apply functions row-wise along the index. Use axis=1 to apply functions column-wise across columns.

df.drop(['Age_Group.1'],axis=1,inplace=True)

df

	CustomerID	Age_Group	Rating(1-5)	Hotel	FoodPreference	Bill	NoOfPax	EstimatedSalary
0	1	20-25	4	Ibis	veg	1300	2	40000
1	2	30-35	5	LemonTree	Non-Veg	2000	3	59000
2	3	25-30	6	RedFox	Veg	1322	2	30000
3	4	20-25	-1	LemonTree	Veg	1234	2	120000
4	5	35+	3	Ibis	Vegetarian	989	2	45000
5	6	35+	3	Ibys	Non-Veg	1909	2	122220
6	7	35+	4	RedFox	Vegetarian	1000	-1	21122
7	8	20-25	7	LemonTree	Veg	2999	-10	345673
8	9	25-30	2	Ibis	Non-Veg	3456	3	-99999
9	10	30-35	5	RedFox	non-Veg	-6755	4	87777

The function . loc is typically used for label indexing and can access multiple columns.

df.CustomerID.loc[df.CustomerID<0]=np.nan

df.Bill.loc[df.Bill<0]=np.nan

df.EstimatedSalary.loc[df.EstimatedSalary<0]=np.nan

df

```
C:\Users\Ayyadurai\AppData\Local\Temp\ipykernel_5300\2580639570.py:1: S
ettingWithCopyWarning:
A value is trying to be set on a copy of a slice from a DataFrame
See the caveats in the documentation: https://pandas.pydata.org/pandas-
docs/stable/user_guide/indexing.html#returning-a-view-versus-a-copy
  df.CustomerID.loc[df.CustomerID<0]=np.nan
df.Bill.loc[df.Bill<0]=np.nan
C:\Users\Ayyadurai\AppData\Local\Temp\ipykernel_5300\2580639570.py:2: S
ettingWithCopyWarning:
A value is trying to be set on a copy of a slice from a DataFrame
df.EstimatedSalary.loc[df.EstimatedSalary<0]=np.nan
```

	CustomerID	Age_Group	Rating(1-5)	Hotel	FoodPreference	Bill	NoOfPax	EstimatedSalary
0	1.0	20-25	4.0	Ibis	veg	1300.0	2	40000.0
1	2.0	30-35	5.0	LemonTree	Non-Veg	2000.0	3	59000.0
2	3.0	25-30	NaN	RedFox	Veg	1322.0	2	30000.0
3	4.0	20-25	NaN	LemonTree	Veg	1234.0	2	120000.0
4	5.0	35+	3.0	Ibis	Vegetarian	989.0	2	45000.0
5	6.0	35+	3.0	Ibys	Non-Veg	1909.0	2	122220.0
6	7.0	35+	4.0	RedFox	Vegetarian	1000.0	-1	21122.0
7	8.0	20-25	NaN	LemonTree	Veg	2999.0	-10	345673.0
8	9.0	25-30	2.0	Ibis	Non-Veg	3456.0	3	NaN
9	10.0	30-35	5.0	RedFox	non-Veg	NaN	4	87777.0

df['NoOfPax'].loc[(df['NoOfPax']<1) | (df['NoOfPax']>20)]=np.nan

df

```
C:\Users\Ayyadurai\AppData\Local\Temp\ipykernel_5300\2129877948.py:1: S
ettingWithCopyWarning:
A value is trying to be set on a copy of a slice from a DataFrame

See the caveats in the documentation: https://pandas.pydata.org/pandas-
docs/stable/user_guide/indexing.html#returning-a-view-versus-a-copy
  df['NoOfPax'].loc[(df['NoOfPax']<1) | (df['NoOfPax']>20)]=np.nan
```

	CustomerID	Age_Group	Rating(1-5)	Hotel	FoodPreference	Bill	NoOfPax	EstimatedSalary
0	1.0	20-25	4.0	Ibis	veg	1300.0	2.0	40000.0
1	2.0	30-35	5.0	LemonTree	Non-Veg	2000.0	3.0	59000.0
2	3.0	25-30	NaN	RedFox	Veg	1322.0	2.0	30000.0
3	4.0	20-25	NaN	LemonTree	Veg	1234.0	2.0	120000.0
4	5.0	35+	3.0	Ibis	Vegetarian	989.0	2.0	45000.0
5	6.0	35+	3.0	Ibys	Non-Veg	1909.0	2.0	122220.0
6	7.0	35+	4.0	RedFox	Vegetarian	1000.0	NaN	21122.0
7	8.0	20-25	NaN	LemonTree	Veg	2999.0	NaN	345673.0
8	9.0	25-30	2.0	Ibis	Non-Veg	3456.0	3.0	NaN
9	10.0	30-35	5.0	RedFox	non-Veg	NaN	4.0	87777.0

df.Age_Group.unique()

```
array(['20-25', '30-35', '25-30', '35+'], dtype=object)
```

df.Hotel.unique()

```
array(['Ibis', 'LemonTree', 'RedFox', 'Ibys'], dtype=object)
```

Using the inplace=True keyword in a pandas method changes the default behaviour such that the operation on the dataframe doesn't return anything, it instead 'modifies the underlying data

df.Hotel.replace(['Ibys'],'Ibis',inplace=True)

df.FoodPreference.unique

```
<bound method Series.unique of 0           veg
1       Non-Veg
2           Veg
3           Veg
4    Vegetarian
5       Non-Veg
6    Vegetarian
7           Veg
8       Non-Veg
9       non-Veg
Name: FoodPreference, dtype: object>
```

df.FoodPreference.replace(['Vegetarian','veg'],'Veg',inplace=True)

df.FoodPreference.replace(['non-Veg'],'Non-Veg',inplace=True)

Fillna is a Pandas function to fill the NA/NaN values with the specified method.

If column or feature is numerical continuous data then replace the missing(NaN) value by taking mean value.

If column or feature is numerical discrete data then replace the missing(NaN) value by taking median value.

If column or feature is non-numerical i.e Categorical data then replace the missing(NaN) value by taking mode value.

df.EstimatedSalary.fillna(round(df.EstimatedSalary.mean()),inplace=True)

df.NoOfPax.fillna(round(df.NoOfPax.median()),inplace=True)

df['Rating(1-5)'].fillna(round(df['Rating(1-5)'].median()), inplace=True)

df.Bill.fillna(round(df.Bill.mean()),inplace=True)

df

	CustomerID	Age_Group	Rating(1-5)	Hotel	FoodPreference	Bill	NoOfPax	EstimatedSalary
0	1.0	20-25	4.0	Ibis	Veg	1300.0	2.0	40000.0
1	2.0	30-35	5.0	LemonTree	Non-Veg	2000.0	3.0	59000.0
2	3.0	25-30	4.0	RedFox	Veg	1322.0	2.0	30000.0
3	4.0	20-25	4.0	LemonTree	Veg	1234.0	2.0	120000.0
4	5.0	35+	3.0	Ibis	Veg	989.0	2.0	45000.0
5	6.0	35+	3.0	Ibis	Non-Veg	1909.0	2.0	122220.0
6	7.0	35+	4.0	RedFox	Veg	1000.0	2.0	21122.0
7	8.0	20-25	4.0	LemonTree	Veg	2999.0	2.0	345673.0
8	9.0	25-30	2.0	Ibis	Non-Veg	3456.0	3.0	96755.0
9	10.0	30-35	5.0	RedFox	Non-Veg	1801.0	4.0	87777.0

RESULT: Thus, experiment to handle missing values and inappropriate data in a given data set.