Exp 15: EXPERIMENT TO UNDERSTAND THE DATA PREPROCESSING IN DATA SCIENCE.

AIM: Understand the importance of Data preprocessing in data science.

SAMPLE CODE:

```
import numpy as np
import pandas as pd

df = pd.read_csv("/content/pre-process_datasample.csv")
df

df.info()

df.Country.mode()

df.Country.mode()[0]

type(df.Country.mode())

df.Country.fillna(df.Country.mode()[0], inplace=True)

df.Age.fillna(df.Age.median(), inplace=True)

df.Salary.fillna(round(df.Salary.mean()), inplace=True)
```

```
df
```

```
pd.get_dummies(df.Country)
```

```
updated_dataset = pd.concat([pd.get_dummies(df.Country), df.iloc[:, 1:]], axis=1)
```

```
updated_dataset
```

```
df.info()
```

```
updated_dataset.Purchased.replace(['No', 'Yes'], [0, 1], inplace=True)
```

```
updated_dataset
```

OUTPUT:

```
import numpy as np
import pandas as pd
df=pd.read_csv("/content/pre-process_datasample.csv")
df
```

	Country	Age	Salary	Purchased
0	France	44.0	72000.0	No
1	Spain	27.0	48000.0	Yes
2	Germany	30.0	54000.0	No
3	Spain	38.0	61000.0	No
4	Germany	40.0	NaN	Yes
5	France	35.0	58000.0	Yes
6	Spain	NaN	52000.0	No
7	France	48.0	79000.0	Yes
8	NaN	50.0	83000.0	No
9	France	37.0	67000.0	Yes

Double-click (or enter) to edit

```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 10 entries, 0 to 9
Data columns (total 4 columns):
 #   Column     Non-Null Count  Dtype  
---  ------     --------------  -----  
 0   Country    9 non-null      object 
 1   Age        9 non-null      float64
 2   Salary     9 non-null      float64
 3   Purchased  10 non-null     object 
dtypes: float64(2), object(2)
memory usage: 448.0+ bytes
```

```
df.Country.mode()
```

	Country
0	France

```
df.Country.mode()[0]
```

```
type(df.Country.mode())
```

```
pandas.core.series.Series
def __init__(data=None, index=None, dtype: Dtype | None=None, name=None, copy: bool | None=None,
fastpath: bool=False) -> None
```

```
    index is not None, the resulting Series is reindexed with the index values.
dtype : str, numpy.dtype, or ExtensionDtype, optional
    Data type for the output Series. If not specified, this will be
    inferred from `data`.
    See the :ref:`user guide <basics.dtypes>` for more usages.
name : Hashable, default None
    The name to give to the Series.
```

```
df.Country.fillna(df.Country.mode()[0],inplace=True)

df.Age.fillna(df.Age.median(),inplace=True)

df.Salary.fillna(round(df.Salary.mean()),inplace=True)

df

updated_dataset
```

	France	Germany	Spain	Age	Salary	Purchased
0	True	False	False	44.0	72000.0	0
1	False	False	True	27.0	48000.0	1
2	False	True	False	30.0	54000.0	0
3	False	False	True	38.0	61000.0	0
4	False	True	False	40.0	63778.0	1
5	True	False	False	35.0	58000.0	1
6	False	False	True	38.0	52000.0	0
7	True	False	False	48.0	79000.0	1
8	True	False	False	50.0	83000.0	0

Start coding or generate with AI.

	Country	Age	Salary	Purchased
0	France	44.0	72000.0	No
1	Spain	27.0	48000.0	Yes
2	Germany	30.0	54000.0	No
3	Spain	38.0	61000.0	No
4	Germany	40.0	63778.0	Yes
5	France	35.0	58000.0	Yes
6	Spain	38.0	52000.0	No
7	France	48.0	79000.0	Yes
8	France	50.0	83000.0	No

```
pd.get_dummies(df.Country)
```

	France	Germany	Spain
0	True	False	False
1	False	False	True
2	False	True	False
3	False	False	True
4	False	True	False
5	True	False	False
6	False	False	True
7	True	False	False
8	True	False	False

```
updated_dataset=pd.concat([pd.get_dummies(df.Country),df.iloc[:,[1,
```

```
updated_dataset
```

	France	Germany	Spain	Age	Salary	Purchased
0	True	False	False	44.0	72000.0	No
1	False	False	True	27.0	48000.0	Yes
2	False	True	False	30.0	54000.0	No
3	False	False	True	38.0	61000.0	No
4	False	True	False	40.0	63778.0	Yes
5	True	False	False	35.0	58000.0	Yes
6	False	False	True	38.0	52000.0	No
7	True	False	False	48.0	79000.0	Yes
8	True	False	False	50.0	83000.0	No

```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 10 entries, 0 to 9
Data columns (total 4 columns):
 #   Column     Non-Null Count  Dtype  
---  ------     --------------  -----  
 0   Country    10 non-null     object 
 1   Age        10 non-null     float64
 2   Salary     10 non-null     float64
 3   Purchased  10 non-null     object 
dtypes: float64(2), object(2)
memory usage: 448.0+ bytes
```

```
updated_dataset.Purchased.replace(['No','Yes'],[0,1],inplace=True)
```

RESULT: Thus, the experiment to understand the data preprocessing in data science is conducted.