



Algorithm (recursion)



Essential parts of codes

- In order to make each element a starting point, I used a double-layer loop in the main program (posted below) to iterate over each number in a two-dimensional array.

First, with fixed R3(row), increment R4(column) and each time enter recursion(when return from the recursion, reset the counter R2 to 1, CON part from line 10 to line 14), until R4 is equal to M(line 5).

When R4 is equal to M, plus one to R3 and clear R4(from line 7 to line 9), then repeat this process, until R3 is equal to N(line 2). Finally, assign MAX to R2 as our output, and over the program.

1	RE1 LD	R5, _N	
2	ADD	R1, R3, R5	; R3 - N
3	BRZ	PUTOUT	
4	RE2 LD	R5, _M	
5	ADD	R1, R4, R5	; R4 - M
6	BRN	CON	

```

7      AND      R4,R4,#0      ; R4 = 0
8      ADD      R3,R3,#1      ; R3++
9      BR       RE1
10     CON JSR   RE
11     ADD      R4,R4,#1      ; R4++
12     AND      R2,R2,#0
13     ADD      R2,R2,#1      ; R2 = 1
14     BR       RE2

```

- The essential part of my codes is about **recursion**, and to reduce the repetition, I only keep one of the four directions(up and down, left and right) for analysis. The code posted below is also simplified.

One more thing to note before I analyze the codes is that I use two subroutines in recursion, which are LOADMAP and SAVE.(This is not the core part of the code, so I did not post their code in the report.)

For LOADMAP, it will make R0 equal to MAP [R3].[R4] (namely the element with row R3 and column R4 in the two-dimensional array MAP).

And for SAVE, it compares the value of R2 and MAX, then assigns the bigger one to MAX.

Based on the current point, judge whether it can go up, down, left and right in turn (the value in this point is greater than the value in the next point, written as $map > map'$ in the following report). There are two steps here. The first step is whether there is a way to go(the next point exists), the second step is whether the conditions($map' < map$) are met.

Here we take direction UP for example. If the first step does not fit, jump to the next direction(line 8, jump to DOWN part starting from line 20). And if the second step doesn't fit, plus one to R3(line 19, U1 part) before jump to next direction(line 14 and DOWN part). (R3 plus one to keep the current point the same as the base point of recursion at this level, namely the same point when enter UP part.)

If all of two conditions are fit, the program plus one to counter R2(line 15) and enter subroutine SAVE(line 16, to keep the value of MAX biggest in the running process). Then enter recursion(line 17), and take the current point as the base point in recursion at this new level. When return from recursion, recovery R2 and R3(line 18,19) to keep the state the same as in this recursion.

Finally, with all four directions having gone through, restore the registers and quit this recursion(line 28).

```

1  RE  ; recursion
2      ...                ; save registers
3      JSR   LOADMAP
4      ADD   R1,R0,#0      ; R1 = MAP[R3][R4]
5      ;
6  UP
7      ADD   R3,R3,#0      ; R3 > 0 ?
8      BRZ   DOWN
9      ADD   R3,R3,#-1
10     JSR   LOADMAP      ; R0 = MAP'
11     NOT   R5,R0

```

```

12      ADD      R5,R5,#1      ; R5 = - MAP'
13      ADD      R5,R1,R5      ; MAP - MAP'
14      BRnz     U1
15      ADD      R2,R2,#1
16      JSR      SAVE
17      JSR      RE
18      ADD      R2,R2,#-1
19  U1  ADD      R3,R3,#1
20  DOWN
21      ...
22  LEFT
23      ...
24  RIGHT
25      ...
26  OVER ; over this recursion
27      ...                ; restore registers
28      RET

```

Q&A

I talked about the idea of writing code, and introduced the the meaning of the registers used in the program and the algorithms used in the code to TA.

In addition, the TA asked me how I could modify my program to reduce the time it takes to run it. I think it is only necessary to set aside another space as large as the array MAP. And after calculating the MAX of a point, store it in the corresponding space of that point. So in the next point which runs through this point, you can directly call the result without running again, which saves a lot time.