
Practical Malware Analysis



Ch 2: Malware Analysis in Virtual Machines

Updated 1-16-17

Dynamic Analysis

- Running malware deliberately, while monitoring the results
- Requires a safe environment
- Must prevent malware from spreading to production machines
- Real machines can be airgapped -no network connection to the Internet or to other machines

Real Machines

Disadvantages

- No Internet connection, so parts of the malware may not work
- Can be difficult to remove malware, so reimaging the machine will be necessary

Advantage

 Some malware detects virtual machines and won't run properly in one

Virtual Machines

- The most common method
- We'll do it that way
- This protects the host machine from the malware
 - Except for a few very rare cases of malware that escape the virtual machine and infect the host

VMware Player

- Free but limited
- Cannot take snapshots
- VMware Workstation or Fusion is a better choice, but they cost money
- You could also use VirtualBox, Hyper-V, Parallels, or Xen.

Windows XP

- The malware we are analyzing targets Windows XP, as most malware does
- Win XP has passed its end-of-life, so we'll use Windows Server 2008

Configuring VMware

- You can disable networking by disconnecting the virtual network adapter
- Host-only networking allows network traffic to the host but not the Internet





Figure 3-3. Host-only networking in VMware

Connecting Malware to the Internet

- NAT mode lets VMs see each other and the Internet, but puts a virtual router between the VM and the LAN
- Bridged networking connects the VM directly to the LAN
- Can allow malware to do some harm or spread - controversial
- You could send spam or participate in a DDoS attack

Snapshots



Risks of Using VMware for Malware Analysis

- Malware may detect that it is in a VM and run differently
- VMware has bugs: malware may crash or exploit it
- Malware may spread or affect the host don't use a sensitive host machine
- All the textbook samples are harmless

Practical Malware Analysis

Ch 3: Basic Dynamic Analysis

Why Perform Dynamic Analysis?

- Static analysis can reach a dead-end, due to
 - Obfuscation
 - Packing
 - Examiner has exhausted the available static analysis techniques
- Dynamic analysis is efficient and will show you exactly what the malware does

Sandboxes: The Quick-and-Dirty Approach

Sandbox

- All-in-one software for basic dynamic analysis
- Virtualized environment that simulates network services
- Examples: Norman Sandbox, GFI Sandbox, Anubis, Joe Sandbox, ThreatExpert, BitBlaze, Comodo Instant Malware Analysis
- They are expensive but easy to use
- They produce a nice PDF report of results

Running Malware

Launching DLLs

- EXE files can be run directly, but DLLs can't
- Use Rundll32.exe (included in Windows) rundll32.exe *DLLname*, *Export arguments*
- The Export value is one of the exported functions you found in Dependency Walker, PEview, or PE Explorer.

Launching DLLs

- Example
 - rip.dll has these exports: **Install** and **Uninstall** rundll32.exe rip.dll, **Install**
- Some functions use ordinal values instead of names, like
 - rundll32.exe xyzzy.dll, #5
- It's also possible to modify the PE header and convert a DLL into an EXE


Monitoring with Process Monitor

Process Monitor


- Monitors registry, file system, network, process, and thread activity
- All recorded events are kept, but you can filter the display to make it easier to find items of interest
- Don't run it too long or it will fill up all RAM and crash the machine

Launching Calc.exe

Many, many events recorded



Process Monitor Toolbar




Filtering with Exclude


- One technique: hide normal activity before launching malware
- Right-click each Process Name and click Exclude
- Doesn't seem to work well with these samples

Filtering with Include

Most useful filters: Process Name,
 Operation, and Detail




Viewing Processes with Process Explorer



Coloring


- Services are pink
- Processes are blue
- New processes are green briefly
- Terminated processes are red

DLL Mode




Properties

- Shows DEP (Data Execution Prevention) and ASLR (Address Space Layout Randomization) status
- Verify button checks the disk file's Windows signature
 - But not the RAM image, so it won't detect process replacement



Strings

 Compare Image to Memory strings, if they are very different, it can indicate process replacement




Detecting Malicious Documents

- Open the document (e.g. PDF) on a system with a vulnerable application
- Watch Process Explorer to see if it launches a process
- The Image tab of that process's Properties sheet will show where the malware is

Comparing Registry Snapshots with Regshot


Regshot

- Take 1st shot
- Run malware
- Take 2nd shot
- Compare them to see what registry keys were changed



Faking a Network

Using ApateDNS to Redirect DNS Resolutions



ApateDNS Does Not Work


- I couldn't get it to redirect any traffic in Win XP or 7
- nslookup works, but you don't see anything in a browser or with ping
- I decided to ignore it and use INetSim instead

Ncat Listener


- Using Ncat.exe, you can listen on a single TCP port in Windows
 - In Linux, use nc (netcat)
- This will allow malware to complete a TCP handshake, so you get some rudimentary information about its requests
- But it's not a real server, so it won't reply to requests after the handshake

Monitoring with Ncat (included with Nmap)

```
C:\Windows\System32\ncat -1 80
GET / HTTP/1.1
Host: 127.0.0.1
Connection: keep-alive
Accept: text/html.application/xhtml+xml.application/xml;q=0.9,*/*;q=0.8
User-Agent: Mozilla/S.0 (Windows NT 6.1) AppleWebKit/537.36 (KHTML, like Gecko) Chrone/29.0.1547.57
Safari/S37.36
Accept-Encoding: gzip,deflate,sdch
Accept-Language: en-US,en;q=0.8
```




Packet Sniffing with Wireshark




Follow TCP Stream

 Can save files from streams here too



Using INetSim


inetsim



INetSim Fools a Browser



INetSim Fools Nmap



Basic Dynamic Tools in Practice

Using the Tools

- Procmon
 - Filter on the malware executable name and clear all events just before running it
- Process Explorer
- Regshot
- Virtual Network with INetSim
- Wireshark




Figure 4-12. Example of a virtual network