

# **JZ-HDL WAVEFORM FORMAT SPECIFICATION (JZW)**

**State: Beta — Version: 0.1.8**

## Contents

|                                          |    |
|------------------------------------------|----|
| 1. OVERVIEW . . . . .                    | 3  |
| 2. FILE STRUCTURE . . . . .              | 4  |
| 2.1 File Extension . . . . .             | 4  |
| 2.2 SQLite Version . . . . .             | 4  |
| 2.3 Journal Mode . . . . .               | 4  |
| 2.4 Creation Sequence . . . . .          | 4  |
| 3. DATABASE SCHEMA . . . . .             | 5  |
| 3.1 Metadata Table . . . . .             | 5  |
| 3.2 Signals Table . . . . .              | 6  |
| 3.3 Value Changes Table . . . . .        | 6  |
| 3.4 Annotations Table . . . . .          | 7  |
| 3.5 Clocks Table . . . . .               | 8  |
| 4. VALUE ENCODING . . . . .              | 10 |
| 4.1 Single-Bit Signals . . . . .         | 10 |
| 4.2 Multi-Bit Signals . . . . .          | 10 |
| 4.3 No X Values . . . . .                | 10 |
| 5. ANNOTATION DIRECTIVES . . . . .       | 11 |
| 5.1 @alert . . . . .                     | 11 |
| 5.2 @mark . . . . .                      | 11 |
| 5.3 @select . . . . .                    | 12 |
| 5.4 Trace Annotations . . . . .          | 12 |
| 5.5 Color Names . . . . .                | 12 |
| 5.6 Annotation Placement Rules . . . . . | 13 |
| 6. WRITE PERFORMANCE . . . . .           | 14 |
| 6.1 Transaction Batching . . . . .       | 14 |
| 6.2 Prepared Statements . . . . .        | 14 |
| 6.3 Pragmas . . . . .                    | 14 |
| 7. CLI USAGE . . . . .                   | 15 |
| 7.1 Output Format Selection . . . . .    | 15 |
| 8. QUERYING EXAMPLES . . . . .           | 16 |
| 9. EXAMPLE . . . . .                     | 17 |

## 1. OVERVIEW

This specification defines the **JZW (JZ-HDL Waveform)** file format, a SQLite-based waveform storage format for JZ-HDL simulation output. JZW is the native waveform format for the JZ-HDL toolchain.

**Motivation:** Standard waveform formats (VCD, FST) store only signal value changes. They have no mechanism for timestamped annotations, colored markers, conditional alerts, or any form of simulation metadata beyond the raw signal data. JZW extends value-change storage with first-class support for annotations, enabling richer simulation analysis in JZ-HDL viewers.

### Design Principles:

- **SQLite as the container.** JZW files are standard SQLite 3 databases. Any SQLite client can open, query, and inspect them. No custom binary parser is required.
- **Change-based storage.** Only value changes are recorded. If a signal does not change at a given time, no row is written. Time 0 provides an initial value for every signal, establishing the baseline.
- **Picosecond resolution.** All time values are stored as 64-bit unsigned integers representing picoseconds, consistent with the simulation engine's internal representation (Simulation Specification Section 2.1). There is no timescale ambiguity.
- **Annotation-native.** Alerts, markers, and selection ranges are stored alongside value changes in dedicated tables, tied to the same picosecond timeline.
- **Streaming-compatible.** Using SQLite WAL (Write-Ahead Logging) mode, a viewer can read the database while the simulator is still writing to it, enabling real-time waveform display.

### Relationship to VCD and FST:

JZW does not replace VCD or FST output. The simulator supports all three formats via CLI flags (`--vcd`, `--fst`, `--jzw`). VCD and FST remain available for interoperability with third-party tools (e.g., GTKWave).

## 2. FILE STRUCTURE

### 2.1 File Extension

JZW files use the `.jzw` extension.

### 2.2 SQLite Version

JZW files must be valid SQLite 3 databases. The minimum required SQLite version is 3.8.0 (for common table expression support and WAL mode reliability). The database must use UTF-8 encoding.

### 2.3 Journal Mode

The simulator opens the database in **WAL (Write-Ahead Logging)** mode. This allows concurrent read access from a viewer process while the simulation is running. The simulator sets `PRAGMA journal_mode=WAL` immediately after creating the database.

### 2.4 Creation Sequence

When the simulator creates a JZW file:

1. Create the SQLite database file.
2. Set `PRAGMA journal_mode=WAL`.
3. Set `PRAGMA synchronous=NORMAL` (balance between durability and write performance).
4. Create all tables and indexes (Section 3).
5. Populate the meta table (Section 3.1).
6. Populate the `signals` table with all monitored signals (Section 3.2).
7. Populate the `clocks` table with clock configuration and runtime parameters (Section 3.5).
8. Begin simulation, writing value changes and annotations as the simulation progresses.
9. On simulation completion, write the `sim_end_time` metadata key and close the database.

### 3. DATABASE SCHEMA

#### 3.1 Metadata Table

```
CREATE TABLE meta (  
    key TEXT PRIMARY KEY,  
    value TEXT NOT NULL  
);
```

The meta table stores key-value pairs describing the simulation context. The following keys are defined:

| Key              | Required | Description                                                                                                                                           |
|------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| jzw_version      | Yes      | Schema version. This specification defines version 1.                                                                                                 |
| timescale        | Yes      | Always 1ps. Informational; confirms that all time values are in picoseconds.                                                                          |
| sim_start_time   | Yes      | Simulation start time in picoseconds. Always 0.                                                                                                       |
| sim_end_time     | Yes      | Simulation end time in picoseconds. Written when the simulation completes. If the simulation is still running or was aborted, this key may be absent. |
| date             | Yes      | ISO 8601 date-time when the simulation was run (e.g., 2026-03-09T14:30:00Z).                                                                          |
| source_file      | Yes      | Path to the JZ-HDL source file that was simulated.                                                                                                    |
| compiler_version | Yes      | JZ-HDL compiler version string (e.g., 0.1.0).                                                                                                         |
| seed             | Yes      | Simulation seed in hexadecimal (e.g., 0xDEADBEEF).                                                                                                    |
| tick_ps          | Yes      | Tick resolution in picoseconds (the GCD of all clock half-periods).                                                                                   |
| module_name      | Yes      | Name of the top-level module under simulation.                                                                                                        |

Implementations may add additional keys. Readers must ignore unrecognized keys.

### 3.2 Signals Table

```
CREATE TABLE signals (  
  id      INTEGER PRIMARY KEY,  
  name    TEXT      NOT NULL,  
  scope   TEXT      NOT NULL,  
  width   INTEGER NOT NULL,  
  type    TEXT      NOT NULL  
);
```

Each row defines a monitored signal. Signal IDs are assigned sequentially starting from 1.

| Column | Description                                                                                                                                                       |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| id     | Unique signal identifier. Referenced by the changes and annotations tables.                                                                                       |
| name   | Signal name without hierarchy (e.g., wr_ptr).                                                                                                                     |
| scope  | Hierarchical scope path using dot separators (e.g., clocks, wires, dut, dut.sub). Matches the VCD scope grouping defined in Simulation Specification Section 6.2. |
| width  | Bit width of the signal (e.g., 1, 8, 32).                                                                                                                         |
| type   | Signal type. One of: clock, wire, tap.                                                                                                                            |

#### Scope conventions:

- Signals from the CLOCK block have scope clocks.
- Signals from the WIRE block have scope wires.
- Signals from the TAP block use the instance hierarchy as scope (e.g., TAP { dut.wr\_ptr; } produces scope dut, name wr\_ptr).

### 3.3 Value Changes Table

```
CREATE TABLE changes (  
  time      INTEGER NOT NULL,  
  signal_id INTEGER NOT NULL,  
  value     TEXT     NOT NULL,  
  FOREIGN KEY (signal_id) REFERENCES signals(id)  
);  
  
CREATE INDEX idx_changes_time ON changes(time);  
CREATE INDEX idx_changes_signal ON changes(signal_id, time);
```

Each row records a single value change for a single signal at a specific time.

| Column | Description                                              |
|--------|----------------------------------------------------------|
| time   | Simulation time in picoseconds when the change occurred. |

| Column    | Description                                            |
|-----------|--------------------------------------------------------|
| signal_id | References signals.id.                                 |
| value     | The new signal value as a text string (see Section 4). |

#### Rules:

- **Time 0 baseline.** At time 0, exactly one row must be written for every signal in the signals table. This establishes the initial value of every signal before any clock edge fires.
- **Change-only storage.** After time 0, a row is written for a signal only when its value differs from its most recent recorded value. If a signal holds the same value across consecutive ticks, no row is written.
- **Monotonic time.** Rows are inserted in non-decreasing time order. Multiple signals may change at the same time, but a given signal may have at most one change per time value.

### 3.4 Annotations Table

```
CREATE TABLE annotations (
  id          INTEGER PRIMARY KEY,
  time        INTEGER NOT NULL,
  type        TEXT      NOT NULL,
  signal_id   INTEGER,
  message     TEXT,
  color       TEXT,
  end_time    INTEGER,
  FOREIGN KEY (signal_id) REFERENCES signals(id)
);

CREATE INDEX idx_annotations_time ON annotations(time);
```

Annotations are timestamped metadata entries associated with the simulation timeline. They are generated by annotation directives in the simulation source (Section 5).

| Column    | Description                                                                                                                                                                |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| id        | Auto-incrementing unique identifier.                                                                                                                                       |
| time      | Simulation time in picoseconds when the annotation was created.                                                                                                            |
| type      | Annotation type string. One of: alert, mark, select, trace.                                                                                                                |
| signal_id | Optional. References signals.id. If non-NULL, the annotation is associated with a specific signal. If NULL, it is a global annotation (applies to the entire time column). |
| message   | Optional. Human-readable text describing the annotation.                                                                                                                   |
| color     | Optional. Display color hint. One of the predefined color names (Section 5.4).                                                                                             |

| Column   | Description                                                                                                      |
|----------|------------------------------------------------------------------------------------------------------------------|
| end_time | Optional. For range annotations (e.g., select), the end time in picoseconds. NULL for point-in-time annotations. |

### 3.5 Clocks Table

```
CREATE TABLE clocks (
  id          INTEGER PRIMARY KEY,
  name        TEXT      NOT NULL,
  period_ps   INTEGER NOT NULL,
  phase_ps    INTEGER NOT NULL DEFAULT 0,
  jitter_pp_ps INTEGER NOT NULL DEFAULT 0,
  jitter_sigma_ps REAL   NOT NULL DEFAULT 0.0,
  drift_max_ppm REAL   NOT NULL DEFAULT 0.0,
  drift_actual_ppm REAL  NOT NULL DEFAULT 0.0,
  drifted_period_ps REAL NOT NULL DEFAULT 0.0
);
```

The clocks table stores the configuration and runtime parameters of each clock in the simulation. One row is written per clock at simulation initialization, before any value changes are recorded.

| Column           | Description                                                                                                                                                                                           |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| id               | Auto-incrementing unique identifier.                                                                                                                                                                  |
| name             | Clock name as declared in the CLOCK block (e.g., clk_wr).                                                                                                                                             |
| period_ps        | Nominal full period in picoseconds (twice the half-period / toggle interval).                                                                                                                         |
| phase_ps         | Phase offset in picoseconds. 0 if no phase offset is specified.                                                                                                                                       |
| jitter_pp_ps     | Peak-to-peak jitter in picoseconds. 0 if jitter is not enabled for this clock. See Simulation Specification Section 2.2.1.                                                                            |
| jitter_sigma_ps  | Jitter standard deviation in picoseconds (jitter_pp_ps / 6). 0.0 if jitter is disabled.                                                                                                               |
| drift_max_ppm    | Maximum drift in parts per million as configured via --drift. 0.0 if drift is not enabled. See Simulation Specification Section 2.2.2.                                                                |
| drift_actual_ppm | Actual drift value selected at simulation start from a Gaussian distribution clamped to $\pm$ drift_max_ppm. Positive values mean the clock runs fast; negative means slow. 0.0 if drift is disabled. |



| Column            | Description                                                                                                                                                                                                                                           |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| drifted_period_ps | Drift-adjusted full period in picoseconds as a floating-point value ( $\text{period\_ps} \times (1 + \text{drift\_actual\_ppm} / 1,000,000)$ ). Stored as REAL to preserve sub-picosecond precision from accumulated drift. 0.0 if drift is disabled. |

**Notes:**

- The `clocks` table is written once at simulation start and is not updated during simulation.
- Clock names in this table correspond to signal names in the `signals` table where `type = 'clock'` and `scope = 'clocks'`.
- Viewers can use this table to display clock properties (frequency, jitter bounds, drift) without parsing metadata keys or computing values from signal transitions.
- For backward compatibility, readers should tolerate the absence of this table in older JZW files.

## 4. VALUE ENCODING

Signal values are stored as text strings in the value column of the changes table. The encoding depends on the signal width:

### 4.1 Single-Bit Signals

Single-bit signals (width 1) are stored as a single character:

| Value | Meaning                         |
|-------|---------------------------------|
| 0     | Logic low                       |
| 1     | Logic high                      |
| z     | High impedance (tri-state only) |

### 4.2 Multi-Bit Signals

Multi-bit signals (width > 1) are stored as binary strings of 0, 1, and z characters, MSB first. The string length equals the signal width.

**Examples:**

| Width | Value    | Meaning                                       |
|-------|----------|-----------------------------------------------|
| 8     | 10101010 | 8'hAA                                         |
| 4     | 0000     | 4'h0                                          |
| 3     | 1zz      | 3 bits: MSB is 1, two LSBs are high-impedance |

### 4.3 No X Values

Consistent with JZ-HDL semantics (Simulation Specification Section 2.5), x never appears as a runtime value. All storage is initialized to concrete 0/1 bits via seed-based randomization. The x character is not a valid value encoding in JZW files.

## 5. ANNOTATION DIRECTIVES

Annotation directives are source-level constructs that generate entries in the JZW annotations table during simulation. They have no effect on VCD or FST output.

### 5.1 @alert

#### Syntax:

```
@alert(<condition>, <color>)  
@alert(<condition>, <color>, "<message>")
```

Creates an annotation of type alert when <condition> evaluates to true (non-zero) at the current simulation time.

- <condition> is a testbench WIRE identifier or hierarchical signal reference.
- <color> is a color name (Section 5.4).
- <message> is an optional string literal describing the alert.
- If <condition> is a multi-bit signal, it is truthy if any bit is 1.
- The alert fires after combinational settling, at the same evaluation point as @print\_if.
- If the condition is true on consecutive ticks, an annotation is created for each tick where the condition holds.

#### Example:

```
@alert(full, RED, "FIFO full")  
@alert(overflow, RED)
```

**Behavior during @run:** When an @alert directive is in scope, the simulator evaluates its condition at every tick during @run, @run\_until, and @run\_while execution. This is distinct from @print, which executes only at the point it appears in the simulation sequence.

### 5.2 @mark

#### Syntax:

```
@mark(<color>)  
@mark(<color>, "<message>")
```

Creates a global annotation of type mark at the current simulation time. Marks are unconditional — they fire exactly once at the simulation time where they appear in the source.

- <color> is a color name (Section 5.4).
- <message> is an optional string literal.
- The signal\_id in the annotations table is NULL (marks are global, not signal-specific).

#### Example:

```
@update {  
    rst_n <= 1'b1;  
}  
@mark(GREEN, "Reset released")
```

### 5.3 @select

#### Syntax:

```
@select(<signal>, <color>)
```

Creates a range annotation of type `select` that highlights a signal for the duration of the next `@run` directive. The annotation's time is the current simulation time, and `end_time` is the simulation time after the following `@run` completes.

- `<signal>` is a testbench WIRE identifier or hierarchical signal reference.
- `<color>` is a color name (Section 5.4).
- The `signal_id` is set to the referenced signal's ID.
- `@select` must be immediately followed by a `@run`, `@run_until`, or `@run_while` directive. A compile error is reported if `@select` is followed by any other directive.

#### Example:

```
@select(data_out, YELLOW)
@run(ns=100)
// Highlights data_out for the 100ns window
```

### 5.4 Trace Annotations

The `@trace` directive (Simulation Specification Section 4.9) generates annotations of type `trace` in the JZW database. These are automatically created by the simulator when `@trace(state=on)` or `@trace(state=off)` is encountered.

| Column    | Value                                                   |
|-----------|---------------------------------------------------------|
| type      | "trace"                                                 |
| time      | Simulation time when trace state changed (picoseconds). |
| signal_id | NULL (trace is global, not signal-specific).            |
| message   | "on" or "off".                                          |
| color     | NULL.                                                   |
| end_time  | NULL.                                                   |

Viewers should use trace annotations to visually indicate periods where waveform recording was disabled (e.g., grayed-out regions, gap markers, or collapsed time ranges).

### 5.5 Color Names

The following color names are valid for annotation directives:

| Name   | Intended Use                        |
|--------|-------------------------------------|
| RED    | Errors, violations, critical alerts |
| ORANGE | Warnings, caution                   |
| YELLOW | Highlights, attention               |
| GREEN  | Success, milestones                 |

| Name   | Intended Use           |
|--------|------------------------|
| BLUE   | Informational markers  |
| PURPLE | Debug, custom grouping |
| CYAN   | Timing, clock-related  |
| WHITE  | Neutral                |

Color names are case-insensitive in source but stored as uppercase in the database. Viewers map these names to specific RGB values at their discretion.

## 5.6 Annotation Placement Rules

| Rule    | Description                                                                                       |
|---------|---------------------------------------------------------------------------------------------------|
| ANN-001 | @alert must appear at the top level of a @simulation block (not inside @setup, @update, or @new). |
| ANN-002 | @mark must appear at the top level of a @simulation block (not inside @setup, @update, or @new).  |
| ANN-003 | @select must be immediately followed by @run, @run_until, or @run_while.                          |
| ANN-004 | @alert condition must reference a signal in scope (declared in WIRE, CLOCK, or TAP).              |
| ANN-005 | @select signal must reference a signal in scope (declared in WIRE, CLOCK, or TAP).                |
| ANN-006 | Color name must be one of the predefined names (Section 5.4).                                     |

## 6. WRITE PERFORMANCE

### 6.1 Transaction Batching

The simulator must batch value-change and annotation inserts within transactions to achieve acceptable write performance. The recommended strategy is to wrap each tick's inserts (all value changes and annotations at a single time point) in one transaction. Alternatively, the simulator may batch across multiple ticks (e.g., every 1000 ticks) for higher throughput, at the cost of increased latency for real-time viewers.

### 6.2 Prepared Statements

The simulator should use prepared statements for the `INSERT INTO` changes and `INSERT INTO` annotations operations, as these are executed millions of times during a typical simulation.

### 6.3 Pragmas

The following pragmas are recommended for write performance:

```
PRAGMA journal_mode = WAL;  
PRAGMA synchronous = NORMAL;  
PRAGMA cache_size = -8000;      -- 8MB cache  
PRAGMA temp_store = MEMORY;
```

## 7. CLI USAGE

### 7.1 Output Format Selection

```
jz-hdl --simulate sim_file.jz --jzw           # produces sim_file.jzw  
jz-hdl --simulate sim_file.jz --jzw -o output.jzw # explicit output path
```

The `--jzw` flag may be combined with `--vcd` or `--fst` to produce multiple output formats simultaneously:

```
jz-hdl --simulate sim_file.jz --vcd --jzw      # produces both .vcd and .jzw
```

If no format flag is specified, the default output format is VCD (unchanged from the Simulation Specification).

## 8. QUERYING EXAMPLES

Because JZW files are standard SQLite databases, they can be queried directly from the command line or any SQLite client.

### List all signals:

```
sqlite3 output.jzw "SELECT id, scope, name, width, type FROM signals;"
```

### Get all value changes for a signal in a time range:

```
sqlite3 output.jzw "  
  SELECT time, value FROM changes  
  WHERE signal_id = 3 AND time BETWEEN 50000 AND 100000  
  ORDER BY time;  
"
```

### Get all alerts:

```
sqlite3 output.jzw "  
  SELECT a.time, s.name, a.message, a.color  
  FROM annotations a  
  LEFT JOIN signals s ON a.signal_id = s.id  
  WHERE a.type = 'alert'  
  ORDER BY a.time;  
"
```

### List all clocks with their properties:

```
sqlite3 output.jzw "  
  SELECT name, period_ps, phase_ps, jitter_pp_ps, drift_actual_ppm  
  FROM clocks;  
"
```

### Get the value of all signals at a specific time (most recent change at or before T=50000ps):

```
sqlite3 output.jzw "  
  SELECT s.scope, s.name, c.value  
  FROM signals s  
  JOIN changes c ON c.signal_id = s.id  
  WHERE c.time = (  
    SELECT MAX(c2.time) FROM changes c2  
    WHERE c2.signal_id = s.id AND c2.time <= 50000  
  );  
"
```



## 9. EXAMPLE

Given the simulation from Simulation Specification Section 7, using annotation directives:

```
@simulation fifo_ctrl
    @import "fifo.jz";

    CLOCK {
        clk_wr = { period=10.0 };
        clk_rd = { period=25.0 };
    }

    WIRE {
        rst_n [1];
        wr_en [1];
        rd_en [1];
        data_in [8];
        data_out [8];
        full [1];
        empty [1];
    }

    TAP {
        dut.wr_ptr;
        dut.rd_ptr;
    }

    @new dut async_fifo {
        clk_wr [1] = clk_wr;
        clk_rd [1] = clk_rd;
        rst_n [1] = rst_n;
        wr_en [1] = wr_en;
        rd_en [1] = rd_en;
        din [8] = data_in;
        dout [8] = data_out;
        full [1] = full;
        empty [1] = empty;
    }

    // Alert whenever FIFO is full
    @alert(full, RED, "FIFO full")

    @setup {
        rst_n    <= 1'b0;
        wr_en    <= 1'b0;
        rd_en    <= 1'b0;
        data_in  <= 8'h00;
    }
```

```

@run(ns=50)

@update {
    rst_n <= 1'b1;
}
@mark(GREEN, "Reset released")

@run(ns=50)

@update {
    wr_en    <= 1'b1;
    data_in <= 8'hAA;
}
@mark(BLUE, "Write burst start")

@select(data_out, YELLOW)
@run(ns=10)

@update {
    data_in <= 8'hBB;
}
@run(ns=10)

@update {
    wr_en <= 1'b0;
    rd_en <= 1'b1;
}

@run(ns=100)
@endsim

```

This simulation produces a .jzw file containing:

- **meta table:** 10 rows with simulation context (version, seed, tick resolution, etc.).
- **signals table:** 9 rows (2 clocks, 5 wires, 2 taps).
- **clocks table:** 2 rows (one per clock: `clk_wr` with period 10000 ps, `clk_rd` with period 25000 ps), plus jitter/drift columns if `--jitter` or `--drift` flags were used.
- **changes table:** 9 rows at time 0 (one per signal), plus one row for each subsequent value change.
- **annotations table:** Entries for the `@mark` directives at reset release and write burst start, the `@select` on `data_out`, and any ticks where the `@alert` condition on `full` was true.