node_modules	2023/5/27 15:18	文件夹		
public	2023/5/27 15:17	文件夹		
src	2023/5/27 15:17	文件夹		
.gitignore	2023/5/27 15:16	文本文档	1 KB	
package.json	2023/5/27 15:17	JSON 文件	1 KB	
package-lock.json	2023/5/27 15:17	JSON 文件	667 KB	
README.md	2023/5/27 15:16	MD 文件	4 KB	
App.css	2023/5/27 15:16	层叠样式表文档	1 KB	
App.js	2023/5/27 15:16	JavaScript 文件	1 KB	
App.test.js	2023/5/27 15:16	JavaScript 文件	1 KB	
index.css	2023/5/27 15:16	层叠样式表文档	1 KB	
index.js	2023/5/27 15:16	JavaScript 文件	1 KB	
logo.svg	2023/5/27 15:16	Microsoft Edge ...	3 KB	
reportWebVitals.js	2023/5/27 15:16	JavaScript 文件	1 KB	
setupTests.js	2023/5/27 15:16	JavaScript 文件	1 KB	

MINGW64:/c/Users/76553/git/csci3130/GroupProject/group17/React... — ☐ ✕

```
> trello-frontend@0.1.0 start
> react-scripts start

(node:10496) [DEP_WEBPACK_DEV_SERVER_ON_AFTER_SETUP_MIDDLEWARE] DeprecationWarni
ng: 'onAfterSetupMiddleware' option is deprecated. Please use the 'setupMiddlewa
res' option.
(Use `node --trace-deprecation ...` to show where the warning was created)
(node:10496) [DEP_WEBPACK_DEV_SERVER_ON_BEFORE_SETUP_MIDDLEWARE] DeprecationWarn
ing: 'onBeforeSetupMiddleware' option is deprecated. Please use the 'setupMiddle
wares' option.
Starting the development server...

Compiled successfully!

You can now view trello-frontend in the browser.

  Local:            http://localhost:3000
  On Your Network:  http://192.168.56.1:3000

Note that the development build is not optimized.
To create a production build, use npm run build.

webpack compiled successfully
```

Top screenshot

React App

localhost:3000

最终幻想XIV中文维... · FFXIVHunt.com · Fate/GO 卡西敦王... · FFXIV ARMOURY... · 奴隷との生活 -Tea... · FF14俺tools: 装備... · Hero Damage · xivanalysis · 优雷卡天气预报 · Monster Hunter... · メインページ - 同... · Steam 社区 :: 指南... · TheDuchy – Rope...

DevTools is now available in Chinese! Always match Chrome's language | Switch DevTools to Chinese | Don't show again

Elements   Console   Sources   Network   Performance   Memory   Application   Security

```
<!DOCTYPE html>
<html lang="en">
▶ <head> ⋯ </head>
▼ <body> == $0
    <noscript>You need to enable JavaScript to run this app.</noscript>
  ▶ <div id="root"> ⋯ </div>
    <!--
        This HTML file is a template.
        If you open it directly in the browser, you will see an empty page.

        You can add webfonts, meta tags, or analytics to this file.
        The build step will place the bundled scripts into the <body> tag.

        To begin the development, run `npm start` or `yarn start`.
        To create a production bundle, use `npm run build` or `yarn build`.
    -->
  </body>
</html>
```

html   body

Styles   Computed   Layout   Event Listeners

Filter   :hov .cls

```
element.style {
}
body {                              index.css:1
    margin: ▶ 0;
    font-family: -apple-system,
        BlinkMacSystemFont, 'Segoe UI',
        'Roboto', 'Oxygen', 'Ubuntu',
        'Cantarell', 'Fira Sans', 'Droid Sans',
        'Helvetica Neue', sans-serif;
    -webkit-font-smoothing: antialiased;
    -moz-osx-font-smoothing: grayscale;
}
body {                     user agent stylesheet
    display: block;
    margin: ▶ 8px;
}
```

Edit src/App.js and save to reload.

Learn React

Console   What's New ✕

Highlights from the Chrome 113 update

Override HTTP response headers in the Network panel

Specify HTTP response headers locally to experiment with different values.

Better debugging in Nuxt and Vite

new

Bottom screenshot

React App

localhost:3000

最终幻想XIV中文维... · FFXIVHunt.com · Fate/GO 卡西敦王... · FFXIV ARMOURY... · 奴隷との生活 -Tea... · FF14俺tools: 装備... · Hero Damage · xivanalysis · 优雷卡天气预报 · Monster Hunter... · メインページ - 同... · Steam 社区 :: 指南... · TheDuchy – Rope...

DevTools is now available in Chinese! Always match Chrome's language | Switch DevTools to Chinese | Don't show again

Elements   Console   Sources   Network   Performance   Memory   Application   Security

Page   Filesystem   App.css   index.css

```
▼ □ top
  ▼ ○ localhost:3000
    ▼ □ static
      ▼ □ js
        ▼ ● C:/Users/76553/git/csci3730/
          ▶ □ node_modules
          ▼ □ src
              ● App.css
              ● App.js
              ● index.css
              ● index.js
              ● logo.svg
              ● reportWebVitals.js
          ▼ □ webpack
            ▼ □ runtime
              □ after-startup
              □ before-startup
              □ bootstrap
              □ startup
            □ bundle.js
        ▼ □ media
            □ logo.6ce24c58023cc2f8fd88f4e
      □ (index)
  ▼ ○ .
    ▼ □ src
        ● App.css
        ● index.css
  ▼ □ trello-frontend
    ▼ □ src
        ● App.css
        ● index.css
```

```
1  body {
2    margin: 0;
3    font-family: -apple-system, BlinkMacSystemFont, 'Se
4      'Ubuntu', 'Cantarell', 'Fira Sans', 'Droid Sans',
5      sans-serif;
6    -webkit-font-smoothing: antialiased;
7    -moz-osx-font-smoothing: grayscale;
8  }
9
10 code {
11   font-family: source-code-pro, Menlo, Monaco, Consol
12     monospace;
13 }
14
```

▶ Watch
▼ Breakpoints
  □ Pause on uncaught exceptions
  □ Pause on caught exceptions
▼ Scope
           Not paused
▼ Call Stack
           Not paused
▶ XHR/fetch Breakpoints
▶ DOM Breakpoints
▶ Global Listeners
▶ Event Listener Breakpoints
▶ CSP Violation Breakpoints

{} (From localhost/) Coverage: n/a

Edit src/App.js and save to reload.

Learn React

Console   What's New ✕

Highlights from the Chrome 113 update

Override HTTP response headers in the Network panel

Specify HTTP response headers locally to experiment with different values.

Better debugging in Nuxt and Vite

new