

Permutation importance

Sijin Zhang

Dark Blue	Dark Blue	Dark Blue	Yellow
Light Blue	Light Blue	Light Blue	Yellow
White	White	White	Yellow
Light Blue	Light Blue	Light Blue	Yellow
White	White	White	Yellow
Light Blue	Light Blue	Light Blue	Yellow
White	White	White	Yellow

Assuming that we have the
above dataset, with 3 features
and 1 target

Step 1: use the **training dataset** to fit a model

Assuming that we have the
above dataset, with 3 features
and 1 target

Assuming that we have the above dataset, with 3 features and 1 target

Step 1: use the **training dataset** to fit a model

Step 2: use **test data** to evaluate the trained model's performance (e.g., we can use ACC or something else)

0.9

accuracy = 0.9

Step 1: use the **training dataset** to fit a model

Step 2: use **test data** to evaluate the trained model's performance (e.g., we can use ACC or something else)

0.9

This is used as the
baseline performance

Assuming that we have the
above dataset, with 3 features
and 1 target

Assuming that we have the
above dataset, with 3 features
and 1 target

Step 1: use the **training dataset** to fit a model

Step 2: use **test data** to evaluate the trained model's performance (e.g., we
can use ACC or something else)

0.9

Step 3: data permutation

Step 1: use the **training dataset** to fit a model

Step 2: use **test data** to evaluate the trained model's performance (e.g., we can use ACC or something else) **0.9**

Step 3: test data permutation

For 1st feature, we randomly permute the column


Assuming that we have the
above dataset, with 3 features
and 1 target

Step 1: use the **training dataset** to fit a model


Step 2: use **test data** to evaluate the trained model's performance (e.g., we can use ACC or something else) **0.9**

Step 3: test data permutation

For 1st feature, we randomly permute the column



Assuming that we have the above dataset, with 3 features and 1 target




Step 1: use the **training dataset** to fit a model


Step 2: use **test data** to evaluate the trained model's performance (e.g., we can use ACC or something else) **0.9**

Step 3: test data permutation

For 1st feature, we randomly permute the column



Assuming that we have the above dataset, with 3 features and 1 target



1.4			
1.1			
-0.1			
2.2			

For example, we randomly "shuffle" the 1st feature (the order for sample is changed)

1.1			
-0.1			
2.2			
1.4			

Note that we are not touching any other features and the target


Assuming that we have the above dataset, with 3 features and 1 target

Step 1: use the **training dataset** to fit a **model**

Step 2: use **test data** to evaluate the **trained model's** performance (e.g., we can use ACC or something else) **0.9**

Step 3: test data permutation

For 1st feature, we randomly permute the column



Note that we are not touching any other features and the target

Then we use the permuted data to evaluate the **trained model's** performance

Step 1: use the **training dataset** to fit a **model**

Step 2: use **test data** to evaluate the **trained model's** performance (e.g., we can use ACC or something else) **0.9**

Step 3: test data permutation

For 1st feature, we randomly permute the column

Assuming that we have the above dataset, with 3 features and 1 target

1.4			
1.1			
-0.1			
2.2			

For example, we randomly "shuffle" the 1st feature (the order for sample is changed)

1.1			
-0.1			
2.2			
1.4			

Note that we are not touching any other features and the target

accuracy = 0.7


Then we use the permuted data to evaluate the **trained model's** performance **0.7**

Step 1: use the **training dataset** to fit a **model**


Step 2: use **test data** to evaluate the **trained model's** performance (e.g., we can use ACC or something else) **0.9**

Step 3: test data permutation

For 1st feature, we randomly permute the column



Assuming that we have the above dataset, with 3 features and 1 target



1.4			
1.1			
-0.1			
2.2			

For example, we randomly "shuffle" the 1st feature (the order for sample is changed)

1.1			
-0.1			
2.2			
1.4			

Note that we are not touching any other features and the target

accuracy = 0.7

Then we use the permuted data to evaluate the **trained model's** performance **0.7**
(usually we shuffle the dataset many times and get the average performance ...)


Step 1: use the **training dataset** to fit a **model**

Step 2: use **test data** to evaluate the **trained model's** performance (e.g., we can use ACC or something else) **0.9**

Step 3: test data permutation

For 1st feature, we randomly permute the column

Assuming that we have the above dataset, with 3 features and 1 target



Note that we are not touching any other features and the target

accuracy = 0.7

Then we use the permuted data to evaluate the **trained model's** performance **0.7**
(usually we shuffle the dataset many times and get the average performance ...)

We would repeat the above process for all the features (in this case there are three features)

Assuming that we have the above dataset, with 3 features and 1 target

Step 1: use the **training dataset** to fit a **model**

Step 2: use **test data** to evaluate the **trained model's** performance (e.g., we can use ACC or something else) **0.9**

Step 3: test data permutation

For 1st feature

0.7

0.2

e.g., $0.9 - 0.7 = 0.2$

For 2nd feature

0.4

0.5

For 3rd feature

0.6

0.3

Difference between the base model performance (0.9) and the one with permuted dataset

Assuming that we have the above dataset, with 3 features and 1 target

Step 1: use the **training dataset** to fit a **model**

Step 2: use **test data** to evaluate the **trained model's** performance (e.g., we can use ACC or something else) **0.9**

Step 3: test data permutation

For 1st feature

0.7

0.2

For 2nd feature

0.4

0.5

For 3rd feature

0.6

0.3

Difference between the base model performance (0.9) and the one with permuted dataset

We can think about the value as how much the model relies on this feature

Assuming that we have the above dataset, with 3 features and 1 target

Step 1: use the **training dataset** to fit a **model**

Step 2: use **test data** to evaluate the **trained model's** performance (e.g., we can use ACC or something else) **0.9**

Step 3: test data permutation

For 1st feature

0.7

0.2

For 2nd feature

0.4

0.5

For 3rd feature

0.6

0.3

Difference between the base model performance (0.9) and the one with permuted dataset

We can think about the value as how much the model relies on this feature

The larger the skill drops, the more the model relies on that particular feature

Assuming that we have the above dataset, with 3 features and 1 target

Step 1: use the **training dataset** to fit a **model**

Step 2: use **test data** to evaluate the **trained model's** performance (e.g., we can use ACC or something else) **0.9**

Step 3: test data permutation

For 1st feature

0.7

0.2

For 2nd feature

0.4

0.5

For 3rd feature

0.6

0.3

Difference between the base model performance (0.9) and the one with permuted dataset

We can think about the value as how much the model relies on this feature

The larger the skill drops, the more the model relies on that particular feature

Therefore, in this example, **feature2** is the most important feature, and **feature 1** is the least important feature

Step 1: use the **training dataset** to fit a **model**

Step 2: use **test data** to evaluate the **trained model's** performance (e.g., we can use ACC or something else) **0.9**

Step 3: test data permutation

For 1st feature

0.7

0.2

For 2nd feature

0.4

0.5

For 3rd feature

0.6

0.3

Difference between the
base model
performance (0.9) and
the one with permuted
dataset

We can think about the
value as how much the
model relies on this
feature

The larger the skill
drops, the more the
model relies on that
particular feature

Therefore, in this
example, **feature2** is the
most important feature,
and feature 1 is the least
important feature

Note that there is a similar method called “column-drop” method

The difference is that:

- Instead of shuffle the feature, we remove the entire feature, and “refit” a model
- We compare the base model performance (the one with entire dataset) and the “refitted” model performance (the one with one less feature)
- The feature corresponds to the most dropped skill is usually considered the most important feature

Step 1: use the **training dataset** to fit a **model**

Step 2: use **test data** to evaluate the **trained model's** performance (e.g., we can use ACC or something else) **0.9**

Step 3: test data permutation

For 1st feature

0.7

0.2

For 2nd feature

0.4

0.5

For 3rd feature

0.6

0.3

Difference between the
base model
performance (0.9) and
the one with permuted
dataset

We can think about the
value as how much the
model relies on this
feature

The larger the skill
drops, the more the
model relies on that
particular feature

Therefore, in this
example, **feature2** is the
most important feature,
and feature 1 is the least
important feature

Note that there is a similar method called “column-drop” method

The difference is that:

- Instead of shuffle the feature, we remove the entire feature, and “refit” a model
- We compare the base model performance (the one with entire dataset) and the “refitted” model performance (the one with one less feature)
- The feature corresponds to the most dropped skill is usually considered the most important feature

Compared to the permutation method, “column-drop” method is usually more accurate, but more expensive (we need to refit the model)