

RNN: simple RNN

Why RNN

Why RNN ?

There are two radar points obtained at (t-1) and (t), we want to predict the radar point at (t+1)

Training


$x(t-1)$			
	$x(t)$		
		y	

- $x(t-1)$: the radar point obtained at (t-1)
- $x(t)$: the radar point obtained at (t)
- y : the truth in the training data at (t+1)

Why RNN ?


There are two radar points obtained at (t-1) and (t), we want to predict the radar point at (t+1)

Training




- $x(t-1)$: the radar point obtained at (t-1)
- $x(t)$: the radar point obtained at (t)
- y : the truth in the training data at (t+1)

Wrong prediction



For a **DNN**, $x(t-1)$ and $x(t)$ are treated independently, just like x_1 and x_2 ~ and we are trying to predict y



Does not matter where $x(t-1)$ and $x(t)$ sits (e.g., which node is $x(t-1)/x(t)$)

Expected prediction

If we use a neural network such as Densely connected NN, we are not able to tell the sequential information for "x", therefore, the prediction might end up the wrong direction

How RNN works: concept

How RNN works?


In order to make such a prediction right, we need a sequential of training dataset and model, e.g.,

Training

$x(t-1)$			
	$x(t)$		
		y	


How RNN works?

In order to make such a prediction right, we need a sequential of training dataset and model, e.g.,




How RNN works?

In order to make such a prediction right, we need a sequential of training dataset and model, e.g.,




How RNN works?

In order to make such a prediction right, we need a sequential of training dataset and model, e.g.,



How RNN works?


In order to make such a prediction right, we need a sequential of training dataset and model, e.g.,



How RNN works?

Compared to an ANN model, RNN requires more parameters to be trained. To make it simpler, let's we only have 1 neuron here:

$x(t-1)$			
	$x(t)$		
		y	



If it is an ANN model, we will have to train 3 parameters ($w1$, $w2$, and $w3$)


If it is a RNN model, in addition to the 3 parameters ($w1$, $w2$, and $w3$), there is an additional parameter to be trained (w_n) to represent the information passing from $(t-1)$ to (t)

How RNN works: a simple example

How RNN works?


Let's look at a real example, to make it simple, let's say we only have one neuron

Step 1



Step 2

Since it's an RNN, the neuron is split into a 2 steps process for $(t-1)$ and (t)




How RNN works?

Let's look at a real example, to make it simple, let's say we only have one neuron


Step 2

Since it's an RNN, the neuron is split into a 2 steps process for $(t-1)$ and (t)



Step 3

The neuron output for $(t-1)$ is $f(2w1)$, where f is the activation function




How RNN works?

Let's look at a real example, to make it simple, let's say we only have one neuron


Step 3

The neuron output for $(t-1)$ is $f(2w1)$, where f is the activation function



Step 4

The intermediate neuron output (*without activation function and the information from $(t-1)$*) for (t) is




How RNN works?

Let's look at a real example, to make it simple, let's say we only have one neuron


Step 3

The neuron output for $(t-1)$ is $f(2w1)$, where f is the activation function



Step 4

The intermediate neuron output (*without activation function and the information from $(t-1)$*) for (t) is




How RNN works?

Let's look at a real example, to make it simple, let's say we only have one neuron


Step 3

The neuron output for $(t-1)$ is $f(2w1)$, where f is the activation function



Step 4

The intermediate neuron output (*without activation function and the information from $(t-1)$*) for (t) is




How RNN works?

Let's look at a real example, to make it simple, let's say we only have one neuron


Step 4

The intermediate neuron output (*without activation function and the information from (t-1)*) for (t) is



Step 5

The neuron output there can be represented as




How RNN works?

Let's look at a real example, to make it simple, let's say we only have one neuron

Step 5

The neuron output there can be represented as



Step 6

So the final output can be calculated as: $w3 * f(4w2 + wn * f(2w1))$


Note: All the weights, $w1$, $w2$, $w3$ and wn are to be trained by the model



Issues in RNN


The RNN issues

In the above example, we have two inputs (t-1) and (t)




The RNN issues

In the above example, we have two inputs ($t-1$) and (t)




but if we have a very long input lists, e.g., ($t-50$) to (t), even we still just have one neuro, we will have:




The RNN issues

In the above example, we have two inputs ($t-1$) and (t)




but if we have a very long input lists, e.g., ($t-50$) to (t), even we still just have one neuro, we will have:

Let's assume the activation function does not do anything, e.g., $f(x)=x$, the output of a time step dependant neuron can be written as **below**:




The RNN issues

In the above example, we have two inputs (t-1) and (t)




but if we have a very long input lists, e.g., (t-50) to (t), even we still just have one neuro, we will have:

Let's assume the activation function does not do anything, e.g., $f(x)=x$, the output of a time step dependant neuron can be written as **below**:




The RNN issues

In the above example, we have two inputs (t-1) and (t)




but if we have a very long input lists, e.g., (t-50) to (t), even we still just have one neuro, we will have:

Let's assume the activation function does not do anything, e.g., $f(x)=x$, the output of a time step dependant neuron can be written as **below**:




The RNN issues

In the above example, we have two inputs (t-1) and (t)



but if we have a very long input lists, e.g., (t-50) to (t), even we still just have one neuro, we will have:


Let's assume the activation function does not do anything, e.g., $f(x)=x$, the output of a time step dependant neuron can be written as below:



The RNN issues

but if we have a very long input lists, e.g., $(t-50)$ to (t) , even we still just have one neuro, we will have:

Let's assume the activation function does not do anything, e.g., $f(x)=x$, the output of a time step dependant neuron can be written as **below**:




When the weight w_n is less than one, the older inputs, e.g., $x(t-50)$ and $x(t-49)$, will become extremely small, and therefore their impacts on the backpropagation cost function minimization will be negligible, we call this “**Vanishing gradient**”

The RNN issues

but if we have a very long input lists, e.g., $(t-50)$ to (t) , even we still just have one neuro, we will have:

Let's assume the activation function does not do anything, e.g., $f(x)=x$, the output of a time step dependant neuron can be written as **below**:




When the weight w_n is less than one, the older inputs, e.g., $x(t-50)$ and $x(t-49)$, will become extremely small, and therefore their impacts on the backpropagation cost function minimization will be negligible, we call this “**Vanishing gradient**”

So RNN tends to forget any older inputs and will only remember the recent inputs

The RNN issues

but if we have a very long input lists, e.g., $(t-50)$ to (t) , even we still just have one neuro, we will have:

Let's assume the activation function does not do anything, e.g., $f(x)=x$, the output of a time step dependant neuron can be written as **below**:



When the weight w_n is less than one, the older inputs, e.g., $x(t-50)$ and $x(t-49)$, will become extremely small, and therefore their impacts on the backpropagation cost function minimization will be negligible, we call this “**Vanishing gradient**”


When the weight w_n is bigger than one, the older inputs, e.g., $x(t-50)$ and $x(t-49)$, will become extremely big, and therefore their impacts on the backpropagation cost function minimization will dominate, we call this “**Exploding gradient**”

So RNN tends to forget any older inputs and will only remember the recent inputs

The RNN issues

but if we have a very long input lists, e.g., $(t-50)$ to (t) , even we still just have one neuro, we will have:

Let's assume the activation function does not do anything, e.g., $f(x)=x$, the output of a time step dependant neuron can be written as **below**:



When the weight w_n is less than one, the older inputs, e.g., $x(t-50)$ and $x(t-49)$, will become extremely small, and therefore their impacts on the backpropagation cost function minimization will be negligible, we call this “**Vanishing gradient**”

So RNN tends to forget any older inputs and will only remember the recent inputs

When the weight w_n is bigger than one, the older inputs, e.g., $x(t-50)$ and $x(t-49)$, will become extremely big, and therefore their impacts on the backpropagation cost function minimization will dominate, we call this “**Exploding gradient**”

So RNN tends to forget recent inputs and will only remember the old stuff