

Bagging

Bagging

Low pressure	High Temperature	High humidity	Wind Speed	Rain
No	No	No	10.0	No
Yes	Yes	Yes	30.0	Yes
Yes	Yes	No	20.0	No
Yes	No	Yes	50.0	No
No	No	Yes	70.0	Yes

Assuming that we have the above data

Bagging

Low pressure	High Temperature	High humidity	Wind Speed	Rain
No	No	No	10.0	No
Yes	Yes	Yes	30.0	Yes
Yes	Yes	No	20.0	No
Yes	No	Yes	50.0	No
No	No	Yes	70.0	Yes

Not selected

Not selected

Low pressure	High Temperature	High humidity	Wind Speed	Rain
Yes	Yes	Yes	30.0	Yes
Yes	No	Yes	50.0	No
No	No	No	10.0	No
No	No	No	10.0	No

Assuming that we have the above data

To create a bootstrap dataset with the same predictors as the original dataset, we just randomly select samples here

For example in this case, the first row gets selected twice, while the 3rd and last row are not selected at all

Bagging

Low pressure	High Temperature	High humidity	Wind Speed	Rain
No	No	No	10.0	No
Yes	Yes	Yes	30.0	Yes
Yes	Yes	No	20.0	No
Yes	No	Yes	50.0	No
No	No	Yes	70.0	Yes

Not selected

Not selected

Low pressure	High Temperature	High humidity	Wind Speed	Rain
Yes	Yes	Yes	30.0	Yes
Yes	No	Yes	50.0	No
No	No	No	10.0	No
No	No	No	10.0	No

High Temperature	Wind Speed	Rain
Yes	30.0	Yes
No	50.0	No
No	10.0	No
No	10.0	No

Assuming that we have the above data

To create a bootstrap dataset with the same predictors as the original dataset, we just randomly select samples here

For example in this case, the **first row** gets selected twice, while the **3rd** and **last row** are not selected at all

Furthermore, instead of considering all four predictors, we only consider two here ~ “high temp” and “wind speed” (usually they are selected randomly)

Bagging

Low pressure	High Temperature	High humidity	Wind Speed	Rain
No	No	No	10.0	No
Yes	Yes	Yes	30.0	Yes
Yes	Yes	No	20.0	No
Yes	No	Yes	50.0	No
No	No	Yes	70.0	Yes

Not selected

Not selected

Assuming that we have the above data

Low pressure	High Temperature	High humidity	Wind Speed	Rain
Yes	Yes	Yes	30.0	Yes
Yes	No	Yes	50.0	No
No	No	No	10.0	No
No	No	No	10.0	No

To create a bootstrap dataset with the same predictors as the original dataset, we just randomly select samples here

For example in this case, the first row gets selected twice, while the 3rd and last row are not selected at all

High Temperature	Wind Speed	Rain
Yes	30.0	Yes
No	50.0	No
No	10.0	No
No	10.0	No

Furthermore, instead of considering all four predictors, we only consider two here ~ “high temp” and “wind speed” (usually they are selected randomly)

By “randomly” repeat the above process, we can have many bootstrapped dataset

Bagging

Low pressure	High Temperature	High humidity	Wind Speed	Rain
No	No	No	10.0	No
Yes	Yes	Yes	30.0	Yes
Yes	Yes	No	20.0	No
Yes	No	Yes	50.0	No
No	No	Yes	70.0	Yes

Not selected

Not selected

Assuming that we have the above data

Low pressure	High Temperature	High humidity	Wind Speed	Rain
Yes	Yes	Yes	30.0	Yes
Yes	No	Yes	50.0	No
No	No	No	10.0	No
No	No	No	10.0	No

High Temperature	Wind Speed	Rain
Yes	30.0	Yes
No	50.0	No
No	10.0	No
No	10.0	No

To create a bootstrap dataset with the same predictors as the original dataset, we just randomly select samples here

For example in this case, the first row gets selected twice, while the 3rd and last row are not selected at all


Furthermore, instead of considering all four predictors, we only consider two here ~ “high temp” and “wind speed” (usually they are selected randomly)



We can grow many trees out of these randomly bootstrapped dataset (e.g., random forest)

By “randomly” repeat the above process, we can have many bootstrapped dataset

Bagging




Then we have a testing data

Low pressure	High Temperature	High humidity	Wind Speed	Rain
No	Yes	No	40.0	?

Bootstrapping

Bagging



Bootstrapping

Then we have a testing data


Low pressure	High Temperature	High humidity	Wind Speed	Rain
No	Yes	No	40.0	?

- So we take the test data, run it through the **first** tree we made



The first tree says "YES"
(It will rain)

Bagging




Bootstrapping

Then we have a testing data

Low pressure	High Temperature	High humidity	Wind Speed	Rain
No	Yes	No	40.0	?

- So we take the test data, run it through the **first** tree we made → The first tree says "YES" (It will rain)
- We take the test data, run it through the **2nd** tree we made → The 2nd tree says "YES" (It will rain)

Bagging




Bootstrapping

Then we have a testing data

Low pressure	High Temperature	High humidity	Wind Speed	Rain
No	Yes	No	40.0	?

- So we take the test data, run it through the **first** tree we made → The first tree says "YES" *(It will rain)*
- We take the test data, run it through the **2nd** tree we made → The 2nd tree says "YES" *(It will rain)*
-
- We take the test data, run it through the **nth** tree we made → The nth tree says "NO" *(It won't rain)*

Bagging



Bootstrapping

Then we have a testing data


Low pressure	High Temperature	High humidity	Wind Speed	Rain
No	Yes	No	40.0	?

- So we take the test data, run it through the **first** tree we made → The first tree says "YES" (It will rain)
- We take the test data, run it through the **2nd** tree we made → The 2nd tree says "YES" (It will rain)
-
- We take the test data, run it through the **nth** tree we made → The nth tree says "NO" (It won't rain)

After running the dataset through all the "random" trees, we see which option gets more votes, e.g.,

Rain: YES	Rain: NO
15	3

Bagging



Bootstrapping

Then we have a testing data

Low pressure	High Temperature	High humidity	Wind Speed	Rain
No	Yes	No	40.0	?

- So we take the test data, run it through the **first** tree we made → The first tree says "YES" (It will rain)
- We take the test data, run it through the **2nd** tree we made → The 2nd tree says "YES" (It will rain)
-
- We take the test data, run it through the **nth** tree we made → The nth tree says "NO" (It won't rain)


After running the dataset through all the "random" trees, we see which option gets more votes, e.g.,

Rain: YES	Rain: NO
15	3



Final output: YES

Bagging



Bootstrapping

Then we have a testing data

Low pressure	High Temperature	High humidity	Wind Speed	Rain
No	Yes	No	40.0	?

- So we take the test data, run it through the **first** tree we made ➡ The first tree says "YES" (It will rain)
- We take the test data, run it through the **2nd** tree we made ➡ The 2nd tree says "YES" (It will rain)
-
- We take the test data, run it through the **nth** tree we made ➡ The nth tree says "NO" (It won't rain)


After running the dataset through all the "random" trees, we see which option gets more votes, e.g.,

Rain: YES	Rain: NO
15	3

➡ Final output: YES

Aggregation

Bagging



Bootstrapping

Then we have a testing data

Low pressure	High Temperature	High humidity	Wind Speed	Rain
No	Yes	No	40.0	?

- So we take the test data, run it through the **first** tree we made → The first tree says "YES" (It will rain)
- We take the test data, run it through the **2nd** tree we made → The 2nd tree says "YES" (It will rain)
-
- We take the test data, run it through the **nth** tree we made → The nth tree says "NO" (It won't rain)

After running the dataset through all the "random" trees, we see which option gets more votes, e.g.,

Rain: YES	Rain: NO
15	3

Final output: YES

Aggregation

Bootstrapping the data + Using **AGG**regation to get the decision = **BAGGING**