Supplementary Material: Learning-Aware Lyapunov Resource Control for Correlated Multi-Agent Markov Learning

Jialin Zhuang and Vincent K. N. Lau

I. Proof of the Same-Stream Actual-Risk Enclosure

Consider the stationary common factor in the main paper, with independent private observation noise and a deterministic probe $d = (q_d, b_d, n_d)$ ending at $T = n_d b_d$. The probe sigma-field $\mathcal{H}_d$ contains its observations; spatial contrasts contain no additional information about the common factor. Under true instance j, Gaussian filtering gives

$$C_T \mid \mathcal{H}_d \sim \mathcal{N}(m_j, P_j), \quad m_j \sim \mathcal{N}(0, s_j^2), \quad s_j^2 = \theta_j - P_j. \tag{S1}$$

The posterior variance P_j is deterministic because the probe schedule is fixed before data. Starting from variance θ_j, the observation update is $P \leftarrow P/(1+q_d P)$; between observations it is $P \leftarrow \lambda^{2b_d} P + (1-\lambda^{2b_d})\theta_j$. The last update has no subsequent prediction.

Fix either downstream program a, including its budget, initialization, sample spacing and deterministic weights. All learning observations occur strictly after T. With $r_a = \lambda^{b_a}$ and the notation of main Eq. (38), its unconditional stationary risk is

$$J_{j,a} = d_a^2 + \theta_j \sum_{t,u=1}^{N_a} \omega_{a,t}\omega_{a,u} r_a^{|t-u|} + q_a^{-1} \sum_{t=1}^{N_a} \omega_{a,t}^2. \tag{S2}$$

Conditional means of future common states are $\lambda^{b_a t} m_j$. Their conditional covariance is their stationary covariance minus $s_j^2 \lambda^{b_a(t+u)}$. Private learning noise is independent of the probe. Therefore

$$\mathbb{E}_j[Z_a^2 \mid \mathcal{H}_d] = J_{j,a} + 2 d_a k_a m_j + k_a^2 (m_j^2 - s_j^2). \tag{S3}$$

This identity includes the posterior mean, which is unbounded across probe histories; no uniform conditional Gaussian bound is invoked.

Let E_j be the event that the decision selects the wrong frozen program, and let $p_j = \Pr_j(E_j) \le \delta$. Subtracting Eq. (S3) for the correct and wrong programs gives

$$\mathbb{E}_j Z_{\widehat{a}}^2 = J_{j,a_c} + p_j \Delta J_j + \mathbb{E}_j[\mathbf{1}_{E_j} U_j], \tag{S4}$$

where

$$U_j = 2(d_{a_w} k_{a_w} - d_{a_c} k_{a_c}) m_j + (k_{a_w}^2 - k_{a_c}^2)(m_j^2 - s_j^2). \tag{S5}$$

The centered Gaussian first and second moments are orthogonal, with variances s_j^2 and $2s_j^4$. Consequently $\mathbb{E}_j U_j = 0$ and $\mathbb{E}_j U_j^2 = \Gamma_j^2$ as defined in the main paper. Cauchy–Schwarz gives $|\mathbb{E}_j[\mathbf{1}_{E_j} U_j]| \le \sqrt{p_j}\Gamma_j \le \sqrt{\delta}\Gamma_j$. Bounding the signed term $p_j \Delta J_j$ and using nonnegative squared risk proves main Theorem 5.

II. Exact Weights of the Implemented Learners

Let $M_a = \min\{\lfloor B'_m/(h+q_a)\rfloor, \lfloor B'_e/b_a\rfloor\}$ be the number of scheduled observations after subtracting probe costs. All M_a observations are paid. The FIFO withholding convention leaves $N_a = (M_a - D)_+$ usable observations, not a free replacement budget. For $N_a = 0$ the reported parameter is one, so $d_a = 1$ and the weight vector is empty.

A. Running mean

The Layer-A output is $(1+\sum_{t=1}^{N_a} \bar{X}_t)/(N_a+1)$. Thus $d_a = 1/(N_a+1)$ and every $\omega_{a,t} = 1/(N_a+1)$. Main Eq. (38) then gives

$$k_a = \frac{r_a(1 - r_a^{N_a})}{(N_a+1)(1-r_a)}. \tag{S6}$$

B. Averaged FIFO affine learner

In Layer B, an increment $\eta(\bar{X}_t - \mu w_{t-1})$ is computed before enqueueing and is applied after D opportunities. The original implementation fixes $\mu = 1/2$ and $\eta = 0.1/[\mu(D+1)]$, starts from parameter one with an empty queue, and averages the applied parameters. Indexing these applied parameters as z_n gives

$$z_n = z_{n-1} - \eta\mu z_{n-D-1} + \eta \bar{X}_n, \quad z_{-D} = \cdots = z_0 = 1. \tag{S7}$$

Define $h_0 = 1$, $h_t = 0$ for $t < 0$, and $h_t = h_{t-1} - \eta\mu h_{t-D-1}$ for $t \geq 1$. For $N = N_a > 0$, the output $N^{-1}\sum_{n=1}^{N} z_n$ has exact coefficients

$$\omega_{a,t} = \frac{\eta}{N}\sum_{v=0}^{N-t} h_v, \quad d_a = 1 - \mu\sum_{t=1}^{N}\omega_{a,t}. \tag{S8}$$

To verify the deterministic term, constant input $\bar{X}_n = \mu$ keeps the initial history at one; linearity then yields the identity for d_a. Eq. (S8) represents the average of applied iterates; all scheduled observations remain charged.

III. Shrinking-Risk and Budget-Shift Interface

Suppose the finite action catalogue has $|\lambda| \leq 1 - \gamma < 1$, bounded D, and strictly stable affine recursions. For the registered step rule this stability follows directly from the characteristic polynomial $z^{D+1} - z^D + t$, $t = \eta\mu$. At small $t > 0$, the root at one moves inside the unit disk and the other roots remain inside. Writing a first unit-circle crossing as $z = e^{i\omega}$ yields $t = 2\sin(\omega/2)$ and the smallest positive crossing $\omega = \pi/(2D+1)$. Thus $0 < t < 2\sin[\pi/(4D+2)]$ is stable; the registered $t = 0.1/(D+1)$ lies strictly inside this interval. The impulse response consequently decays geometrically, and $\sum_{v\geq 0} h_v = 1/(\eta\mu)$.

The interior weights in Eq. (S8) are $1/(\mu N)$ up to a summable end correction: their difference from these constant weights has ℓ_1 norm $O(N^{-1})$ and maximum absolute value $O(N^{-1})$. The homogeneous transient is summable, so its average d_a is $O(N^{-1})$. The AR(1) covariance kernel has uniformly bounded absolute row sums. Substitution into Eq. (S2) therefore gives

$$J_{j,a} = \frac{1}{\mu^2 N_a}\left[\frac{1}{q_a} + \theta_j\frac{1+r_a}{1-r_a}\right] + O(N_a^{-2}). \tag{S9}$$

The running mean has the same expansion with $\mu = 1$. These constants are uniform over the finite catalogue and bounded instance class. On a budget ray, $N_a = s/c_a + O(v+D+1)$ with $c_a = \max\{(h+q_a)/\beta_m, b_a/\beta_e\}$ and fixed probe charge v. Hence $J_{j,a} = K_{j,a}/s + O((v+D+1)/s^2)$, with

$$K_{j,a} = \frac{c_a}{\mu^2}\left[\frac{1}{q_a} + \theta_j\frac{1+r_a}{1-r_a}\right]. \tag{S10}$$

Subtracting a fixed probe charge changes N_a by at most $O(v+D+1)$, giving the claimed budget-shift remainder. Moreover $k_a = O(N_a^{-1})$ because the weights are uniformly $O(N_a^{-1})$ and $\sum_{t\geq 1}|r_a|^t$ is bounded. Since $s_j^2 \leq \theta_j$, main Eq. (39) yields

$$\sqrt{\delta}\Gamma_j = O(\sqrt{\delta}/s^2). \tag{S11}$$

For a pair of frozen actions satisfying the main phase theorem's leading-gap and wrong-decision assumptions, adding this remainder to admission changes only its second-order class constants. The same necessary-information and sufficient-scale argument then applies to the corrected actual-risk rule. This is an averaged, additive Gaussian affine result; it does not remove the nonzero noise floor of a fixed-step unaveraged learner or the conditional-history requirements of the general Markov theorem.

TABLE I
Population enclosures for mean information-only minus learning-aware risk, rounded outward. All means use the listed complete stratum.

Layer	Stratum	Cells	Lower	Upper
A	All	1184	.0506	.0706
A	Intermediate	576	.0770	.1180
A	Original practical	446	.1607	.1952
A	Search-censored	32	.4879	.4880
B	All	608	.0079	.0223
B	Intermediate	288	-.0049	.0252
B	Original practical	222	.0562	.0773
B	Search-censored	32	.1957	.1958

IV. Complete Existing-Evidence Reanalysis

The calculation uses all registered EXP-016B budget points, both regimes and all eight policies: 14,336 policy cells, each with its original 192-seed empirical mean. Layer A contains 104 scenario families and Layer B its original 56, including eight search-censored families in each layer. For fixed policies Eq. (S2) is exact. For probe policies main Eq. (40) supplies population-risk bounds. When information-only and learning-aware policies execute the same frozen program, their paired difference is identically zero, not the difference of two independent interval bounds. Otherwise subtract their one-sided bounds.

Below identification, all 208 Layer-A and 112 Layer-B comparisons are identical programs; above finite value thresholds the corresponding counts are 384 and 192. In the original practical subset, 323/446 Layer-A and 176/222 Layer-B cells have strictly positive improvement lower bounds, while 101 and 33 have strictly negative upper bounds; the remaining 22 and 13 are inconclusive. These include regime-specific losses even when the stratum-average improvement is positive. No new admission rule was executed and no old gate was replaced. The old probe-length routine used the sufficient exponent $\log(0.5/0.025)$, giving an equal-prior average-error target of 0.025 rather than a directional guarantee of 0.025. The reanalysis uses each probe's exact affinity $\exp(-I_B)$ as a valid bound on either directional error; over all 104 frozen probe designs these bounds range from 0.0352271 to 0.0497465. Failure of this sufficient directional certificate does not establish that the actual

directional errors exceed 0.025. No outcomes or probe lengths are changed to obtain a smaller error bound. This outcome-known reanalysis gives population enclosures, not new confidence intervals for empirical means.

V. Complete Threshold-Sandwich Scale Calculation

For the independently initialized Gaussian running mean, let $c_a = \max\{(h+q)/\beta_m, b/\beta_e\}$ and $r = \lambda^b$. The exact horizon is $N_a = s/c_a + O(1)$, with bounded terminal charges and rounding. Main Eq. (8) and Eq. (13) give $K_j(a) = c_a\{q^{-1}+\theta_j(1+r)/(1-r)\}$ and a uniform $O(s^{-2})$ remainder. Removing probe charge v changes N_a by $O(v+1)$ and hence risk by $O((v+1)/s^2)$ for $s \geq s_0(v+1)$; compact persistence and the finite catalogue make these constants uniform. Thus the phase-theorem risk conditions have a concrete Gaussian realization, separately from the constant-step affine certificate. Write $d_\delta = \mathrm{kl}(1-\delta,\delta)$, $r_0 = 1-\gamma < 1$, and $Q = \max \mathcal{Q}$. Under either true instance, predictable spacing gives $\|C_{S_k}\|_{L^2} \leq r_0\|C_{S_{k-1}}\|_{L^2} + \sqrt{\theta_+}$, hence a uniform bound $M_C = \sqrt{\theta_+}/(1-r_0)$. The normalized observation $Y_k/\sqrt{q_k}$ has L^2 norm at most $M_C + 1$. For either candidate filter, write its posterior mean as $(1-t_{j,k})m^-_{j,k} + t_{j,k}Y_k/\sqrt{q_k}$, with predictable $0 \leq t_{j,k} \leq 1$. Prediction multiplies this mean by a factor of magnitude at most r_0; the triangle inequality bounds both predictive means uniformly in L^2 by $M_F = r_0(M_C+1)/(1-r_0)$, starting from zero. Both predictive variances are at most θ_+, so $1 \leq V_{j,k} \leq V_+ = 1 + Q\theta_+$. Main Eq. (26) gives the expected, rather than pointwise, bound $\mathbb{E}_j\mathcal{I}_{j,1-j}(Z_k, A_k) \leq i_+$, where $i_+ = (\log V_+ + V_+ + 4QM_F^2)/2$ is finite. Extend a stopped rule predictably after stopping; nonnegativity and its deterministic budget bound $n_{\max}(s) \leq c_B s$ imply $\mathbb{E}_j \sum_{k\leq\tau}\mathcal{I}_{j,1-j} \leq i_+ n_{\max}(s)$. Together with main Eq. (30), this proves $B_N \geq c_N d_\delta$. The fixed probe has information at least $i_- > 0$, so $n_\delta = \lceil i_-^{-1}\log(1/\delta)\rceil$ observations suffice and cost at most $c_p n_\delta + D_{\max}$. Continuity of $\log(1/\delta)/d_\delta$ gives $n_\delta \leq c_0 + c_1 d_\delta \leq c_0 + c_2 B_N$. Write $u_\delta \leq c_p n_\delta + D_{\max}$ for the full probe charge. The assumed expansion and budget-shift inequality give a high-instance improvement over the full-budget fallback certificate of at least $g_{\min}/s - \{2M + L(u_\delta+1)\}/s^2 - \delta w_+/s$. It is strictly positive for $s > \{4M+2L(u_\delta+1)\}/g_{\min}$, also requiring $s \geq s_0(u_\delta+1)$. On instance zero, the assumed coefficient ordering gives $\epsilon_{\mathrm{safe}} \leq \{2M + L(u_\delta+1)\}/s^2 + \delta_0 w_+/s$. Thus $s \geq \sqrt{2\{2M + L(u_\delta+1)\}/\bar{\epsilon} + 2\delta_0 w_+/\bar{\epsilon}}$ suffices. Using $2\sqrt{xy} \leq x+y$, all three requirements are bounded by a class-constant multiple of $n_\delta + B_{\mathrm{oracle}} + B_\epsilon + 1$. Taking the maximum proves the upper bound in main Eq. (43); its lower bound follows because every admitted δ-correct probe obeys both information constraints.

VI. Robust-Certificate Sensitivity Details

This section supplies the proof of main Corollary 2. Write $\delta^+ = C_q(r_q^+)^b$. On the coverage event, $\delta^+ \geq \delta$ and monotonicity on $\mu - 2L\delta^+ > 0$ gives $a^+ \geq a$ and $\beta^+ \geq \beta$. Evaluating the delayed Young inequality at the shared $\lambda^+ = \sqrt{h/a^+}$ proves the upper recursion; separately optimized forcing terms need not be monotone. For $\Delta\delta = \delta^+ - \delta$, $\Delta K = K_q^+ - K_q$, and $\Delta\Omega = \Omega_q^+ - \Omega_q$,

$$\begin{aligned}
\Delta a &= 2\eta^2\Delta K + (2\eta L + 4\eta^2 L^2)\Delta\delta,\\
\Delta\beta &= 2\eta^2\Delta\Omega + 4\eta^2 G^2\Delta\delta\\
&\quad + 4\eta G^2\left[\frac{(\delta^+)^2}{\mu - 2L\delta^+} - \frac{\delta^2}{\mu - 2L\delta}\right],\\
\Delta c &= (\sqrt{a^+}+\sqrt{h})^2 - (\sqrt{a}+\sqrt{h})^2. \qquad \text{(S12)}
\end{aligned}$$

For $h > 0$,

$$\begin{aligned}
\Delta d &\leq (1+\sqrt{h/a^+})\Delta\beta + \sqrt{h}\left(\frac{1}{\sqrt{a}} - \frac{1}{\sqrt{a^+}}\right)\beta\\
&\quad + \frac{\sqrt{a^+}-\sqrt{a}}{\sqrt{h}}g, \qquad \text{(S13)}
\end{aligned}$$

and $\Delta d = \Delta\beta$ when $h = 0$. For $U(c,d) = d/(1-c) + c^n(R_0 - d/(1-c))_+$, $|\partial_d U| \leq (1-\bar{c})^{-1}$ and $|\partial_c U| \leq nR_0 + \bar{d}(1-\bar{c})^{-2}$. The mean-value bound proves main Eq. (45); applying it to the upper- and exact-score minimizers gives $U_{\widehat{a}} \leq U_{a^\star} + 2\max_a \varepsilon_a$.

VII. Stochastic-Delay Interpretation

The controlled stochastic delay differential equation associated with one fixed resource action is

$$dE(t) = -A_q E(t-\tau(t))dt + \sqrt{\eta}\,\Sigma_q^{1/2}(E_t)dW(t). \qquad \text{(S14)}$$

Here $\Sigma_q(E_t)$ retains both additive innovation covariance and the state-dependent quadratic variation of random temporal-difference Jacobians. For $V(E) = \|E\|^2$, Itô's formula gives

$$\mathcal{L}_a V(E_t) = -2E(t)^\top A_q E(t-\tau(t)) + \eta\,\mathrm{tr}\,\Sigma_q(E_t). \qquad \text{(S15)}$$

Participation controls spatial covariance, spacing controls mixing, and η controls their scale; the discrete theorem retains finite steps, integer delays and rounding.

VIII. Constructing a Certificate from a Known Finite Model

Let Z be the finite augmented state containing all sources needed for the retained joint TD tuple. For each participation q, suppose its kernel M_q and stationary law π_q are known, and the marginal target policy and reward law are preserved. Tabulate $H_i(z)$ and $c_i(z)$, put $A = \mathbb{E}_{\pi_q}H_i$, $c = \mathbb{E}_{\pi_q}c_i$, and solve $Aw^\star = c$. Check that these means are common to all actors and

all q, and that $\mu = \lambda_{\min}((A + A^\top)/2) > 0$. With $\xi_i(z) = c_i(z) - H_i(z)w^\star$, compute

$$L = \max_{i,z} \|H_i(z)\|_2, \qquad G = \max_{i,z} \|\xi_i(z)\|,$$
$$K_q = \lambda_{\max}\left(\sum_z \pi_q(z)\bar{H}_q(z)^\top \bar{H}_q(z)\right),$$
$$\Omega_q = \sum_z \pi_q(z)\|\bar{\xi}_q(z)\|^2,$$
$$\beta_q(g) = \max_z \frac{1}{2}\sum_{z'} |M_q^g(z, z') - \pi_q(z')|. \tag{S16}$$

Here bars denote actor averages, not averages of squared norms. The integer g is the number of transitions of the augmented tuple chain between the conditioning state and the retained tuple; it must be derived from the declared physical schedule, not identified with a state lag or drain charge.

Proposition 1 (Constructive finite-model interface)**.** *If M_q is irreducible and aperiodic and the above common-mean and positivity checks pass, Assumption 1's boundedness, centering and conditional mixing inputs hold with Eq.* (S16) *and $\delta = \beta_q(g)$. For every action whose resulting μ_δ, a_δ and $c_{\mathrm{aff}} < 1$ pass the main paper's shield, the affine certificate is valid from any declared initial augmented state.*

Proof. The finite maxima bound every sample and stationarity gives $\mathbb{E}_{\pi_q}\xi_i = 0$. Conditional on any earlier history, the Markov property expresses the next tuple law as a mixture of rows of M_q^g. Convexity of total variation bounds its distance from π_q by $\beta_q(g)$, uniformly over that history. The drift proof uses only this total-variation distance, so the geometric envelope can be replaced by this exact finite-gap value. The stated positivity and contraction checks are precisely the remaining hypotheses of the affine bound. □

This is a construction, not a statistical estimator of an unknown kernel. A dense joint-state table may grow exponentially with participation; its offline construction cost is separate from the online scalar score. In the seven-state shared/private-source model, a product coupling gives the cheaper bound $\beta_q(g) \le \min\{1, (q+1)\beta_{\mathrm{pair}}(g)\}$, where $\beta_{\mathrm{pair}}(g) = \max_x \|M_{\mathrm{pair}}^g(x, \cdot) - \pi_{\mathrm{pair}}\|_{\mathrm{TV}}$. This uses the actual consecutive-pair chain and independent latent source chains; fresh selector coins are integrated by data processing. The existing implementation computes these pair kernels and the same-time aggregate moments directly. For a moving target policy, a frozen-kernel table does not certify mixed histories: either supply uniform bounds for the nonhomogeneous kernel products or reset the learner and exclude all pre-reset target updates.

IX. Executable Actual-Risk Gate and Saved-Result Reconstruction

For each fixed candidate probe, Gaussian filtering gives P_j, the formulas above give $(J_{j,a}, d_a, k_a)$, and the probe likelihood laws give a directional error bound δ_j under each hypothesis. The exact Gaussian affinity is one valid choice: a zero-threshold likelihood-ratio decision obeys $\Pr_j(\mathrm{error}) \le \int \sqrt{p_0 p_1}$ in each direction. An equal-prior average-error bound is not interchangeable with this directional bound. Compute both hypothetical-instance quantities before probing; the actual unknown instance is not a gate input.

Proposition 2 (Actual-risk admission)**.** *Fix the two hypotheses, noise law, learner initialization and deterministic linear program weights as in Theorem 5. Given a finite public probe catalogue, choose a feasible design satisfying Eq.* (41) *before any probe observations, with deterministic tie breaking. After its likelihood decision, execute its frozen selected program on the continuing stream. Then $\mathbb{E}_1 Z^2 < F_1$ and $\mathbb{E}_0 Z^2 \le F_0 + \bar{\epsilon}$. If none passes, no probe is executed and the actual risk is exactly F_j.*

Proof. For each fixed design Theorem 5 gives $\mathbb{E}_j Z^2 \le U_j(d)$. Pre-observation deterministic choice leaves its fixed-design hypothesis intact. The two gate inequalities imply the conclusions. In the rejection branch the stationary full-budget commitment defines F_j. □

Thus the procedure is: price the probe, compute the remaining horizons and exact weights for both branch programs, compute U_0, U_1, F_0, F_1, apply the two inequalities, and only then acquire data. An observation-adaptive choice of probe duration or of program weights is not covered by this fixed-design argument.

We reconstruct this gate on the existing EXP-016B outcomes, using its single registered information-only probe candidate and the original scenario-specific allowances 0.1 or 0.2. All 896 public layer/scenario/budget designs and both regimes are retained, including search-censored families. The corrected gate admits 480 designs, versus 505 without the carryover term; it removes 25 admissions. The outcome-known zero-allowance stress case admits none under either rule. It is retained separately: a paid probe can reduce the low-instance learning horizon even with perfect identification.

The gate is a deterministic function of public design quantities, so an admitted design takes the saved information-only outcome and a rejected design takes the saved no-probe fallback outcome. The simulator's potential observations are policy independent and shared across these branches; this reconstructs their empirical means without generating or resampling a trajectory. Table II is therefore a retrospective policy comparison,

TABLE II
SAVED-RESULT GATE RECONSTRUCTION: MEAN SQUARED RISK OVER ALL BUDGET/REGIME CELLS, WITHOUT NEW TRAJECTORIES. EACH ORIGINAL CELL MEAN CONTAINS ALL 192 SAVED SEEDS.

	A high	A low	B high	B low
Full-budget fallback	.63455	.09201	.82703	.54369
Information-only	.54814	.24062	.76422	.62515
Original learning-aware	.57637	.09304	.79121	.55825
No-carryover gate	.52548	.09488	.74204	.56252
Corrected gate	.52989	.09393	.74242	.56068

not fresh execution or independent confirmation. Against fallback, the corrected gate retains $13/592$ and $4/304$ empirically adverse high-instance cells in A and B; finite-sample cell means need not satisfy the population ordering. Its low-instance mean risks exceed fallback by $.00192$ and $.01699$, respectively, within the declared nonzero safety allowances, not a claim of zero-harm safety. The no-carryover ablation has slightly lower high-instance means but higher low-instance means; the correction trades admissions for a valid population-risk guarantee, not uniformly better observed risk. All eight original policies, per-cell costs, both replay variants and their complete cell tables are preserved. The new comparison was specified after earlier outcomes were known and supplies no new confidence interval.

X. NEAREST-WORK ASSUMPTIONS AND OBJECTIVES

The comparison uses the accessible full preprints, with theorem and proof locators recorded in the accompanying source-reading matrix; it is not an exhaustive priority claim. DASA [25], Assumption 3 and Theorem 1, combines independent agent chains with median-based update filtering to obtain average-delay dependence and parallel speedup. Its Lemma 2 uses cross-agent independence in the noise cross terms. Our bounded deterministic delay condition is narrower; our added object is covariance-dependent paid learning risk, not a stronger delay rate.

Perazzone et al. [20], Theorem 1 and Eqs. (12)–(23), link inverse participation probabilities to a nonconvex convergence bound, then optimize a time-average convergence/communication surrogate with power queues. Their solver and instantaneous-channel formulation address a different operational problem; our finite-budget probe debit and same-stream decision-event correction do not follow from that time-average objective. Yu et al. [26], Sections III–IV and Propositions 12–14, use an SDDE/arrival-process approximation to optimize worker activation, including a finite-service queue. That queue model and its delay law are not established by our fixed-delay experiment.

Saad et al. [32], Assumption 1, Protocol 1 and Theorems 4.1/5.1, adapt joint arm queries to unknown covariance with independent rounds and a fixed-confidence identification objective. Our dependence hypotheses are supplied, rather than learned nonparametrically; our comparison instead prices identification through the subsequent learner. Li et al. [35], Theorem 4.12, remove unknown mixing/eigenvalue inputs from a regularized TD step schedule. That reduces tuning requirements that our general confidence interface still has, but does not construct a calibrated multi-action terminal-risk shield. Li et al. [36], Assumptions 1–7 and Theorem 1, give shrinking-tube reliability for projected adaptive-kernel SA using uniform drift/minorization and kernel continuity. Their mixed-history result is broader than a frozen-kernel table; our Gaussian decision correction and paid finite horizon are different outputs, not a replacement for their regularity assumptions. Reference numbers in this supplement refer to the main paper's bibliography.

XI. COMPLETE TRACKING PROOF

Set $R_\star = d/(1-c)$ and $\Gamma_r = (Z_r - R_\star)_+$. The explicitly assumed uniform-history drift and the positive-part replacement argument give

$$\begin{aligned} \widetilde{Z}_{r+1} &\le R_\star + c\Gamma_r, \\ \Gamma_{r+1} &\le (1+\chi)c\Gamma_r + \chi R_\star + (1+\chi^{-1})v^2. \end{aligned} \tag{S17}$$

The second line follows by applying Young's inequality to the target shift and subtracting $R_\star$. Iteration and $\Gamma_0 \le Z_0$ prove Eq. (20) whenever $\bar{c} = (1+\chi)c < 1$. Finally, $\widehat{A}_w - A^\star = \{\gamma\phi(s') - \phi(s)\}^\top (w - w_n^\star)$ and $\|\gamma\phi(s') - \phi(s)\| \le (1+\gamma)\Phi$; Cauchy–Schwarz proves Eq. (21).

XII. COMPLETE OCCUPATION-MEASURE PROOF

Let $\Delta_j(z,a) \ge 0$ be the one-step opportunity loss relative to the instance-j certified oracle. For a stopped predictable policy, define

$$\nu_j(G,a) = \mathbb{E}_j^\pi \sum_{k \le \tau} \mathbf{1}\{Z_k \in G, A_k = a\}. \tag{S18}$$

Every δ-correct policy induces an occupation measure satisfying the controlled Kalman flow constraints,

$$\begin{aligned} \int \mathcal{I}_{j,1-j}(z,a)\nu_j(dz,da) &\ge \mathrm{kl}(1-\delta,\delta), \\ \int (h + q(a))\nu_j(dz,da) &\le B_{\mathrm{msg}}, \\ \int b(a)\nu_j(dz,da) + \ell\mathbb{P}_j(\tau > 0) &\le B_{\mathrm{env}}. \end{aligned} \tag{S19}$$

Let T_a be the belief transition and ζ_j the terminal belief law. For every bounded measurable f, predictability and stopped telescoping give

$$\int f(z)\zeta_j(dz) - f(z_1) = \int \Big[\int f(z')T_a(z, dz') - f(z)\Big]\,\nu_j(dz, da). \tag{S20}$$

Moreover,

$$\mathbb{E}_j^{\pi} \sum_{k\le\tau} \Delta_j(Z_k, A_k) = \int \Delta_j(z, a)\nu_j(dz, da). \tag{S21}$$

Eq. (29), Eq. (6), and Eq. (S20) place every admissible occupation measure in the controlled feasible set. Taking the infimum of its exact loss over that larger set proves Proposition 4.

XIII. Complete Cooperative Policy-Learning Transfer Results

Held-out MAPPO transfer studies match message/environment budgets and charge a disjoint critic-residual probe that selects participation without evaluation return. Both studies use eight fresh seeds per dependence regime and compare against fixed $q \in \{1, 2, 4, 8\}$. We compare regime-wise fixed envelopes and the strongest single fixed action for an unknown regime.

In PettingZoo `simple_spread_v2`, the controller commits to $q = 8$ in all eight independent-stream runs and $q = 1$ in all eight shared-stream runs. It lies within 0.357 and 0.889 percent of the corresponding regime-wise fixed envelopes. Against the strongest single fixed action, $q = 8$, the mean of the regime–seed normalized AUC gains is 2.319 percent; normalization precedes averaging.

In MaMuJoCo `HalfCheetah-v2/2x3`, the task-specific prespecified catalogue is $\{2, 8\}$, while evaluation still includes all four fixed actions. The controller selects $q = 8$ in all eight independent-stream runs and $q = 2$ in all eight shared-stream runs. Relative to the corresponding regime-wise fixed envelopes, its AUC changes are -0.542 and -0.997 percent, both within the prespecified two-percent noninferiority margin. When the regime is unknown, the strongest single fixed action is $q = 8$. Forming each seed's equal-regime mixture before normalization gives a mean paired AUC gain of 8.341 percent, a one-sided 95 percent lower bound of 1.107 percent, seven of eight positive pairs ($p = 0.0352$), and a final-return gain of 4.637 percent.

Fig. 1 shows the unsmoothed deterministic team-return curves against the maximum charged dual-budget fraction. Probes consume at most 0.768 percent of messages; selection overhead is below 10^{-6} of training time.

XIV. Direct Fixed-Model Validation of the Actual-Risk Gate

A. Models, learners, and paid protocol

This study executes the actual-risk gate prospectively on new seeds, rather than reconstructing decisions from the earlier saved study. The 16 public families cross $Q \in \{8, 32\}$, high-instance variance $\theta_1 \in \{0.5, 2\}$, common-factor persistence $\lambda \in \{0.2, 0.8\}$, and withheld-update delay $D \in \{0, 8\}$. The low-instance variance is $\theta_0 = 0.05$, private variance is one, and message overhead is $h = 8$. Each family is evaluated under both true instances, each learner, and scales $s \in \{32, 128, 512, 2048\}$, with $B_{\mathrm{msg}} = (h+Q)s$ and $B_{\mathrm{env}} = 4s$. The 128 new seeds are $20571001, \ldots, 20571128$, screened against the historical seed registries before execution. All six policies share policy-independent potential observations within each seed, family, true instance, and learner, including across budget scales. They do not share potential observations across learners.

The common observation component is stationary Gaussian autoregressive noise, with coefficient λ and marginal variance θ_j; each actor has independent unit-variance Gaussian private noise. An average over the first q actors therefore has private variance $1/q$. Both learners start from one with a constant-one initial history. The running mean uses its exact averaging weights; the averaged delayed affine learner uses $\mu = 0.5$ and $\eta = 0.2/(D + 1)$ with the first-in, first-out recurrence analyzed above. Every scheduled block is paid, including the last D withheld updates: M scheduled updates give $N = \max\{0, M - D\}$ learner updates. There is no free startup or independent learning reset after a probe. The measured endpoint is squared parameter error at the exact zero target, not an unobserved within-run convergence curve.

Before data, the fixed probe uses $q_d = Q$, $b_d = 1$, and the smallest integer $n_d \in \{1, \ldots, 4096\}$ whose exact Gaussian affinity is at most 0.025. The log-likelihood threshold is zero, with ties assigned to the low instance. An infeasible or unavailable probe falls back to the full-budget all-agent program. After charging the probe, the two commitment programs minimize exact stationary risk under their respective supplied hypotheses over powers-of-two $q \le Q$ and $b \in \{1, 2, 4, 8\}$, breaking ties lexicographically in (q, b). Both programs are fixed before observing the probe; the true instance is not an input to any deployment decision. Writing F_j for the full-budget all-agent population risk and U_j for the same-stream population upper bound, the gate requires $U_1 < F_1$ and $U_0 \le F_0 + 0.1$. The no-carryover ablation deletes only the $\sqrt{\delta_j}\Gamma_j$ contribution from that admission calculation. The other controls are information-only




Fig. 1. Fully charged MAPPO team-return learning curves on two cooperative environments with fixed $q \in \{1, 2, 4, 8\}$ and the Lyapunov probe-then-commit controller (eight held-out seeds per regime; shaded bands are controller 95 percent confidence intervals). The controller selects $q = 8$ for independent streams in both environments, $q = 1$ for shared MPE streams, and $q = 2$ for shared MaMuJoCo streams.

probing, all-agent fallback, fixed $(q, b) = (2, 1)$, and a known-instance oracle used only for evaluation.

The complete grid contains $16 \times 2 \times 2 \times 4 \times 6 \times 128 = 196608$ trajectories. Every trajectory is regenerated in a full semantic replay, including its paid ledgers and decisions. Two analyses reproduce all seven output tables byte for byte. No failed, infeasible, adverse, or partial-cost record is removed.

B. All macro comparisons and counterevidence

For each learner, instance, and scale, we average the paired fallback-minus-policy squared-risk difference across all 16 families within each seed. Table III reports all 16 corrected-gate macro means and descriptive percentile intervals from 2,000 paired-seed bootstrap resamples. These are cellwise descriptive intervals, not a familywise significance or equivalence claim.

All eight high-instance macro intervals are positive, as are seven of eight low-instance intervals. The exception is the low-instance running mean at scale 32, where probing can spend resources without compensating risk reduction. At the finer family level, 23 of 256 corrected-gate mean improvements are negative (four high and nineteen low); 174 intervals are strictly positive, nine strictly negative, and 73 include zero or are exactly zero. The permitted low-instance population-risk increase is 0.1, so this adverse result does not contradict a zero-harm condition: no such condition was imposed.

The corrected gate admits probing on 113 of 128 public designs, exactly as does the no-carryover gate. Their probe-use indicators, actions, and risks coincide on all 32,768 paired policy rows. The selection-dependence term remains necessary to the stated bound, but its incremental empirical decision benefit is unresolved on this grid. Small differences between separately resampled bootstrap endpoints for the two identical policies do not constitute performance differences. The prespecified zero-allowance admission diagnostic admits 100 of 128 designs; it uses saved branch calculations, not additional trajectories.

Table IV retains all six policies' pooled risks and paid costs. Pooling gives equal weight to heterogeneous families, instances, learners, and scales, so it is descriptive rather than a universal ranking or a comparison at identical realized costs. Fixed $(q, b) = (2, 1)$ has lower pooled risk and environment cost than the corrected gate, whereas the gate sends fewer messages. The oracle is an instance-aware reference and is not deployable without the unknown label.

C. Probe validity and the scope of the enclosures

There are 8,192 distinct deduplicated potential probe decisions and thirteen observed classification errors, an empirical fraction of 0.001587. The exact affinity bounds range from 0.021139 to 0.024380, each below 0.025 under both supplied hypotheses. This new fixed-probe construction does not retroactively validate the earlier probe's nominal 0.025 directional interpretation, which bounded equal-prior average error instead. The historical reanalysis continues to use its larger exact affinities.

The risk enclosures concern population expectations under known binary Gaussian hypotheses and deterministic linear programs. In 123 of 256 corrected-gate cells, the finite sample mean exceeds the corresponding population upper bound; such an exceedance is not by itself a population-bound violation. In particular, fallback risk is an exact model expectation, not a simultaneous upper confidence limit for noisy sample means. The study therefore does not establish samplewise coverage, calibration for unknown kernels, or a general neural policy-learning guarantee.

Figs. 2–5 show every policy against budget scale, actual paid messages, and actual paid environment units, separately for each learner and instance. Each point

TABLE III
ALL CORRECTED-GATE MACRO RISK IMPROVEMENTS OVER ALL-AGENT FALLBACK. POSITIVE VALUES FAVOR THE GATE; BRACKETS GIVE DESCRIPTIVE 95 PERCENT PAIRED-BOOTSTRAP INTERVALS.

Learner	Scale	High instance: mean [interval]	Low instance: mean [interval]
Running mean	32	$0.07820\ [0.06227, 0.09303]$	$-0.002290\ [-0.003226, -0.001357]$
	128	$0.03452\ [0.03051, 0.03840]$	$0.000763\ [0.000530, 0.000986]$
	512	$0.009436\ [0.008400, 0.010491]$	$0.000373\ [0.000324, 0.000422]$
	2048	$0.002268\ [0.001998, 0.002550]$	$0.0000860\ [0.0000736, 0.0000985]$
Delayed affine	32	$0.10001\ [0.08038, 0.11922]$	$0.06114\ [0.05777, 0.06469]$
	128	$0.14696\ [0.13225, 0.16261]$	$0.07750\ [0.07538, 0.07955]$
	512	$0.04006\ [0.03541, 0.04538]$	$0.010206\ [0.009663, 0.010712]$
	2048	$0.008698\ [0.007723, 0.009715]$	$0.000914\ [0.000838, 0.000993]$

TABLE IV
DESCRIPTIVE POOLED MEANS OVER ALL 256 CELLS FOR EACH POLICY; EVERY CELL HAS 128 SEEDS.

Policy	Squared risk	Paid messages	Paid environment	Probe fraction
All agents	0.114864	19040.000	680.000	0
Fixed $(2, 1)$	0.062931	19037.500	1903.750	0
Information only	0.099064	18509.108	2467.163	0.937500
Oracle (evaluation only)	0.051335	18508.477	2509.625	0
Without carryover	0.079311	18509.341	2463.203	0.882813
Corrected gate	0.079311	18509.341	2463.203	0.882813

averages all 16 families and all 128 seeds; connecting points does not imply a within-trajectory learning curve or equal realized cost.

XV. ADDITIONAL RESOURCE-ACTION AND PROBE-VALUE PLOTS

Fig. 6 retains the complete action plot for the joint-controller study in the main paper. Fig. 7 retains its controlled probe-value comparisons; no data, caption or graphical content has changed.

A. Retained confidence-stress and reproducibility details


The Markov temporal-difference task has seven states on a ring, a bounded sinusoidal reward, four stationary-distribution-orthonormal features, and an exact projected fixed point. Cross-agent dependence is induced by shared and private Markov sources while preserving every agent's marginal transition law. The policy-learning studies use MAPPO with parameter-shared actors and a centralized critic [41]. They cover PettingZoo's multi-agent particle environment `simple_spread_v2` [42] and the multi-agent MuJoCo (MaMuJoCo) `HalfCheetah-v2/2x3` benchmark [43]. Bootstrap comparisons resample paired seeds and report percentile intervals for the ratio of geometric-mean risks. The confidence-interface study uses 64 disjoint confirmation seeds and 157,440 checkpoint rows. The moderate stress inflates K_q and Ω_q by 10 percent and weakens the certified mixing log-rate by 0.05; the strong stress uses 25 percent and 0.10. Both shields retain the nominal action in all twelve cells, all 24 stress-by-cell one-sided 99 percent upper means remain below the robust certificate, and neither shield changes empirical terminal risk. Controlled statistics/curves reproduce byte for byte; robustness uses eight development and 64 disjoint confirmation seeds. Each policy-learning study has 80 finite, exactly budgeted runs spanning both regimes and all policies; all 160 runs reproduce aggregate curves byte for byte. These ablations quantify the terminal parameter-risk gain from the finite-horizon objective; the joint-action study isolates the response to correlation, spacing, and delay.

XVI. SIGNED CONTINUING-STREAM RISK AND FIXED-PROGRAM SEPARATION

The design-utility formulation is classical [37]; selection dependence and perfect-information value are also established objects [38]. Here these tools are specialized to the paid, continuing-stream learner in main Eq. (38). The distinctions below are the sign of its actual-risk transfer, explicit one-sided constants, and a full-budget comparator, not new general association, truncation, or decision-theory principles.


A. Exact signed transfer for a fixed likelihood decision

Freeze a_0, a_1, their remaining-budget horizons, and all weights before a deterministic probe. Its vector Y has laws $\mathcal{N}(0, \Sigma_j)$, where $0 \prec \Sigma_0 \preceq \Sigma_1$. Use a fixed likelihood threshold and a fixed data-independent tie rule, selecting one for the outside event $Y^\top(\Sigma_0^{-1} - \Sigma_1^{-1})Y > c$. Let E_j be the wrong-decision event, $p_j = \Pr_j(E_j)$, $\Delta J_j = J_{j,a_{1-j}} - J_{j,a_j}$, and $\Delta_k = k_{a_1}^2 - k_{a_0}^2$. The



(a) Budget scale (b) Paid messages (c) Paid environment units

Fig. 2. Direct validation, running mean and low instance: all-policy risk versus allocated scale and actual paid resources. Corrected and no-carryover curves coincide.



(a) Budget scale (b) Paid messages (c) Paid environment units

Fig. 3. Direct validation, running mean and high instance, with the same complete-family averaging and all six policies.


coefficient k_a is common to the hypotheses, as their persistence parameter is the same. Write $\mathcal{C}_j = \mathbb{E}_j[(m_j^2 - s_j^2)\mathbf{1}_{E_j}]$. Symmetry and association give

$$R_0 = J_{0,a_0} + p_0\Delta J_0 + \Delta_k\mathcal{C}_0, \tag{S22}$$

$$R_1 = J_{1,a_1} + p_1\Delta J_1 - \Delta_k\mathcal{C}_1, \tag{S23}$$


$$\mathcal{C}_0 \geq 0, \quad \mathcal{C}_1 \leq 0. \tag{S24}$$

To see this, subtract Eq. (S3) for the wrong and correct programs. The decision event is even in Y, whereas m_j is linear and odd, so $\mathbb{E}_j[m_j\mathbf{1}_{E_j}] = 0$, including nonzero deterministic initialization. Whiten Y under each true instance and orthogonally diagonalize the positive semidefinite decision quadratic. The resulting coordinates G_i are independent standard normal variables and the outside event is increasing in each G_i^2. Writing $m_j = \sum_i v_i G_i$, coordinate sign symmetry eliminates all cross products. Each diagonal covariance $\mathrm{Cov}(G_i^2, \mathbf{1}_{\mathrm{outside}})$ is nonnegative by association of independent variables [39], Theorem 2.1. For completeness, condition on the other squares and use $2\,\mathrm{Cov}(f(X), g(X)) = \mathbb{E}[(f(X) - f(X'))(g(X) - g(X'))] \geq 0$ for increasing f, g and an independent copy X'. The inside event is the complement, which proves the other sign. Thus $\Delta_k > 0$ permits harmful carryover, $\Delta_k < 0$ permits beneficial carryover, and $\Delta_k = 0$ removes it exactly; strictness needs a nonconstant event



(a) Budget scale (b) Paid messages (c) Paid environment units

Fig. 4. Direct validation, averaged delayed affine learner and low instance; every scheduled update is charged, including withheld terminal updates.



(a) Budget scale (b) Paid messages (c) Paid environment units

Fig. 5. Direct validation, averaged delayed affine learner and high instance; exact overlap of the two gates is retained without graphical offsets.

and an aligned posterior component. In the implemented model $\Sigma_j = I + Q\theta_j R_\lambda$, covariance ordering follows from $\theta_1 > \theta_0$.

B. Classical tail moments and a learner-specific corollary

Let φ and Φ be the standard normal density and distribution function. For $0 < p < 1$, define

$$t_p = \Phi^{-1}(1 - p/2), \qquad h_+(p) = 2t_p\varphi(t_p),$$
$$u_p = \Phi^{-1}((1+p)/2), \qquad h_-(p) = 2u_p\varphi(u_p).$$

Set both $h_\pm(0) = 0$ by continuity. The truncated-normal moment calculation is classical [40], Sections 2–3 and 5. For any event E of probability p and $m \sim \mathcal{N}(0, s^2)$,

$$-s^2 h_-(p) \le \mathbb{E}[(m^2 - s^2)\mathbf{1}_E] \le s^2 h_+(p). \qquad \text{(S25)}$$

This also allows E to depend on other variables. Indeed, condition its indicator on m to obtain an acceptance function $g(m) \in [0,1]$ of Gaussian mass p. With $f(m) = m^2 - s^2$, let g_* select the tails $|m| > st_p$ and $c = s^2(t_p^2 - 1)$. Then $(f - c)(g_* - g) \ge 0$ pointwise, and the equal-mass constraint gives $\mathbb{E}[fg_*] \ge \mathbb{E}[fg]$. Selecting the central interval $|m| \le su_p$ proves the minimum in the same way. Integration by parts gives




Fig. 6. Joint actions selected by the finite-time Lyapunov certificate. The left panel reports participation and the right panel reports Markov spacing; persistence values occupy categorical positions.




Fig. 7. Relative risk reductions of the learning-aware rule over information-only probing. All percentages use information-only risk as the denominator.

$\int_t^\infty (x^2-1)\varphi(x)\,dx = t\varphi(t)$, establishing Eq. (S25) and its sharp scalar constants.

Proposition 3 (Ordered-Gaussian continuing-risk corollary)**.** *Under the fixed-program, fixed-probe and centered ordered-covariance conditions above, suppose* $p_j \le \delta_j \le 1/4$. *Then*

$$R_0 \le J_{0,a_0} + \delta_0[\Delta J_0]_+ + [\Delta_k]_+ s_0^2 h_+(\delta_0), \qquad \text{(S26)}$$
$$R_1 \le J_{1,a_1} + \delta_1[\Delta J_1]_+ + [\Delta_k]_+ s_1^2 h_-(\delta_1). \qquad \text{(S27)}$$

Proof. On $[0,1/4]$, $h'_+(p) = t_p^2 - 1 \ge 0$ and $h'_-(p) = 1 - u_p^2 \ge 0$. Combine Eq. (S24) with Eq. (S25) and $p_j \Delta J_j \le \delta_j [\Delta J_j]_+$. When $\Delta_k \le 0$, the transfer term is nonpositive under both instances and can be omitted from an upper bound. □

For small δ, $h_+(\delta) = O(\delta \log(1/\delta))$ and $h_-(\delta) = O(\delta)$. The sharpness is for the scalar event-moment problem, not every finite probe geometry. Data-dependent probe stopping, noncentered likelihoods, sign-sensitive classifiers, and data-selected program weights require a different analysis; main Theorem 5 remains available at its stated scope.

C. Why independent-mixture transport can be insufficient

Let G, W be independent standard normals, $Y = \sqrt{3}(\rho G + \sqrt{1-\rho^2}W)$, and choose between the frozen programs $Z_0 = 1$ and $Z_1 = (1+Y)/2$ using $E = \{|G| > t\}$. Both unconditional squared risks equal one, yet

$$\mathbb{E} Z^2_{\text{selected}} = 1 + \frac{3}{4}\rho^2\, 2t\varphi(t) > 1 \qquad \text{(S28)}$$

for $\rho \ne 0$ and $0 < t < \infty$. Conditioning on G gives $\mathbb{E}[Z_1^2 \mid G] = 1 + (\sqrt{3}/2)\rho G + (3/4)\rho^2(G^2-1)$; the odd term cancels and Eq. (S25) evaluates the rest. At $t = 3$ and $\rho = 1/2$, the event probability is 0.002699796 and the risk is 1.004985829. An independent mixture incorrectly gives one even with the exact decision probability, because its unconditional branch-risk gap is zero. This establishes the need to account for selection dependence in this linear Gaussian class, not necessity of a positive penalty when its signed transfer is beneficial. It is an analytical example outside the registered family grid, not a counterexample to both tests of the executed AND-admission rule or a claim about cost-optimal branch choices.

D. Classical decision comparison with paid continuing learners

Fix the public family, learner, step rule and full budget, and let $\mathcal{A}_{\text{fix}}$ contain all original full-budget fixed (q,b) programs. For a stated prior $\pi \in (0,1)$, define

$$I_\pi = \min_{a \in \mathcal{A}_{\text{fix}}} \{(1-\pi)J_0(a) + \pi J_1(a)\},$$
$$O_\pi = (1-\pi)\min_a J_0(a) + \pi \min_a J_1(a),$$
$$V_\pi = I_\pi - O_\pi.$$

This is the finite-action value-of-perfect-information comparison already used in [38], Section 2.6, with loss rather than utility. The finite catalogue gives $V_\pi > 0$ exactly when the two risk functions have no common minimizer: each fixed action's excess over O_π is a positively weighted sum of two nonnegative excess risks, and the minimum is attained. If B_j is a valid actual-risk upper bound for the executed policy, main Eq. (42) proves lower prior-weighted risk than every fixed catalogue action, including every regime-independent randomized mixture by linearity. To expose the cost balance, let $L_j = J^{\text{post}}_{j,a_j} - \min_a J_j(a)$ and $D_j = B_j - J^{\text{post}}_{j,a_j}$. The same sufficient condition is

$$V_\pi > (1-\pi)(L_0 + D_0) + \pi(L_1 + D_1). \qquad \text{(S29)}$$

TABLE V
FULL ORIGINAL-GRID, BALANCED-PRIOR POPULATION CERTIFICATES USING THE EXECUTED GATE'S ORIGINAL BOUND, NOT A NEWLY EXECUTED POLICY.

Budget scale	Running mean	Delayed affine
32	0/16	0/16
128	0/16	0/16
512	6/16	2/16
2048	12/16	9/16

Here L_j can be signed unless risk monotonicity in horizon has separately been proved for the affine transient. Thus decision opportunity must exceed remaining-horizon and decision-event risk, not merely produce an accurate classification. The reference O_π allows a regime-informed fixed commitment, not arbitrary state-adaptive programs; $V_\pi = 0$ does not exclude useful same-stream state selection. The comparison fixes the learner, step rule and catalogue and is prior-specific, rather than a statement about all fixed algorithms, unknown priors or minimax risk.

E. Complete original-design diagnostic

This outcome-known deterministic calculation retains all 128 original designs and introduces no trajectory, seed or confidence interval. The catalogues contain 16 actions at $Q = 8$ and 24 at $Q = 32$, including all original spacings and full-budget affordable horizons. Of 120 feasible probes, 44 have potentially harmful transfer, 32 beneficial transfer and 44 zero transfer; eight infeasible designs remain included. The original and sign-refined admission counts are both 113/128. All 44 harmful designs were already admitted under the original enclosure, and removing the penalty does not rescue the seven feasible rejections. These deterministic decisions explain the unchanged no-carryover ablation without attributing its equality to seed noise.

For $\pi = 1/2$, 72/128 designs have positive V_π, while the original gate's bound certifies separation in 29/128, as shown in Table V. Their relative certified margins range from 0.1314 to 7.2032 percent of $I_{1/2}$; this range is not an average empirical effect. All 99 uncertified balanced cases remain; zero of 128 satisfy the separate sufficient minimax comparison $\max_j B_j < \min_a \max_j J_j(a)$. These population-model diagnostics explain conditional usefulness and do not replace the validation's prespecified regime-stratified endpoints. The original adverse low-budget result, 23/256 adverse cell means, identical corrected/no-carryover trajectories, and fixed $(2, 1)$ pooled risk advantage all remain unchanged.