

# 08-edge-detection

January 13, 2020

## 1 Edge Detection

### 1.1 Line Profile

```
In [ ]: import skimage.io
        from matplotlib import pyplot as plt

        image = skimage.io.imread("../data/07-bw.jpg")
        plt.plot(image[200, :])
        plt.plot(image[400, :])
        plt.plot(image[600, :])


In [ ]: # zoom in on the image
        skimage.io.imshow(image[200:250, 380:430])

In [ ]: # zoomed in, where would you place the edge?!
        plt.plot(range(380, 430), image[200, 380:430])
```

### 1.2 Canny Edge Detection

```
In [ ]: # created by John Canny in 1986
        # fancy algorithm composed of multiple steps
        # algorithm steps:
            # gaussian blur, remove noise; !sigma
            # sobel edge detection: derivative of curve fitted to pixels
            # non-maximum suppression
            # double threshold
            # hysteresis
        # important part: parameters -> sigma, low, high threshold
        # read image as grayscale:
        import skimage.feature
        import skimage.viewer
        import skimage

        image = skimage.io.imread("../data/07-shapes.tif", as_gray=True)
        sigma = 2
        low_threshold = 0.1
        high_threshold = 0.3
```



An Edge

```
edges = skimage.feature.canny(
    image=image,
    sigma=sigma,
    low_threshold=low_threshold,
    high_threshold=high_threshold,
)
plt.imshow(edges)
# to get rid of artifacts
# plt.imshow(edges, interpolation='bicubic')
# plt.rc("image", interpolation='bilinear')
```

### 1.3 Viewer plugins: Interact with the image viewer

```
In [ ]: # parameters are interdependent, hard to "guess"
        image = skimage.io.imread("../data/07-beads.jpg", as_gray=True)

        viewer = skimage.viewer.ImageViewer(image)

        canny_plugin = skimage.viewer.plugins.Plugin(image_filter=skimage.feature.canny)
        canny_plugin.name = "Canny Filter Plugin"

        # Add sliders for the parameters
        # The filter function will be called with the slider parameters according to their names
        canny_plugin += skimage.viewer.widgets.Slider(
```



beads result

```

        name="sigma", low=0.0, high=7.0, value=2.0
    )
    canny_plugin += skimage.viewer.widgets.Slider(
        name="low_threshold", low=0.0, high=1.0, value=0.1
    )
    canny_plugin += skimage.viewer.widgets.Slider(
        name="high_threshold", low=0.0, high=1.0, value=0.2
    )
    viewer += canny_plugin
    viewer.show()

```

### 1.3.1 Exercise:

Load the `beads.jpg` image from the data folder and use the interactive viewer to find the values that produce the following result after filtering:

```

In [ ]: # img = skimage.io.imread("../fig/07-beads.jpg", as_gray=True)
        # edge = skimage.feature.canny(img, sigma=5, low_threshold=0.01, high_threshold=0.04)
        # edge = skimage.img_as_ubyte(edge)
        # skimage.io.imsave("../fig/07-beads-out.png", arr=edge)

```

### 1.3.2 Exercise: Using sliders for thresholding

Let's apply what we know about creating sliders to another, similar situation: Consider this image (`../data/maize-roots.tif`) of a collection of maize seedlings, and suppose we wish to use simple

fixed-level thresholding to **mask out** everything that is not part of one of the plants.

```
In [ ]: image = skimage.io.imread("../data/maize-roots.tif", as_gray=True)

def filter_function(image, sigma, threshold):
    masked = image.copy()
    masked[skimage.filters.gaussian(image, sigma=sigma) <= threshold] = 0
    return masked

smooth_threshold_plugin = skimage.viewer.plugins.Plugin(
    image_filter=filter_function
)

smooth_threshold_plugin.name = "Smooth and Threshold Plugin"

smooth_threshold_plugin += skimage.viewer.widgets.Slider(
    "sigma", low=0.0, high=7.0, value=1.0
)
smooth_threshold_plugin += skimage.viewer.widgets.Slider(
    "threshold", low=0.0, high=1.0, value=0.5
)

viewer = skimage.viewer.ImageViewer(image=image)
viewer += smooth_threshold_plugin
viewer.show()
```

### 1.3.3 Keypoints

- The `skimage.viewer.ImageViewer` is extended using a `skimage.viewer.plugins.Plugin`.
- We supply a filter function callback when creating a `Plugin`.
- Parameters of the callback function are manipulated interactively by creating sliders with the `skimage.viewer.widgets.slider()` function and adding them to the plugin.