

MINIMAX CLASS RULES

Version 1.0

1. Construction

The MiniMax yacht is intended to be a one-design, two-channel radio-controlled yacht. Yachts may be built by individuals or commercial manufacturers using FDM 3D printing only.

The hull, keel, rudder, mast joiner fitting, boom joiner fitting and sheet guide fitting shall be produced by FDM 3D printing. No alternative methods of manufacture are permitted for these components.

2. Official Parts

The hull, keel, rudder, mast joiner fitting and boom joiner fitting shall be produced from the official MiniMax STL files.

No modification to these files or printed parts is permitted.

Printed components may be sanded, painted, coated with resin, or otherwise finished for appearance and durability, provided the original shape is not altered.

3. Servos

Servos shall fit within the hull recesses provided in the official design without modification to the hull.

4. Rudder Linkage

The rudder linkage may be constructed by any method.

5. Sheet Control

Sheet control shall be by means of a servo arm or lever operating through approximately 90 degrees.

No drum winches, continuous rotation systems, multi-turn winches, or other methods of sheet control are permitted.

6. Rig Dimensions

Rig dimensions shall conform to the official MiniMax sail templates.

Compliance may be checked by laying the completed rig over the appropriate A, B, C or D rig template.

7. Spars

Masts and booms shall be constructed from solid carbon fibre rod of the dimensions specified in the building instructions.

8. Sails

Sails shall be constructed from a single piece of sail film or fabric using the official sail templates.

Reinforcements are permitted provided they remain within the dimensions shown on the sail template.

9. Sail Identification

Each yacht shall display a single-digit identification number from 1 to 9.

Numbers shall be 30 mm high and positioned as shown on the sail templates.

The number on the starboard side shall be placed above the number on the port side.

10. Weight and Centre of Gravity

The minimum ready-to-sail weight shall be 120 grams.

The maximum ready-to-sail weight shall be 130 grams.

The maximum distance from the bottom of the hull to the yacht's centre of gravity shall be X mm.

Compliance shall be determined using the official MiniMax centre-of-gravity measuring jig.

11. Spirit of the Class

The MiniMax is intended to be an inexpensive, easily built, one-design radio-controlled yacht that emphasizes close racing, simplicity and enjoyment.

Any modification, construction method, component, or arrangement whose primary purpose is to obtain a performance advantage outside the intent of these rules is prohibited, whether specifically mentioned in these rules or not.

In the event of doubt, the interpretation that best preserves the one-design nature of the class shall apply.