

Home Task 5

Name: Trimann Kaur
Branch: B.E. CSE (AIML)
Semester: 5
Subject Name: ADBMS

UID: 24BAI70511
Section: 24AIT_KRG-1_B
Date of Performance: 10.08.2026
Subject Code: 24CSP-310

1.

Julia asked her students to create some coding challenges. Write a query to print the hacker_id, name, and the total number of challenges created by each student. Sort your results by the total number of challenges in descending order. If more than one student created the same number of challenges, then sort the result by hacker_id. If more than one student created the same number of challenges and the count is less than the maximum number of challenges created, then exclude those students from the result.

Input Format

The following tables contain challenge data:

Column	Type
hacker_id	Integer
name	String

- Hackers: The hacker_id is the id of the hacker, and name is the name of the hacker.
- Challenges: The challenge_id is the id of the challenge, and hacker_id is the id of the student who created the

Column	Type
challenge_id	Integer
hacker_id	Integer

challenge.

Solution:

```
SELECT H.HACKER_ID,
H.NAME,
COUNT(C.CHALLENGE_ID) AS TOTAL_CHALLENGES
FROM HACKERS AS H
JOIN CHALLENGES AS C
ON H.HACKER_ID = C.HACKER_ID

GROUP BY H.HACKER_ID, H.NAME
HAVING COUNT(C.CHALLENGE_ID) = (
    SELECT MAX(CNT)
    FROM (
        SELECT COUNT(*) AS CNT
        FROM CHALLENGES
```

```

GROUP BY HACKER_ID
) AS TEMP
)
OR COUNT(C.CHALLENGE_ID) IN (
SELECT CNT
FROM (
SELECT COUNT(*) AS CNT
FROM CHALLENGES
GROUP BY HACKER_ID
) AS TEMP
GROUP BY CNT
HAVING COUNT(*) = 1
)
ORDER BY TOTAL_CHALLENGES DESC, H.HACKER_ID;

```

2.

You did such a great job helping Julia with her last coding contest challenge that she wants you to work on this one, too!

The total score of a hacker is the sum of their maximum scores for all of the challenges. Write a query to print the hacker_id, name, and total score of the hackers ordered by the descending score. If more than one hacker achieved the same total score, then sort the result by ascending hacker_id. Exclude all hackers with a total score of 0 from your result.

Input Format

The following tables contain contest data:

Column	Type
hacker_id	Integer
name	String

- Hackers: The hacker_id is the id of the hacker, and name is the name of the hacker.
- Submissions: The submission_id is the id of the submission, hacker_id is the id of the hacker who made the submission, challenge_id is the id of the challenge for which the submission belongs to, and score is the score of the submission.

Column	Type
submission_id	Integer
hacker_id	Integer
challenge_id	Integer
score	Integer

Solution:

```

SELECT H.HACKER_ID,
H.NAME,

```



```
SUM(X.MAX_SCORE) AS TOTAL_SCORE

FROM HACKERS AS H
JOIN (
    SELECT HACKER_ID, CHALLENGE_ID, MAX(SCORE) AS MAX_SCORE
    FROM SUBMISSIONS
    GROUP BY HACKER_ID, CHALLENGE_ID
) AS X
ON H.HACKER_ID = X.HACKER_ID
GROUP BY H.HACKER_ID, H.NAME
HAVING SUM(X.MAX_SCORE) > 0
ORDER BY TOTAL_SCORE DESC, H.HACKER_ID
```