Lab 8 | Circular Sorted List

SortedType<int> - actual and expected results

C++17 | Microsoft Visual C++ 19.44 | /W4 /WX | Exit status 0

Lab 8 | int test run

Actual executable output captured from: lab8.exe (section: int) | Exit status: 0

```
=== int ===
Empty length: 0 (expected 0)
IsFull: 0 (expected 0)
Length after inserts: 3 (expected 3)
Forward: 10 20 30
Expected: 10 20 30
Reverse: 30 20 10
Expected: 30 20 10
Find existing item: 1 (expected 1)
Find missing item: 0 (expected 0)
After ResetList: 10 (expected 10)
Wrap to first: 10 (expected 10)
Insert duplicate, delete one: 10 20 30
Expected: 10 20 30
Delete missing, length: 3 (expected 3)
Delete middle: 10 30
Expected: 10 30
Delete tail: 10
Expected: 10
Delete head: 30
Expected: 30
Delete only node, length: 0 (expected 0)
MakeEmpty length: 0 (expected 0)
Empty reverse (blank line):

Reuse after clearing: 30
Expected: 30
```

Screenshot of captured executable output; complete transcript: test_output.txt.

Simple tests for int, double, and char. Example: X Y Z -> Z Y X.

Lab 8 | Circular Sorted List

SortedType<double> - actual and expected results

C++17 | Microsoft Visual C++ 19.44 | /W4 /WX | Exit status 0

Lab 8 | double test run

Actual executable output captured from: lab8.exe (section: double) | Exit status: 0

```
=== double ===
Empty length: 0 (expected 0)
IsFull: 0 (expected 0)
Length after inserts: 3 (expected 3)
Forward: 1.5 2.5 3.5
Expected: 1.5 2.5 3.5
Reverse: 3.5 2.5 1.5
Expected: 3.5 2.5 1.5
Find existing item: 1 (expected 1)
Find missing item: 0 (expected 0)
After ResetList: 1.5 (expected 1.5)
Wrap to first: 1.5 (expected 1.5)
Insert duplicate, delete one: 1.5 2.5 3.5
Expected: 1.5 2.5 3.5
Delete missing, length: 3 (expected 3)
Delete middle: 1.5 3.5
Expected: 1.5 3.5
Delete tail: 1.5
Expected: 1.5
Delete head: 3.5
Expected: 3.5
Delete only node, length: 0 (expected 0)
MakeEmpty length: 0 (expected 0)
Empty reverse (blank line):

Reuse after clearing: 3.5
Expected: 3.5
```

Screenshot of captured executable output; complete transcript: test_output.txt.

Simple tests for int, double, and char. Example: X Y Z -> Z Y X.

Lab 8 | Circular Sorted List

SortedType<char> - actual and expected results

C++17 | Microsoft Visual C++ 19.44 | /W4 /WX | Exit status 0

Lab 8 | char test run

Actual executable output captured from: lab8.exe (section: char) | Exit status: 0

```
=== char ===
Empty length: 0 (expected 0)
IsFull: 0 (expected 0)
Length after inserts: 3 (expected 3)
Forward: X Y Z
Expected: X Y Z
Reverse: Z Y X
Expected: Z Y X
Find existing item: 1 (expected 1)
Find missing item: 0 (expected 0)
After ResetList: X (expected X)
Wrap to first: X (expected X)
Insert duplicate, delete one: X Y Z
Expected: X Y Z
Delete missing, length: 3 (expected 3)
Delete middle: X Z
Expected: X Z
Delete tail: X
Expected: X
Delete head: Z
Expected: Z
Delete only node, length: 0 (expected 0)
MakeEmpty length: 0 (expected 0)
Empty reverse (blank line):

Reuse after clearing: Z
Expected: Z
```

Screenshot of captured executable output; complete transcript: test_output.txt.

Simple tests for int, double, and char. Example: X Y Z -> Z Y X.