C1 Houlsby continued checkpoint: Methodology and Evidence

CS781 Capstone – Krishna K Karthikeya G N

12 November 2026

Status. Post-run methodology reconstruction grounded in archived source and reports. This document is not an executed historical notebook.

Research question

See whether more updates on the selected C1 Houlsby lineage improve summary quality. The continued run's own report supplies its selected checkpoint and validation negative NLL; its prediction ZIP is a separate submitted export.

Architecture and mechanism

The same C1 architecture and bottleneck adapters resume from their own checkpoint and continue optimization. This is not a fresh architecture.

Measured result

Scored submission	1030988
Codabench BERTScore F1	0.7671
Archived local metric	-1.9365 validation negative NLL; BERTScore not measured in this report

Codabench BERTScore F1 fell from 0.7700 to 0.7671. More training alone did not improve the observed hidden score.

Limitations and next check

A small score decrease does not identify whether overfitting, decoding variation, or stochastic evaluation drove the change. Local, pilot, and hidden metrics are deliberately kept distinct. A single scored run does not establish a causal architecture effect or statistical significance.

Source and reproducibility

Original source modules: c1_houlsby.py, train_phase6.py. SHA-256 hashes, the original report, and the prediction ZIP receipt are in the companion provenance file. The explanatory notebook was written after the historical run; original execution output is never implied. Reproduction requires authorized course data, the Phase 1 parent weights/tokenizer, and the dependencies in the archived source.

Documentation disclosure

AI assistance was used to organize the archived evidence and draft this explanatory document. All numerical claims above come from saved run records or the provided finished-submission screenshot; missing evidence is labelled as such.