Reselected neural-lexical ensemble: Methodology and Evidence

CS781 Capstone – Krishna K Karthikeya G N

12 November 2026

Status. Post-run methodology reconstruction grounded in archived source and reports. This document is not an executed historical notebook.

Research question

After self-match removal, re-evaluate blend selection using valid candidate rankings. This variant checks whether a blend favored by earlier dev selection remains useful after the ranking contract changes.

Architecture and mechanism

Row-normalized neural scores and lexical TF-IDF scores are blended, excluding self before choosing seven unique candidates. The reselected weights are an export-level choice, not a new trained backbone.

Measured result

Scored submission	1039894
Codabench micro-F1@7	0.4017
Archived local metric	not independently reported after correction

Codabench micro-F1@7 was 0.4017, below the 0.4064 full and selected-ensemble exports. The corrected report does not claim a full independent post-selection dev estimate.

Limitations and next check

Multiple blend choices on 118 dev queries can overfit; hidden scores should be reported separately. Local, pilot, and hidden metrics are deliberately kept distinct. A single scored run does not establish a causal architecture effect or statistical significance.

Source and reproducibility

Original source modules: phase7_export.py, phase7_run.py. SHA-256 hashes, the original report, and the prediction ZIP receipt are in the companion provenance file. The explanatory notebook was written after the historical run; original execution output is never implied. Reproduction requires authorized course data, the Phase 1 parent weights/tokenizer, and the dependencies in the archived source.

Documentation disclosure

AI assistance was used to organize the archived evidence and draft this explanatory document. All numerical claims above come from saved run records or the provided finished-submission screenshot; missing evidence is labelled as such.